

# **glossaries-extra.sty v1.48: an extension to the glossaries package**

Nicola L.C. Talbot

Dickimaw Books

<http://www.dickimaw-books.com/>

2021-11-22

## **Abstract**

The `glossaries-extra` package is an extension to the `glossaries` package, providing additional features. Some of the features provided by this package are only available with `glossaries` version 4.19 (or above). This document assumes familiarity with the `glossaries` package.

The file `example-glossaries-xr.tex` contains dummy entries with cross-references that may be used for creating minimal working examples for testing the `glossaries-extra` package. (The base `glossaries` package provides additional files, but this one needs `glossaries-extra`.) There are equivalent `.bib` files for use with `bib2gls`.

**The `glossaries-extra` package uses a different set of defaults to the base `glossaries` package.** See the Introduction for more details.

Since `glossaries-extra` internally loads the `glossaries` package, you also need to have `glossaries` installed and all the packages that `glossaries` depends on (including, but not limited to, `tracklang`, `mfirstuc`, `etoolbox`, `xkeyval` (at least version dated 2006/11/18), `textcase`, `xfor`, `datatool-base` and `amsgen`. These packages are all available in the current  $\text{\TeX}$  Live and  $\text{Mik}\text{\TeX}$  distributions. If any of them are missing, please update your  $\text{\TeX}$  distribution using your update manager. (For help on this see, for example, [How do I update my  \$\text{\TeX}\$  distribution?](#) or [Updating  \$\text{\TeX}\$  on Linux](#).)

Additional resources:

- The `glossaries-extra` documented code [glossaries-extra-code.pdf](#).
- The [glossaries-extra gallery](#).
- `glossaries-extra` and `bib2gls`: An Introductory Guide. ([bib2gls-begin.pdf](#)).
- [Incorporating `makeglossaries` or `makeglossaries-lite` or `bib2gls` into the document build](#).

- The `bib2gls` application.
- The base `glossaries` package.

# Contents

<b>1</b>	<b>Introduction</b>	<b>6</b>
1.1	Package Defaults	6
1.2	New or Modified Package Options	10
<b>2</b>	<b>Modifications to Existing Commands and Styles</b>	<b>22</b>
2.1	Defining Entries	22
2.2	Entry Indexing	24
2.3	Cross-References (“see” and “see also”)	30
2.4	Entry Display Style Modifications	35
2.5	Entry Counting Modifications	38
2.6	First Use Flag	39
2.7	Plurals	42
2.8	Nested Links	43
2.9	Acronym Style Modifications	49
2.10	Glossaries	51
2.11	Glossary Style Modifications	53
2.11.1	Style Hooks	53
2.11.2	Number List	56
2.11.3	The glossaries-extra-stylemods Package	58
<b>3</b>	<b>New Glossary Styles</b>	<b>67</b>
3.1	glossary-bookindex package	67
3.2	glossary-longextra package	72
3.3	glossary-topic package	81
<b>4</b>	<b>Abbreviations</b>	<b>85</b>
4.1	Tagging Initials	87
4.2	Abbreviation Styles	88
4.3	Shortcut Commands	91
4.4	Predefined Abbreviation Styles	91
4.4.1	Predefined Abbreviation Styles that Set the Regular Attribute	99
4.4.2	Predefined Abbreviation Styles that Don’t Set the Regular Attribute	102
4.5	Defining New Abbreviation Styles	114
<b>5</b>	<b>Entries in Sectioning Titles, Headers, Captions and Contents</b>	<b>121</b>
5.1	Simplistic Approach	121
5.2	New Commands Designed for Chapter/Section Headings	122

<b>6</b>	<b>Multi (or Compound) Entries</b>	<b>127</b>
6.1	Examples	130
6.1.1	Example: Hierarchical	130
6.1.2	Example: Suffix	131
6.1.3	Example: Category Suffix	131
6.1.4	Example: Separators	132
6.1.5	Example: Skipping Elements (Fragment Element)	133
6.1.6	Example: Skipping Elements (Prefix and Post-Link Hooks)	135
6.2	Main and Other Elements	139
6.3	Prefixes and Suffixes	140
6.4	Separators	142
6.5	\mgls Element Hooks	145
6.6	Post-Link Hook	146
6.6.1	Last Element	147
6.6.2	Main Element	148
6.7	Multi-Entry First Use	149
6.8	Multi-Entry Category	150
6.9	Multi-Entry Settings	150
6.9.1	Indexing	151
6.9.2	Location Formats (Encaps)	151
6.9.3	Post-Link Hooks	151
6.9.4	Prefixes and Suffixes	152
6.9.5	Skipping Elements	152
6.9.6	General	153
6.10	\mgls Options	154
6.11	Variants of \mgls	155
6.11.1	\gls-like	156
6.11.2	Abbreviations	157
6.11.3	Other Fields	157
6.11.4	Support for glossaries-prefix (\pgls)	159
6.12	Cross-References	160
6.13	Additional Commands	161
6.14	bib2gls	162
<b>7</b>	<b>Categories</b>	<b>165</b>
<b>8</b>	<b>Counting References</b>	<b>176</b>
8.1	Entry Counting (First Use Flag)	176
8.2	Link Counting	182
<b>9</b>	<b>Auto-Indexing</b>	<b>186</b>
<b>10</b>	<b>bib2gls: Managing Reference Databases</b>	<b>189</b>
10.1	Selection	191

10.2	Sorting and Displaying the Glossary . . . . .	192
10.3	The glossaries-extra-bib2gls package . . . . .	196
10.3.1	Supplemental Locations . . . . .	197
10.3.2	Nameref Record . . . . .	197
10.3.3	Helper Commands for Resource Options . . . . .	200
10.4	Supplementary Commands . . . . .	211
10.5	Record Counting . . . . .	217
<b>11</b>	<b>Miscellaneous New Commands</b>	<b>222</b>
11.1	Entry Fields . . . . .	222
11.2	Display All Entries Without Sorting or Indexing . . . . .	233
11.2.1	Hooks . . . . .	234
11.2.2	Filtering . . . . .	235
11.3	Partial Glossaries . . . . .	238
11.4	Standalone Entry Items . . . . .	243
11.5	Entry Aliases . . . . .	246
<b>12</b>	<b>On-the-Fly Document Definitions</b>	<b>248</b>
<b>13</b>	<b>Supplemental Packages</b>	<b>250</b>
13.1	Prefixes or Determiners . . . . .	250
13.2	Accessibility Support . . . . .	250
<b>14</b>	<b>Sample Files</b>	<b>255</b>
<b>15</b>	<b>Multi-Lingual Support</b>	<b>258</b>
	<b>Glossary</b>	<b>262</b>
	<b>Index</b>	<b>263</b>

# 1 Introduction

The glossaries package is a flexible package, but it's also a heavy-weight package that uses a lot of resources. As package developer, I'm caught between those users who complain about the drawbacks of a heavy-weight package with a large user manual and those users who want more features (which necessarily adds to the package weight and manual size).

The glossaries-extra package is an attempt to provide a compromise for this conflict. Version 4.22 of the glossaries package is the last version to incorporate new features.<sup>1</sup> Future versions of glossaries will just be bug fixes. New features will instead be added to glossaries-extra. This means that the base glossaries package won't increase in terms of package loading time and allocation of resources, but those users who do want extra features available will have more of a chance of getting their feature requests accepted.

## 1.1 Package Defaults

I'm not happy with some of the default settings assumed by the glossaries package, and, judging from code I've seen, other users also seem unhappy with them, as certain package options are often used in questions posted on various sites. I can't change the default behaviour of glossaries as it would break backward compatibility, but since glossaries-extra is a separate package, I have decided to implement some of these commonly-used options by default. You can switch them back if they're not appropriate.

The new defaults are:

- `toc=true` (add the glossaries to the table of contents). Use `toc=false` to switch this back off.
- `nopostdot=true` (suppress the terminating full stop after the description in the glossary). Use `nopostdot=false` or just `postdot` to restore the terminating full stop (period).
- `noredefwarn=true` (suppress the warnings that occur when the `theglossary` environment and `\printglossary` are redefined while glossaries is loading). To restore the warnings, use `noredefwarn=false`. Note that this won't have any effect if the glossaries package has already been loaded before you use the glossaries-extra package.
- If babel has been loaded, the `translate=babel` option is switched on. To revert to using the translator interface, use `translate=true`. There is no change to the default if babel hasn't been loaded.

---

<sup>1</sup>4.21 was originally intended as the last release of glossaries to incorporate new features, but a few new minor features slipped in with some bug fixes in v4.21.

- The default style used by `\newacronym` is `short-nolong`. (That is, the long form is not shown on `first use`.)

The examples below illustrate the difference in explicit package options between `glossaries` and `glossaries-extra`. There may be other differences resulting from modifications to commands provided by `glossaries` (see Section 2).

### 1. Basic defaults:

```
\documentclass{article}
\usepackage{glossaries-extra}
```

This is like:

```
\documentclass{article}
\usepackage[toc,nopostdot]{glossaries}
\usepackage{glossaries-extra}
```

### 2. Language defaults:

```
\documentclass[british]{article}
\usepackage{babel}
\usepackage{glossaries-extra}
```

This is like:

```
\documentclass[british]{article}
\usepackage{babel}
\usepackage[toc,nopostdot,translate=babel]{glossaries}
\usepackage{glossaries-extra}
```

### 3. Combined with memoir

```
\documentclass{memoir}
\usepackage{glossaries-extra}
```

This is like:

```
\documentclass{memoir}
\usepackage[toc,nopostdot,noredefwarn]{glossaries}
\usepackage{glossaries-extra}
```

*However*

```
\documentclass{memoir}
\usepackage{glossaries}
\usepackage{glossaries-extra}
```

This is like:

```
\documentclass{memoir}
\usepackage[toc,nopostdot]{glossaries}
\usepackage{glossaries-extra}
```

Since by the time `glossaries-extra` has been loaded, `glossaries` has already redefined `memoir`'s glossary-related commands.

4. Abbreviations are defined with `\newabbreviation`:

```
\usepackage{glossaries-extra}
\newabbreviation{svm}{SVM}{support vector machine}
\begin{document}
First use: \gls{svm}. Explicit full form: \glsxtrfull{svm}.
\end{document}
```

This is the closest to:

```
\usepackage{glossaries}
\newacronym{svm}{SVM}{support vector machine}
\begin{document}
First use: \gls{svm}. Explicit full form: \acrfull{svm}.
\end{document}
```

If you want to continue using `\newacronym` then you will need to change the style for the acronym category:

```
\usepackage{glossaries-extra}
\setabbreviationstyle[acronym]{long-short}
\newacronym{svm}{SVM}{support vector machine}
\begin{document}
First use: \gls{svm}. Explicit full form: \glsxtrfull{svm}.
\end{document}
```

Another noticeable change is that by default `\printglossary` will now display information text in the document if the external glossary file doesn't exist. This is explanatory text to help new users who can't work out what to do next to complete the document build. Once the document is set up correctly and the external files have been generated, this text will disappear.

This change is mostly likely to be noticed by users with one or more redundant empty glossaries who ignore transcript messages, explicitly use `makeindex/xindy` on just the non-empty glossary (or glossaries) and use the iterative `\printglossaries` command instead of `\printglossary`. For example, consider the following:

```
\documentclass{article}

\usepackage[acronym]{glossaries}
```



```

\makeglossaries

\newacronym{laser}{laser}{light amplification by stimulated
emission of radiation}

\begin{document}

\gls{laser}

\printglossaries

\end{document}

```

The above document will only display the list of acronyms at the place where `\printglossaries` occurs. However it will also attempt to input the `.gls` file associated with the main glossary.

If you use `makeglossaries`, you'll get the warning message:

```

Warning: File 'test.glo' is empty.
Have you used any entries defined in glossary 'main'?
Remember to use package option 'nomain' if you
don't want to use the main glossary.

```

(where the original file is called `test.tex`) but if you simply call `makeindex` directly to generate the `.acr` file (without attempting to create the `.gls` file) then the transcript file will always contain the message:

```
No file test.gls.
```

This doesn't occur with `makeglossaries` as it will create the `.gls` file containing the single command `\null`.

If you simply change from `glossaries` to `glossaries-extra` in this document, you'll find a change in the resulting PDF if you don't use `makeglossaries` and you only generate the `.acr` file with `makeindex`.

The transcript file will still contain the message about the missing `.gls`, but now you'll also see information in the actual PDF document. The simplest remedy is to follow the advice inserted into the document at that point, which is to add the `nomain` package option:

```

\documentclass{article}

\usepackage[nomain,acronym,postdot]{glossaries-extra}

\makeglossaries

\setabbreviationstyle[acronym]{long-short}

\newacronym{laser}{laser}{light amplification by stimulated
emission of radiation}

\begin{document}

```

```
\gls{laser}

\printglossaries

\end{document}
```

(Note the need to set the acronym style using `\setabbreviationstyle` before `\newacronym`. See Section 4 for further details.)

## 1.2 New or Modified Package Options

If you haven't already loaded `glossaries`, you can use any of the package options provided by `glossaries` when you load `glossaries-extra` and they will automatically be passed to `glossaries` (which `glossaries-extra` will load). If `glossaries` has already been loaded, then those options will be passed to `\setupglossaries`, but remember that not all of the `glossaries` package options may be used in that command.

This section only lists options that are either unrecognised by the `glossaries` package or are a modified version of options of the same name provided by `glossaries`. See the `glossaries` user manual for details about the unmodified options.

The new and modified options provided by `glossaries-extra` are described below:

**debug** The `glossaries` package has a `debug` option that allows the values `false`, `true` and `showtargets`. The `debug=showtargets` option was introduced to `glossaries` v4.32, so if you want to use this option with `glossaries-extra` you must make sure that your version of `glossaries` supports it.

The `glossaries-extra` package extends this option to provide the additional values `debug=showwrgloss` and `debug=all`.

The `debug=showwrgloss` option implements `debug=true` and uses

```
\glsxtrwrglossmark
```

to show a mark `·` just before the write operation performed by the indexing commands. If you use `record=hybrid` there will be a mark for the write operation to the `.aux` file for `bib2gls` and a mark for the write operation to the associated glossary file for `makeindex` or `xindy`.

The `debug=all` option implements both `debug=showtargets` and `debug=showwrgloss`.

**showtargets** This implements `debug=showtargets` and can also adjust the way the targets are shown. By default, any links that occur in  $\TeX$ 's "outer" mode are placed in the margin according to `\glsshowtargetouter` (provided by the base `glossaries` package). This can lead to the "too many floats" error if there are multiple instances of commands like `\gls` in

a single line. This option provides a way of changing this to an in-line annotation. Available values:

**left** A marker is placed to the left of the link/target and a marginal note is used in outer mode;

**right** A marker is placed to the right of the link/target and a marginal note is used in outer mode;

**innerleft** A marker and annotation are placed to the left of the link/target in all modes;

**innerright** A marker and annotation are placed to the right of the link/target in all modes;

**annoteleft** Markers are placed on either side of the link/target and the annotation is on the left;

**annoteright** Markers are placed on either side of the link/target and the annotation is on the right.

**postdot** (New to version 1.12.) This option is just a shortcut for `nopostdot=false`.

**postpunc** (New to version 1.21.) This option sets the post-description punctuation to the given value. For example: `postpunc=;` does

```
\renewcommand{\glspostdescription}{;}
```

The value may also be one of the following keywords:

**comma:** `postpunc=comma` is equivalent to

```
\renewcommand{\glspostdescription}{,}
```

**dot:** `postpunc=dot` is equivalent to

```
\renewcommand{\glspostdescription}{.\spacefactor\sfcode`. }
```

**none:** `postpunc=none` is equivalent to

```
\renewcommand{\glspostdescription}{}
```

The default definition is

```
\newcommand*{\glspostdescription}{%
  \ifglsnopostdot\else.\spacefactor\sfcode`. \fi
}
```

where the conditional is determined by the `nopostdot` package option. The `postpunc` option removes the conditional from the definition of `\glspostdescription`. The package options `nopostdot` and `postdot` will restore the original definition of `\glspostdescription`.

The `glossaries-extra-stylemods` package adjusts the predefined styles that had a hard-coded `\space` before the **number list** so that they use `\glsxtrprelocation` instead (which is defined to `\space`). You can therefore redefine this command in combination with `postpunc` to alter the separator before the number list. For example, to have a comma followed by `\hfil`:

```
\usepackage[postpunc=comma,stylemods]{glossaries-extra}
\renewcommand{\glsxtrprelocation}{\hfil}
```

Be careful with doing this as it will look odd if the number list is missing. (With `bib2gls` you can instead redefine `\glsxtrprelocation` to do nothing and set the location prefixes with `loc-prefix` which will only apply if the entry has a number list.)

**prefix** Load the `glossaries-prefix` package (if not already loaded).

**accsupp** Load the `glossaries-accsupp` package (if not already loaded).

The `glossaries-accsupp` package is still experimental and so accessibility features are liable to change.

If you want to define styles that can interface with the accessibility support provided by `glossaries-accsupp` use the `\glsaccess<xxx>` type of commands instead of `\glsentry<xxx>` (for example, `\glsaccessstext` instead of `\glsentrytext`). If `glossaries-accsupp` hasn't been loaded those commands are equivalent (for example, `\glsaccessstext` just does `\glsentrytext`) but if it has been loaded, then the `\glsaccess<xxx>` commands will add the accessibility information. (See Section 13.2 for further details.)

Note that the `accsupp` option can only be used as a package option (and can't be set with `\glossariesextrasetup`) since the `glossaries-accsupp` package must be loaded before `glossaries-extra` if it's required.

**stylemods** This is a `<key>=<value>` option used to load the `glossaries-extra-stylemods` package. The value may be a comma-separated list of options to pass to that package. (Remember to group `<value>` if it contains any commas.) The value may be omitted if no options need to be passed. See Section 2.11 for further details. There are two special keyword values: `stylemods=default` (equivalent to omitting the value) and `stylemods=all`, which loads all the predefined styles.

**undefaction** This is a `<key>=<value>` option, which has two allowed values: `warn` and `error`. This indicates what to do if an undefined glossary entry is referenced. The default behaviour is `undefaction=error`, which produces an error message (the default for `glossaries`). You can switch this to a warning message (and `??` appearing in the text) with `undefaction=warn`.

Undefined entries can't be picked up by any commands that iterate over a glossary list. This includes `\forglentries` and `\glsaddall`.

Note that `\ifglsused` will display `??` in the document text with `undefaction=warn` if the entry hasn't been defined, as the underlying boolean variable doesn't exist and so is neither true nor false. (There will also be a warning in the transcript.) See Section 2.6 for further details.

**indexcrossrefs** This is a boolean option. If true, this will automatically index any cross-referenced entries that haven't been marked as used at the end of the document. Note that

this necessarily adds to the overall document build time, especially if you have defined a large number of entries, so this defaults to false, but it will be automatically switched on if you use the see or seealso keys in any entries (unless `autoseeindex=false`). To force it off, even if you use the see or seealso key, you need to explicitly set `indexcrossrefs` to false.

Note that `bib2gls` can automatically find dependent entries when it parses the `.bib` source file. The `record` option automatically implements `indexcrossrefs=false`.

**autoseeindex** (New to v1.16.) This is a boolean option. If true (default), this makes the see and seealso keys automatically index the cross-reference when an entry is defined. If false, the value of those keys will still be stored in their corresponding fields (and can be accessed using commands like `\glxtrusee` and `\glxtruseealso`) but cross-reference won't be automatically indexed.

Note that the `record=only` option automatically implements `autoseeindex=false`.

For example, if an entry is defined as

```
\newglossaryentry{foo}{name={foo},description={},see={bar,baz}}
```

then with `autoseeindex=true`, this is equivalent to

```
\newglossaryentry{foo}{name={foo},description={}}
\glssee{foo}{bar,baz}
\glossariesextrasetup{indexcrossrefs=true}
\GlsXtrSetField{foo}{see}{bar,baz}
```

but with `autoseeindex=false`, this is equivalent to

```
\newglossaryentry{foo}{name={foo},description={}}
\GlsXtrSetField{foo}{see}{bar,baz}
```

Note that `indexcrossrefs` isn't automatically implemented by the presence of the see key when `autoseeindex` is false.

It's therefore possible to remove the cross-references from the location lists and set their position within the glossary style.

Another method of preventing the automatic indexing is to define the entries before the external indexing files have been opened with `\makeglossaries`. Since the appropriate file isn't open, the information can't be written to it. This will need the package option `seenindex=ignore` (provided by `glossaries`) to prevent an error occurring.

**record** (New to v1.08.) This is a `<key>=<value>` option provided for the benefit of `bib2gls` (see Section 10). If you want to use `bib2gls`, the recommended setting is `record=nameref` if you have hyperlinks and `record=only` if you don't have hyperlinks.

The option may only be set in the preamble and can't be used after `\GlsXtrLoadResources`. If the value is missing `record=only` is assumed. Permitted values:

- off** This is the default setting. The indexing is performed as normal using either `\makeglossaries` or `\makenoidxglossaries`. This setting implements `undefaction=error`.
- only** The indexing (recording) is performed by `bib2gls` (see Section 10). Neither `\makeglossaries` nor `\makenoidxglossaries` is permitted. This setting implements `undefaction=warn` and automatically loads the supplementary `glossaries-extra-bib2gls` package. (There should be no need to explicitly load `glossaries-extra-bib2gls`.)
- The glossaries should be displayed using `\printunsrtglossary` (or `\printunsrtglossaries`).

The document build process is (assuming the file is called `myDoc.tex`):

```
pdflatex myDoc
bib2gls myDoc
pdflatex myDoc
```

If you want letter groups you will need the `--group` or `-g` switch when invoking `bib2gls`:

```
pdflatex myDoc
bib2gls -g myDoc
pdflatex myDoc
```

Note that `record=only` will prevent the see from automatically implementing `\glssee`. (`bib2gls` deals with the see field.) You may explicitly use `\glssee` in the document, but `bib2gls` will ignore the cross-reference if the see field was already set for that entry.

The `record=only` option will automatically set the `glossaries` package's `sort=none` option if available. (That option value was only introduced to `glossaries` v4.30.)

- nameref** (New to v1.37 and requires `bib2gls` v1.8+.) This option is like `record=only` but additionally records the current label information given by `\@currentlabel` and `\@currentHref`, and provides a more reliable way of saving the `\theH{counter}` for the given location. This option requires `hyperref` otherwise it will fall back on the usual location records. Remember that `\@currentHref` is always globally updated whenever `\refstepcounter` is used, but `\@currentlabel` isn't. This can cause some undesired side-effects with some settings. Remember also that the `indexcounter` option increments the associated counter every time an entry is indexed, which affects this option. See Section 10.3.2 for further details.

This option is best used with `counter=chapter` or `counter=section` if you want the title included in the location list. If the indexing counter is the default page, only the location number is shown. Similarly for `counter=equation` (or `equations=true`).

- alsoindex** Deprecated synonym of `hybrid`.

- hybrid** This is a hybrid setting that uses `bib2gls` to fetch entry information from `.bib` files, but uses `makeindex` or `xindy` to create the glossary files (which are input with `\printglossary`). Note that this requires a slower and more complicated build process (see below).

This hybrid approach is provided for the rare instances where an existing `xindy` rule or module is too complicated to convert to a `bib2gls` rule but the entries need to be fetched from a `bib` file. There's no benefit in using this option with `makeindex`.

Since it's redundant to make `bib2gls` also sort, use `sort=none` in `\GlsXtrLoadResources` for a faster build.

This option must be used with `\makeglossaries` but not with its optional argument. This option should not be used with `\makenoidxglossaries`. You may need to change the transcript file used by `bib2gls` to avoid a clash with the transcript file used by `makeindex` or `xindy`. (This can be done with `bib2gls`'s `--log-file` or `-t` option.)

Each glossary should be displayed using `\printglossary` (or `\printglossaries` for all of them). This option is expected to be used with `bib2gls`'s `sort=none` setting and so `glossaries-extra-bib2gls` is not automatically loaded.

The document build process is (assuming the file is called `myDoc.tex`):

```
pdflatex myDoc
bib2gls myDoc
pdflatex myDoc
makeglossaries myDoc
pdflatex myDoc
```

Note that, in this case, it's redundant to call `bib2gls` with the `--group` or `-g` switch as `makeindex/xindy` will insert the group heading information into the corresponding glossary file. (If you want `bib2gls` to form the letter groups then this hybrid method is inappropriate.)

With the recording on (`record=only`, `record=nameref` or `record=hybrid`), any of the commands that would typically index the entry (such as `\gls`, `\glstext` or `\glsadd`) will add a `\glsextr@record` entry to the `.aux` file. `bib2gls` can then read these lines to find out which entries have been used. (Remember that commands like `\glsentryname` don't index, so any use of these commands won't add a corresponding `\glsextr@record` entry to the `.aux` file.) See Section 10 for further details.

The hybrid method additionally performs the standard indexing action that's required for `makeindex` or `xindy` to work.

**equations** (New to v1.37.) This option will cause the default location counter to automatically switch to equation when inside a numbered equation environment, such as `equation` or `align`. The counter can be explicitly overridden with `counter` in the optional arguments of commands like `\glslink` or `\gls` as usual.

**floats** (New to v1.37.) This option will cause the default location counter to automatically switch to the corresponding counter when inside a floating environment, such as `figure` or `table`. The counter can be explicitly overridden with `counter` in the optional arguments of commands

like `\glslink` or `\gls` as usual. Remember that within floats it's the `\caption` command that actually uses `\refstepcounter`, so indexing before the caption will result in the wrong reference. The commands for use in captions and sections, such as `\glsfmttext` and `\glsfmtshort`, don't index. (See Section 5). You may want to consider using `\glsadd` after the caption (not before). For example:

```
\begin{figure}[htbp]
  \centering
  \includegraphics{example-image}
  \caption{Sample \glsfmttext{foobar} figure}
  \glsadd{foobar}
\end{figure}
```

**indexcounter** (New to v1.29.) This option (which doesn't take a value) is primarily intended for use with `bib2gls` (v1.4+) and `hyperref`. It can be used with `makeindex` or `xindy` but it will interfere with the `number list` collation, so you won't have ranges and you'll have duplicate page numbers present (but each page number will link to the relevant part of the page where the indexing occurred). This option automatically implements `counter=wr glossary`.

This option works by incrementing `wrglossary` and adding `\label`. This can cause a problem if the indexing occurs in an equation environment as `amsmath` forbids multiple occurrences of `\label` (resulting in the "Multiple `\label`'s" error). It's best to change the counter to `page` or `equation` when in maths mode with this option. For example:

```
\renewcommand{\glslinkpresetkeys}{%
  \ifmmode \setkeys{glslink}{counter=equation}\fi}
\renewcommand{\glsaddpresetkeys}{%
  \ifmmode \setkeys{glossadd}{counter=equation}\fi}
```

By default (with `hyperref`), the page numbers in number lists link back to the top of the relevant page (provided the format uses `\gls hypernumber`). The `indexcounter` option is designed to link back to the place within the page where the indexing occurred. It does this by creating a new counter (called `wrglossary`) that's incremented with `\refstepcounter` every time an entry is indexed (but not via cross-referencing commands, such as `\glssee`). A `\label` is placed immediately after the increment command allowing the back-referenced to be obtained with `\pageref`. The location, as seen by the indexing application, is the value of the `wrglossary` counter but this value is substituted with the page reference when number list is typeset. Since the counter is used by all entries and is incremented every time any indexing occurs, neither `makeindex` nor `xindy` can correctly collate the lists. For example, if the first term to be referenced is indexed three times on page 5 without any intervening terms then the actual locations obtained from `wrglossary` will be 1, 2 and 3, which `xindy` and `makeindex` will try to form into the range 1–3, but they should actually all simply appear as page 5, whereas it can actually end up with 5–5. Conversely, a range may not be formed where it would naturally occur if just the page counter was used.



Since `bib2gls` is designed specifically to work with `glossaries-extra`, `bib2gls` (v1.4+) will check for `wrglossary` locations. If the default `--merge-wrglossary-records` is on, then any records for the same page for a given entry will be merged. In the above example with three references on page 5, only a single record for page 5 for that entry will be added to the number list and it will link back to the first instance on that page. Whereas if you use the `--no-merge-wrglossary-records` switch, the number list will contain three instance of page 5, with each linking to the corresponding place on that page. In both cases, consecutive pages can form ranges, but it may look strange in the second case.

See the `bib2gls` documentation for the `save-index-counter` resource option for more details.

**docdef** This option governs the use of `\newglossaryentry`. It was originally a boolean option, but as from version 1.06, it can now take one of the following values (if the value is omitted, true is assumed):

- `docdef=false`: `\newglossaryentry` is not permitted in the document environment (default).
- `docdef=true`: `\newglossaryentry` behaves as it does in the base `glossaries` package. That is, where its use is permitted in the document environment, it uses the `.glsdefs` temporary file to store the entry definitions so that on the next `LATEX` run the entries are defined at the beginning of the document environment. This allows the entry information to be referenced in the glossary, even if the glossary occurs before `\newglossaryentry`. (For example, when the glossary is displayed in the front matter.) This method of saving the definitions for the next `LATEX` run has drawbacks that are detailed in the `glossaries` user manual.

Remember that if `\newglossaryentry` wouldn't be allowed in the document environment with the base `glossaries` package, then it still won't be allowed with `docdefs=true`. If your `glossaries` occur at the end of the document, consider using `docdef=restricted` instead.

- `docdef=restricted`: (new to version 1.06) `\newglossaryentry` is permitted in the document environment without using the `.glsdefs` file. This means that all entries must be defined before the glossary is displayed, but it avoids the complications associated with saving the entry details in a temporary file. You will still need to take care about any changes made to characters that are required by the `<key>=<value>` mechanism (that is, the comma and equal sign) and any `makeindex` or `xindy` character that occurs in the sort key or label. If any of those characters are made active in the document, then it can cause problems with the entry definition. This option will allow `\newglossaryentry` to be used in the document with `\makenoidxglossaries`, but note that `\longnewglossaryentry` remains a preamble-only command.

With this option, if an entry appears in the glossary before it has been defined, an error will occur (or a warning if the `undefaction=warn` option is used.) If you edit your document and either remove an entry or change its label, you may need to delete the document's temporary files (such as the `.aux` and `.gls` files).

- `docdef=atom`: (new to version 1.34) This option behaves like `docdef=restricted` but creates the `.glsdefs` file for `atom`'s `autocomplete` support. This file isn't input by `glossaries-extra` and so associated problems with the use of this file are avoided, but it allows the `autocomplete` support to find the labels in the file. As with `docdef=restricted`, entries may be defined in the preamble or anywhere in the document, but they may only be referenced after they have been defined. Entries must be defined before the associated glossary is displayed.

If you need a list of all entry labels for the use of an editor or helper script you may also want to consider the package options `writeglslabels` and `writeglslabelnames` provided by the base `glossaries` package. Note that with these options and `docdef=atom`, only the entry labels visible to  $\LaTeX$  can be saved. So if you are using `bib2gls` you will only get the labels of the entries that are selected by `bib2gls`.

The `glossaries` package allows `\newglossaryentry` within the document environment (when used with `makeindex` or `xindy`) but the user manual warns against this usage. By default the `glossaries-extra` package *prohibits* this, only allowing definitions within the preamble. If you are really determined to define entries in the document environment, despite all the associated drawbacks, you can restore this with `docdef=true`. Note that this doesn't change the prohibitions that the `glossaries` package has in certain circumstances (for example, when using "option 1"). See the `glossaries` user manual for further details. A better option if document definitions are required is `docdef=restricted`. Only use `docdef=true` if document definitions are necessary and one or more of the `glossaries` occurs in the front matter.

This option affects commands that internally use `\newglossaryentry`, such as `\newabbreviation`, but not the "on-the-fly" commands described in Section 12.

**`nomissinggls`** This is a boolean option. If true, this will suppress the warning written to the transcript and the warning text that will appear in the document if the external glossary files haven't been generated due to an incomplete document build. However, it's probably simpler just to fix whatever has caused the failure to build the external file or files.

**`abbreviations`** This option has no value and can't be cancelled. If used, it will automatically create a new glossary with the label `abbreviations` and redefines `\glsxtrabbrvtype` to this label. (The file extensions are `glg-abr`, `gls-abr` and `glo-abr`.) In addition, this option defines a shortcut command

```
\printabbreviations[<options>]
```

which is equivalent to

```
\printglossary[type=\glsxtrabbrvtype,<options>]
```

If `glossaries-extra-bib2gls` is also loaded then this option will additionally provide:

```
\printunsrtabbreviations[\langle options \rangle]
```

which uses `\printunsrtglossary`.

The title of the new glossary is given by

```
\abbreviationsname
```

If this command is already defined, it's left unchanged. Otherwise it's defined to "Abbreviations" if `babel` hasn't been loaded or `\acronymname` if `babel` has been loaded. However, if you're using `babel` it's likely you will need to change this. (See Section 15 for further details.)

If you don't use the `abbreviations` package option, the `\abbreviationsname` command won't be defined (unless it's defined by an included language file).

If the `abbreviations` option is used and the `acronym` option provided by the `glossaries` package hasn't been used, then `\acronymtype` will be set to `\glsxtrabbrvtype` so that acronyms defined with `\newacronym` can be added to the list of abbreviations. If you want acronyms in the main glossary and other abbreviations in the `abbreviations` glossary then you will need to redefine `\acronymtype` to `main`:

```
\renewcommand*{\acronymtype}{main}
```

Note that there are no analogous options to the `glossaries` package's `acronymlists` option (or associated commands) as the abbreviation mechanism is handled differently with `glossaries-extra`.

**symbols** This is passed to `glossaries` but will additionally define

```
\glsxtrnewsymbol[\langle options \rangle]{\langle label \rangle}{\langle symbol \rangle}
```

which is equivalent to

```
\newglossaryentry{\langle label \rangle}{name={\langle symbol \rangle},  
sort={\langle label \rangle},type=symbols,category=symbol,\langle options \rangle}
```

Note that the sort key is set to the `\langle label \rangle` not the `\langle symbol \rangle` as the symbol will likely contain commands.

If `glossaries-extra-bib2gls` is also loaded then this option will additionally provide:

```
\printunsrtsymbols[\langle options \rangle]
```

which uses `\printunsrtglossary`.

**numbers** This is passed to glossaries but will additionally define

```
\glxtrnewnumber [options] {number}
```

which is equivalent to

```
\newglossaryentry{label}{name={number},  
sort={label},type=numbers,category=number,options}
```

If glossaries-extra-bib2gls is also loaded then this option will additionally provide:

```
\printunsrtnumbers [options]
```

which uses `\printunsrtglossary`.

**acronyms (or acronym)** This is passed to glossaries but if glossaries-extra-bib2gls is also loaded then this option will additionally provide:

```
\printunsrtacronyms [options]
```

which uses `\printunsrtglossary`.

This option defines a new glossary with the label `acronym` not `acronyms`. You may find it easier to reference it with the command `\acronymtype`.

**index** This is passed to glossaries but if glossaries-extra-bib2gls is also loaded then this option will additionally provide:

```
\printunsrtindex [options]
```

which uses `\printunsrtglossary`.

**shortcuts** Unlike the glossaries package option of the same name, this option isn't boolean but has multiple values:

- `shortcuts=acronyms` (or `shortcuts=acro`): set the shortcuts provided by the glossaries package for acronyms (such as `\ac`). Note that the short and long forms don't use `\glxtrshort` and `\glxtrlong` but use the original `\acrshort` and `\acrlong`, which don't recognise multiple abbreviation styles. The better option with glossaries-extra is `shortcuts=ac`.
- `shortcuts=ac`: set the shortcuts provided by the glossaries package for acronyms (such as `\ac`) but uses the glossaries-extra interface (such as `\glxtrshort` rather than `\acrshort`). In this case `\ac` is defined as `\cgl` rather than `\gl`.

- `shortcuts=abbreviations` (or `shortcuts=abbr`): set the abbreviation shortcuts provided by `glossaries-extra`. (See Section 4.3.) These settings don't switch on the acronym shortcuts provided by the `glossaries` package.
- `shortcuts=other`: set the “other” shortcut commands, but not the shortcut commands for abbreviations or the acronym shortcuts provided by `glossaries`. The “other” shortcuts are:
  - `\newentry` equivalent to `\newglossaryentry`
  - `\newsym` equivalent to `\glstrnewsymbol` (see the `symbols` option).
  - `\newnum` equivalent to `\glstrnewnumber` (see the `numbers` option).
- `shortcuts=all` (or `shortcuts=true`): implements `shortcuts=ac`, `shortcuts=abbreviations` and `shortcuts=other`.
- `shortcuts=none` (or `shortcuts=false`): don't define any of the shortcut commands (default).

Note that multiple invocations of the `shortcuts` option *within the same option list* will override each other.

After the `glossaries-extra` package has been loaded, you can set available options using

```
\glossariesextrasetup{<options>}
```

The `abbreviations` and `docdef` options may only be used in the preamble. Additionally, `docdef` can't be used after `\makenoidxglossaries`.

## 2 Modifications to Existing Commands and Styles

### 2.1 Defining Entries

The glossaries package provides `\nopostdesc` which may be used in the description to suppress the post-description hook. The glossaries-extra package provides another command

```
\glxtrnopostpunc
```

which has a similar function but only suppresses the post-description punctuation. It doesn't suppress the use of `\glxtrpostdescription` which allows the use of category-dependent post-description hooks. (Note that the punctuation, which is in the original base hook `\glspostdescription`, comes after the extended post-description hook `\glxtrpostdescription` not before.) The post-description hook can counter-act the effect of `\glxtrnopostpunc` using

```
\glxtrrestorepostpunc
```

These commands have no effect outside of the glossary (except with standalone entries that use `\glxtractivateno` and `\glspostdescription`, see Section 11.4).

The commands used by glossaries to automatically produce an error if an entry is undefined (such as `\glsglue`) are changed to take the `undefaction` option into account.

The `\newglossaryentry` command has three new keys:

- `category`, which sets the category label for the given entry. By default this is `general`. See Section 7 for further information about categories.
- `alias`, which allows an entry to be alias to another entry. See Section 11.5 for further details.
- `seealso`, which performs much like `see`, but allows for separate “see” and “see also” treatment. See Section 2.3 for further details.

This apply to all entry defining commands (such as `\newabbreviation`).

The test file `example-glossaries-xr.tex` contains dummy entries with a mixture of `see`, `alias` and `seealso` keys for use with minimal working examples. There are also `example-glossaries-*.bib` files that correspond to each `example-glossaries-*.tex` file for testing `bib2gls`.

The `\longnewglossaryentry` command now has a starred version (as from v1.12) that doesn't automatically insert

```
\leavevmode\unskip\nopostdesc
```

at the end of the description field.

```
\longnewglossaryentry*{<label>}{<options>}{<description>}
```

The `descriptionplural` key is left unset unless explicitly set in `<options>`.

The unstarred version no longer hard-codes the above code (which removes trailing space and suppresses the post-description hook) but instead uses:

```
\glxtrpostlongdescription
```

This can be redefined to allow the post-description hook to work but retain the `\unskip` part if required. For example:

```
\renewcommand*{\glxtrpostlongdescription}{\leavevmode\unskip}
```

This will discard unwanted trailing space at the end of the description but won't suppress the post-description hook.

The unstarred version also alters the base `glossaries` package's treatment of the `descriptionplural` key. Since a plural description doesn't make much sense for multi-paragraph descriptions, the default behaviour with `glossaries-extra`'s `\longnewglossaryentry` is to simply leave the plural description unset unless explicitly set using the `descriptionplural` key. The `glossaries.sty` version of this command sets the description's plural form to the same as the singular.<sup>1</sup>

Note that this modified unstarred version doesn't append `\glxtrpostlongdescription` to the description's plural form.

The `\newterm` command (defined through the `index` package option) is modified so that the category defaults to `index`. The `\newacronym` command is modified to use the new abbreviation interface provided by `glossaries-extra`. (See Section 4.)

The `\makeglossaries` command now has an optional argument.

```
\makeglossaries[<list>]
```

If `<list>` is empty, `\makeglossaries` behaves as per its original definition in the `glossaries` package, otherwise `<list>` can be a comma-separated list of glossaries that need processing with an external indexing application.

This command is not permitted with the `record=only` package option. Without the optional argument, it's required with `record=hybrid`. With the optional argument, it's only permitted with the default `record=off`.

It should then be possible to use `\printglossary` for those glossaries listed in `<list>` and `\printnoidxglossary` for the other glossaries. (See the accompanying file `sample-mixedsort.tex` for an example.)

---

<sup>1</sup>The `descriptionplural` key is a throwback to the base package's original acronym mechanism before the introduction of the long and short keys, where the long form was stored in the description field and the short form was stored in the symbol field.

If you use the optional argument *<list>*, you can't define entries in the document (even with the `docdef` option).

You will need at least version 2.20 of `makeglossaries` or at least version 1.3 of the Lua alternative `makeglossaries-lite` (both distributed with `glossaries v4.27`) to allow for this use of `\makeglossaries[<list>]`. Alternatively, use the `automake` option.

## 2.2 Entry Indexing

As from version 1.31, there is a new command like `\glsadd` where the mandatory argument is a comma-separated list of labels:

```
\glsaddeach[<options>]{<list>}
```

This simply iterates over *<list>* and does `\glsadd[<options>]{<label>}` for each entry in the list.

As from version 1.37, you can make commands like `\gls` or `\glslink` automatically use `\glsadd` with specific options when a given format is used (identified with `format={<format>}` in the optional argument of the corresponding `\gls`, `\glslink` etc).

```
\GlsXtrAutoAddOnFormat[<label>]{<format list>}{<glsadd options>}
```

The optional argument *<label>* defaults to `\glslabel` and indicates the label to use in `\glsadd` and so needs to be expandable. The *<format list>* is a comma-separated list of format values that will trigger the automated adding. The *<glsadd options>* are the options to pass to `\glsadd` with `format={<format>}` prepended to the list.

For example, with:

```
\GlsXtrAutoAddOnFormat{hyperbf}{counter=chapter}
```

then `\gls[format=hyperbf]{sample}` will be equivalent to

```
\glsadd[format=hyperbf,counter=chapter]{sample}\gls[format=hyperbf]{sample}
```

Note that the explicit range markers will prevent a match unless you include them in *<format list>* (in which case, be sure to add both the start and end formats).

Here's another example:

```
\GlsXtrAutoAddOnFormat[dual.\glslabel]{hyperbf}{}
```

In this case `\gls[format=hyperbf]{sample}` will now be equivalent to:

```
\glsadd[format=hyperbf]{dual.sample}\gls[format=hyperbf]{sample}
```

`\GlsXtrAutoAddOnFormat` is not applied to `\glsadd` as it could cause an infinite loop.

The `glossaries-extra` package provides extra keys for commands like `\gls` and `\glsnext`:



**noindex** This is a boolean key. If true, this suppresses the indexing. (That is, it prevents `\gls` or whatever from adding a line to the external glossary file.) This is more useful than the `indexonlyfirst` package option provided by glossaries, as the `first use` might not be the most pertinent use. (If you want to apply `indexonlyfirst` to selected entries, rather than all of them, you can use the `indexonlyfirst` attribute, see Section 7 for further details.) Note that the `noindex` key isn't available for `\glsadd` (and `\glsaddall`) since the whole purpose of that command is to index an entry.

**wrgloss** (New to v1.14.) This is may only take the values before or after. By default, commands that both index and display link text (such as `\gls`, `\glsstext` and `\glslink`), perform the indexing before the link text as the indexing creates a whatsit that can cause problems if it occurs after the link text. However, it may be that in some cases (such as long phrases) you may actually want the indexing performed after the link text. In this case you can use `wrgloss=after` for specific instances. Note that this option doesn't have an effect if the indexing has been suppressed through other settings (such as `noindex`).

The default value is set up using

```
\glstrinitwrgloss
```

which is defined as:

```
\newcommand*{\glstrinitwrgloss}{%
  \glsifattribute{\glslabel}{wrgloss}{after}%
  {%
    \glstrinitwrglossbeforefalse
  }%
  {%
    \glstrinitwrglossbeforetrue
  }%
}
```

This sets the conditional

```
\ifglstrinitwrgloss
```

which is used to determine where to perform the indexing.

This means you can set the `wrgloss` attribute to `after` to automatically use this as the default for entries with that category attribute. (Note that adding `wrgloss` to the default options in `\GlsXtrSetDefaultGlsOpts` will override `\glstrinitwrgloss`.)

**hyperoutside** (New to v1.21.) This is a boolean key. The default is `hyperoutside=true`, which puts the hyperlink outside `\glsstextformat`, so that commands like `\gls` will effectively do

```
\hyperlink{<target>}{\glsstextformat{<link text>}}
```

This is the same behaviour as with the base glossaries package. With `hyperoutside=false`, `\hyperlink` is placed inside the argument of `\glstextformat`:

```
\glstextformat{\hyperlink{<target>}{<link text>}}
```

You can use the `hyperoutside` category attribute to set the default for a given category. This can be combined with the use of the `textformat` attribute to counteract any interference caused by `\hyperlink`. For example:

```
\glssetcategoryattribute{mathrelation}{hyperoutside}{false}
```

will set `hyperoutside=false` for all entries that are assigned to the category `mathrelation` and

```
\glssetcategoryattribute{mathrelation}{textformat}{mathrel}
```

will use `\mathrel` instead of `\glstextformat` resulting in:

```
\mathrel{\hyperlink{<target>}{<link text>}}
```

for entries with the category key set to `mathrelation`.

**textformat** This key must have a control sequence name as its value. The command formed from this name must exist and must take one argument. (Use `relax` for default behaviour.) If set, this overrides the `textformat` attribute and `\glstextformat`. See the soul example in Section 2.6.

**prefix** Locally redefines `\glslinkprefix` to the given value. It should match the prefix for the desired glossary.

**thevalue** Explicitly set the location to this value (see below).

**theHvalue** Set the corresponding hyperlink location (see below).

You can set the default options used by `\glslink`, `\gls` etc with:

```
\GlsXtrSetDefaultGlsOpts{<options>}
```

For example, if you mostly don't want to index entries then you can do:

```
\GlsXtrSetDefaultGlsOpts{noindex}
```

and then use, for example, `\gls [noindex=false] {sample}` when you actually want the location added to the `number list`. These defaults may be overridden by other settings (such as category attributes) in addition to any settings passed in the option argument of commands like `\glslink` and `\gls`.

Note that if you don't want *any* indexing, just omit `\makeglossaries` and `\printglossaries` (or analogous commands). If you want to adjust the default for `wrgloss`, it's better to do this by redefining `\glstrinitwrgloss` instead.

`\GlsXtrSetDefaultGlsOpts` doesn't affect `\glsadd`.

If you want to change the default value of `format`, you can instead use:

`\GlsXtrSetDefaultNumberFormat{<format>}`

This has the advantage of also working for `\glsadd`. For example, if you want all locations in the back matter to appear in italic (unless explicitly overridden):

```
\backmatter
\GlsXtrSetDefaultNumberFormat{hyperit}
```

Commands like `\gls` have star (\*) and plus (+) modifiers as a short cut for `hyper=false` and `hyper=true`. The `glossaries-extra` package provides a way to add a third modifier, if required, using

`\GlsXtrSetAltModifier{<char>}{<options>}`

where `<char>` is the character used as the modifier and `<options>` is the default set of options (which may be overridden). Note that `<char>` must be a single character (not a UTF-8 character, unless you are using `XYLaTeX` or `LuaXTeX`).

When choosing the character `<char>` take care of any changes in category code.

Example:

```
\GlsXtrSetAltModifier{!}{noindex}
```

This means that `\gls!{sample}` will be equivalent to `\gls[noindex]{sample}`. It's not possible to mix modifiers. For example, if you want to do

```
\gls[noindex,hyper=false]{sample}
```

you can use `\gls*[noindex]{sample}` or `\gls![hyper=false]{sample}` but you can't combine the \* and ! modifiers.

There is a new hook that's used each time indexing information is written to the external glossary files:

`\glstrdowrglossaryhook{<label>}`

where `<label>` is the entry's label. This does nothing by default but may be redefined. (See, for example, the accompanying sample file `sample-indexhook.tex`, which uses this hook to determine which entries haven't been indexed.)

There's also a new hook (from v1.26) that's used immediately before the options are set by the `\gls-like` and `\glstext-like` commands:

```
\glslinkpresetkeys
```

(The base package provides `\glslinkpostsetkeys` that's used immediately after the options are set.)

As from version 1.30 there are also similar hooks for `\glsadd`:

```
\glsaddpresetkeys
```

and

```
\glsaddpostsetkeys
```

For example, to default to using the equation counter in maths mode:

```
\renewcommand{\glslinkpresetkeys}{%  
  \ifmmode \setkeys{glslink}{counter=equation}\fi}  
\renewcommand{\glsaddpresetkeys}{%  
  \ifmmode \setkeys{glossadd}{counter=equation}\fi}
```

In this case, the counter can be overridden with an explicit use of `counter` in the optional argument of `\gls` or `\glsadd`. (As from version 1.37, a simpler method is to just use the `equations` package option.)

Alternatively, to enforce this (overriding the option argument):

```
\renewcommand{\glslinkpostsetkeys}{%  
  \ifmmode \setkeys{glslink}{counter=equation}\fi}  
\renewcommand{\glsaddpostsetkeys}{%  
  \ifmmode \setkeys{glossadd}{counter=equation}\fi}
```

As from version 1.14, there are two new keys for `\glsadd`: `thevalue` and `theHvalue`. These keys are designed for manually adding explicit locations rather than obtaining the value from the associated counter. As from version 1.19, these two keys are also available for commands like `\gls` and `\glslink`. The `thevalue` key is intended primarily for adding locations in supplementary material that can't be obtained from a counter.

The principle key `thevalue` is for the location value. The other key `theHvalue` can be used to extract a prefix value for the first argument of commands like `\glsnoidxdisplayloc`. Its value must be in the format `<prefix><location>`. In general, there's little need for this key as the prefix is typically associated with a counter that can be used to form `hypertargets`.

If you use `thevalue`, you must make sure that you use an indexing application that will accept the given value.

For example, `makeindex` will only accept locations in the form `[<num><sep>]*<num>` where `<num>` is an arabic number (0, 1, ...), roman numeral (i, ii, ... or I, II, ...) or a character from

a, ..., z or A, ..., Z, and [*num*]*sep*)\* indicates zero or more instances of a number followed by the recognised separator character (set with `\glsSetCompositor`). This means that `makeindex` won't accept, for example,

```
\glsadd[thevalue={Supplementary Material}]{sample}
```

This location value will be accepted by `bib2gls`, since it will allow any location and will only try forming ranges if the location matches any of its numerical patterns. In the case of `xindy`, you'll need to add a rule that can match the value. If you're using `hyperref`, you may need to use the `format` key to prevent a hyperlink if one can't naturally be formed from the prefix, counter and location value.

For example, suppose the file `suppl.tex` contains:

```
\documentclass{article}

\usepackage{glossaries-extra}

\newglossaryentry{sample}{name={sample},description={an example}}

\renewcommand{\thepage}{S.\arabic{page}}

\begin{document}
First page.
\newpage
\gls{sample}.
\end{document}
```

This has an entry on page S.2. Suppose another document wants to include this location in the glossary. Then this can be done by setting `thevalue` to S.2. For example:

```
\documentclass{article}

\usepackage{glossaries-extra}

\makeglossaries

\newglossaryentry{sample}{name={sample},description={an example}}

\begin{document}
Some \gls{sample} text.

\printglossaries
\glsadd[thevalue={S.2}]{sample}
\end{document}
```

This location value will be accepted by `makeindex` as it's in the form *num**sep**num*.

If you want hyperlinks, things are more complicated. First you need to set the `externallocation` attribute to the location of the PDF file. For example:

```
\glssetcategoryattribute{supplemental}{externallocation}{suppl.pdf}
```

```
\newglossaryentry{sample}{category=supplemental,  
name={sample},description={an example}}
```

Next you need to add `glsxtrsupphypernumber` as the format:

```
\glsadd[thevalue={S.2},format=glsxtrsupphypernumber]{sample}
```

Both documents will need to use the `hyperref` package. Remember that the counter used for the location also needs to match. If `\theH<counter>` is defined in the other document and doesn't match in the referencing document, then you need to use `\theHvalue` to set the appropriate value. See the accompanying sample files `sample-suppl-hyp.tex` and `sample-suppl-main-hyp.tex` for an example that uses `hyperref`.

The hyperlink for the supplementary location may or *may not* take you to the relevant place in the external PDF file *depending on your PDF viewer*. Some may not support external links, and some may take you to the first page or last visited page.

For example, if both `sample-suppl-hyp.pdf` and `sample-suppl-main-hyp.pdf` are in the same directory, then viewing `sample-suppl-main-hyp.pdf` in Evince will take you to the correct location in the linked document (when you click on the S.2 external link), but Okular will take you to the top of the first page of the linked document.

This method can only be used where there is one external source for the designated category (identified by the `externallocation` attribute). For multiple sources, you need to use `bib2gls` version 1.7+, which is the better method in general as it can automatically fetch the relevant locations from the `.aux` files of the designated external documents without the need to explicitly use `\glsadd`.

## 2.3 Cross-References (“see” and “see also”)

The value of the `see` key is now saved as a field. This isn't the case with glossaries, where the `see` value is simply used to directly write a line to the corresponding glossary file and is then discarded. This is why the `see` key can't be used before `\makeglossaries` (since the file hasn't been opened yet).

This modification allows `glossaries-extra` to provide

```
\glsxtraddallcrossrefs
```

which is used at the end of the document to automatically add any unused cross-references unless the package option `indexcrossrefs` was set to `false`.

Note that even though the `see` key will now work for entries defined in the document environment, it's still best to define entries in the preamble, and the `see` key still can't perform any indexing before the file has been opened by `\makeglossaries`. Note that `glossaries v4.24` introduced the `seenoindex` package option, which can be used to suppress the error when the `see` key is used before `\makeglossaries`, so `seenoindex=ignore` will allow the `see` value to be stored even though it may not be possible to index it at that point.

As from version 1.06, you can display the cross-referenced information for a given entry using

```
\glxtrusee{\label}
```

This internally uses

```
\glxtruseeformat{\tag}{\xr list}
```

where  $\langle tag \rangle$  and  $\langle xr list \rangle$  are obtained from the value of the entry's see field (if non-empty). By default, this just does `\glsseeformat[\tag]{\xr list}{}`, which is how the cross-reference is displayed in the **number list**. Note that `\glxtrusee` does nothing if the see field hasn't been set for the entry given by  $\langle label \rangle$ .

As with the base glossaries package, `\glsseeformat` is defined to do `\emph{\tag} \glseeelist{\xr list}`. The third argument is always ignored and is present for `makeindex`, which always requires a final argument to encapsulate the associated location. The command

```
\glseeelist{\xr list}
```

used to iterate over the list of cross-reference labels is also unchanged from the base glossaries package, with each item in the list formatted according to:

```
\glseeitem{\label}
```

This is defined by the glossaries package to:

```
\glshyperlink[\glseeitemformat{\label}]{\label}
```

So the actual formatting for each cross-referenced entry is performed by `\glseeitemformat`, which is redefined by `glossaries-extra`, as described in Section 2. This now displays the value of the text field for abbreviations and the value of the name field otherwise. There's no indication of the entry hierarchy, which could confuse the reader. Therefore, as from `glossaries-extra v1.37`, there are some new commands that include the hierarchical information. You may prefer to redefine `\glseeitemformat` to use one of this if you have sub-entries. For example:

```
\renewcommand*\glseeitemformat[1]{\glxtrhiername{#1}}
```

The glossaries package provides

```
\glseeitemformat{\label}
```

to format items in a cross-reference list (identified with the see key or `\glsee`). This was originally defined to use `\glsenryname{\label}` since it makes more sense for the cross-reference to match the way the term appears in the glossary. Unfortunately this caused a problem when the name field was sanitized, which used to be the default setting, so `glossaries v3.0` changed the default definition of this command to use `\glsenrytext` instead. Since the name and text field are quite often the same, this change usually doesn't have a noticeable effect. However, now that the name field is

no longer sanitized (following the redesign of glossaries v4.0) it makes more sense to restore this command to its original behaviour, but to take account of abbreviations glossaries-extra redefines this as:

```
\renewcommand*\glsseeitemformat}[1]{%
  \ifglshasshort{\glslabel}{\glsfmttext{#1}}{\glsfmtname{#1}}%
}
```

(Note that as from glossaries-extra version 1.42, this now uses `\glsfmttext` and `\glsfmtname` instead of just referencing the text and name fields. This helps to ensure that any formatting is correctly applied.)

If you want to restore the glossaries v3.0+ definition just do:

```
\renewcommand*\glsseeitemformat}[1]{\glsentrytext{#1}}
```

The glossaries-extra package provides `\glsxtrhiername` and its case-changing variants that may be used within the definition of `\glsseeitemformat` if required. These display the hierarchy for sub-entries rather than just the name, which may be more helpful in cross-references.

```
\glsxtrhiername{<label>}
```

performs a recursive action:

1. If the entry given by *<label>* has a parent, then `\glsxtrhiername{<parent label>}` is done followed by `\glsxtrhiernamesep` then:
2. If the entry given by *<label>* is an abbreviation (that is, it has the short field set) then the short form is displayed (using `\glsfmtshort`) otherwise the name is displayed (using `\glsfmtname`).

The first step above is skipped if the entry doesn't have a parent. Each level is separated by:

```
\glsxtrhiernamesep
```

which defaults to “▷”. This can be redefined as appropriate.

There are some case-changing variants:

```
\Glsxtrhiername{<label>}
```

The top-level has the first letter changed to upper case (either `\Glsfmtshort` or `\Glsfmtname`). There's no case-change for sub-entries.

```
\GlsXtrhiername{<label>}
```

All levels have the first letter changed to upper case (either `\Glsfmtshort` or `\Glsfmtname`).



```
\GLSxtrhiername{<label>}
```

The top-level is converted to upper case (either `\GLSfmtshort` or `\GLSfmtname`). There's no case-change for sub-entries.

```
\GLSXTRhiername{<label>}
```

All levels are converted to upper case (either `\GLSfmtshort` or `\GLSfmtname`).

Suppose you want to suppress the number list using `nonumberlist`. This will automatically prevent the cross-references from being displayed. The `seeautonumberlist` package option will automatically enable the number list for entries that have the see key set, but this will also show the rest of the number list.

Another approach in this situation is to use the post description hook with `\glxtrusesee` to append the cross-reference after the description. For example:

```
\renewcommand*{\glxtrpostdescgeneral}{%
  \ifglshasfield{see}{\glscurrententrylabel}
  {, \glxtrusesee{\glscurrententrylabel}}%
  }%
}
```

Now the cross-references can appear even though the number list has been suppressed.

As from v1.16, there's a separate `seealso` key. Unlike `see`, this doesn't have an optional part for the textual tag. The syntax `seealso={<xr-labels>}` works in much the same way as using `see=[\seealsoname]{<xr-labels>}` but the information is stored in a separate field. If you need a different tag, use the `see` key instead (or redefine `\seealsoname` or `\glxtruseseealsoformat`, described below).

You can display the formatted list of cross-references stored in the `seealso` key using:

```
\glxtruseseealso{<label>}
```

This works in much the same way as `\glxtrusesee` but it internally uses

```
\glxtruseseealsoformat{<xr list>}
```

For example:

```
\renewcommand*{\glxtrpostdescgeneral}{%
  \ifglshasfield{see}{\glscurrententrylabel}
  {, \glxtrusesee{\glscurrententrylabel}}%
  }%
  \ifglshasfield{seealso}{\glscurrententrylabel}
  { (\glxtruseseealso{\glscurrententrylabel})}%
  }%
}
```

The alias key only contains a single label not a list, but if you want to ensure consistent formatting with `\glxtrusesee` and `\glxtruseseealso` you can use (from v1.42):

```
\glxtrusealias{<label>}
```

The actual unformatted comma-separated list *<xr-list>* stored in the *seealso* field can be accessed with:

```
\glxtrseealsolabels{<label>}
```

This will just expand to the *<xr-labels>* provided in the value of the *seealso* key. There's no corresponding command to access the *see* field. If you really need to access it, you can use commands like `\glxtrfielduse`, but remember that it may start with [*<tag>*], so it can't be automatically treated as a simple comma-separated list.

As mentioned above, the base *glossaries* package provides `\glsseelist`, which requires a comma-separated list of labels as the argument. The argument isn't fully expanded, so it's not suitable to use, for example, `\glxtrseealsolabels{<label>}` as the argument. For convenience, *glossaries-extra* provides

```
\glxtrseeelist{<xr list>}
```

which fully expands its argument and passes it to `\glsseelist`.

As from v1.47, *glossaries-extra* redefines `\glsseelist` to make it more flexible. The base package provides `\glsseelistitem{<label>}` which is used to format each element in the list and `\glsseelistsep` for the separator between the final two items (`\glsseelistsep` is used between the other items). The modifications provide two additional commands:

```
\glsseefirstitem{<label>}
```

This defaults to `\glsseelistitem{<label>}` and is used to format the first label in the list.

```
\glsseelastoxfordsep
```

This defaults to `\glsseelistsep` and is used if the list consists of three or more labels.

The *seealso* key implements the automatic indexing using

```
\glxtrindexseealso{<label>}{<xr list>}
```

which just does

```
\glsee[\seealsoname]{<label>}{<xr list>}
```

unless the **xindy** option is used with *glossaries* v4.30+, in which case a distinct *seealso* cross-reference class is used instead.

The command that produces this “see also” text is

```
\seealsoname
```

If `\alsoname` (provided by language packages) is defined then `\seealsoname` will simply be

defined to `\alsiname` otherwise it will be defined to `see also`.

The language-sensitive `\alsiname` is used by general indexing packages, such as `makeidx`, so if you redefine `\alsiname` the change will apply to normal indexes as well as glossaries. If you only want to change the text produced by the `seealso` key without affecting general indexing (with `\index`) then redefine `\seealsiname` instead.

## 2.4 Entry Display Style Modifications

Recall from the `glossaries` package that commands such as `\gls` display text at that point in the document (optionally with a hyperlink to the relevant line in the glossary). This text is referred to as the “**link-text**” regardless of whether or not it actually has a hyperlink. The actual text and the way it’s displayed depends on the command used (such as `\gls`) and the entry format.

The default entry format (`\glsentryfmt`) used in the link-text by commands like `\gls`, `\glsxtrfull`, `\glsxtrshort` and `\glsxtrlong` (but not commands like `\glslink`, `\glsfirst` and `\glstext`) is changed by `glossaries-extra` to test for regular entries, which are determined as follows:

- If an entry is assigned to a category that has the **regular** attribute set (see Section 7), the entry is considered a regular entry, even if it has a value for the short key. In this case `\glsentryfmt` uses `\glsgenentryfmt` (provided by `glossaries`), which uses the first (or firstplural) value on **first use** and the text (or plural) value on subsequent use.
- An entry that doesn’t have a value for the short key is assumed to be a regular entry, even if the **regular** attribute isn’t set to “true” (since it can’t be an abbreviation without the short form). In this case `\glsentryfmt` uses `\glsgenentryfmt`.
- If an entry does has a value for the short key and hasn’t been marked as a regular entry through the **regular** attribute, it’s not considered a regular entry. In this case `\glsentryfmt` uses `\glsxtrgenabbrvfmt` (defined by `glossaries-extra`) which is governed by the abbreviation style (see Section 4.2).

This means that entries with a short form can be treated as regular entries rather than abbreviations if it’s more appropriate for the desired style.

As from version 1.04, `\glsentryfmt` now puts `\glsgenentry` in the argument of the new command

```
\glsxtrregularfont{<text>}
```

This just does its argument `<text>` by default. This means that if you want regular entries in a different font but don’t want that font to apply to abbreviations, then you can redefine `\glsxtrregularfont`. This is more precise than changing `\glstextformat` which is applied to all linking commands for all entries, unless overridden by the **textformat** attribute.

For example:

```
\renewcommand*{\glsxtrregularfont}[1]{\textsf{#1}}
```

You can access the label through `\glslabel`. For example, you can query the category:

```
\renewcommand*{\glsxtrregularfont}[1]{%
  \glsifcategory{\glslabel}{general}{\textsf{#1}}{#1}}
```

or query the category attribute, for example, provide a custom attribute called `font`:

```
\glssetcategoryattribute{general}{font}{sf}

\renewcommand*{\glsxtrregularfont}[1]{%
  \glsifattribute{\glslabel}{font}{sf}{\textsf{#1}}{#1}}
```

As from version 1.21, it's simpler to just do, for example:

```
\glssetcategoryattribute{general}{textformat}{textsf}
```

without redefining `\glsxtrregularfont`.

As from version 1.30, there is also a command for abbreviations that encapsulates `\glsxtrgenabbrvfmt`:

```
\glsxtrabbreviationfont{<text>}
```

This also just does its argument by default. Font changes made by abbreviation styles are within *<text>*.

The `\glspostlinkhook` provided by the `glossaries` package to insert information after the **link-text** produced by commands like `\gls` and `\gls{text}` is redefined to

```
\glsxtrpostlinkhook
```

This command will discard a following full stop (period) if the `discardperiod` attribute is set to “true” for the current entry’s category. It will also do

```
\glsxtrpostlink
```

if a full stop hasn’t be discarded and

```
\glsxtrpostlinkendsentence
```

if a full stop has been discarded.

It may be that you want to check some other setting (rather than a category attribute) to determine whether or not to discard a following full stop. In which case you can redefine:

```
\glsxtrifcustomdiscardperiod{<true>}{<false>}
```

You can access the field’s label using `\glslabel`. This command should do *<true>* if the post-link hook should check if a period follows and *<false>* otherwise. The default definition is simply:

```
\newcommand*{\glsxtrifcustomdiscardperiod}[2]{#2}
```

which means that no additional checks are performed. (Only the recognised category attributes will be checked.)

Avoid the use of `\gls`-like and `\gls`text-like commands within the post-link hook as they will cause interference. Consider using commands like `\glsentrytext`, `\glsaccessstext` or `\glsxtrp` (Section 2.8) instead.

By default `\glsxtrpostlink` just does `\glsxtrpostlink<category>` if it exists, where `<category>` is the category label for the current entry. (For example, for the general category, `\glsxtrpostlinkgeneral` if it has been defined.)

You can define the post-link hook command using `\newcommand`, for example:

```
\newcommand*\glsxtrpostlinkgeneral{%  
  \glsxtrpostlinkAddDescOnFirstUse  
}
```

or, as from v1.31, you can use

```
\glsdefpostlink{<category>}{<definition>}
```

This is simply a shortcut for:

```
\csdef{glsxtrpostlink<category>}{<definition>}
```

Note that it doesn't check if the command has already been defined.

The sentence-ending hook is slightly more complicated. If the command `\glsxtrpostlink<category>` is defined the hook will do that and then insert a full stop with the space factor adjusted to match the end of sentence. If `\glsxtrpostlink<category>` hasn't been defined, the space factor is adjusted to match the end of sentence. This means that if you have, for example, an entry that ends with a full stop, a redundant following full stop will be discarded and the space factor adjusted (in case the entry is in uppercase) unless the entry is followed by additional material, in which case the following full stop is no longer redundant and needs to be reinserted.

There are some convenient commands you might want to use when customizing the post-link-text category hooks:

```
\glsxtrpostlinkAddDescOnFirstUse
```

This will add the description in parentheses on **first use**.

For example, suppose you want to append the description in parentheses on first use for entries in the symbol category:

```
\newcommand*\glsxtrpostlinksymbol{%  
  \glsxtrpostlinkAddDescOnFirstUse  
}
```

```
\glxtrpostlinkAddSymbolOnFirstUse
```

This will append the symbol (if defined) in parentheses on first use. (Does nothing if the symbol hasn't been set.)

```
\glxtrpostlinkAddSymbolDescOnFirstUse
```

(New to v1.31.) On **first use**, this will append `\space(<symbol>, <description>)` if the symbol is defined otherwise it just appends `\space(<description>)`.

If you want to provide your own custom format be aware that you can't use `\ifglused` within the post-**link-text** hook as by this point the **first use flag** will have been unset. Instead you can use

```
\glxtrifwasfirstuse{<true>}{<false>}
```

This will do *<true>* if the last used entry was the first use for that entry, otherwise it will do *<false>*. (Requires at least glossaries v4.19 to work properly.) This command is locally set by commands like `\gls`, so don't rely on it outside of the post-link-text hook.

Note that commands like `\glsfirst` and `\glxtrfull` fake first use for the benefit of the post-link-text hooks by setting `\glxtrifwasfirstuse` to `\@firstoftwo`. (Although, depending on the styles in use, they may not exactly match the text produced by `\gls`-like commands on first use.) However, the **short-postfootnote** style alters `\glxtrfull` so that it fakes non-first use otherwise the inline full format would include the footnote, which is inappropriate.

For example, if you want to place the description in a footnote after the link-text on first use for the general category:

```
\newcommand*{\glxtrpostlinkgeneral}{%
  \glxtrifwasfirstuse{\footnote{\glsentrydesc{\glslabel}}}{}%
}
```

The **short-postfootnote** abbreviation style uses the post-link-text hook to place the footnote after trailing punctuation characters.

## 2.5 Entry Counting Modifications

If you are using `bib2gls` you may find it more convenient to use the record count commands described in Section 10 instead.

The `\glsenableentrycount` command is modified to allow for the **entrycount** attribute. This means that you not only need to enable entry counting with `\glsenableentrycount`, but you also need to set the appropriate attribute (see Section 7).

For example, instead of just doing:

```
\glsenableentrycount
```

you now need to do:

```
\glsenableentrycount
\glssetcategoryattribute{abbreviation}{entrycount}{1}
```

This will enable the entry counting for entries in the abbreviation category, but any entries assigned to other categories will be unchanged.

Further information about entry counting, including the new per-unit feature, is described in Section 8.1.

## 2.6 First Use Flag

The glossaries package provides

```
\ifglsused{<label>}{<true>}{<false>}
```

to determine whether or not an entry has been used. This requires the entry to have been defined. If the entry is undefined, then the underlying boolean variable doesn't exist and so is neither true nor false. This command will produce an error with the default `undefaction=error` mode and a warning with `undefaction=warn` and, where appropriate, displays ?? in the document text to denote an undefined reference. With both modes, neither `<true>` nor `<false>` will be performed if `<label>` doesn't exist.

The `record` option automatically implements `undefaction=warn` since no entries will be defined until they have been selected by `bib2gls`. In this case, you may prefer to use:

```
\GlsXtrIfUnusedOrUndefined{<label>}{<true>}{<false>}
```

(new to v1.34) which does `<true>` if the entry given by `<label>` is undefined or if the entry is marked as unused. Remember that neither `\ifglsused` nor `\GlsXtrIfUnusedOrUndefined` should be used in the post-link hook as the `first use flag` will have already been unset before the hook is performed. (Instead, `\glsxtrifwasfirstuse` should be used, see Section 2.4.)

There are two new commands provided with version 1.31+:

```
\glslocalreseteach{<list>}
```

and

```
\glslocalunseteach{<list>}
```

These behave like `\glslocalreset` and `\glslocalunset` but the argument is a comma-separated list of labels.

The internal command used by `\glsunset` is modified first to allow for the changing in entry counting, described above, but also to allow for buffering pending unsets when commands like `\gls` are used in a context where changing a boolean variable can cause things to go wrong. One example of this is using `\gls` in one of the commands provided with the package. For example:

```
\ul{Some text about \gls{html}.}
```

This causes the confusing error:

```
Glossary entry `{html}' has not been defined.
```

The simplest workaround is to put `\gls{html}` inside the argument of `\mbox`. For example:

```
\ul{Some text about \mbox{\gls{html}}.}
```

This can work provided it's not the first use of this entry. If it is, then unsetting the first use flag causes a problem and results in the error:

```
! Package soul Error: Reconstruction failed.
```

The glossaries-extra package provides a way of temporarily switching off `\glsunset` so that it just makes a note of the entry's label but doesn't actually perform the change:

```
\GlsXtrStartUnsetBuffering
```

The unstarred version doesn't check for duplicates, so the internal list may end up with multiple occurrences of the same label. The starred version only adds a label to the internal list if it's not already in it. Note that this buffering only applies to the global `\glsunset` and does not affect the local `\glslocalunset`.

Later you can restore `\glsunset` and unset all buffered labels using:

```
\GlsXtrStopUnsetBuffering
```

The starred form `\GlsXtrStopUnsetBuffering*` uses `\glslocalunset` instead. For example:

```
\documentclass{article}

\usepackage[T1]{fontenc}
\usepackage{soul}
\usepackage{glossaries-extra}

\newabbreviation{html}{HTML}{hypertext markup language}

\begin{document}
\GlsXtrStartUnsetBuffering
\ul{Some text about \mbox{\gls{html}}.}
\GlsXtrStopUnsetBuffering

Next use: \gls{html}.
\end{document}
```

Before you stop the unset buffering, you can iterate over the current buffer using

```
\GlsXtrForUnsetBufferedList{<cs>}
```

where `<cs>` is a control sequence that takes a single argument (which is the entry label). This is best used with the starred version `\GlsXtrStartUnsetBuffering*` to avoid duplicates.



You can discard the buffer and restore `\glsunset` to its normal behaviour with (new to v1.42):

```
\GlsXtrDiscardUnsetBuffering
```

Note that since the change in the first use flag now doesn't occur until `\GlsXtrStopUnsetBuffering`, multiple references of the same term within the buffering zone will always be treated as first use (if the term wasn't used before the buffering started).

There can still be a problem here as content within `\mbox` can't break across a line so you may end up with an overfull line or excessive white space within the paragraph.

An alternative is to use `\protect`:

```
\GlsXtrStartUnsetBuffering
\ul{Some text about \protect\gls{html}.}
\GlsXtrStopUnsetBuffering
```

but the formatting (underlining in this example) won't be applied. Another possibility is:

```
\usepackage[T1]{fontenc}
\usepackage{soul}
\usepackage{glossaries-extra}

\newabbreviation{html}{HTML}{hypertext markup language}

\newrobustcmd{\gul}[1]{%
  {%
    \def\glsxtrabbreviationfont##1{\GlsXtrExpandedFmt{\ul}{##1}}%
    \def\glsxtrregularfont##1{\GlsXtrExpandedFmt{\ul}{##1}}%
    #1%
  }%
}

\begin{document}
\ul{Some text about }\gls[textformat=gul]{html}.

Next use: \gls{html}.
\end{document}
```

This moves `\gls` outside of `\ul` and uses `textformat` to locally change the formatting command used by `\gls` (which is normally given by `\gls{textformat}` or the `textformat` attribute) to a custom command `\gul`, which locally changes the regular font and the default abbreviation font to use `\ul`. It then uses

```
\GlsXtrExpandedFmt{<cs>}{<text>}
```

which (protected) fully expands `<text>` before applying `<cs>`, which must be a control sequence that takes a single argument. This allows `\ul` to move much further inside and increases its chances of

working. It can still break if *<text>* expands to something that `\u.l` can't deal with. For example, if an abbreviation style is used that contains complex formatting or if the field value contains problematic content.

## 2.7 Plurals

Some languages, such as English, have a general rule that plurals are formed from the singular with a suffix appended. This isn't an absolute rule. There are plenty of exceptions (for example, geese, children, churches, elves, fairies, sheep). The glossaries package allows the plural key to be optional when defining entries. In some cases a plural may not make any sense (for example, the term is a symbol) and in some cases the plural may be identical to the singular.

To make life easier for languages where the majority of plurals can simply be formed by appending a suffix to the singular, the glossaries package lets the plural field default to the value of the text field with `\glspluralsuffix` appended. This command is defined to be just the letter "s". This means that the majority of terms don't need to have the plural supplied as well, and you only need to use it for the exceptions.

For languages that don't have this general rule, the plural field will always need to be supplied, where needed.

There are other plural fields, such as `firstplural`, `longplural` and `shortplural`. Again, if you are using a language that doesn't have a simple suffix rule, you'll have to supply the plural forms if you need them (and if a plural makes sense in the context).

If these fields are omitted, the glossaries package follows these rules:

- If `firstplural` is missing, then `\glspluralsuffix` is appended to the first field, if that field has been supplied. If the first field hasn't been supplied but the plural field has been supplied, then the `firstplural` field defaults to the plural field. If the plural field hasn't been supplied, then both the plural and `firstplural` fields default to the text field (or name, if no text field) with `\glspluralsuffix` appended.
- If the `longplural` field is missing, then `\glspluralsuffix` is appended to the long field, if the long field has been supplied.
- If the `shortplural` field is missing then, *with the base glossaries acronym mechanism*, `\acrpluralsuffix` is appended to the short field.

This *last case is changed* with `glossaries-extra`. With this extension package, the `shortplural` field defaults to the short field with `\abbrvpluralsuffix` appended unless overridden by category attributes. This suffix command is set by the abbreviation styles. This means that every time an abbreviation style is implemented, `\abbrvpluralsuffix` is redefined. In most cases its redefined to use

```
\glsxtrabbrvpluralsuffix
```

which defaults to just `\glspluralsuffix`. Some of the abbreviation styles have their own command for the plural suffix, such as `\glsxtrscsuffix`, so if you want to completely strip all the

plural suffixes used for abbreviations then you need to redefine `\glstrabbrvpluralsuffix` *not* `\abbrvpluralsuffix`, which changes with the style. Redefining `\acrpluralsuffix` will have no affect, since it's not used by the new abbreviation mechanism.

If you require a mixture (for example, in a multilingual document), there are two attributes that affect the short plural suffix formation. The first is `aposplural` which uses the suffix

```
'\abbrvpluralsuffix
```

That is, an apostrophe followed by `\abbrvpluralsuffix` is appended. The second attribute is `noshortplural` which suppresses the suffix and simply sets `shortplural` to the same as `short`.

## 2.8 Nested Links

Complications arise when you use `\gls` in the value of the name field (or text or first fields, if set). This tends to occur with abbreviations that extend other abbreviations. For example, SHTML is an abbreviation for SSI enabled HTML, where SSI is an abbreviation for Server Side Includes and HTML is an abbreviation for Hypertext Markup Language.

Things can go wrong if we try the following with the glossaries package:

```
\newacronym{ssi}{SSI}{Server Side Includes}
\newacronym{html}{HTML}{Hypertext Markup Language}
\newacronym{shtml}{S\gls{html}}{\gls{ssi} enabled \gls{html}}
```

The main problems are:

1. The first letter upper casing commands, such as `\Gls`, won't work for the `shtml` entry on **first use** if the long form is displayed before the short form (which is the default abbreviation style). This will attempt to do

```
\gls{\uppercase ssi} enabled \gls{html}
```

which just doesn't work. Grouping the `\gls{ssi}` doesn't work either as this will effectively try to do

```
\uppercase{\gls{ssi}} enabled \gls{html}
```

This will upper case the label `ssi` so the entry won't be recognised. This problem will also occur if you use the all capitals version, such as `\GLS`.

2. The long and abbreviated forms accessed through `\glsentrylong` and `\glsentryshort` are no longer expandable and so can't be used in contexts that require this, such as PDF bookmarks.
3. The nested commands may end up in the sort key, which will confuse the indexing.
4. The `shtml` entry produces inconsistent results depending on whether the `ssi` or `html` entries have been used. Suppose both `ssi` and `html` are used before `shtml`. For example:

```
This section discusses \gls{ssi}, \gls{html} and \gls{shtml}.
```

This produces:

This section discusses server side includes (SSI), hypertext markup language (HTML) and SSI enabled HTML (SHTML).

So the **first use** of the `shtml` entry produces “SSI enabled HTML (SHTML)”.

Now let’s suppose the `html` entry is used before the `shtml` but the `ssi` entry is used after the `shtml` entry, for example:

The sample files are either `\gls{html}` or `\gls{shtml}`, but let's first discuss `\gls{ssi}`.

This produces:

The sample files are either hypertext markup language (HTML) or server side includes (SSI) enabled HTML (SHTML), but let’s first discuss SSI.

So the first use of the `shtml` entry now produces “server side includes (SSI) enabled HTML (SHTML)”, which looks a bit strange.

Now let’s suppose the `shtml` entry is used before (or without) the other two entries:

This article is an introduction to `\gls{shtml}`.

This produces:

This article is an introduction to server side includes (SSI) enabled hypertext markup language (HTML) (SHTML).

So the first use of the `shtml` entry now produces “server side includes (SSI) enabled hypertext markup language (HTML) (SHTML)”, which is even more strange.

This is all aggravated by setting the style using the `glossaries` package’s `\setacronymstyle`. For example:

```
\setacronymstyle{long-short}
```

as this references the label through the use of `\glslabel` when displaying the long and short forms, but this value changes with each use of `\gls`, so instead of displaying “(SHTML)” at the end of the first use, it now displays “(HTML)”, since `\glslabel` has been changed to `html` by `\gls{html}`.

Another oddity occurs if you reset the `html` entry between uses of the `shtml` entry. For example:

```
\gls{shtml} ... \glsreset{html}\gls{shtml}
```

The next use of `shtml` produces “Shypertext markup language (HTML)”, which is downright weird.

Even without this, the short form has nested formatting commands, which amount to `\acronymfont{S\acronymfont{HTML}}`. This may not be a problem for some styles, but if you use one of the “sm” styles (that use `\textsmaller`), this will produce an odd result.

5. Each time the `shtml` entry is used, the `html` entry will also be indexed and marked as used, and on first use this will happen to both the `ssi` and `html` entries. This kind of duplication in the location list isn't usually particularly helpful to the reader.
6. If `hyperref` is in use, you'll get nested hyperlinks and there's no consistent way of dealing with this across the available PDF viewers. If on the **first use** case, the user clicks on the "HTML" part of the "SSI enabled HTML (SHTML)" link, they may be directed to the HTML entry in the glossary or they may be directed to the SHTML entry in the glossary.

For these reasons it's better to use the simple expandable commands like `\glsentrytext` or `\glsentryshort` in the definition of other entries (although that doesn't fix the first problem).

Alternatively use something like:

```
\newacronym
[description={\acrshort{ssi} enabled \acrshort{html}}]
{shtml}{SHTML}{SSI enabled HTML}
```

with glossaries or:

```
\newabbreviation
[description={\glsxtrshort{ssi} enabled \glsxtrshort{html}}]
{shtml}{SHTML}{SSI enabled HTML}
```

with `glossaries-extra`. This fixes all the above listed problems (as long as you don't use `\glsdesc`). Note that replacing `\gls` with `\acrshort` in the original example may fix the first use issue, but it doesn't fix any of the other problems listed above.

If it's simply that you want to use the abbreviation font, you can use `\glsabbrvfont`:

```
\setabbreviationstyle{long-short-sc}

\newabbreviation{ssi}{ssi}{server-side includes}
\newabbreviation{html}{html}{hypertext markup language}
\newabbreviation{shtml}{shtml}{\glsabbrvfont{ssi} enabled
\glsabbrvfont{html}}
```

This will pick up the font style setting of the outer entry (`shtml`, in the above case). This isn't a problem in the above example as all the abbreviations use the same style.

If the term can simply be treated as a series of previously defined entries, then consider using multi-entries (or compound sets). See Section 6 for further details.

However, if you're really determined to use `\gls` in a field that may be included within some **link-text**, `glossaries-extra` patches internals used by the linking commands so that if `\gls` (or plural or case changing variants) occurs in the link-text it will behave as though you used `\gls{text}[hyper=false,noindex]` instead. Grouping is also added so that, for example, when `\gls{shtml}` is used for the first time the long form

```
\gls{ssi} enabled \gls{html}
```

is treated as

```
{\gls{text}[hyper=false,noindex]{ssi}} enabled
{\gls{text}[hyper=false,noindex]{html}}
```

This overcomes problems 4, 5 and 6 listed above, but still doesn't fix problems 1 and 2. Problem 3 usually won't be an issue as most abbreviation styles set the sort key to the short form, so using these commands in the long form but not the short form will only affect entries with a style that sorts according to the long form (such as `long-noshort-desc`).

Additionally, any instance of the long form commands, such as `\glxtrlong` or `\acrlong` will be temporarily redefined to just use

```
{\glentrylong{<label>}{<insert>}}
```

(or case-changing versions). Similarly the short form commands, such as `\glxtrshort` or `\acrshort` will use `\glentryshort` in the argument of either `\glabbrvfont` (for `\glxtrshort`) or `\acronymfont` (for `\acrshort`). So if the `shtml` entry had instead been defined as:

```
\newacronym{shtml}{SHTML}{\acrshort{ssi} enabled \acrshort{html}}
```

then (using the `long-short` style) the **first use** will be like

```
{\acronymfont{\glentryshort{ssi}}} enabled  
{\acronymfont{\glentryshort{html}}} (SHTML)
```

whereas if the entry is defined as:

```
\newabbreviation{shtml}{SHTML}{\glxtrshort{ssi} enabled  
\glxtrshort{html}}
```

then the first use will be like:

```
{\glabbrvfont{\glentryshort{ssi}}} enabled  
{\glabbrvfont{\glentryshort{html}}} (SHTML)
```

Note that the first optional argument of `\acrshort` or `\glxtrshort` is ignored in this context. (The final optional argument will be inserted, if present.) The abbreviation style that governs `\glabbrvfont` will be set for `\glxtrshort`. Note that `\acrshort` doesn't set the abbreviation style.

Alternatively you can use:

```
\glxtrp{<field>}{<label>}
```

where `<field>` is the field label and corresponds to a command in the form `\gl<field>` (e.g. `\glstext`) or in the form `\glxtr<field>` (e.g. `\glxtrshort`).

There's a shortcut command for the most common fields:

```
\glsp{s}{<label>}
```

which is equivalent to `\glxtrp{short}{<label>}`, and

```
\glsp{t}{<label>}
```

which is equivalent to `\glxtrp{text}{<label>}`.

The `\glstrp` command behaves much like the `\glfmt<field>` commands described in Section 5 but the post-link hook is also suppressed and extra grouping is added. It automatically sets `hyper` to `false` and `noindex` to `true`. If you want to change this, you can use

```
\glstrsetpopts{<options>}
```

For example:

```
\glstrsetpopts{hyper=false}
```

will just switch off the hyperlinks but not the indexing. Be careful using this command or you can end up back to the original problem of nested links.

The hyper link is re-enabled within glossaries. This is done through the command:

```
\glossxtrsetpopts
```

which by default just does

```
\glstrsetpopts{noindex}
```

You can redefine this if you want to adjust the setting when `\glstrp` is used in the glossary. For example:

```
\renewcommand{\glossxtrsetpopts}{\glstrsetpopts{noindex=false}}
```

For example,

```
\glstrp{short}{ssi}
```

is equivalent to

```
{\let\glspostlinkhook\relax
 \glstrshort[hyper=false,noindex]{ssi} []%
}
```

in the main body of the document or

```
{\let\glspostlinkhook\relax
 \glstrshort[noindex]{ssi} []%
}
```

inside the glossary. (Note the post-link hook is locally disabled.)

If `\glstrp{short}{ssi}` occurs in a sectioning mark, it's equivalent to

```
{\glstrheadshort{ssi}}
```

(which recognises the `headuc` attribute.)

If `hyperref` has been loaded, then the bookmark will use `\glentry<field>` (`\glentryshort{ssi}` in the above example).

There are similar commands

```
\Glsxtrp{<field>}{<label>}
```

for first letter upper case and

```
\GLSxtrp{<field>}{<label>}
```

for all upper case.

If you use any of the case-changing commands, such as `\Gls` or `\Glstext`, (either all caps or first letter upper casing) don't use any of the linking commands, such as `\gls` or `\glstext`, in the definition of entries for any of the fields that may be used by those case-changing commands.

You can, with care, protect against issue 1 by inserting an empty group at the start if the long form starts with a command that breaks the first letter uppercasing commands like `\Gls`, but you still won't be able to use the all caps commands, such as `\GLS`.

If you *really need* nested commands, the safest method is

```
\newabbreviation{shtml}{shtml}{} \glsxtrp{short}{ssi} enabled  
\glsxtrp{short}{html}
```

but be aware that it may have some unexpected results occasionally.

Example document:

```
\documentclass{report}  
  
\usepackage[utf8]{inputenc}  
\usepackage[T1]{fontenc}  
\usepackage{slantsc}  
\usepackage[colorlinks]{hyperref}  
\usepackage[nopostdot=false]{glossaries-extra}  
  
\makeglossaries  
  
\setabbreviationstyle{long-short-sc}  
  
\newabbreviation{ssi}{ssi}{server-side includes}  
\newabbreviation{html}{html}{hypertext markup language}  
\newabbreviation{shtml}{shtml}{} \glsps{ssi} enabled {} \glsps{html}  
  
\pagestyle{headings}  
  
\glssetcategoryattribute{abbreviation}{headuc}{true}  
\glssetcategoryattribute{abbreviation}{glossdesc}{title}  
  
\begin{document}  
  
\tableofcontents
```



```
\chapter{\glsfmtfull{shtml}}
```

First use: `\gls{shtml}`, `\gls{ssi}` and `\gls{html}`.

Next use: `\gls{shtml}`, `\gls{ssi}` and `\gls{html}`.

```
\newpage
```

Next page.

```
\printglossaries
```

```
\end{document}
```

## 2.9 Acronym Style Modifications

The `glossaries-extra` package provides a new way of dealing with abbreviations and redefines `\newacronym` to use `\newabbreviation` (see Section 4). The simplest way to update a document that uses `\newacronym` from `glossaries` to `glossaries-extra` is do just add

```
\setabbreviationstyle[acronym]{long-short}
```

before you define any entries. If you have used commands like `\acrshort`, `\acrlong` and `\acrfull`, you need to substitute them with `\glsextrshort`, `\glsextrlong` and `\glsextrfull`. (This includes plural and case-changing forms.) Your text editor's search and replace function should help with this. If you have used the `shortcuts` package option then use `shortcuts=ac` in order to continue using the shortcut commands like `\ac`. With this setting, `\acs` will use `\glsextrshort` instead of `\acrshort` etc.

For example, the following document using just `glossaries`

```
\documentclass{article}
\usepackage[acronym,nopostdot,toc]{glossaries}
\makeglossaries
\setacronymstyle{long-short}
\newacronym{html}{HTML}{hypertext markup language}
\begin{document}
\gls{html}
\printglossaries
\end{document}
```

can be easily adapted to use `glossaries-extra`:

```
\documentclass{article}
\usepackage[acronym]{glossaries-extra}
\makeglossaries
\setabbreviationstyle[acronym]{long-short}
\newacronym{html}{HTML}{hypertext markup language}
\begin{document}
\gls{html}
\printglossaries
\end{document}
```

Table 2.1 lists the nearest equivalent glossaries-extra abbreviation styles for the predefined acronym styles provided by glossaries, but note that the new styles use different formatting commands. See Section 4.4 for further details.

Table 2.1: Old Acronym Styles `\setacronymstyle{⟨old-style-name⟩}` Verses New Abbreviation Styles `\setabbreviationstyle[⟨category⟩]{⟨new-style-name⟩}`

Old Style Name	New Style Name
long-sc-short	<code>long-short-sc</code>
long-sm-short	<code>long-short-sm</code>
long-sp-short	<code>long-short</code>
	with <code>\renewcommand{\glstrfullsep}[1]{\glscspace{#1}}</code>
short-long	<code>short-long</code>
sc-short-long	<code>short-sc-long</code>
sm-short-long	<code>short-sm-long</code>
long-short-desc	<code>long-short-desc</code>
long-sc-short-desc	<code>long-short-sc-desc</code>
long-sm-short-desc	<code>long-short-sm-desc</code>
long-sp-short-desc	<code>long-short-desc</code>
	with <code>\renewcommand{\glstrfullsep}[1]{\glscspace{#1}}</code>
short-long-desc	<code>short-long-desc</code>
sc-short-long-desc	<code>short-sc-long-desc</code>
sm-short-long-desc	<code>short-sm-long-desc</code>
dua	<code>long-noshort</code>
dua-desc	<code>long-noshort-desc</code>
footnote	<code>short-footnote</code>
footnote-sc	<code>short-sc-footnote</code>
footnote-sm	<code>short-sm-footnote</code>
footnote-desc	<code>short-footnote-desc</code>
footnote-sc-desc	<code>short-sc-footnote-desc</code>
footnote-sm-desc	<code>short-sm-footnote-desc</code>

The reason for introducing the new style of abbreviation commands provided by glossaries-extra is because the original acronym commands provided by glossaries are too restrictive to work with the internal modifications made by glossaries-extra. However, if you really want to restore the generic acronym function provided by glossaries you can use

`\RestoreAcronyms`

(before any use of `\newacronym`).

`\RestoreAcronyms` should not be used in combination with the newer glossaries-extra abbreviations. Don't combine old and new style entries with the same type. The original glossaries acronym mechanism doesn't work well with the newer glossaries-extra commands.

If you use `\RestoreAcronyms`, don't use any of the commands provided by `glossaries-extra` intended for abbreviations (such as `\glstrshort` or `\glstshort`) with entries defined via `\newacronym` as it will cause unexpected results.

In general, there's rarely any need for `\RestoreAcronyms`. If you have a document that uses `\newacronymstyle`, then it's best to either stick with just `glossaries` for that document or define an equivalent abbreviation style with `\newabbreviationstyle`. (See Section 4.5 for further details.)

```
\glsacspace{<label>}
```

The space command `\glsacspace` used by the long-sp-short acronym style provided by `glossaries` is modified so that it uses

```
\glsacspacemax
```

instead of the hard-coded 3em. This is a command not a length and so can be changed using `\renewcommand`.

Any of the new abbreviation styles that use `\glstrfullsep` (such as `long-short`) can easily be changed to use `\glsacspace` with

```
\renewcommand*{\glstrfullsep}[1]{\glsacspace{#1}}
```

The **first use** acronym font command

```
\firstacronymfont{<text>}
```

is redefined to use the first use abbreviation font command `\glsfirstabbrvfont`. This will be reset if you use `\RestoreAcronyms`.

The subsequent use acronym font command

```
\acronymfont{<text>}
```

is redefined to use the subsequent use abbreviation font command `\glsabbrvfont`. This will be reset if you use `\RestoreAcronyms`.

## 2.10 Glossaries

The `\newignoredglossary{<type>}` command now (as from v1.11) has a starred version that doesn't automatically switch off the hyperlinks. This starred version may be used with the `targeturl` attribute to create a link to an external URL. (See Section 7 for further details.) As from v1.12 both the starred and unstarred version check that the glossary doesn't already exist. (The `glossaries` package omits this check.)

You can now provide an ignored glossary with:

```
\provideignoredglossary{<type>}
```

which will only define the glossary if it doesn't already exist. This also has a starred version that doesn't automatically switch off hyperlinks.

The individual glossary displaying commands `\printglossary`, `\printnoidxglossary` and `\printunsrtglossary` have extra keys:

- `target`. This is a boolean key which can be used to switch off the automatic `hypertarget` for each entry. Unlike `\gl:disablehyper` this doesn't switch off hyperlinks, so any cross-references within the glossary won't be affected. This is a way of avoiding duplicate target warnings if a glossary needs to be displayed multiple times.
- `targetnameprefix={<prefix>}`. Another way of avoiding duplicate target names is to set a prefix used for the names. Unlike changing `\glo:linkprefix` this doesn't affect any hyperlinks (such as those created with `\gls`).

This doesn't include the navigation hyper group targets in styles such as `listhypergroup`. The link name for these is given by `\glsnavhyperlinkname`.

- `prefix={<prefix>}`. If you do actually want to locally change `\glo:linkprefix`, you can use the `prefix` key instead. You need to use the matching prefix key in commands like `\gls`.
- `label={<label>}`. Labels the glossary with `\label{<label>}` and also defines `\@currentlabelname` to the glossary's TOC title (to provide text for `\nameref`). You can also set the label before the glossary using:

```
\glsxtrsetglossarylabel{<label>}
```

but take care of duplicate labels if it's not scoped.

- `groups`. This is a boolean key (new to v1.44) designed for use with `\printunsrtglossary` (and other `\printunsrt...` variations). It has no effect with `\printglossary` and `\printnoidxglossary`.

If true (default), group formation (group header and group skip) will be attempted if the `group` key has been defined and set. Note that some styles ignore the header and group skip commands so there may not be a noticeable difference in those cases. If this key is set to false, no group formation will occur so there won't be any group markup to separate letter groups so there will be no visual separation regardless of style or the group skip setting.

- `leveloffset`. This key (new to v1.44) is designed for use with `\printunsrtglossary` (and other `\printunsrt...` variations). It has no effect with `\printglossary` and `\printnoidxglossary`.

The value may either be a simple integer  $\langle n \rangle$  to indicate assignment or in the form  $++\langle n \rangle$  to indicate an increment. This will locally assign or increment the level offset. The default value is 0. This will cause entries to be displayed as though their hierarchical level is  $N$  more than it would normally be (where  $N$  is the level offset). For example, a top-level entry (that is, an entry without a parent) would normally have a hierarchical level of 0. With a level offset of 1, it would be treated by the glossary style as though it was actually a level 1 entry. (Remember that some styles don't support hierarchical glossaries.)

Note that the group formation (if supported) will still occur between entries that don't have a parent, regardless of the level offset. This can cause odd results but can be switched off with groups. See [Gallery: Inner or Nested Glossaries](#) for an example.

## 2.11 Glossary Style Modifications

The `glossaries-extra-stylemods` package (more conveniently loaded through the `glossaries-extra-stylemods` option) modifies some of the predefined styles that are provided with the `glossaries` package. These modifications are described in more detail in Section 2.11.3.

The `glossaries` package tries to determine the group title from its label by first checking if `\langle label \rangle groupname` exists. If it doesn't exist, then the title is assumed to be the same as the label. For example, when typesetting the “A” letter group, `glossaries` first checks if `\Agroupname` exists. This could potentially cause conflict with another package that may have some other meaning for `\Agroupname`, so `glossaries-extra` first checks for the existence of the internal command `\glxtr@grouptitle@⟨label⟩` which shouldn't clash with another package. You can set the group title using

```
\glxtrsetgrouptitle{⟨label⟩}{⟨title⟩}
```

For example:

```
\glxtrsetgrouptitle{A}{A (a)}
```

This uses a global assignment. If you need to scope the change you can use

```
\glxtrlocalsetgrouptitle{⟨label⟩}{⟨title⟩}
```

### 2.11.1 Style Hooks

The commands `\glossentryname` and `\glossentrydesc` are modified to take into account the `glossname`, `glossnamefont`, `glossdesc` and `glossdescfont` attributes (see Section 7). This means you can make simple font or case-changing modifications to the name and description without defining a new glossary style.

(New to version 1.42.) The command `\glossentrysymbol` is modified to take into account the `glossymbolfont` attribute. Note that, unlike the above, there's no corresponding attribute to

change the case as it's usually not appropriate to change the case of a symbol (and for some symbols, such as pictographs, there's no concept of case). If `\texorpdfstring` has been defined `\glossentrysymbol` will be defined to do:

```
\texorpdfstring{<TEX code>}{<PDF>}
```

The `<TEX code>` part is robust and deals with the actual typesetting of the symbol. The `<PDF>` part is simply:

```
\glsentrypdfsymbol{<label>}
```

which is defined to just do `\glsentrysymbol{<label>}`. The chances are that the code in the symbol key won't be valid in the PDF bookmarks, so you can redefine `\glsentrypdfsymbol` to use a more appropriate field. (If you do redefine this command, remember that it needs to fully expand.)

For example, if you are using `glossaries-accsupp`, you could use the `symbolaccess` field:

```
\renewcommand{\glsentrypdfsymbol}[1]{\glsentrysymbolaccess{#1}}
```

Alternatively, if you are using `bib2gls` you can use the `TEX` parser library to interpret a copy of the symbol field and use that. For example, with the resource options:

```
replicate-fields={symbol=user1},
interpret-fields={user1}
```

This stores the interpreted value of the symbol in the `user1` field, so you can then do:

```
\renewcommand{\glsentrypdfsymbol}[1]{\glsentryuseri{#1}}
```

(You may need `XYLATEX` or `LuaLATEX` with this method.) This allows `\glossentrysymbol` to be used in a section heading with standalone definitions.

If you want to adapt a style to use another field instead of `name`, you can use

```
\glossentrynameother{<label>}{<field>}
```

This behaves just like `\glossentryname` (that is, it obeys the `glossname` attribute, uses either the `glossnamefont` attribute or `\glsnamefont` to format the text, and uses the post-name hook) but it uses the given `<field>` instead of `name`. The `<field>` argument must be the internal field name (for example `desc` rather than `description`). See the key to field mappings table in the `glossaries` user manual.

There is a hook after `\glossentryname` and `\Glossentryname`:

```
\glsxtrpostnamehook{<label>}
```

By default this checks the `indexname` attribute. If the attribute exists for the category to which the label belongs, then the name is automatically indexed using

```
\glxtrdoautoindexname{<label>}{indexname}
```

See Section 9 for further details.

As from version 1.04, the post-name hook `\glxtrpostnamehook` will also use `\glxtrpostname<category>` if it exists. You can use `\glscurrententrylabel` to obtain the entry label with the definition of this command. For example, suppose you are using a glossary style the doesn't display the symbol, you can insert the symbol after the name for a particular category, say, the "symbol" category:

```
\newcommand*{\glxtrpostnamesymbol}{\space  
(\glentrysymbol{\glscurrententrylabel})}
```

For convenience, as from v1.31, you can use

```
\glstdefpostname{<category>}{<definition>}
```

This is simply a shortcut for:

```
\csdef{glxtrpostname<category>}{<definition>}
```

Note that it doesn't check if the command has already been defined.

As from version 1.25, the post-name hook also does

```
\glsextrapostnamehook{<label>}
```

(before `\glxtrpostname<category>`) to allow for additional non-category related code. This does nothing by default.

The post-description code used within the glossary is modified so that it also does

```
\glxtrpostdescription
```

This occurs before the original `\glspostdescription`, so if the `nopostdot=false` option is used, it will be inserted before the terminating full stop.

This new command will do `\glxtrpostdesc<category>` if it exists, where `<category>` is the category label associated with the current entry. For example `\glxtrpostdescgeneral` for entries with the category set to general or `\glxtrpostdescacronym` for entries with the category set to acronym. For convenience, as from v1.31, you can use

```
\glstdefpostdesc{<category>}{<definition>}
```

This is simply a shortcut for:

```
\csdef{glxtrpostdesc<category>}{<definition>}
```

Note that it doesn't check if the command has already been defined.

Since both `\glossentry` and `\subglossentry` set

```
\glscurrententrylabel
```

to the label for the current entry, you can use this within the definition of these post-description hooks if you need to reference the label.

For example, suppose you want to insert the plural form in brackets after the description in the glossary, but only for entries in the general category, then you could do:

```
\renewcommand{\glsxtrpostdescgeneral}{\space  
(plural: \glsentryplural{\glscurrententrylabel})}
```

This means you don't have to define a custom glossary style, which you may find more complicated. (It also allows more flexibility if you decide to change the underlying glossary style.)

This feature can't be used for glossary styles that ignore `\glspostdescription` or if you redefine `\glspostdescription` without including `\glsxtrpostdescription`. (For example, if you redefine `\glspostdescription` to do nothing instead of using the `nopostdot` option to suppress the terminating full stop.) See Section 2.11.3 to patch the predefined styles provided by glossaries that are missing `\glspostdescription`.

### 2.11.2 Number List

The `number list` is now placed inside the argument of

```
\GlsXtrFormatLocationList{<number list>}
```

This is internally used by `\glossaryentrynumbers`. The `nonumberlist` option redefines `\glossaryentrynumbers` so that it doesn't display the number list, but it still saves the number list in case it's required.

If you want to suppress the number list always use the `nonumberlist` option instead of redefining `\glossaryentrynumbers` to do nothing.

For example, to change the font for the entire number list redefine `\GlsXtrFormatLocationList` as appropriate. Don't modify `\glossaryentrynumbers`.

Sometimes users like to insert "page" or "pages" in front of the number list. This is quite fiddly to do with the base glossaries package, but `glossaries-extra` provides a way of doing this. First you need to enable this option and specify the text to display using:

```
\GlsXtrEnablePreLocationTag{<page>}{<pages>}
```

where `<page>` is the text to display if the number list only contains a single location and `<pages>` is the text to display otherwise. For example:

```
\GlsXtrEnablePreLocationTag{Page: }{Pages: }
```



An extra run is required when using this command.

Use `glsignore not @gobble` as the format if you want to suppress the page number (and only index the entry once).

See the accompanying sample file `sample-pages.tex`.

Note that `bib2gls` can be instructed to insert a prefix at the start of non-empty location lists, which can be used as an alternative to `\GlsXtrEnablePreLocationTag`.

**Location lists** displayed with `\printnoidxglossary` internally use

```
\glsnoidxdisplayloc{<prefix>}{<counter>}{<format>}{<location>}
```

This command is provided by `glossaries`, but is modified by `glossaries-extra` to check for the start and end range formation identifiers ( `&` and `&` ) which are discarded to obtain the actual control sequence name that forms the location formatting command.

If the range identifiers aren't present, this just uses

```
\glsxtrdisplaysingleloc{<format>}{<location>}
```

otherwise it uses

```
\glsxtrdisplaystartloc{<format>}{<location>}
```

for the start of a range (where the identifier has been stripped from `<format>`) or

```
\glsxtrdisplayendloc{<format>}{<location>}
```

for the end of a range (where the identifier has been stripped from `<format>`).

By default the start range command saves the format in

```
\glsxtrlocrangefmt
```

and does

```
\glsxtrdisplaysingleloc{<format>}{<location>}
```

(If the format is empty, it will be replaced with `glsnumberformat`.)

The end command checks that the format matches the start of the range, does

```
\glsxtrdisplayendlochook{<format>}{<location>}
```

(which does nothing by default), followed by

```
\glsxtrdisplaysingleloc{<format>}{<location>}
```

and then sets `\glsxtrlocrangefmt` to empty.

This means that the list

```
\glsnoidxdisplayloc{}{page}{(textbf){1},
\glsnoidxdisplayloc{}{page}{textbf}{1},
\glsnoidxdisplayloc{}{page}{}textbf}{1}.
```

doesn't display any differently from

```
\glsnoidxdisplayloc{}{page}{textbf}{1},
\glsnoidxdisplayloc{}{page}{textbf}{1},
\glsnoidxdisplayloc{}{page}{textbf}{1}.
```

but it does make it easier to define your own custom list handler that can accommodate the ranges.

### 2.11.3 The `glossaries-extra-stylemods` Package

As from v1.02, `glossaries-extra` now includes the package `glossaries-extra-stylemods` that will redefine the predefined styles to include the post-description hook (for those that are missing it). You will need to make sure the styles have already been defined before loading `glossaries-extra`. For example:

```
\usepackage{glossaries-extra}
\usepackage{glossary-longragged}
\usepackage{glossaries-extra-stylemods}
```

Alternatively you can load `glossary-⟨name⟩.sty` at the same time by passing `⟨name⟩` as a package option to `glossaries-extra-stylemods`. For example:

```
\usepackage{glossaries-extra}
\usepackage[longragged]{glossaries-extra-stylemods}
```

Another option is to use the `stylemods` key when you load `glossaries-extra`. You can omit a value if you only want to use the predefined styles that are automatically loaded by `glossaries` (for example, the `long3col` style):

```
\usepackage[style=long3col,stylemods]{glossaries-extra}
```

Or the value of `stylemods` may be a comma-separated list of the style package identifiers. For example:

```
\usepackage[style=mcoltree,stylemods=mcols]{glossaries-extra}
```

Remember to group the value if it contains any commas:

```
\usepackage[stylemods={mcols,longbooktabs}]{glossaries-extra}
```

**Inline Style** Note that the inline style is dealt with slightly differently. The original definition provided by the glossary-inline package uses `\glspostdescription` at the end of the glossary (not after each entry description) within the definition of `\glspostinline`. The style modification changes this so that `\glspostinline` just does a full stop followed by space factor adjustment, and the description `\glsinlinedescformat` and sub-entry description formats `\glsinlinesubdescformat` are redefined to include `\glsxtrpostdescription` (not `\glspostdescription`). This means that the modified inline style isn't affected by the `nopost-dot` option, but the post-description category hook can still be used.

**Tabular Styles** The tabular-like styles, such as long are adjusted so that the `\ifglsnogroupskip` conditional (set with `nogroupskip`) is moved outside of the definition of `\glsgroupskip` to avoid problems that cause an “Incomplete `\iftrue`” error with `\printunsrtglossary` and `\printnoidxglossary`. This means that if you want to change this conditional using `\setupglossaries` or using the `nogroupskip` option in `\printglossary`, `\printnoidxglossary` or `\printunsrtglossary`, you must also reset the glossary style.

As from version 1.21, the hard-coded `\space` before the `number list` in many of the predefined styles is replaced with

```
\glsxtrprelocation
```

This just defaults to `\space` but may be redefined as required. For example:

```
\renewcommand{\glsxtrprelocation}{\dotfill}
```

**List Styles** The list styles use

```
\glslistprelocation
```

(which defaults to `\glsxtrprelocation`) for top-level items and

```
\glslistchildprelocation
```

(which defaults to `\glslistprelocation`) for child items.

As from v1.31, the description (including the post-description hook) is governed by:

```
\glslistdesc{<label>}
```

for the list and altlist styles (but not the listdotted variations).

As from v1.47, the item is governed by:

```
\glslistitem{<label>}
```

The altlist styles use:

```
\glsaltlistitem{<label>}
```

which internally uses `\glslistitem`. The header item (for the list styles that should the group title) is governed by:

```
\glslistgroupheaderitem{<group-label>}{<header code>}
```

This ignores the *<group-label>* by default and simply places the second argument in the optional argument of `\item`. The *<header code>* is the formatted group title, possibly including a hypertext. The spacing after the group item is given by:

```
\glslistgroupafterheader
```

For just the list style and its letter group variations (not the `altlist` or `listdotted` variations) the **number list** for child entries is followed by

```
\glslistchildpostlocation
```

which defaults to a full stop.

The default value of `\glslistdottedwidth` is changed so that it's set at the start of the document (if it hasn't been changed in the preamble). This should take into account situations where `\hsize` isn't set until the start of the document.

The separator between groups (if not **nogroupskip**) is now given by:

```
\glslistgroupskip
```

This defaults to `\indexspace` with penalties to deter page breaks. This command isn't used if **nogroupskip** is set.

The glossary-tree package introduced new commands in v4.22, `\glstreegroupheaderfmt` and `\glstreenavigationfmt`, which are used to format the letter group headings and the navigation elements for the appropriate styles. These two new commands are defined in terms of `\glstreenamefmt` since that was the command originally used for the group headings and navigation. This now allows these different elements to be defined independently, but the most common redefinition is for `\glstreenamefmt` to remove the bold in the name. If the bold is still required for the group heading and navigation elements, then both other commands also need redefining. To simplify matters, if `\glstreenamefmt` has been defined, as from v1.31 `glossaries-extra-stylemods` defines:

```
\glstreedefaultnamefmt{<text>}
```

which simply does `\textbf{<text>}` and redefines `\glstreenamefmt`, `\glstreegroupheaderfmt` and `\glstreenavigationfmt` all in terms of `\glstreedefaultnamefmt`.

This means that if you want to change all three to use a particular style you only need to re-define `\glstreedefaultnamefmt`, but if you only want to redefine `\glstreenamefmt` without

affecting the other two commands, then you now can.

The separator between groups without headers is given by:

```
\glstreegroupskip
```

This defaults to just `\indexspace` without penalties. This command isn't used if `nogroupskip` is set. (The penalties introduced in v1.41 were moved to `\glstreeheadergroupskip` in v1.42 as they are inappropriate when there's no header.)

The separator between groups with headers is now given by (as from v1.42):

```
\glstreegroupheaderskip
```

This defaults to `\glstreegroupskip` with penalties to deter page breaks after the group heading.

The styles that display the group titles now use:

```
\glstreePreHeader{<label>}{<title>}
```

where *<label>* is the group label and *<title>* is the group title. This does nothing by default and is inserted before the group title. You can redefine it to add the group title to the PDF bookmarks. For example, if the glossary title uses `\chapter` then:

```
\renewcommand{\glstreePreHeader}[2]{%
  \pdfbookmark[1]{#2}{\currentglossary.#1}%
}
```

will insert section-level bookmarks. The use of `\currentglossary` helps to provide unique bookmark labels in the event of multiple glossaries.

The glossary-tree package provides the commands

```
\glstreepredesc
```

and

```
\glstreechildpredesc
```

(which both default to a space) and uses them in the tree-like styles, but not for the `almtree` style. The `glossaries-extra-stylemods` package modifies the `almtree` style so that it has equivalent hooks:

```
\glsalmtreepredesc
```

and

```
\glsalmtreechildpredesc
```

These do nothing by default.

The index-like and tree-like styles insert the pre-number list space with

```
\glstreeprelocation
```

(which defaults to `\glstxtrprelocation`) for top-level items and

```
\glstreechildprelocation
```

(which defaults to `\glstreeprelocation`) for child items.

As from version 1.31, the `glossaries-extra-stylemods` package also provides:

```
\glstreenonamedesc{<label>}
```

which is used by the `treenoname` styles to display the pre-description separator, the description and the post-description hook. Similarly for the symbol:

```
\glstreenonamesymbol{<label>}
```

The above are just used for top-level entries. Child entries don't have the name or symbol displayed for the `treenoname` styles, so there's only a command for the child description:

```
\glstreenamechilddesc{<label>}
```

For the tree styles (but not the `treenoname` or `almtree` styles), the description is displayed using:

```
\glstreedesc{<label>}
```

and the symbol with:

```
\glstreesymbol{<label>}
```

Again the above two commands are just for top-level entries. The child entries use:

```
\glstreechilddesc{<label>}
```

for the description and

```
\glstreechildsymbol{<label>}
```

for the symbol. As from version 1.41, there are now wrapper commands for `\glstreedesc` and `\glstreechilddesc` that check for the description and symbol to determine what separator to use before the page list. These are:

```
\glstreeDescLoc{<label>}{<location>}
```

for top-level entries and

```
\glstreeChildDescLoc{<label>}{<location>}
```

for sub-entries.

If either the symbol or description is present these will use `\glstreeprelocation` or `\glstreechildprelocation`, respectively. Otherwise, both will use (from v1.42):

```
\glstreeNoDescSymbolPreLocation
```

The default is a space. This means that you could have, say, a comma followed by a space for terms that are simply an alias, but just have a space for terms that have a description that ends with a full stop (or that just have a symbol without a description) where the comma would be inappropriate.

Note that version 1.42 has corrected an error that was introduced to v1.41 that caused the name to run into the location list if there was no symbol and no description.

As from version 1.05, the `glossaries-extra-stylemods` package provides some additional commands for use with the `alttree` style to make it easier to modify. These commands are only defined if the `glossary-tree` package has already been loaded, which is typically the case unless the `notree` option has been used when loading `glossaries`.

```
\gglsetwidest [ <level> ] { <name> }
```

(New to version 1.21.) This is like `\glssetwidest` (provided by `glossary-tree`) but performs a global assignment.

```
\eglssetwidest [ <level> ] { <name> }
```

This is like `\glssetwidest` but performs a protected expansion on `<name>`. This has a localised effect. For a global setting, use

```
\xglssetwidest [ <level> ] { <name> }
```

The following only set the value if `<name>` is wider than the current value (new to version 1.23). Local update:

```
\glsupdatewidest [ <level> ] { <name> }
```

Global update:

```
\gglupdatewidest [ <level> ] { <name> }
```

Locale update (expands `<name>`):

```
\eglsupdatewidest [ <level> ] { <name> }
```

Global update (expands `<name>`):

```
\xglsupdatewidest[⟨level⟩]{⟨name⟩}
```

The widest entry value can later be retrieved using

```
\glsgetwidestname
```

for the top-level entries and

```
\glsgetwidestsubname{⟨level⟩}
```

for sub-entries, where *⟨level⟩* is the level number.

Note that if you are using `bib2gls`, you can use the resource option `set-widest` which will try to determine the widest name of all the selected entries. This isn't guaranteed to work as it may depend on fonts or commands that `bib2gls` can't replicate, but it should be suitable for names that just consist of text, and can be more efficient than iterating over all the defined entries using `TEX`.

The command `\glsfindwidesttoplevelname` provided by `glossary-tree` has a `CamelCase` synonym:

```
\glsFindWidestTopLevelName[⟨glossary list⟩]
```

Similar commands are also provided:

```
\glsFindWidestUsedTopLevelName[⟨glossary list⟩]
```

This has an additional check that the entry has been used. Naturally this is only useful if the glossaries that use the `alttree` style occur at the end of the document. This command should be placed just before the start of the glossary. (Alternatively, place it at the end of the document and save the value in the auxiliary file for the next run.)

```
\glsFindWidestUsedAnyName[⟨glossary list⟩]
```

This is like the previous command but if doesn't check the parent key. This is useful if all levels should have the same width for the name.

```
\glsFindWidestAnyName[⟨glossary list⟩]
```

This is like the previous command but doesn't check if the entry has been used.

```
\glsFindWidestUsedLevelTwo[⟨glossary list⟩]
```

This is like `\glsFindWidestUsedTopLevelName` but also sets the first two sub-levels as well. Any entry that has a great-grandparent is ignored.



```
\glsFindWidestLevelTwo[⟨glossary list⟩]
```

This is like the previous command but doesn't check if the entry has been used.

```
\glsFindWidestUsedAnyNameSymbol[⟨glossary list⟩]{⟨register⟩}
```

This is like `\glsFindWidestUsedAnyName` but also measures the symbol. The length of the widest symbol is stored in `⟨register⟩`.

```
\glsFindWidestAnyNameSymbol[⟨glossary list⟩]{⟨register⟩}
```

This is like the previous command but it doesn't check if the entry has been used.

```
\glsFindWidestUsedAnyNameSymbolLocation[⟨glossary list⟩]{⟨symbol register⟩}{⟨location register⟩}
```

This is like `\glsFindWidestUsedAnyNameSymbol` but also measures the **number list**. This requires `\glsentrynumberlist` (see the glossaries user manual). The length of the widest symbol is stored in `⟨symbol register⟩` and the length of the widest number list is stored in `⟨location register⟩`.

```
\glsFindWidestAnyNameSymbolLocation[⟨glossary list⟩]{⟨symbol register⟩}{⟨location register⟩}
```

This is like the previous command but it doesn't check if the entry has been used.

```
\glsFindWidestUsedAnyNameLocation[⟨glossary list⟩]{⟨register⟩}
```

This is like `\glsFindWidestUsedAnyNameSymbolLocation` but doesn't measure the symbol. The length of the widest number list is stored in `⟨register⟩`.

```
\glsFindWidestAnyNameLocation[⟨glossary list⟩]{⟨register⟩}
```

This is like the previous command but doesn't check if the entry has been used.

The layout of the symbol, description and number list is governed by

```
\glsxtralttreeSymbolDescLocation{⟨label⟩}{⟨number list⟩}
```

for top-level entries and

```
\glsxtralttreeSubSymbolDescLocation{⟨label⟩}{⟨number list⟩}
```

for sub-entries.

There is now a user level command that performs the initialisation for the alttree style:

```
\glxtralttreeInit
```

The paragraph indent for subsequent paragraphs in multi-paragraph descriptions is provided by the length

```
\glxtrAltTreeIndent
```

For additional commands that are available with the `alttree` style, see the documented code (`glossaries-extra-code.pdf`). See also the accompanying sample files `sample-alttree.tex`, `sample-alttree-sym.tex` and `sample-alttree-marginpar.tex`.

## 3 New Glossary Styles

The glossaries-extra package comes with some new styles. The associated style package needs to be loaded. This can be done with `\usepackage` but it's simpler to use the `stylemods` option.

### 3.1 glossary-bookindex package

As from v1.21, glossaries-extra has a new supplementary package `glossary-bookindex` which provides the `glossary` style `bookindex`. This is very similar to the `mcolindexgroup` style but is designed for indexes, so by default only the name and location list are displayed. You can either load this package explicitly and then set the style:

```
\usepackage{glossaries-extra}
\usepackage{glossary-bookindex}
\setglossarystyle{bookindex}
```

or use both the `stylemods` and style options:

```
\usepackage[stylemods=bookindex,style=bookindex]{glossaries-extra}
```

The `bookindex` style only supports a maximum hierarchical level of 2 (top-level, level 1 and level 2). It's primarily designed for use with `bib2gls`. It may be used with other indexing options, but some features may not be present and UTF-8 characters may cause a problem with non-Unicode engines in letter group headings or PDF bookmarks. (`bib2gls` uses numeric identifies by default to avoid these problems. If numbers show up in the group headings instead of the appropriate characters, check that you have used the `record` package option.)

The number of columns is given by

```
\glstrbookindexcols
```

which defaults to 2.

This style uses the `multicols` environment. If the command

```
\glstrbookindexcolspread
```

isn't empty then it's supplied as the optional argument following `\begin{multicols}{<n>}`. You can switch from `multicols` to `multicols*` by redefining

```
\glstrbookindexmulticolseenv
```

For example

```
\renewcommand{\glstrbookindexmulticolseenv}{multicols*}
```

Each top-level entry is displayed using

```
\glsxtrbookindexname{<label>}
```

where the entry is identified by *<label>*. This just does `\glossentryname{<label>}` by default. For example, if you want the symbol to be included:

```
\renewcommand*\glsxtrbookindexname}[1]{%
  \glossentryname{#1}%
  \ifglshassymbol{#1}{\space (\glossentrysymbol{#1})}{}%
}
```

or if you want the description (if set):

```
\renewcommand*\glsxtrbookindexname}[1]{%
  \glossentryname{#1}%
  \ifglshasdesc{#1}{\space \glossentrydesc{#1}\glspostdescription}{}%
}
```

(which picks up the post-description hook).

Alternatively you can use the `\glsxtrpostname<category>` hook to append information after the name according to the entry's category.

Sub-entries are displayed using

```
\glsxtrbookindexsubname{<label>}
```

which just defaults to `\glsxtrbookindexname{<label>}`.

The separator used before the location list for top-level entries is given by

```
\glsxtrbookindexprelocation{<label>}
```

where *<label>* is the entry's label. This checks if the location field has been set. If it has, it does `,\glsxtrprelocation`

otherwise it just does `\glsxtrprelocation` (which defaults to `\space`). If you're not using **bib2gls**, the location field won't be set.

The separator used before the location list for sub-entries is given by

```
\glsxtrbookindexsubprelocation{<label>}
```

which defaults to `\glsxtrbookindexprelocation{<label>}`.

The actual location list is encapsulated with:

```
\glsxtrbookindexlocation{<label>}{<location list>}
```

for top-level entries and

```
\glxtrbookindexsublocation{<label>}{<location list>}
```

for sub-entries. These both just do *<location list>* by default.

The separator used between a top-level parent and child entry is given by

```
\glxtrbookindexparentchildsep
```

This defaults to `\nopagebreak`.

The separator used between a sub-level parent and child entry is given by

```
\glxtrbookindexparentschildsep
```

This defaults to `\glxtrbookindexparentchildsep`.

The separator between top-level entries is given by

```
\glxtrbookindexbetween{<label1>}{<label2>}
```

This comes after the entry given by *<label1>*, if the entry has no children, or after the last descendent otherwise, so it always comes immediately before the entry given by *<label2>* unless the entry occurs at the start of a group. This does nothing by default.

The separator between two level 1 entries is given by

```
\glxtrbookindexsubbetween{<label1>}{<label2>}
```

The separator between two level 2 entries is given by

```
\glxtrbookindexsubsubbetween{<label1>}{<label2>}
```

At the end of each letter group, the following hooks are done in order:

```
\glxtrbookindexsubsubatendgroup{<sub-sub-label>}
```

```
\glxtrbookindexsubatendgroup{<sub-label>}
```

```
\glxtrbookindexatendgroup{<label>}
```

where *<sub-sub-label>* is the label of the last level 2 entry, *<sub-label>* is the label of the last level 1 entry and *<label>* is the label of the last level 0 entry.

For example, the resource option `seealso=omit` instructs `bib2gls` to omit the `seealso` cross-reference from the location list. (The `see` cross-reference will still be added unless you also have `see=omit`.) The `seealso` cross-reference can instead be appended after the child entries using:

```
\renewcommand{\glxtrbookindexatendgroup}[1]{%
```

```

\glxtrifhasfield{seealso}{#1}{\glstreesubitem\glxtruseealso{#1}}{}%
}
\renewcommand{\glxtrbookindexbetween}[2]{%
\glxtrbookindexatendgroup{#1}%
}%

\renewcommand{\glxtrbookindexsubatendgroup}[1]{%
\glxtrifhasfield{seealso}{#1}{\glstreesubsubitem\glxtruseealso{#1}}{}%
}

\renewcommand{\glxtrbookindexsubbetween}[2]{%
\glxtrbookindexsubatendgroup{#1}%
}

\renewcommand{\glxtrbookindexsubsubatendgroup}[1]{%
\glxtrifhasfield{seealso}{#1}%
{\glstreeitem\hspace*{40pt}\glxtruseealso{#1}}{}%
}

\renewcommand{\glxtrbookindexsubsubbetween}[2]{%
\glxtrbookindexsubsubatendgroup{#1}%
}

```

This uses `\glstreesubitem` and `\glstreesubsubitem` to indent the cross-reference according to the next level down, so the cross-reference for a top-level entry is aligned with the sub-entries, and a level 1 entry has its cross-reference aligned with sub-sub-entries. In the event that a level 2 entry has a cross-reference, this is indented a bit further (but it won't be aligned with any deeper level as the bookindex style only supports a maximum of two sub-levels).

The bookindex style uses group headings. (If you use `bib2gls` remember to invoke it with the `--group` or `-g` switch.) The heading will use

```
\glxtrbookindexbookmark{<group title>}{<name>}
```

If `\pdfbookmark` has been defined, this will use that command to bookmark the group title. If `section=chapter` is set (default if chapters are defined) then this uses level 1 otherwise it uses level 2. You can redefine this command if this isn't appropriate. If `\pdfbookmark` hasn't been defined, this command does nothin.

The group heading is formatted according to

```
\glxtrbookindexformatheader{<group title>}
```

which is defined as

```
\newcommand*{\glxtrbookindexformatheader}[1]{%
\par{\centering\glstreegroupheaderfmt{#1}\par}%
}
```

where `\glstreegroupheaderfmt` is provided by the `glossary-tree` package, which is automatically loaded. Note that the entry names aren't encapsulated with `\glstreenamfmt`.

The glossary-bookindex package provides some supplementary commands that aren't used by default, but may be used when adjusting the style. These commands should only be used within one of the `\print...glossary` commands. (That is, they should only be used in glossary styles.)

```
\glxtrbookindexmarkentry{<label>}
```

This writes information to the `.aux` file that can be read on the next run to obtain the first and last entry on each page of the glossary.

You can display the first entry associated with the current page using:

```
\glxtrbookindexfirstmark
```

and the last entry associated with the current page using:

```
\glxtrbookindexlastmark
```

These do nothing if there are no entries marked on the current page (or if the document build isn't up to date).

The entry is formatted using:

```
\glxtrbookindexfirstmarkfmt{<label>}
```

for the first instance and

```
\glxtrbookindexlastmarkfmt{<label>}
```

for the last.

These commands are designed for use in page headers or footers where the page number is stable. For example, `\glxtrbookindexname` can be redefined to mark the current entry:

```
\renewcommand{\glxtrbookindexname}[1]{%  
  \glxtrbookindexmarkentry{#1}%  
  \glossentryname{#1}%  
}
```

If you only want to mark the top-level entries, remember to redefine `\glxtrbookindexsubname` as it defaults to `\glxtrbookindexname`:

```
\renewcommand{\glxtrbookindexsubname}[1]{%  
  \glossentryname{#1}%  
}
```

Then if you're using `fancyhdr` you can set the page style to show the first and last entry for the current page with:

```
\pagestyle{fancy}%  
\thead{\thepage}%  
\tfoot{\glxtrbookindexfirstmark}%
```

```
\cfoot{}%
\rfoot{\glxtrbookindexlastmark}%
```

## 3.2 glossary-longextra package

As from version 1.37, the glossaries-extra package comes with the supplementary package glossary-longextra that provides additional styles, listed below, that use the longtable environment. If you know that your glossary won't span more than a page and you need to use it in a context that's incompatible with longtable, you can instead setup these styles to use tabular instead. In order to do this you must use

```
\GlsLongExtraUseTabulartrue
```

*before the style is set.* For example:

```
\GlsLongExtraUseTabulartrue
\setglossarystyle{long-name-desc}
```

or

```
\GlsLongExtraUseTabulartrue
\printunsrtglossary[style={long-name-desc}]
```

If you use this setting, you can change the default vertical alignment with:

```
\glslongextraTabularVAlign
```

The default definition is `c`.

The column titles are formatted according to:

```
\glslongextraHeaderFmt{<text>}
```

which simply does `\textbf{<text>}` by default.

The name column has the title given by `\entryname` and the column alignment is given by:

```
\glslongextraNameAlign
```

which expands to `l` (left) by default.

The symbol column (where applicable) has the title given by `\symbolname` and the column alignment is given by:

```
\glslongextraSymbolAlign
```

which expands to `c` (centred) by default.

The location list column (where applicable) has the title given by `\pagelistname` and the column alignment is given by:



```
\glslongextraLocationAlign
```

which expands to

```
>\raggedright}p{\glspagelistwidth}
```

by default. (Ragged-right paragraph, `\glspagelistwidth` is defined in `glossary-long`, which is automatically loaded.)

The description column has the title given by `\descriptionname` and the column alignment is given by:

```
\glslongextraDescAlign
```

which expands to

```
>\raggedright}p{\glsdescwidth}
```

by default. (Ragged-right paragraph, `\glsdescwidth` is defined in `glossary-long`, which is automatically loaded.)

Unlike the long styles provided by the base glossaries package, these new styles try to determine the value of `\glsdescwidth` at the start of the glossary according to the number of columns provided by the style. The calculations are performed by the following commands:

```
\glslongextraSetDescWidth
```

This is used by the styles that have a name and description column. The value of `\glsdescwidth` is computed as:

$$\glsdescwidth = \linewidth - 4\text{tabcolsep} - W$$

where  $W$  is a guess at the width of the name column. This is first set to the width of the name column header:

```
\settowidth{\width}{\glslongextraHeaderFmt\entryname}
```

If any names in that column are larger than this, then you need to specify the widest name using:

```
\glslongextraSetWidest{\widest name}
```

or

```
\glslongextraUpdateWidest{\text}
```

These work like the analogous commands `\glssetwidest` and `\glsupdatewidest` provided with the `almtree` style, but in this case there's no hierarchy. The default widest name is obtained from the `almtree` top-level name if set, otherwise it's empty, so you can use `bib2gls's` `set-widest` option. If you have the entry counter enabled, you will need to include this with the name for the extra material to be taken into account.

The name isn't shown for child entries by default, but if you change this and you want to use bib2gls's set-widest option (for bib2gls v1.8+) then you need to redefine:

```
\glslongextraUpdateWidestChild{<level>}{<text>}
```

This does nothing by default, but if you are including the child names then you need to redefine this command:

```
\renewcommand{\glslongextraUpdateWidestChild}[2]{%
  \glslongextraUpdateWidest{#2}%
}
```

If you prefer to set an explicit width for the description column then you need to redefine \glslongextraSetDescWidth. For example:

```
\renewcommand{\glslongextraSetDescWidth}{%
  \setlength{\glsdescwidth}{0.6\linewidth}%
}
```

The styles that have a name, symbol and description, \glsdescwidth is set with:

```
\glslongextraSymSetDescWidth
```

This first uses \glslongextraSetDescWidth and then subtracts 2\tabcolsep and the width of the symbol column header from \glsdescwidth. This assumes that the symbol column header is larger than any of the symbols. If this isn't appropriate then you can redefine this command. For example:

```
\renewcommand{\glslongextraSymSetDescWidth}{%
  \glslongextraSetDescWidth
  \addtolength{\glsdescwidth}{-3cm}%
}
```

or

```
\renewcommand{\glslongextraSymSetDescWidth}{%
  \setlength{\glsdescwidth}{.5\linewidth}%
}
```

For the styles that have a name, description and location column, \glsdescwidth is set using:

```
\glslongextraLocSetDescWidth
```

This uses \glslongextraSetDescWidth and then subtracts 2\tabcolsep and \glspagelistwidth from \glsdescwidth. You can redefine this command to set both \glsdescwidth and \glspagelistwidth if appropriate.

For the styles that have a name, description, symbol and location column, \glsdescwidth is set using:

```
\glslongextraSymLocSetDescWidth
```

This uses `\glslongextraSymSetDescWidth` and then subtracts `2\tabcolsep` and `\glspagelistwidth` from `\glsdescwidth`. Again, you can redefine this command to explicitly set both lengths.

In all cases, the top-level name is formatted according to:

```
\glslongextraNameFmt{<label>}
```

This does

```
\glsentryitem{<label>}\glstarget{<label>}{\glossentryname{<label>}}
```

which includes the entry counter (if enabled), the target and the post-name link.

The top-level description is formatted according to:

```
\glslongextraDescFmt{<label>}
```

This does `\glossentrydesc{<label>}` followed by the post-description hook.

The styles that have a symbol column format the symbol using:

```
\glslongextraSymbolFmt{<label>}
```

This just does `\glossentrysymbol{<label>}`.

The styles that have a location list column format the list using:

```
\glslongextraLocationFmt{<label>}{<locations>}
```

This just does `<locations>` and ignores the label.

The child entries have their name formatted according to:

```
\glslongextraSubNameFmt{<level>}{<label>}
```

where `<level>` is the hierarchical level. This defaults to:

```
\glssubentryitem{<label>}\glstarget{<label>}{\strut}
```

This includes the sub-entry counter (if enabled) and the target but doesn't show the name. The child description is formatted according to:

```
\glslongextraSubDescFmt{<level>}{<label>}
```

which defaults to just `\glslongextraDescFmt{<label>}`

The child symbol is formatted (where appropriate) according to:

```
\glslongextraSubSymbolFmt{<level>}{<label>}
```

This just does `\glslongextraSymbolFmt{<label>}` by default.

The styles that have a location list column format the list for child entries using:

```
\glslongextraSubLocationFmt<level>{\<label>}{\<locations>}
```

This just does *<locations>* and ignores the level and label.

The letter group headings are formatted according to:

```
\glslongextraGroupHeading{\<n>}{\<label>}
```

which does nothing by default. The first argument *<n>* is the number of columns in the table. The second argument *<label>* is the group label (not the title, although they may happen to be the same).

This can be redefined to show the group heading. For example:

```
\renewcommand*\glslongextraGroupHeading}[2]{%
  \glsxrgetgrouptitle{#2}{\thisgrptitle}%
  \glslongextraHeaderFmt{\thisgrptitle}%
  \tabularnewline
  \noalign{\vskip\normalbaselineskip}%
}
```

This ignores the first argument and just puts the group title in the first column formatted according to `\glslongextraHeaderFmt` (to match the column header).

Remember that you can also adjust the styles through category attributes. The name column's title is given by `\entryname`, the description column's title is given by `\descriptionname` and (where present) the symbol column's title is given by `\symbolname`, as for the other long styles that have headers.

**long-name-desc** This is like the `longragged-booktabs` style but doesn't show the location list (regardless of the `nonumberlist` option). The name is shown in the first column and the description in the second.

The symbol is not displayed. The header row is produced with:

```
\glslongextraNameDescHeader
```

This essentially uses the same code as for `longragged-booktabs` but makes it easier to adjust the header without having to define a new style. This is defined as:

```
\glslongextraNameDescTabularHeader\endhead
\glslongextraNameDescTabularFooter\endfoot
```

where:

```
\glslongextraNameDescTabularHeader
```

sets up the header and

```
\glslongextraNameDescTabularFooter
```

sets up the footer. If you have setup the tabular version of this style then the above two commands are used at the start and end of the tabular environment (and `\glslongextraNameDescHeader` isn't used).

For example, to simply remove the header and footer (for the default longtable version of the style):

```
\renewcommand{\glslongextraNameDescHeader}{}{}
```

Or to change the name alignment to centred:

```
\renewcommand{\glslongextraNameAlign}{c}
```

`long-name-desc-loc` This is like the `long-name-desc` style but has a third column for the location list. The longtable header is given by:

```
\glslongextraNameDescLocationHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraNameDescLocationTabularHeader
```

and

```
\glslongextraNameDescLocationTabularFooter
```

`long-desc-name` This is like the `long-name-desc` style but swaps the columns. Note that if the entry counter is displayed it will appear at the start of the second column by default. The longtable header is formatted according to:

```
\glslongextraDescNameHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraDescNameTabularHeader
```

and

```
\glslongextraDescNameTabularFooter
```

long-loc-desc-name This has three columns containing the location list, description and name.  
The longtable header is formatted according to:

```
\glslongextraLocationDescNameHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraLocationDescNameTabularHeader
```

and

```
\glslongextraLocationDescNameTabularFooter
```

long-name-desc-sym This is has three columns, with the name in the first, the description in the second and the symbol in the third.

The longtable header row is produced with:

```
\glslongextraNameDescSymHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraNameDescSymTabularHeader
```

and

```
\glslongextraNameDescSymTabularFooter
```

long-name-desc-sym-loc This is has four columns, with the name in the first, the description in the second, the symbol in the third and the location list in the fourth.

The longtable header row is produced with:

```
\glslongextraNameDescSymLocationHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraNameDescSymLocationTabularHeader
```

and

```
\glslongextraNameDescSymLocationTabularFooter
```

long-name-sym-desc This is like the long-name-desc-sym but the second and third column are swapped. The longtable header row is given by:

```
\glslongextraNameSymDescHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraNameSymDescTabularHeader
```

and

```
\glslongextraNameSymDescTabularFooter
```

long-name-sym-desc-loc This is like the long-name-desc-sym-loc but the second and third column are swapped. The longtable header row is given by:

```
\glslongextraNameSymDescLocationHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraNameSymDescLocationTabularHeader
```

and

```
\glslongextraNameSymDescLocationTabularFooter
```

long-sym-desc-name This has the symbol in the first column, the description in the second and the name in the third. The longtable header row is given by:

```
\glslongextraSymDescNameHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraSymDescNameTabularHeader
```

and

```
\glslongextraSymDescNameTabularFooter
```

long-loc-sym-desc-name This has the location list in the first column, symbol in the second column, the description in the third and the name in the fourth. The longtable header row is given by:

```
\glslongextraLocationSymDescNameHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraLocationSymDescNameTabularHeader
```

and

```
\glslongextraLocationSymDescNameTabularFooter
```

long-desc-sym-name This has the description in the first column, the symbol in the second and the name in the third. The longtable header row is given by:

```
\glslongextraDescSymNameHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraDescSymNameTabularHeader
```

and

```
\glslongextraDescSymNameTabularFooter
```

long-loc-desc-sym-name This has the location list in the first column, the description in the second column, the symbol in the third and the name in the fourth. The longtable header row is given by:

```
\glslongextraLocationDescSymNameHeader
```

which similarly defined in terms of the commands used for the tabular version:

```
\glslongextraLocationDescSymNameTabularHeader
```

and



```
\glslongextraLocationDescSymNameTabularFooter
```

### 3.3 glossary-topic package

As from version 1.40, the glossaries-extra package comes with the supplementary package glossary-topic that provides glossary styles designed for hierarchical glossaries where the top-level entries are topic titles. This package automatically loads the multicols package. If the glossary-tree package is also loaded then commands like `\glssetwidest` can be used on these styles in much the same way as for the `almtree` style. If a `widest` value isn't set then these styles behave more like the `tree` style.

**topic** This style is similar to the `tree` style but the indentation doesn't start until the second sub-item level. The top-level entries have the name displayed in a larger font with the description following in a new paragraph. This style doesn't support the `nogroupskip` setting.

**topicmcols** This style is like the `topic` style but the sub-entries are placed inside a `multicols` environment. The environment name is supplied in the value of the command:

```
\glstopicColsEnv
```

You can change this to the starred form. For example:

```
\renewcommand{\glstopicColsEnv}{multicols*}
```

The number of columns is given by the command:

```
\glstopicCols
```

The default value is 2.

Both styles use the following commands.

```
\glstopicParIndent
```

This command is a length that's used for the paragraph indentation in any multi-paragraph description for top-level entries, but not for the first paragraph (at the start of the description) which isn't indented.

```
\glstopicSubIndent
```

This command is a length that's used to calculate the hanging indentation for sub-entries. The level 1 sub-entries don't indent the name. Level  $n$  sub-entries have the name indented by  $(n - 1) \times \text{\glstopicSubIndent}$ . The hanging indent depends on whether or not a `widest` name has been set for the level.

As from v1.46, there is also a length for additional indentation used in the second paragraph onwards for child entries with multi-paragraph descriptions:

```
\glstopicSubItemParIndent
```

This is initialised to `\parindent` when `glossary-topic` is loaded.

```
\glstopicInit
```

Hook used at the start of the glossary. Does nothing by default.

Although the styles don't support letter groups by default, if you have many topics (top-level entries) and you feel that it would help the reader to divide them up into headed letter groups, you can redefine:

```
\glstopicGroupHeading{\langle group label \rangle}
```

This does nothing by default. If you want to redefine it, you can fetch the title corresponding to the group label with `\glstrgetgrouptitle`. For example:

```
\renewcommand*\glstopicGroupHeading}[1]{%
  \glstrgetgrouptitle{#1}{\thisgrptitle}%
  \section*{\thisgrptitle}%
}
```

Remember that if you use `bib2gls`, you will need the `--group` (or `-g`) switch to support this.

```
\glstopicItem{\langle label \rangle}{\langle location list \rangle}
```

Used to format the name, symbol, description and location list for the top-level entries. This starts with a paragraph break followed by:

```
\glstopicPreSkip
```

which defaults to `\medskip`. There is then a hook:

```
\glstopicMarker{\langle label \rangle}
```

which does nothing by default, but may be redefined. For example, to add a line to the table of contents. The name and symbol are set in the form of a title using:

```
\glstopicTitle{\langle label \rangle}
```

This uses `\Glossentryname` which converts the first letter to upper case. If there's a symbol, this is added in parentheses. Both name and symbol (if present) are encapsulated by

```
\glstopicTitleFont{<text>}
```

This uses a bold, large font by default.

If the entry has the description key set (tested with `\ifglshasdesc`) then a paragraph break is inserted followed by:

```
\glstopicMidSkip
```

which defaults to `\smallskip`. This is followed by the description which is formatted according to:

```
\glstopicDesc{<label>}
```

This just does `\Glossentrydesc{<label>}` followed by the post-description hook.

A paragraph break followed by:

```
\glstopicPostSkip
```

comes next regardless of whether or not the description was displayed. This defaults to `\smallskip`. This is then followed by:

```
\glstopicLoc{<label>}{<location list>}
```

which may be used to display the location list, but does nothing by default.

The sub-entries first set up the paragraph and hanging indentations using:

```
\glstopicAssignSubIndent{<level>}
```

This uses:

```
\glstopicAssignWidest{<level>}
```

to determine if a widest name has been set for the given level.

The sub-entry has its information displayed using:

```
\glstopicSubItem{<level>}{<label>}{<location>}
```

This encapsulates the name with:

```
\glstopicSubNameFont{<text>}
```

By default this just uses `\textbf`. This is followed by:

```
\glstopicSubItemSep
```

which defaults to `\quad`. The name and separator are passed in the *⟨text⟩* argument of:

```
\glstopicSubItemBox{⟨level⟩}{⟨text⟩}
```

If a widest name was set for the given level, this will put *⟨text⟩* inside a box of that width otherwise it just does *⟨text⟩*.

This is followed by the symbol in parentheses if set. Then, if the description is set, the description and post-description hook are displayed followed by:

```
\glstopicSubPreLocSep
```

(This command isn't used if the description isn't set.)

Finally the location list is displayed using:

```
\glstopicSubLoc{⟨label⟩}{⟨location⟩}
```

which just does *⟨location⟩* by default.

## 4 Abbreviations

The new abbreviation system provided by `glossaries-extra` is more flexible than the acronym handling provided by the base `glossaries` package. The `glossaries-extra` package modifies the underlying formatting used by `\gls` (and its variants) so that terms that are recognised as abbreviations can have their formatting dealt with by the style. You therefore need to select an abbreviation style that ensures that `\gls` (and its variants) displays the desired output. See the file [sample-abbr-styles.pdf](#) for samples of all provided abbreviation styles.

Don't use `\glsfirst`, `\Glsfirst` or `\GLSfirst` with abbreviations as they aren't flexible enough to handle some abbreviation styles and unexpected results may occur. (To a lesser degree, this also applies to `\glsstext` etc.) Use commands like `\glsfmttext`, `\glsfmtshort` or `\glsfmtlong` in section headings or captions instead of `\gls`. If you don't want the full form to show on first use of `\gls` use one of the “nolong” or “noshort” styles.

This lack of flexibility in `\glsfirst` can be demonstrated with the following document:

```
\documentclass{article}

\usepackage{glossaries-extra}
\setabbreviationstyle{footnote}
\newabbreviation{ex}{EX}{Example}

\begin{document}
Compare \gls{ex}['s] with \glsfirst{ex}['s].
\end{document}
```

The **first use** `\gls` has the footnote marker after the inserted material “EX<sup>1</sup>” but `\glsfirst` has it before the inserted material “EX<sup>1</sup>’s” which is inappropriate. Note that if the style is changed to `postfootnote`, the footnote marker appears after the inserted material as `\footnote` is in the post-link hook.

There are some instances where `\glsstext` can be useful. It's used internally by `\glsfmttext`, which in turn is used by `\glsseelistformat` if the entry has a short form. If `\glsfmtshort` is used, this enforces the short form, but if `\glsfmttext` is used, then the long form will be used for the “noshort” styles, which is more appropriate. In this particular situation, there's no need to worry about inserted material as the final optional argument isn't supported by `\glsfmttext`.

Abbreviations include acronyms (words formed from initial letters, such as “laser”), initialisms (initial letters of a phrase, such as “html”, that aren't pronounced as words) and contractions (where parts of words are omitted, often replaced by an apostrophe, such as “don't”). The “acronym” code provided by the `glossaries` package is misnamed as it's more often than not used for initialisms instead. Acronyms tend not to be *expanded* on first use (although they may need to be *described*

for readers unfamiliar with the term). They are therefore more like a regular term, which may or may not require a description in the glossary.

The glossaries-extra package corrects this misnomer, and provides better abbreviation handling, with

```
\newabbreviation[⟨options⟩]{⟨label⟩}{⟨short⟩}{⟨long⟩}
```

This sets the category key to `abbreviation` by default, but that value may be overridden in `⟨options⟩`. The category may have attributes that modify the way abbreviations are defined. For example, the `insertdots` attribute will automatically insert full stops (periods) into `⟨short⟩` or the `noshortplural` attribute will set the default value of the `shortplural` key to just `⟨short⟩` (without appending the plural suffix). See Section 7 for further details.

See Section 2.8 regarding the pitfalls of using commands like `\gls` or `\glsxtrshort` within `⟨short⟩` or `⟨long⟩`.

Make sure that you set the category attributes before defining new abbreviations or they may not be correctly applied.

The `\newacronym` command provided by the `glossaries` package is redefined by `glossaries-extra` to use `\newabbreviation` with the category set to `acronym` (see also Section 2.9) so

```
\newacronym[⟨options⟩]{⟨label⟩}{⟨short⟩}{⟨long⟩}
```

is now equivalent to

```
\newabbreviation[type=\acronymtype,category=acronym,⟨options⟩]{⟨label⟩}{⟨short⟩}{⟨long⟩}
```

The `\newabbreviation` command is superficially similar to the `glossaries` package's `\newacronym` but you can apply different styles to different categories. The default style is `short-nolong` for entries in the `acronym` category and `short-long` for entries in the `abbreviation` category. (These aren't the same as the `acronym` styles provided by the `glossaries` package, although they may produce similar results.)

The way the abbreviations are displayed by commands like `\gls` varies according to the abbreviation style. The styles are set according to the entry's category so, unlike the base `glossaries` package, you can have different abbreviation styles within the same glossary.

There are two types of full forms. The display full form, which is used on **first use** by commands like `\gls` and the inline full form, which is used by commands like `\glsxtrfull`. For some of the abbreviation styles, such as `long-short`, the display and inline forms are the same. In the case of styles such as `short-nolong` or `short-footnote`, the display and inline full forms are different.

These formatting commands aren't stored in the `short`, `shortplural`, `long` or `longplural` fields, which means they won't be used within commands like `\glsentryshort` (but they are used within commands like `\glsxtrshort` and `\glsfmtshort`). Note that `\glsxtrlong` and the case-changing variants don't use `\glsfirstlongfont`.

You can apply the formatting command used for the short form to some arbitrary text using

```
\glsuseabbrvfont{<text>}{<category>}
```

where *<category>* is the category label that identifies the abbreviation style. Similarly for the formatting command use by the long form:

```
\glsuselongfont{<text>}{<category>}
```

You can't use the acronym commands provided by the base package with the new abbreviations provided by the `glossaries-extra` package. The style commands that replace `\setacronymstyle`, `\acrshort` etc are described in Section 4.2. The `acronymlists` package option and associated commands aren't supported. The `\forallacronyms` command, which iterates over all acronym lists, should be replaced with:

```
\forallabbreviationlists{<cs>}{<body>}
```

## 4.1 Tagging Initials

If you would like to tag the initial letters in the long form such that those letters are underlined in the glossary but not in the main part of the document, you can use

```
\GlsXtrEnableInitialTagging{<categories>}{<cs>}
```

before you define your abbreviations.

This command (robustly) defines *<cs>* (a control sequence) to accept a single argument, which is the letter (or letters) that needs to be tagged. The normal behaviour of this command within the document is to simply do its argument, but in the glossary it's activated for those categories that have the `tagging` attribute set to "true". For those cases it will use

```
\glsxtrtagfont{<text>}
```

This command defaults to `\underline{<text>}` but may be redefined as required.

The control sequence *<cs>* can't already be defined when used with the unstarred version of `\GlsXtrEnableInitialTagging` for safety reasons. The starred version will overwrite any previous definition of *<cs>*. As with redefining any commands, ensure that you don't redefine something important. In fact, just forget the existence of the starred version and let's pretend I didn't mention it.

The first argument of `\GlsXtrEnableInitialTagging` is a comma-separated list of category names. The `tagging` attribute will automatically be set for those categories. You can later set this attribute for other categories (see Section 7) but this must be done before the glossary is displayed.

The accompanying sample file `sample-mixtures.tex` uses initial tagging for both the acronym and abbreviation categories:

```
\GlsXtrEnableInitialTagging{acronym,abbreviation}{\itag}
```

This defines the command `\itag` which can be used in the definitions. For example:

```
\newacronym
 [description={a system for detecting the location and
 speed of ships, aircraft, etc, through the use of radio
 waves}]% description of this term
 ]
 {radar}% identifying label
 {radar}% short form (i.e. the word)
 {\itag{ra}dio \itag{d}etection \itag{a}nd \itag{r}anging}
```

```
\newabbreviation{xml}{XML}
 {e\itag{x}tensible \itag{m}arkup \itag{l}anguage}
```

The underlining of the tagged letters only occurs in the glossary and then only for entries with the `tagging` attribute set.

## 4.2 Abbreviation Styles

The abbreviation style must be set before abbreviations are defined using:

```
\setabbreviationstyle[<category>]{<style-name>}
```

where `<style-name>` is the name of the style and `<category>` is the category label (abbreviation by default). New abbreviations will pick up the current style according to their given category. If there is no style set for the category, the fallback is the style for the abbreviation category. Some styles may automatically modify one or more of the attributes associated with the given category. For example, the `long-noshort` and `short-nolong` styles set the `regular` attribute to true.

If you want to apply different styles to groups of abbreviations, assign a different category to each group and set the style for the given category.

Note that `\setacronymstyle` is disabled by `glossaries-extra`. Use

```
\setabbreviationstyle[acronym]{<style-name>}
```

instead. The original acronym interface can be restored with `\RestoreAcronyms` (see Section 2.9). However the original acronym interface is incompatible with all the commands described here.

Abbreviations can be used with the standard glossaries commands, such as `\gls`, but don't use the acronym commands like `\acrshort` (which use `\acronymfont`). The short form can be produced with:

```
\glsxtrshort[<options>]{<label>}[<insert>]
```

(Use this instead of `\acrshort`.)



The long form can be produced with

```
\glstrlong[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

(Use this instead of `\acrlong`.)

The *inline* full form can be produced with

```
\glstrfull[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

(This this instead of `\acrfull`.)

In general, it's best not to use commands like `\glstrfirst` for abbreviations, especially if you use the *⟨insert⟩* optional argument. Use either `\gls` (possibly with a `reset`) or `\glstrfull`.

As mentioned earlier, the inline full form may not necessarily match the format used on **first use** with `\gls`. For example, the **short-nolong** style only displays the short form on first use, but the full form will display the long form followed by the short form in parentheses.

If you want to use an abbreviation in a chapter or section title, use the commands described in Section 5 instead.

The arguments *⟨options⟩*, *⟨label⟩* and *⟨insert⟩* are the same as for commands such as `\glstext`. There are also analogous case-changing commands:

First letter upper case short form:

```
\Glsxtrshort[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

First letter upper case long form:

```
\Glsxtrlong[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

First letter upper case inline full form:

```
\Glsxtrfull[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

All upper case short form:

```
\GLSxtrshort[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

All upper case long form:

```
\GLSxtrlong[⟨options⟩]{⟨label⟩}[⟨insert⟩]
```

All upper case inline full form:

```
\GLSxtrfull[<options>]{<label>}[<insert>]
```

Plural forms are also available.

Short form plurals:

```
\glxtrshortpl[<options>]{<label>}[<insert>]
```

```
\Glsxtrshortpl[<options>]{<label>}[<insert>]
```

```
\GLSxtrshortpl[<options>]{<label>}[<insert>]
```

Long form plurals:

```
\glxtrlongpl[<options>]{<label>}[<insert>]
```

```
\Glsxtrlongpl[<options>]{<label>}[<insert>]
```

```
\GLSxtrlongpl[<options>]{<label>}[<insert>]
```

Full form plurals:

```
\glxtrfullpl[<options>]{<label>}[<insert>]
```

```
\Glsxtrfullpl[<options>]{<label>}[<insert>]
```

```
\GLSxtrfullpl[<options>]{<label>}[<insert>]
```

Be careful about using `\glentryfull`, `\Glsentryfull`, `\glentryfullpl` and `\Glsentryfullpl`. These commands will use the currently applied style rather than the style in use when the entry was defined. If you have mixed styles, you'll need to use `\glxtrfull` instead. Similarly for `\glentryshort` etc.

### 4.3 Shortcut Commands

The abbreviation shortcut commands can be enabled using the `shortcuts=abbreviations` package option (or `shortcuts=abbr`) or `shortcuts=ac`. (You can use both settings at the same time.) The provided shortcut commands listed in [table 4.1](#).

Table 4.1: Abbreviation Shortcut Commands

Shortcut ( <code>shortcuts=abbreviations</code> )	Shortcut ( <code>shortcuts=ac</code> )	Equivalent Command
<code>\ab</code>	<code>\ac</code>	<code>\cglS</code>
<code>\abp</code>	<code>\acp</code>	<code>\cglSpl</code>
<code>\as</code>	<code>\acs</code>	<code>\glSxtrshort</code>
<code>\asp</code>	<code>\acsp</code>	<code>\glSxtrshortpl</code>
<code>\al</code>	<code>\acl</code>	<code>\glSxtrlong</code>
<code>\alp</code>	<code>\aclp</code>	<code>\glSxtrlongpl</code>
<code>\af</code>	<code>\acf</code>	<code>\glSxtrfull</code>
<code>\afp</code>	<code>\acfp</code>	<code>\glSxtrfullpl</code>
<code>\Ab</code>	<code>\Ac</code>	<code>\cglS</code>
<code>\Abp</code>	<code>\Acp</code>	<code>\cglSpl</code>
<code>\As</code>	<code>\Acs</code>	<code>\GlSxtrshort</code>
<code>\Asp</code>	<code>\Acsp</code>	<code>\GlSxtrshortpl</code>
<code>\Al</code>	<code>\Acl</code>	<code>\GlSxtrlong</code>
<code>\Alp</code>	<code>\Aclp</code>	<code>\GlSxtrlongpl</code>
<code>\Af</code>	<code>\Acf</code>	<code>\GlSxtrfull</code>
<code>\Afp</code>	<code>\Acfp</code>	<code>\GlSxtrfullpl</code>
<code>\AB</code>	<code>\AC</code>	<code>\cGLS</code>
<code>\ABP</code>	<code>\ACP</code>	<code>\cGLSpl</code>
<code>\AS</code>	<code>\ACS</code>	<code>\GLSxtrshort</code>
<code>\ASP</code>	<code>\ACSP</code>	<code>\GLSxtrshortpl</code>
<code>\AL</code>	<code>\ACL</code>	<code>\GLSxtrlong</code>
<code>\ALP</code>	<code>\ACLp</code>	<code>\GLSxtrlongpl</code>
<code>\AF</code>	<code>\ACF</code>	<code>\GLSxtrfull</code>
<code>\AFP</code>	<code>\ACFP</code>	<code>\GLSxtrfullpl</code>
<code>\newabbr</code>	<code>\newabbr</code>	<code>\newabbreviation</code>

### 4.4 Predefined Abbreviation Styles

There are two types of abbreviation styles: those that treat the abbreviation as a regular entry (so that `\gls` uses `\glsgenentryfmt`) and those that don't treat the abbreviation as a regular entry (so that `\gls` uses `\glSxtrgenabbrvfmt`).

The regular entry abbreviation styles set the `regular` attribute to “true” for the category assigned to each abbreviation with that style. This means that on **first use**, `\gls` uses the value of the first

field and on subsequent use `\gls` uses the value of the text field (and analogously for the plural and case-changing versions). The short and long fields are set as appropriate and may be accessed through commands like `\glsxtrshort`.

The other abbreviation styles don't modify the **regular** attribute. The first and text fields (and their plural forms) are set and can be accessed through commands like `\glsfirst`, but they aren't used by commands like `\gls`, which instead use the short form (stored in the short key) and the display full format (through commands like `\glsxtrfullformat` that are defined by the style).

In both cases, the **first use** of `\gls` may not match the text produced by `\glsfirst` (and likewise for the plural and case-changing versions).

The sample file `sample-abbr-styles.tex` demonstrates all predefined styles described here.

For the “sc” styles that use `\textsc`, be careful about your choice of fonts as some only have limited support. For example, you may not be able to combine bold and small-caps. I recommend that you at least use the `fontenc` package with the `T1` option or something similar.

Many of the styles have helper commands in the form `\glsxtr...name` and `\glsxtr...sort` that are expanded within the name and sort fields when the abbreviation is defined. These commands may use the helper token registers available within `\newabbreviation`, such as `\glsshorttok`. The contents of a register can be accessed with `\the<register>`. It's essential that these expand when the abbreviation is defined so don't hide them behind no-expandable content if you redefine these helper commands.

The parenthetical styles, such as **long-short**, use

```
\glsxtrparen{<text>}
```

to set the parenthetical material. This just puts parentheses around the text: (`<text>`).

The basic abbreviation styles, such as **long-short** and **short-long** use

```
\glsabbrvdefaultfont{<text>}
```

for the short form. This just does `<text>` by default. (That is, no font change is applied.) On first use,

```
\glsfirstabbrvdefaultfont{<text>}
```

is used instead. By default, this just does `\glsabbrvdefaultfont`. The long form is formatted according to

```
\glslongdefaultfont{<text>}
```

which again just does `<text>` (no font change). On first use,

```
\glsfirstlongdefaultfont{<text>}
```

is used instead. This just does `\glslongdefaultfont`. The plural suffix used for the short form is given by

```
\glstrabbrvpluralsuffix
```

which defaults to `\glspluralsuffix`.

The small-cap styles, such as `long-short-sc` and `short-sc-long`, use

```
\glsabbrvscfont{<text>}
```

which uses `\textsc`.<sup>1</sup> On first use

```
\glsfirstabbrvscfont{<text>}
```

is used instead. This uses `\glsabbrvscfont` by default. So redefine, `\glsabbrvscfont` to change first and subsequent uses or `\glsfirstabbrvscfont` to change just the first use.

The long form for the small-cap styles uses `\glslongdefaultfont` or `\glsfirstlongdefaultfont`, as with the basic style. The suffix is given by

```
\glstrscsuffix
```

This is defined as

```
\newcommand*{\glstrscsuffix}{\glstextup{\glstrabbrvpluralsuffix}}
```

The `\glstextup` command is provided by `glossaries` and is used to switch off the small caps font for the suffix. If you override the default short plural using the `shortplural` key when you define the abbreviation you will need to make the appropriate adjustment if necessary. (Remember that the default plural suffix behaviour can be modified through the use of the `aposplural` and `noshortplural` attributes. See Section 7 for further details.)

The small styles, such as `long-short-sm` and `short-sm-long`, use

```
\glsabbrvsmfont{<text>}
```

which uses `\textsmaller`. (This requires the `releases` package, which isn't loaded by `glossaries-extra`, so must be loaded explicitly.) On first use

```
\glsfirstabbrvsmfont{<text>}
```

is used instead. This uses `\glsabbrvsmfont` by default.

---

<sup>1</sup>For compatibility with earlier versions, `\glsabbrvscfont` is defined to `\glstrscfont`, which is defined to use `\textsc`. Direct use of `\glstrscfont` is now deprecated. Likewise for similar commands.

The long form for the smaller styles uses `\glslongdefaultfont` or `\glsfirstlongdefaultfont`, as with the basic style. The suffix is given by

```
\glsxtrmsuffix
```

which defaults to just `\glsxtrabbrvpluralsuffix`.

The “short-em” (emphasize short) styles, such as `long-short-em` or `short-em-long`, use

```
\glsabbrvemfont{<text>}
```

On first use

```
\glsfirstabbrvemfont{<text>}
```

is used instead. This uses `\glsabbrvemfont` by default. The suffix is given by

```
\glsxtremsuffix
```

which defaults to just `\glsxtrabbrvpluralsuffix`. The long form is as for the basic style unless the style is a “long-em” style.

The “long-em” (emphasize long) styles, such as `long-em-short-em` or `short-em-long-em`, use

```
\glsfirstlongemfont{<long-form>}
```

instead of `\glsfirstlongdefaultfont{<long-form>}` and

```
\gslongemfont{<long-form>}
```

instead of `\gslongdefaultfont{<long-form>}`. The first form `\glsfirstlongemfont` is initialised to use `\gslongemfont`.

The user styles have similar commands:

```
\glsabbrvuserfont{<text>}
```

for the short form,

```
\glsfirstabbrvuserfont{<text>}
```

for the first use short form,

```
\gslonguserfont{<text>}
```

for the long form,

```
\glsfirstlonguserfont{\langle text \rangle}
```

for the first use long form, and

```
\glsextrusersuffix
```

for the short plural suffix.

Similarly for the hyphen styles:

```
\glsabbrvhyphenfont{\langle text \rangle}
```

for the short form,

```
\glsfirstabbrvhyphenfont{\langle text \rangle}
```

for the first use short form,

```
\glslonghyphenfont{\langle text \rangle}
```

for the long form,

```
\glsfirstlonghyphenfont{\langle text \rangle}
```

for the first use long form, and

```
\glsextrhyphensuffix
```

for the short plural suffix.

Similarly for the “only” styles, such as **long-only-short-only**:

```
\glsabbrvonlyfont{\langle text \rangle}
```

for the short form,

```
\glsfirstabbrvonlyfont{\langle text \rangle}
```

for the first use short form,

```
\glslongonlyfont{\langle text \rangle}
```

for the long form,

```
\glsfirstlongonlyfont{\langle text \rangle}
```

for the first use long form, and

```
\glxtronlysuffix
```

for the short plural suffix.

The “short-sc-only” styles, such as **long-only-short-sc-only**:

```
\glsabbrvsonlyfont{<text>}
```

for the short form (which uses `\glsabbrvscfont`), and

```
\glsfirstabbrvsonlyfont{<text>}
```

which uses `\glsabbrvsonlyfont`. The short plural suffix is obtained from:

```
\glxtrsconlysuffix
```

This uses `\glxtrscsuffix`. For other font types, use the one of “short-only” styles and redefine `\glsabbrvonlyfont` as required. (The smallcaps style is a special case as its plural suffix is awkward.)

The “postshort-sc-user” styles, such as **long-postshort-sc-user**:

```
\glsabbrvscuserfont{<text>}
```

for the short form (which uses `\glsabbrvscfont`), and

```
\glsfirstabbrvscuserfont{<text>}
```

which uses `\glsabbrvscuserfont`. The short plural suffix is obtained from:

```
\glxtrscusersuffix
```

This uses `\glxtrscsuffix`.

Note that by default inserted material (provided in the final optional argument of commands like `\gls`), is placed outside the font command in the predefined styles. To move it inside, use:

```
\glxtrininsertinsidetrue
```

This applies to all the predefined styles. For example:

```
\setabbreviationstyle{long-short}  
\renewcommand*{\glsfirstlongdefaultfont}[1]{\emph{#1}}  
\glxtrininsertinsidetrue
```

This will make the long form and the inserted text emphasized, whereas the default (without `\glxtrininsertinsidetrue`) would place the inserted text outside of the emphasized font.

Note that for some styles, such as the **short-long**, the inserted text would be placed inside the font command for the short form (rather than the long form in the above example).



Remember that `\textsc` renders *lowercase* letters as small capitals. Uppercase letters are rendered as normal uppercase letters, so if you specify the short form in uppercase, you won't get small capitals unless you redefine `\glsabbrvscfont` to convert its argument to lowercase. For example:

```
\renewcommand*\glsabbrvscfont}[1]{\textsc{\MakeLowercase{#1}}}
```

If you want to easily switch between the “sc” and “sm” styles, you may find it easier to redefine this command to convert case:

```
\renewcommand*\glsabbrvscfont}[1]{\textsc{\MakeTextLowercase{#1}}}  
\renewcommand*\glsabbrvsmfont}[1]{\textsmaller{\MakeTextUppercase{#1}}}
```

Some of the styles use

```
\glsxtrfullsep{<label>}
```

as a separator between the long and short forms. This is defined as a space by default, but may be changed as required. For example:

```
\renewcommand*\glsxtrfullsep}[1]{~}
```

or

```
\renewcommand*\glsxtrfullsep}[1]{\glsacspace{#1}}
```

The new naming scheme for abbreviation styles is as follows:

- $\langle field1 \rangle [-\langle modifier1 \rangle] [-\text{post}] \langle field2 \rangle [-\langle modifier2 \rangle] [-\text{user}]$

This is for the parenthetical styles. The  $-\langle modifier \rangle$  parts may be omitted. These styles display  $\langle field1 \rangle$  followed by  $\langle field2 \rangle$  in parentheses. If  $\langle field1 \rangle$  or  $\langle field2 \rangle$  starts with “no” then that element is omitted from the display style (no parenthetical part) but is included in the inline style.

If the  $-\langle modifier \rangle$  part is present, then the field has a font changing command applied to it. The special modifier `-only` indicates that field is only present according to whether or not the entry has been used.

If `post` is present then  $\langle field2 \rangle$  is placed after the **link-text** using the post-link hook.

If the `-user` part is present, then the `user1` value, if provided, is inserted into the parenthetical material. (The field used for the inserted material may be changed.)

Examples:

- **long-noshort-sc**:  $\langle field1 \rangle$  is the long form, the short form is set in smallcaps but omitted in the display style.
- **long-em-short-em**: both the long form and the short form are emphasized. The short form is in parentheses.
- **long-short-em**: the short form is emphasized but not the long form. The short form is in parentheses.

- **long-short-user**: if the `user1` key has been set, this produces the style `<long>` (`<short>`, `<user1>`) otherwise it just produces `<long>` (`<short>`).
- **long-hyphen-postshort-hyphen**: the short form and the inserted material (provided by the final optional argument of commands like `\gls`) is moved to the post-link hook. The long form is formatted according to `\glslonghyphenfont` (or `\glsfirstlonghyphenfont` on first use). The short form is formatted according to `\glsabbrvhyphenfont` (or `\glsfirstabbrvhyphenfont` on first use).

- `<style>-noreg`

Some styles set the **regular** attribute. In some cases, there's a version of the style that doesn't set this attribute. For example, **long-em-noshort-em** sets the **regular** attribute. The **long-em-noshort-em-noreg** style is a minor variation that style that doesn't set the attribute.

There are a few “noshort” styles, such as **long-hyphen-noshort-noreg**, that have “-noreg” version without a regular version. This is because the style won't work properly with the **regular** set, but the naming scheme is maintained for consistency with the other “noshort” styles.

- `<field1>[-<modifier1>]-[post]footnote`

The display style uses `<field1>` followed by a footnote with the other field in it. If `post` is present then the footnote is placed after the **link-text** using the post-link hook. The inline style does `<field1>` followed by the other field in parentheses.

If `-<modifier1>` is present, `<field1>` has a font-changing command applied to it.

Examples:

- **short-footnote**: short form in the text with the long form in the footnote.
- **short-sc-postfootnote**: short form in smallcaps with the long form in the footnote outside of the link-text.

Take care with the footnote styles. Remember that there are some situations where `\footnote` doesn't work.

- `<style>-desc`

Like `<style>` but the description key must be provided when defining abbreviations with this style.

Examples:

- **short-long-desc**: like **short-long** but requires a description.
- **short-em-footnote-desc**: like **short-em-footnote** but requires a description.

Not all combinations that fit the above syntax are provided. Pre-version 1.04 styles that didn't fit this naming scheme are either provided with a synonym (where the former name wasn't ambiguous)

or provided with a deprecated synonym (where the former name was confusing). The deprecated style names generate a warning using:

```
\GlsXtrWarnDeprecatedAbbrStyle{<old-name>}{<new-name>}
```

where *<old-name>* is the deprecated name and *<new-name>* is the preferred name. You can suppress these warnings by redefining this command to do nothing.

#### 4.4.1 Predefined Abbreviation Styles that Set the Regular Attribute

The following abbreviation styles set the **regular** attribute to “true” for all categories that have abbreviations defined with any of these styles.

**short-nolong** This only displays the short form on **first use**. The name is set to the short form through the command

```
\glsxtrshortnolongname
```

(Similarly for the other `short<modifier>-nolong<modifier>` styles, unless indicated otherwise.) This command is expanded as the entry is defined, so any redefinition must be done before `\newabbreviation` (or `\newacronym`) for it to take effect. Make sure to `\protect` any formatting commands (or anything else that shouldn’t be expanded).

The description is set to the long form. The inline full form displays *<short>* (*<long>*). The long form on its own can be displayed through commands like `\glsxtrlong`.

**short** A synonym for **short-nolong**.

**nolong-short** Like **short-nolong** but the inline full form displays *<long>* (*<short>*).

**short-sc-nolong** Like **short-nolong** but redefines `\glsabbrvfont` to use `\glsabbrvscfont` (which defaults to `\textsc`).

**short-sc** A synonym for **short-sc-nolong**.

**nolong-short-sc** Like **short-sc-nolong** but the inline full form displays *<long>* (*<short>*). The name is still obtained from `\glsxtrshortnolongname` (similarly for the other styles in the form `nolong<modifier>-short<modifier>` unless indicated otherwise).

**short-sm-nolong** Like **short-nolong** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont` (which defaults to `\textsmaller`).

**short-sm** A synonym for **short-sm-nolong**.

**nolong-short-sm** Like **short-sm-nolong** but the inline full form displays *<long>* (*<short>*).

**short-em-nolong** Like **short-nolong** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.

**short-em** A synonym for **short-em-nolong**

**nolong-short-em** Like **short-em-nolong** but the inline full form displays  $\langle long \rangle$  ( $\langle short \rangle$ ).

**short-nolong-desc** Like the **short-nolong** style, but the name is set to the full form obtained by expanding

```
\glxtrshortdescname
```

(Similarly for the other  $\text{short}\langle modifier \rangle\text{-nolong}\langle modifier \rangle\text{-desc}$  styles, unless indicated otherwise.) This command is expanded when the entry is defined, so `\protect` fragile and formatting commands and only redefine this command before `\newabbreviation` (or `\newacronym`).

The description must be supplied by the user. You may prefer to use the **short-nolong** style with the post-description hook set to display the long form and override the description key. (See the sample file `sample-acronym-desc.tex`.)

**short-desc** A synonym for **short-nolong-desc**.

**short-sc-nolong-desc** Like **short-nolong** but redefines `\glsabbrvfont` to use `\glsabbrvscfont` (which defaults to `\textsc`).

**short-sc-desc** A synonym for **short-sc-nolong-desc**.

**short-sm-nolong-desc** Like **short-nolong-desc** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont` (which defaults to `\textsmaller`).

**short-sm-desc** A synonym for **short-sm-nolong-desc**.

**short-em-nolong-desc** Like **short-nolong-desc** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.

**short-em-desc** A synonym for **short-em-nolong-desc**.

**long-noshort-desc** This style only displays the long form, regardless of first or subsequent use of commands `\gls`. The short form may be accessed through commands like `\glxtrshort`. The inline full form displays  $\langle long \rangle$  ( $\langle short \rangle$ ).

The sort key are set to the long form. The name key is also set to the long form, but this is done by expanding

```
\glxtrlongnoshortdescname
```

(Similarly for the other  $\text{long}\langle modifier \rangle\text{-noshort}\langle modifier \rangle\text{-desc}$  styles, unless indicated otherwise.) This command should only be redefined before abbreviations are defined, and any fragile or formatting commands within it need protecting.

The description must be provided by the user. The predefined glossary styles won't display the short form. You can use the post-description hook to automatically append the short form to the description. The inline full form will display  $\langle long \rangle$  ( $\langle short \rangle$ ).

**long-desc** A synonym for **long-noshort-desc**.

**long-noshort-sc-desc** Like the **long-noshort-desc** style but the short form (accessed through commands like `\glxtrshort`) use `\glsabbrvscfont`. (This style was originally called `long-desc-sc`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**long-noshort-sm-desc** Like **long-noshort-desc** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`. (This style was originally called `long-desc-sm`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**long-noshort-em-desc** Like **long-noshort-desc** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`. The long form isn't emphasized. (This style was originally called `long-desc-em`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**long-em-noshort-em-desc** New to version 1.04, like **long-noshort-desc** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`. The long form uses `\glsfirstlongemfont` and `\glslongemfont`.

**long-noshort** This style doesn't really make sense if you don't use the short form anywhere in the document, but is provided for completeness. This is like the **long-noshort-desc** style, but the sort key is set to the short form. The name key is also set to the short form, but this is done by expanding

```
\glxtrlongnoshortname
```

(Similarly for other `long<modifier>-noshort<modifier>` styles, unless indicated otherwise.) This command should only be redefined before abbreviations are defined, and fragile or formatting commands should be protected.

The description is set to the long form.

**long** A synonym for **long-noshort**

**long-noshort-sc** Like the **long-noshort** style but the short form (accessed through commands like `\glxtrshort`) use `\glsabbrvscfont`. (This style was originally called `long-sc`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**long-noshort-sm** Like **long-noshort** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`. (This style was originally called `long-sm`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**long-noshort-em** This style is like **long-noshort** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`. The long form isn't emphasized. (This style was originally called `long-em`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**long-em-noshort-em** New to version 1.04, this style is like **long-noshort** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`, `\glsfirstlongfont` to use `\glsfirstlongemfont` and `\glslongfont` to use `\glslongemfont`. The short form isn't used by commands like `\gls`, but can be obtained using `\glsxtrshort`. The related style `long-em-noshort-em-noreg` doesn't set the **regular** attribute.

#### 4.4.2 Predefined Abbreviation Styles that Don't Set the Regular Attribute

The following abbreviation styles will set the **regular** attribute to “false” if it has previously been set. If it hasn't already been set, it's left unset. Other attributes may also be set, depending on the style.

**long-short** On **first use**, this style uses the format `<long> (<short>)`. The inline and display full forms are the same. The sort key is set to the short form. The name is also set to the short form through

```
\glsxtrlongshortname
```

(Similarly for other `long<modifier>-short<modifier>` styles, unless indicated otherwise.) Any redefinition of this command must come before the abbreviations are defined as it expands on definition. Make sure you protect any commands that shouldn't be expanded. The long form can be referenced with `\the\glslongtok` and the short form can be referenced with `\the\glsshorttok`.

The description is set to the long form. The long and short forms are separated by `\glsxtrfullsep`. If you want to insert material within the parentheses (such as a translation), try the **long-short-user** style.

**long-short-sc** Like **long-short** but redefines `\glsabbrvfont` to use `\glsabbrvscfont`.

**long-short-sm** Like **long-short** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`.

**long-short-em** Like **long-short** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.

**long-em-short-em** New to version 1.04, this style is like **long-short-em** but redefines `\glsfirstlongfont` to use `\glsfirstlongemfont`.

**long-only-short-only** New to version 1.17, this style only shows the long form on first use and only shows the short form on subsequent use. The inline full form `\glsxtrfull` shows the long form followed by the short form in parentheses. The name field is obtained from

```
\glsxtronlyname
```

Any redefinition of this command must come before the abbreviations are defined as it expands on definition. Make sure you protect any commands that shouldn't be expanded. The

long form can be referenced with `\the\glslongtok` and the short form can be referenced with `\the\glsshorttok`.

**long-only-short-sc-only** New to version 1.48, this is like `long-only-short-only` but uses small-caps for the short form. The name is obtained from:

```
\glxtrsconlyname
```

**long-only-short-only-desc** New to version 1.17, this style is like `long-only-short-only` but the user must supply the description. The name field is obtained from

```
\glxtronlydescname
```

The sort value is obtained from:

```
\glxtronlydescsort
```

Any redefinition of these commands must come before the abbreviations are defined as it expands on definition. Make sure you protect any commands that shouldn't be expanded. The long form can be referenced with `\the\glslongtok` and the short form can be referenced with `\the\glsshorttok`.

**long-only-short-sc-only-desc** New to version 1.48, this style is like `long-only-short-only-desc` but it uses smallcaps for the short form. The name is obtained from:

```
\glxtrsconlydescname
```

This defaults to `\glxtronlydescname`.

The sort value is obtained from:

```
\glxtrsconlydescsort
```

This defaults to `\glxtronlydescsort`.

**long-em-noshort-em-noreg** New to version 1.17, this style is like `long-em-noshort-em` but doesn't set the `regular` attribute.

**long-short-user** This style was introduced in version 1.04. It's like the `long-short` style but additional information can be inserted into the parenthetical material. This checks the value of the field given by

```
\glxtruserfield
```

(which defaults to `useri`) using `\ifglshasfield` (provided by `glossaries`). If the field hasn't been set, the style behaves like the `long-short` style and produces  $\langle long \rangle$  ( $\langle short \rangle$ ) but if the field has been set, the contents of that field are inserted within the parentheses in the form  $\langle long \rangle$  ( $\langle short \rangle$ ,  $\langle field-value \rangle$ ). The format is governed by

```
\glxtruserparen{\langle text \rangle}{\langle label \rangle}
```

where  $\langle text \rangle$  is the short form (for the `long-short-user` style) or the long form (for the `short-long-user` style). This command first inserts a space using `\glxtrfullsep` and then the parenthetical content (using `\glxtrparen`). The description is set to

```
\gluserdescription{\langle long \rangle}{\langle label \rangle}
```

The default definition ignores the  $\langle label \rangle$  and encapsulates  $\langle long \rangle$  with `\glslonguserfont`. The name is obtained by expanding `\glxtrlongshortname` (see above). The  $\langle text \rangle$  argument includes the font formatting command, `\glsfirstabbrvfont{\langle short \rangle}` in the case of the `long-short-user` style and `\glsfirstlongfont{\langle long \rangle}` in the case of the `short-long-user` style.

For example:

```
\setabbreviationstyle[acronym]{long-short-user}
\newacronym{tug}{TUG}{\TeX\ User Group}
\newacronym
[user1={German Speaking \TeX\ User Group}]
{dante}{DANTE}{Deutschsprachige Anwendervereinigung \TeX\ e.V}
```

On first use, `\gls{tug}` will appear as:

TeX User Group (TUG)

whereas `\gls{dante}` will appear as:

Deutschsprachige Anwendervereinigung TeX e.V (DANTE, German Speaking  
TeX User Group)

The short form is formatted according to

```
\glsabbrvuserfont{\langle text \rangle}
```

and the plural suffix is given by



```
\glxtrusersuffix
```

These may be redefined as appropriate. For example, if you want a smallcaps style, you can just set these commands to those used by the **long-short-sc** style:

```
\renewcommand{\glsabbruserfont}[1]{\glsabbrvscfont{#1}}  
\renewcommand{\glxtrusersuffix}{\glxtrscsuffix}
```

**long-noshort-noreg** This style is like **long-noshort** but it doesn't set the **regular** attribute.

**long-noshort-desc-noreg** This style is like **long-noshort-desc** but it doesn't set the **regular** attribute.

**long-short-desc** On **first use**, this style uses the format *<long>* (*<short>*). The inline and display full forms are the same. The name is set to the full form. The sort key is set to *<long>* (*<short>*). Before version 1.04, this was incorrectly set to the short form. If you want to revert back to this you can redefine

```
\glxtrlongshortdescsort
```

For example:

```
\renewcommand*{\glxtrlongshortdescsort}{\the\glsshorttok}
```

The description must be supplied by the user. The long and short forms are separated by `\glxtrfullsep`. The name field is obtained from

```
\glxtrlongshortdescname
```

(Similarly for other **long<modifier>-short<modifier>-desc** styles, unless indicated otherwise.) Any redefinition of this command must come before the abbreviations are defined as it expands on definition. Make sure you protect any commands that shouldn't be expanded. The long form can be referenced with `\the\glslongtok` and the short form can be referenced with `\the\glsshorttok`.

**long-short-sc-desc** Like **long-short-desc** but redefines `\glsabbrvfont` to use `\glsabbrvscfont`.

**long-short-sm-desc** Like **long-short-desc** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`.

**long-short-em-desc** Like **long-short-desc** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.

**long-em-short-em-desc** New to version 1.04, this style is like **long-short-em-desc** but redefines `\glsfirstlongfont` to use `\glsfirstlongemfont`.

**long-em-noshort-em-desc-noreg** New to version 1.17, this style is like **long-em-noshort-em-desc** but doesn't set the **regular** attribute.

**long-short-user-desc** New to version 1.04, this style is like a cross between the **long-short-desc** style and the **long-short-user** style. The display and inline forms are as for **long-short-user** and the name key is obtained from

```
\glxtrlongshortuserdescname
```

Again, this should only be redefined before `\newabbreviation` (or `\newacronym`), and fragile and formatting commands need protecting.

The description key must be supplied in the optional argument of `\newabbreviation` (or `\newacronym`). The sort key is set to `<long>` (`<short>`) as per the **long-short-desc** style.

**short-nolong-noreg** This is like **short-nolong** but doesn't set the **regular** attribute.

**nolong-short-noreg** This is like **nolong-short** but doesn't set the **regular** attribute.

**short-long** On **first use**, this style uses the format `<short>` (`<long>`). The inline and display full forms are the same. The name and sort keys are set to the short form. The description is set to the long form. The short and long forms are separated by `\glxtrfullsep`. If you want to insert material within the parentheses (such as a translation), try the **short-long-user** style.

The name field is obtained from

```
\glxtrshortlongname
```

(Similarly for other `short<modifier>-long<modifier>` styles, unless indicated otherwise.) Any redefinition of this command must come before the abbreviations are defined as it expands on definition. Make sure you protect any commands that shouldn't be expanded. The long form can be referenced with `\the\glslongtok` and the short form can be referenced with `\the\glsshorttok`.

**short-sc-long** Like **short-long** but redefines `\glsabbrvfont` to use `\glsabbrvscfont`.

**short-sm-long** Like **short-long** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`.

**short-em-long** Like **short-long** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.

**short-em-long-em** New to version 1.04, this style is like **short-em-long** but redefines `\glsfirstlongfont` to use `\glsfirstlongemfont`.

**short-long-user** New to version 1.04. This style is like the **long-short-user** style but with the long and short forms switched. The parenthetical material is governed by the same command `\glxtruserparen`, but the first argument supplied to it is the long form instead of the short form. The name field is obtained by expanding

`\glsxtrshortlongname`

Again, this should only be redefined before `\newabbreviation` (or `\newacronym`) and commands that should be expanded need to be protected. The description is set to `\glsuserdescription{<long>}{<label>}`.

**short-nolong-desc-noreg** This style is like `short-nolong-desc` but it doesn't set the `regular` attribute.

**short-long-desc** On **first use**, this style uses the format `<short> (<long>)`. The inline and display full forms are the same. The name is set to the full form. The description must be supplied by the user. The short and long forms are separated by `\glsxtrfullsep`. The name field is obtained from

`\glsxtrshortlongdescname`

(Similarly for other `short<modifier>-long<modifier>-desc` styles, unless indicated otherwise.) Any redefinition of this command must come before the abbreviations are defined as it expands on definition. Make sure you protect any commands that shouldn't be expanded. The long form can be referenced with `\the\glslongtok` and the short form can be referenced with `\the\glsshorttok`.

**short-sc-long-desc** Like `short-long-desc` but redefines `\glsabbrvfont` to use `\glsabbrvscfont`.

**short-sm-long-desc** Like `short-long-desc` but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`.

**short-em-long-desc** Like `short-long-desc` but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.

**short-em-long-em-desc** New to version 1.04, this style is like `short-em-long-desc` but redefines `\glsfirstlongfont` to use `\glsfirstlongemfont`.

**short-long-user-desc** New to version 1.04, this style is like a cross between the `short-long-desc` style and the `short-long-user` style. The display and inline forms are as for `short-long-user`, but the name key is obtained from

`\glsxtrshortlonguserdescname`

Again, this should only be redefined before `\newabbreviation` (or `\newacronym`), and fragile and formatting commands need protecting.

The description key must be supplied in the optional argument of `\newabbreviation` (or `\newacronym`).

**short-footnote** On first use, this style displays the short form with the long form as a footnote. This style automatically sets the `nohyperfirst` attribute to "true" for the supplied category, so

the first use won't be hyperlinked (but the footnote marker may be, if the hyperref package is used).

The inline full form uses the *⟨short⟩* (*⟨long⟩*) style. The name is set to the short form. The description is set to the long form. The name key is obtained by expanding:

```
\glstrfootnotename
```

(Similarly for other *short⟨modifier⟩-⟨modifier⟩footnote* styles, unless indicated otherwise.) Again, this command should only be redefined before `\newabbreviation` (or `\newacronym`), and fragile or formatting commands should be protected from expansion.

As from version 1.05, all the footnote styles use:

```
\glstfirstlongfootnotefont{⟨text⟩}
```

to format the long form on **first use** or for the full form and

```
\glslongfootnotefont{⟨text⟩}
```

to format the long form elsewhere (for example, when used with `\glstxtrlong`).

As from version 1.07, all the footnote styles use:

```
\glstxtrabbrvfootnote{⟨label⟩}{⟨long⟩}
```

By default, this just does `\footnote{⟨long⟩}` (the first argument is ignored). For example, to make the footnote text link to the relevant place in the glossary:

```
\renewcommand{\glstxtrabbrvfootnote}[2]{%  
  \footnote{\glshyperlink[#2]{#1}}%  
}
```

or to include the short form with a hyperlink:

```
\renewcommand{\glstxtrabbrvfootnote}[2]{%  
  \footnote{\glshyperlink[\glstfmtshort{#1}]{#1}: #2}%  
}
```

Note that I haven't used commands like `\glstxrshort` to avoid interference (see Section 2.4 and Section 2.8).

**footnote** A synonym for **short-footnote**.

**short-sc-footnote** Like **short-footnote** but redefines `\glstabbrvfont` to use `\glstabbrvscfont`. (This style was originally called `footnote-sc`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**short-sc-footnote** Like **short-footnote** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`. (This style was originally called `footnote-sm`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**short-em-footnote** Like **short-footnote** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`. (This style was originally called `footnote-em`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)

**short-footnote-desc** (New to v1.42.) This is similar to **short-footnote**, but the description must be supplied by the user. The name field is obtained from:

```
\glsxtrfootnotedesname
```

which defaults to `<short>` followed by `<long>` in parentheses, and the sort field is obtained from:

```
\glsxtrfootnotedesort
```

which defaults to just the short form. (Similarly for other `short<modifier>-[post]footnote-desc` styles, unless indicated otherwise.)

Any redefinition of these commands must come before the abbreviations are defined as it expands on definition. Make sure you protect any commands that shouldn't be expanded. The long form can be referenced with `\the\glslongtok` and the short form can be referenced with `\the\glsshorttok`.

**footnote-desc** A synonym for **short-footnote-desc**.

**short-sc-footnote-desc** Like **short-footnote-desc** but redefines `\glsabbrvfont` to use `\glsabbrvscfont`.

**short-sm-footnote-desc** Like **short-footnote-desc** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`.

**short-em-footnote-desc** Like **short-footnote-desc** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.

**short-postfootnote** This is similar to the **short-footnote** style but doesn't modify the category attribute. Instead it changes `\glsxtrpostlink<category>` to insert the footnote after the **link-text** on **first use**. This will also defer the footnote until after any following punctuation character that's recognised by `\glsxtrifnextpunc`.

The inline full form uses the `<short>` (`<long>`) style. The name is set to the short form. The description is set to the long form. Note that this style will change `\glsxtrfull` (and its variants) so that it fakes non-first use. (Otherwise the footnote would appear after the inline form.)

**postfootnote** A synonym for **short-postfootnote**.

- short-sc-postfootnote** Like **short-postfootnote** but redefines `\glsabbrvfont` to use `\glsabbrvscfont`. (This style was originally called `postfootnote-sc`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)
- short-sm-postfootnote** Like **short-postfootnote** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`. (This style was originally called `postfootnote-sm`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)
- short-em-postfootnote** Like **short-postfootnote** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`. (This style was originally called `postfootnote-em`. Renamed in version 1.04, but original name retained as a deprecated synonym for backward-compatibility.)
- short-postfootnote-desc** (New to v1.42.) This is similar to **short-postfootnote**, but the description must be supplied by the user. The name and sort are set as for **short-footnote-desc**.
- postfootnote-desc** A synonym for **short-postfootnote-desc**.
- short-sc-postfootnote-desc** Like **short-postfootnote-desc** but redefines `\glsabbrvfont` to use `\glsabbrvscfont`.
- short-sm-postfootnote-desc** Like **short-postfootnote-desc** but redefines `\glsabbrvfont` to use `\glsabbrvsmfont`.
- short-em-postfootnote-desc** Like **short-postfootnote-desc** but redefines `\glsabbrvfont` to use `\glsabbrvemfont`.
- short-postlong-user** This style was introduced in version 1.12. It's like the **short-long-user** style but defers the parenthetical material to after the link-text. This means that you don't have such a long hyperlink (which can cause problems for the DVI  $\LaTeX$  format) and it also means that the user supplied material can include a hyperlink to another location. The name key is obtained from `\glsxtrshortlongname`.
- short-postlong-user-desc** This style was introduced in version 1.12. It's like the above **short-postlong-user** style but the description must be specified. The name is obtained from `\glsxtrshortlonguserdescname`.
- long-postshort-user** This style was introduced in version 1.12. It's like the above **short-postlong-user** style but the long form is shown first and the short form is in the parenthetical material (as for **long-short-user**) style.
- long-postshort-user-desc** This style was introduced in version 1.12. It's like the above **long-postshort-user** style but the description must be specified. The name is obtained from `\glsxtrlongshortuserdescname`.
- long-postshort-sc-user** This style (new to v1.48) is like **long-postshort-user** but uses smallcaps for the short form.

**long-postshort-sc-user-desc** This style (new to v1.48) is like **long-postshort-user-desc** but uses smallcaps for the short form.

**long-hyphen-short-hyphen** This style (new to v1.17) is designed to work with the **markwords** category attribute. The full form is formatted using

```
\glsextrlonghyphenshort{<label>}{<long>}{<short>}{<insert>}
```

where *<insert>* is the inserted material provided in the final optional argument of commands like `\insert`. If *<insert>* start with a hyphen, then this locally redefines `\glsextrwordsep` to a hyphen, which means that if the **markwords** attribute is set then the long form will become hyphenated. (If this attribute isn't set, there's no alteration to the way the long form is displayed.) The name key is obtained from `\glsextrlongshortname`.

Unlike the other *<long>* (*<short>*) type of styles, such as **long-short**, this style also repeats the insertion in the parenthetical part, so that the first use form is:

```
\glsfirstlonghyphenfont{<long>}{<insert>}(\glsfirstabbrvhyphenfont  
{<short>}{<insert>})
```

The space before the parenthetical material is actually given by `\glsextrfullsep{<label>}` which defaults to a space. The *<insert>* may be moved into the formatting commands according to the conditional `\ifglsextrininsertinside`.

For example, if `ip` is defined using:

```
\glssetcategoryattribute{english}{markwords}{true}  
\setabbreviationstyle[english]{long-hyphen-short-hyphen}  
\newabbreviation[category=english]{ip}{IP}{Internet Protocol}
```

then

```
\gls{ip}[-Adressen]
```

will do

Internet-Protocol-Adressen (IP-Adressen)

on first use, whereas

```
\gls{ip}[ Address]
```

will do

Internet Protocol Address (IP Address)

on first use.

Note that the hyphenation isn't applied when using commands like `\glxtrlong`. This means that

```
\glxtrlong{ip}[-Adressen]
```

will do

Internet Protocol-Adressen

If the `markwords` attribute hadn't been set, then the first use of

```
\gls{ip}[-Adressen]
```

would do

Internet Protocol-Adressen (IP-Adressen)

instead.

If the inserted material *<insert>* is likely to contain commands like `\gls`, then use `long-hyphen-postshort-hyphen` instead to avoid nested links.

If you want the short version in small-caps, you can just redefine `\glsabbrvhyphenfont` and `\glxtrhyphensuffix` to use the small-caps versions. For example:

```
\renewcommand{\glsabbrvhyphenfont}{\glsabbrvscfont}  
\renewcommand{\glxtrhyphensuffix}{\glxtrscsuffix}
```

Similarly for other font-changing variations.

**long-hyphen-noshort-desc-noreg** New to version 1.17, this style is like `long-hyphen-short-hyphen-desc` except that the parenthetical part is omitted and the long form is displayed on subsequent use. The short form can be accessed with `\glxtrshort` but just uses the default abbreviation font. There's no regular version of this style as the regular form doesn't have the flexibility to deal with the hyphen switch. The name is obtained from `\glxtrlongnoshortdescname`.

**long-hyphen-noshort-noreg** New to version 1.17, this style is like `long-hyphen-noshort-desc-noreg` but the name is set to the short form and the description is set to the long form.

**long-hyphen-short-hyphen-desc** New to version 1.17. This is similar to `long-hyphen-short-hyphen` but the user supplies the description. The name is obtained from `\glxtrlongshortdescname`.

**long-hyphen-postshort-hyphen** New to version 1.17. This is similar to `long-hyphen-short-hyphen` but the inserted and parenthetical material are moved to the post-link hook. On first use, `\gls{<label>}[<insert>]` will do



`\glxtrlonghyphen{<long>}{<label>}{<insert>}\glxtrposthyphenshort{<label>}{<insert>}`

where

```
\glxtrposthyphenshort{<label>}{<insert>}
```

is in the post-link hook. This uses the format:

```
<insert> (\glsfirstabbrvhyphenfont{<short>}{<insert>})
```

The singular short form is always used here, even with `\glsp1`. (Unlike `long-hyphen-long-hyphen`.)

The part in the link-text on first use:

```
\glxtrlonghyphen{<long>}{<label>}{<insert>}
```

checks if `<insert>` starts with a hyphen. If it does, then `\glxtrwordsep` is locally redefined to a hyphen. This command only uses `<insert>` to test if it starts with a hyphen. The actual insertion code isn't typeset until the post-link hook and it's also localised, which means that you can use commands like `\gls` in `<insert>` for this style without causing nested hyperlinks, but only for commands like `\gls`.

Don't use `\gls` in the `<insert>` part for commands like `\glxtrfull`, `\glxtrshort` or `\glxtrlong`.

The inline full display format used by commands like `\glxtrfull` behaves differently to the first use of `\gls` with this style. It's better to use `\glsreset{<label>}\gls{<label>}` if you want to ensure the full format.

**long-hyphen-postshort-hyphen-desc** New to version 1.17. This is similar to `long-hyphen-postshort-hyphen` but the user supplies the description. The name is obtained from `\glxtrlongshortdescname`.

**short-hyphen-long-hyphen** This style (new to v1.17) is like `long-hyphen-short-hyphen`, except that the short form is displayed first followed by the long form in parentheses. The full form is formatted using

```
\glxtrshorthyphenlong{<label>}{<short>}{<long>}{<insert>}
```

which behaves in an analogous way to `\glxtrlonghyphenshort`. The name is obtained from `\glxtrshortlongname`.

**short-hyphen-long-hyphen-desc** New to version 1.17. This is similar to `short-hyphen-long-hyphen` but the user supplies the description. The name is obtained from `\glxtrshortlongdescname`.

**short-hyphen-postlong-hyphen** This style (new to v1.17) is like `long-hyphen-postshort-hyphen`, but the short form is displayed first followed by the long form in parentheses. On first use, `\gls{<label>}[<insert>]` will do

```
\glxtrshorthyphen{<short>}{<label>}{<insert>}\glxtrposthyphenlong{<label>}{<insert>}
```

where

```
\glxtrposthyphenlong{<label>}{<insert>}
```

is in the post-link hook. These commands behave in an analogous manner to those used with `long-hyphen-postshort-hyphen`. The name is obtained from `\glxtrshortlongname`.

Don't use `\gls` in the `<insert>` part for commands like `\glxtrfull`, `\glxtrshort` or `\glxtrlong`.

The inline full display format used by commands like `\glxtrfull` behaves differently to the first use of `\gls` with this style. It's better to use `\glsreset{<label>}\gls{<label>}` if you want to ensure the full format.

**short-hyphen-postlong-hyphen-desc** New to version 1.17. This is similar to `short-hyphen-postlong-hyphen` but the user supplies the description. The name is obtained from `\glxtrshortlongdescname`.

## 4.5 Defining New Abbreviation Styles

New abbreviation styles may be defined using:

```
\newabbreviationstyle{<name>}{<setup>}{<fmts>}
```

where `<name>` is the name of the new style (as used in the mandatory argument of `\setabbreviationstyle`). This is similar but not identical to the glossaries package's `\newacronymstyle` command.

You can't use styles defined by `\newacronymstyle` with `glossaries-extra` unless you have reverted `\newacronym` back to its generic definition from `glossaries` (using `\RestoreAcronyms`). The acronym styles from the `glossaries` package can't be used with abbreviations defined with `\newabbreviation`.

The `<setup>` argument deals with the way the entry is defined and may set attributes for the given abbreviation category. This argument should redefine

```
\CustomAbbreviationFields
```

to set the entry fields including the name (defaults to the short form if omitted), sort, first, first-plural. Other fields may also be set, such as text, plural and description.

`\CustomAbbreviationFields` is expanded by `\newabbreviation` so take care to protect commands that shouldn't be expanded.

For example, the `long-short` style has the following in `<setup>`:

```
\renewcommand*{\CustomAbbreviationFields}{%
  name={\protect\glsabbrvfont{\the\glsshorttok}},
  sort={\the\glsshorttok},
  first={\protect\glsfirstlongfont{\the\glslongtok}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \glsxtrparen{\protect\glsfirstabbrvfont{\the\glsshorttok}}},%
  firstplural={\protect\glsfirstlongfont{\the\glslongpltok}%
    \protect\glsxtrfullsep{\the\glslabeltok}%
    \glsxtrparen{\protect\glsfirstabbrvfont{\the\glsshortpltok}}},%
  plural={\protect\glsabbrvfont{\the\glsshortpltok}},%
  description={\the\glslongtok}}%
```

Note that the `first` and `firstplural` are set even though they're not used by `\gls`.

The basic styles, such as `long-short`, use commands like `\glsabbrvfont` (which are redefined whenever the style formatting is set) within `\CustomAbbreviationFields`. Other styles, such as `long-em-short-em` directly use their own custom commands, such as `\glsabbrvemfont`. With these styles, commands like `\glsabbrvfont` still need to be defined as appropriate in the `<fmts>` argument even if they're not used within `\CustomAbbreviationFields`.

The `<setup>` argument may also redefine

```
\GlsXtrPostNewAbbreviation
```

which can be used to assign attributes. (This will automatically be initialised to do nothing.)

For example, the `short-footnote` includes the following in `<setup>`:

```
\renewcommand*{\GlsXtrPostNewAbbreviation}{%
  \glssetattribute{\the\glslabeltok}{nohyperfirst}{true}%
  \glsattribute{\the\glslabeltok}{regular}%
  {%
```

```

\glssetattribute{\the\glslabeltok}{regular}{false}%
}%
{}%
}%

```

This sets the `nohyperfirst` attribute to “true”. It also unsets the `regular` attribute if it has previously been set. Note that the `nohyperfirst` attribute doesn’t get unset by other styles, so take care not to switch styles for the same category.

You can access the short, long, short plural and long plural values through the following token registers.

Short value (defined by glossaries):

```
\glsshorttok
```

Short plural value (defined by glossaries-extra):

```
\glsshortpltok
```

(This may be the default value or, if provided, the value provided by the user through the `shortplural` key in the optional argument of `\newabbreviation`.)

Long value (defined by glossaries):

```
\glslongtok
```

Long plural value (defined by glossaries-extra):

```
\glslongpltok
```

(This may be the default value or, if provided, the value provided by the user through the `longplural` key in the optional argument of `\newabbreviation`.)

The short or long values may be modified by attributes (such as `markwords`). The above registers reflect the modification. If you want to access the original (unmodified) short or long form (as provided in the final two arguments of `\newabbreviation`), then use the commands:

```
\glxtrorgshort
```

for the short form and

```
\glxtrorglong
```

for the long form. (These may be useful for the sort key to avoid any formatting that may be added by the attribute setting.)

There are two other registers available that are defined by glossaries:

```
\glslabeltok
```

which contains the entry's label and

```
\glskeylisttok
```

which contains the values provided in the optional argument of `\newabbreviation`.

Remember put `\the` in front of the register command as in the examples above. The category label can be access through the command (not a register):

```
\glscategorylabel
```

This may be used inside the definition of `\GlsXtrPostNewAbbreviation`.

If you want to base a style on an existing style, you can use

```
\GlsXtrUseAbbrStyleSetup{<name>}
```

where *<name>* is the name of the existing style. For example, the `long-noshort-sc-desc` style simply does

```
\GlsXtrUseAbbrStyleSetup{long-noshort-desc}
```

within *<setup>*.

The *<fmts>* argument deals with the way the entry is displayed in the document. This argument should redefine the following commands.

The default suffix for the plural short form (if not overridden by the `shortplural` key):

```
\abbrvpluralsuffix
```

(Note that this isn't used for the plural long form, which just uses the regular `\glspluralsuffix`.)

The font used for the short form on **first use** or in the full forms:

```
\glsfirstabbrvfont{<text>}
```

The font used for the short form on subsequent use or through commands like `\glsxtrshort`:

```
\glsabbrvfont{<text>}
```

The font used for the long form on first use or in the full forms:

```
\glsfirstlongfont{<text>}
```

The font used for the long form in commands like `\glsxtrlong` use:

```
\glslongfont{<text>}
```

Display full form singular no case-change (used by `\gls` on first use for abbreviations without the `regular` attribute set):

```
\glsxtrfullformat{<label>}{<insert>}
```

Display full form singular first letter converted to upper case (used by `\Gls` on `first use` for abbreviations without the `regular` attribute set):

```
\Glsxtrfullformat{<label>}{<insert>}
```

Display full form plural no case-change (used by `\glspl` on first use for abbreviations without the `regular` attribute set):

```
\glsxtrfullplformat{<label>}{<insert>}
```

Display full form plural first letter converted to upper case (used by `\Glspl` on first use for abbreviations without the `regular` attribute set):

```
\Glsxtrfullplformat{<label>}{<insert>}
```

In addition `<fmts>` may also redefine the following commands that govern the inline full formats. If the style doesn't redefine them, they will default to the same as the display full forms.

Inline singular no case-change (used by `\glsentryfull`, `\glsxtrfull` and `\Glsxtrfull`):

```
\glsxtrinlinefullformat{<label>}{<insert>}
```

Inline singular first letter converted to upper case (used by `\Glsentryfull` and `\Glsxtrfull`):

```
\Glsxtrinlinefullformat{<label>}{<insert>}
```

Inline plural no case-change (used by `\glsentryfullpl`, `\glsxtrfullpl` and `\Glsxtrfullpl`):

```
\glsxtrinlinefullplformat{<label>}{<insert>}
```

Inline plural first letter converted to upper case (used by `\Glsentryfullpl` and `\Glsxtrfullpl`):

```
\Glsxtrinlinefullplformat{<label>}{<insert>}
```

(New to version 1.17.) You can also modify the way the subsequent use is formatted by redefining the following four commands, but these won't be used for abbreviations with the `regular` attribute set. If the style doesn't redefine these commands, the default values are used.

Singular with no case-change:

```
\glxtrsubsequentfmt{<label>}{<insert>}
```

Singular with first letter upper case:

```
\Glsxtrsubsequentfmt{<label>}{<insert>}
```

Plural with no case-change:

```
\glxtrsubsequentplfmt{<label>}{<insert>}
```

Plural with first letter upper case:

```
\Glsxtrsubsequentplfmt{<label>}{<insert>}
```

If you want to provide support for glossaries-accsupp use the following `\glsaccess<xxx>` commands (Section 13.2) within the definitions of `\glxtrfullformat` etc instead of the analogous `\glstentry<xxx>` commands. (If you don't use glossaries-accsupp, they will just do the corresponding `\glstentry<xxx>` command.)

For example, the **short-long** style has the following in *fmts*:

```
\renewcommand*{\abbrvpluralsuffix}{\glxtrabbrvpluralsuffix}%
\renewcommand*{\glsabbrvfont}[1]{\glsabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstabbrvfont}[1]{\glsfirstabbrvdefaultfont{##1}}%
\renewcommand*{\glsfirstlongfont}[1]{\glsfirstlongdefaultfont{##1}}%
\renewcommand*{\glslongfont}[1]{\glslongdefaultfont{##1}}%
\renewcommand*{\glxtrfullformat}[2]{%
  \glsfirstabbrvfont{\glsaccessshort{##1}}\ifglxtrinsertinside##2\fi%
  \ifglxtrinsertinside\else##2\fi
  \glxtrfullsep{##1}%
  \glxtrparen{\glsfirstlongfont{\glsaccesslong{##1}}}%
}%
\renewcommand*{\glxtrfullplformat}[2]{%
  \glsfirstabbrvfont{\glsaccessshortpl{##1}}\ifglxtrinsertinside##2\fi%
  \ifglxtrinsertinside\else##2\fi
  \glxtrfullsep{##1}%
  \glxtrparen{\glsfirstlongfont{\glsaccesslongpl{##1}}}%
}%
\renewcommand*{\Glsxtrfullformat}[2]{%
  \glsfirstabbrvfont{\Glsaccessshort{##1}}\ifglxtrinsertinside##2\fi%
  \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\glsfirstlongfont{\Glsaccesslong{##1}}}%
}%
\renewcommand*{\Glsxtrfullplformat}[2]{%
  \glsfirstabbrvfont{\Glsaccessshortpl{##1}}\ifglxtrinsertinside##2\fi%
  \ifglxtrinsertinside\else##2\fi\glxtrfullsep{##1}%
  \glxtrparen{\glsfirstlongfont{\Glsaccesslongpl{##1}}}%
}%
```

Since the inline full commands aren't redefined, they default to the same as the display versions.

If you want to base a style on an existing style, you can use

```
\GlsXtrUseAbbrStyleFmts{<name>}
```

within  $\langle fmts \rangle$ , where  $\langle name \rangle$  is the name of the existing style. For example, the `long-short-desc` style has the following in  $\langle fmts \rangle$ :

```
\GlsXtrUseAbbrStyleFmts{long-short}%
```

Here's an example of an abbreviation style that's based on `long-short` that displays the short form within `\textsf`:

```
\newabbreviationstyle
{custom-sf}% label
{% setup
  \GlsXtrUseAbbrStyleSetup{short-long}%
}%
{% fmts
  \GlsXtrUseAbbrStyleFmts{short-long}%
  \renewcommand*{\glsabbrvfont}[1]{\textsf{##1}}%
}
```

Note that this wouldn't work if it was instead based on one of the modified versions such as `short-sc-long` as they explicitly use their own formatting commands, such as `\glsabbrvemfont`. The base styles, such as `short-long`, use the more generic `\glsabbrvfont` etc which makes them easier to adapt than the modified styles.

For further details, see the "Abbreviations" section in the documented code (`glossaries-extra-code.pdf`).



## 5 Entries in Sectioning Titles, Headers, Captions and Contents

The glossaries user manual cautions against using commands like `\gls` in chapter or section titles. The principle problems are:

- if you have a table of contents, the **first use flag** will be unset in the contents rather than later in the document;
- if you have the location lists displayed in the glossary, unwanted locations will be added to it corresponding to the table of contents (if present) and every page that contains the entry in the page header (if the page style in use adds the chapter or section title to the header);
- if the page style in use adds the chapter or section title to the header and attempts to convert it to upper case, the entry label (in the argument of `\gls` etc) will be converted to upper case and the entry won't be recognised;
- if you use `hyperref`, commands like `\gls` can't be expanded to a simple string and only the label will appear in the PDF bookmark (with a warning from `hyperref`);
- if you use `hyperref`, you will end up with nested hyperlinks in the table of contents.

Similar problems can also occur with captions (except for the page header and bookmark issues).

### 5.1 Simplistic Approach

To get around all these problems, the glossaries user manual recommends using the expandable non-hyperlink commands, such as `\glsentrytext` (for regular entries) or `\glsentryshort` (for abbreviations). This is the simplest solution, but doesn't allow for special formatting that's applied to the entry through commands like `\glsstext` or `\glsxtrshort`. This means that if, for example, you are using one of the abbreviation styles that uses `\textsc` then the short form displayed with `\glsentryshort` won't use small caps. If you only have one abbreviation style in use, you can explicitly enclose `\glsentryshort{<label>}` in the argument of `\glsabbrvfont`, like this:

```
\chapter{A Chapter about \glsabbrvfont{\glsentryshort{html}}}
```

Or, if you are using `hyperref`:

```
\chapter{A Chapter about  
\texorpdfstring{\glsabbrvfont{\glsentryshort{html}}}{\glsentryshort{html}}}
```

Since this is a bit cumbersome, you might want to define a new command to do this for you. However, if you have mixed styles this won't work as commands like `\gls` and `\glsxtrshort` redefine `\glsabbrvfont` to match the entry's style before displaying it. In this case, the above example doesn't take into account the shifting definitions of `\glsabbrvfont` and will use whatever happens to be the last abbreviation style in use. More complicated solutions interfere with the upper casing used by the standard page styles that display the chapter or section title in the page header using `\MakeUppercase`.

The `glossaries-extra` package tries to resolve this by modifying `\markright` and `\markboth` and `\@starttoc`. If you don't like this change, you can restore their former definitions using

```
\glsxtrRevertMarks
```

If you only want to restore `\@starttoc` you can use:

```
\glsxtrRevertTocMarks
```

If you restore the header or table of contents commands, you'll have to use the `glossaries` manual's recommendations of either simply using `\glsentryshort` (as above) or use the sectioning command's option argument to provide an alternative for the table of contents and page header. For example:

```
\chapter[A Chapter about \glsentryshort{html}]{A Chapter about \gls{html}}
```

Alternatively, you need to find a way to insert `\glsxtrmarkhook` and `\@glsxtrinmark` at the start of the header or table of contents either scoped or afterwards cancelled with `\@glsxtrnotinmark` and `\glsxtrrestoremarkhook`.

If you don't revert the mark commands back with `\glsxtrRevertMarks`, you can use the commands described below in the argument of sectioning commands. You can still use them even if the mark commands have been reverted, but only where they don't conflict with the page style.

## 5.2 New Commands Designed for Chapter/Section Headings

The commands listed below are designed for use in chapter or section headings. There are still limitations, but they provide a better solution. They all use `\texorpdfstring` if `hyperref` has been loaded so that the expandable non-formatted version is added to the PDF bookmarks. Note that since the commands that convert the first letter to upper case aren't expandable, the non-case-changing version is used for the bookmarks. If the required field contains non-expandable (robust or fragile) commands that cause a problem for the bookmarks then `\texorpdfstring` will be needed as appropriate in that field. (Take care if the field has its value expanded before being assigned.)

These commands essentially behave as though you have used `\glsxtrshort`, `\glstext` etc with the options `noindex` and `hyper=false`. The text produced won't be converted to upper case in the page headings by default. If you want the text converted to upper case you need to set the `headuc` attribute to "true" for the appropriate category.

If you use one of the `\textsc` styles, be aware that the default fonts don't provide bold small-caps or italic small-caps. This means that if the chapter or section title style uses bold, this may override the small-caps setting, in which case the abbreviation will just appear as lower case bold. If the heading style uses italic, the abbreviation may appear in upright small-caps, *even if you have set the `headuc` attribute* since the all-capitals form still uses `\glsabbrvfont`. You may want to consider using the `slantsc` package in this case.

Display the short form:

```
\glsfmtshort{<label>}
```

Display the plural short form:

```
\glsfmtshortpl{<label>}
```

First letter upper case singular short form:

```
\Glsfmtshort{<label>}
```

(No case-change applied to PDF bookmarks.)

First letter upper case plural short form:

```
\Glsfmtshortpl{<label>}
```

(No case-change applied to PDF bookmarks.)

All caps singular short form:

```
\GLSfmtshort{<label>}
```

(No case-change applied to PDF bookmarks.)

All caps plural short form:

```
\Glsfmtshortpl{<label>}
```

(No case-change applied to PDF bookmarks.)

Display the long form:

```
\glsfmtlong{<label>}
```

Display the plural long form:

```
\glsfmtlongpl{<label>}
```

First letter upper case singular long form:

```
\Glsfmtlong{\label}
```

(No case-change applied to PDF bookmarks.)

First letter upper case plural long form:

```
\Glsfmtlongpl{\label}
```

(No case-change applied to PDF bookmarks.)

All caps singular long form:

```
\GLSfmtlong{\label}
```

(No case-change applied to PDF bookmarks.)

All caps plural long form:

```
\GLSfmtlongpl{\label}
```

(No case-change applied to PDF bookmarks.)

There are similar commands for the full form, but note that these use the *inline* full form, which may be different from the full form used by `\gls`. The PDF version has to be a simple fully expandable command, so one of two commands that are unrelated to the style is used instead:

```
\glspdffmtfull{\label}
```

for the singular form or:

```
\glspdffmtfullpl{\label}
```

for the full form. These simply do the long form followed by the short form in parentheses.

Display the full form:

```
\glsfmtfull{\label}
```

Display the plural full form:

```
\glsfmtfullpl{\label}
```

First letter upper case singular full form:

```
\Glsfmtfull{\label}
```

(No case-change applied to PDF bookmarks.)

First letter upper case plural full form:

```
\Glsfmtfullpl{\label}
```

(No case-change applied to PDF bookmarks.)

All caps singular full form:

```
\GLSfmtfull{\label}
```

(No case-change applied to PDF bookmarks.)

All caps plural full form:

```
\GLSfmtfullpl{\label}
```

(No case-change applied to PDF bookmarks.)

There are also equivalent commands for the value of the text field:

```
\glsfmttext{\label}
```

First letter converted to upper case:

```
\Glsfmttext{\label}
```

(No case-change applied to PDF bookmarks.)

All caps:

```
\GLSfmttext{\label}
```

(No case-change applied to PDF bookmarks.)

The plural equivalents:

```
\glsfmtplural{\label}
```

First letter upper case:

```
\Glsfmtplural{\label}
```

and all caps:

```
\GLSfmtplural{\label}
```

Likewise for the value of the name field:

```
\glsfmtname{\label}
```

First letter converted to upper case:

```
\Glsfmtname{\label}
```

(No case-change applied to PDF bookmarks.)

All caps:

```
\GLSfmtname{\label}
```

(No case-change applied to PDF bookmarks.)

Similarly for the value of the first field:

```
\glsfmtfirst{\label}
```

First letter converted to upper case:

```
\Glsfmtfirst{\label}
```

(No case-change applied to PDF bookmarks.)

All caps:

```
\GLSfmtfirst{\label}
```

(No case-change applied to PDF bookmarks.)

The plural equivalents:

```
\glsfmtfirstpl{\label}
```

First letter upper case:

```
\Glsfmtfirstpl{\label}
```

and all caps:

```
\GLSfmtfirstpl{\label}
```

## 6 Multi (or Compound) Entries

Nested entries (where the entry definition references other entries) are discussed in Section 2.8. This chapter deals with occasions where a term or phrase may consist of multiple sub-terms that are independently defined. (Examples in Section 6.1.5 and Section 6.1.6 provide workarounds for nested entries.)

For example, the names of bacteria, such as *Clostridium botulinum* and *Clostridium perfringens*, are made up of the genus (for example, *Clostridium*) and the species (for example, *botulinum* or *perfringens*). The genus is often abbreviated after **first use**. For example, *C. botulinum*. However, if the name is defined as a single term consisting of both the genus and species then it's not possible to apply the abbreviation when a different species with the same genus is used.

Consider the following document:

```
\documentclass{article}
\usepackage{glossaries-extra}
\setabbreviationstyle{long-only-short-only}
\newabbreviation{cbot}{C. botulinum}{Clostridium botulinum}
\newabbreviation{cperf}{C. perfringens}{Clostridium perfringens}
\begin{document}
\gls{cbot}, \gls{cbot}, \gls{cperf}.
\end{document}
```

The result is:

Clostridium botulinum, C. botulinum, Clostridium perfringens.

However, it should more typically be:

Clostridium botulinum, C. botulinum, C. perfringens.

In this case, the genus should actually be a separate definition:

```
\documentclass{article}
\usepackage{glossaries-extra}
\setabbreviationstyle{long-only-short-only}
\newabbreviation{clostridium}{C.}{Clostridium}
\newglossaryentry{botulinum}{name={botulinum},description={}}
\newglossaryentry{perfringens}{name=perfringens,description={}}
\begin{document}
\gls{clostridium} \gls{botulinum},
\gls{clostridium} \gls{botulinum},
\gls{clostridium} \gls{perfringens}.
\end{document}
```

This is quite awkward to write. This chapter describes how to provide a shortcut for this kind of construct. Each term should be defined as normal (as in the above example), and a “multi-entry” label is then defined with the list of labels of the entries that need to be referenced. This is done with the command:

```
\multiglossaryentry[<options>]{<multi-label>}[<main label>]{<label list>}
```

where *<multi-label>* is the new label and *<label list>* is the list of labels (corresponding to entries that have already been defined).

The *<main label>* may be omitted, in which case the main label will be assumed to be the final element in *<label list>*. If *<main label>* is present, it must also be listed in *<label list>*. This is described in more detail in Section 6.2.

The *<options>* are a comma-separated list of options to override the current settings and are described in Section 6.9.

The earlier example can now be modified to include the following:

```
\multiglossaryentry{cbot}{clostridium,botulinum}
\multiglossaryentry{cperf}{clostridium,perfringens}
```

These commands must come after the definitions of `clostridium`, `botulinum` and `perfringens`.

Once defined, a multi-entry set can be referenced using commands like:

```
\mgls[<options>]{<multi-label>}[<insert>]
```

This command essentially does `\gls{<label>}` for each item in the *<label list>* (with separators, see Section 6.4). If the final optional argument *<insert>* is provided, it will be applied to the final (non-skipped) element in the list. So the document body in the above example, can be rewritten as:

```
\mgls{cbot}, \mgls{cbot}, \mgls{cperf}.
```

There are some variants of `\mgls` listed in Section 6.11. The available *<options>* are listed in Section 6.10. They are applied after the `\multiglossaryentry` options and will override settings for the individual entries.

You can't use *<multi-label>* in commands like `\gls` as this label represents a set of entry labels not a single entry.

The `\multiglossaryentry` command will generate an error if the label has already been defined as a multi-entry. To do nothing if a multi-entry already exists, use:

```
\providemultiglossaryentry[<options>]{<multi-label>}[<main label>]{<label list>}
```

Notes and associated commands applying to `\multiglossaryentry` also apply to `\providemultiglossaryentry` unless otherwise stated.



`\multiglossaryentry` may be placed anywhere after the *<label list>* entries have been defined. A multi-entry label can't be referenced (with commands like `\mgls`) before it has been defined.

There is limited support for `docdef=true`. The multi-entry definition can be picked up from the aux file on the next run to allow cross-references in any glossaries that occur at the start of the document. Any changes made with commands like `\mglsSetMain` won't be carried over to the next run.

By default `\multiglossaryentry` will be localised to the current scope. If you want to globally define a multi-entry you need to first switch on global definitions with:

```
\multiglossaryentryglobaltrue
```

To switch back to local definitions use:

```
\multiglossaryentryglobalfalse
```

If you want to change the multi-entry options (locally) you can use:

```
\mglsSetOptions{<multi-label>}{<new-options>}
```

This removes the original options. If you want to (locally) append to the existing options, use:

```
\mglsAddOptions{<multi-label>}{<new-options>}
```

Note that `\multiglossaryentry` doesn't make any adjustments to the component entries. You will need to use the parent key when you define the entries if you want a hierarchical structure in your glossary. (See the example in Section 6.1.1.)

If you don't want the other elements in the glossary, you can suppress the indexing with `indexothers=false` (Section 6.9.1) or put them in an ignored glossary. For example:

```
\newignoredglossary{common}  
\newabbreviation[type=common]{clostridium}{C.}{Clostridium}
```

The *<multi-label>* can't be used in commands like `\gls` since the label refers to a set of entry labels not to an individual entry. Similarly, an individual entry label can't be used in commands like `\mgls`. It is possible (although potentially confusing) to use the same label for a multi-entry as for an individual entry (see the example in Section 6.1.6). Context will determine which is meant, except in the case of the cross-referencing fields (see, `seealso` and `alias`) where the cross-referenced label will first be tested if it's a known multi-entry label.

If you don't want to have to keep track of which labels refer to multi-entries and which refer to individual entries you can use:

```
\GlsXtrMglsOrGls{<mgls cs>}{<gls cs>}<modifier>[<options>]{<label>}
[<insert>]
```

where *<mgls cs>* is the `\mgls`-like command to use if *<label>* has been defined as a multi-entry and *<gls cs>* is the `\gls`-like command to use otherwise. The *<modifier>* may be omitted, otherwise it is the modifier that may be used with `\mgls` or `\gls` (\*, + or the character identified with `\GlsXtrSetAltModifier`). The modifier and remaining options are passed to the relevant command (*<mgls cs>* or *<gls cs>*).

You may prefer to define your own shortcut commands for common combinations. For example:

```
\newcommand{\ac}{\GlsXtrMglsOrGls{\mgls}{\gls}}
\newcommand{\acpl}{\GlsXtrMglsOrGls{\mglsmainpl}{\glspl}}
\newcommand{\Ac}{\GlsXtrMglsOrGls{\Mgls}{\Gls}}
\newcommand{\Acpl}{\GlsXtrMglsOrGls{\Mglsmainpl}{\Glspl}}
```

## 6.1 Examples

### 6.1.1 Example: Hierarchical

Bacteria names are represented by the genus (for example, Clostridium) followed by the species (for example, botulinum). This example has the genus as a parent of the species.

```
\documentclass{article}

\usepackage[colorlinks]{hyperref}
\usepackage[stylemods=bookindex,style=bookindex]{glossaries-extra}

\makeglossaries

\newcommand{\latinname}[1]{\emph{#1}}
\glssetcategoriesattributes
{genus,species}{textformat,glossnamefont}{latinname}

\setabbreviationstyle[genus]{long-only-short-only-desc}
\newabbreviation
[category=genus,description={}]
{clostridium}{C.}{Clostridium}

\newglossaryentry{botulinum}{name=botulinum,category=species,
description={},parent=clostridium}
\newglossaryentry{perfringens}{name=perfringens,category=species,
description={},parent=clostridium}
\newglossaryentry{tetani}{name=tetani,category=species,
description={},parent=clostridium}

\multiglossaryentry{cbot}{clostridium,botulinum}
\multiglossaryentry{cperf}{clostridium,perfringens}
\multiglossaryentry{ctet}{clostridium,tetani}
```

```

\multiglossaryentrysetup{indexothers=false,hyper=allmain}

\begin{document}
First use:
\mgl{s}{cbot}, \mgl{s}{cperf}, \mgl{s}{ctet}.

Next use:
\mgl{s}{cbot}, \mgl{s}{cperf}, \mgl{s}{ctet}.
\printglossaries
\end{document}

```

This suppresses the indexing of the non-main elements (in this case, the genus). However the genus is included in the glossary (without a **number list**) because it's the parent of the species (which are indexed).

The `hyper=allmain` option makes the entire content of each `\mgl{s}` a hyperlink to the main entry in the glossary. The resulting document text (before the glossary) is:

First use: *Clostridium botulinum*, *C. perfringens*, *C. tetani*.  
Next use: *C. botulinum*, *C. perfringens*, *C. tetani*.

### 6.1.2 Example: Suffix

This example has a minor modification to the previous one. In this case the multi-entries are defined with a suffix:

```

\multiglossaryentry[firstsuffix=botulism]{cbot}{clostridium,botulinum}
\multiglossaryentry[firstsuffix={gas gangrene}]{cperf}{clostridium,perfringens}
\multiglossaryentry[firstsuffix=tetanus]{ctet}{clostridium,tetani}

```

The rest of the document is as in Section 6.1.1. The document text is now:

First use: *Clostridium botulinum* (botulism), *C. perfringens* (gas gangrene), *C. tetani* (tetanus).  
Next use: *C. botulinum*, *C. perfringens*, *C. tetani*.

### 6.1.3 Example: Category Suffix

This is an alternative to the previous example. Instead of storing the extra information in the `firstsuffix` key, the information is stored in the `user1` key of the last element (the species). A category suffix is used to look up the field and print it.

```

\newglossaryentry{botulinum}{name=botulinum,category=species,
  user1={botulism},
  description={},parent=clostridium}
\newglossaryentry{perfringens}{name=perfringens,category=species,
  user1={gas gangrene},
  description={},parent=clostridium}

```

```

\newglossaryentry{tetani}{name=tetani,category=species,
  user1={tetanus},
  description={},parent=clostridium}

\mglstdefcategorysuffix{bacteria}{%
  \mglstisfirstuse
  {\glstxtrifhasfield{useri}{\mglstlastelementlabel}{ (\glstcurrentfieldvalue)}}}%
  {}%
}

\multiglossaryentry[category=bacteria]{cbot}{clostridium,botulinum}
\multiglossaryentry[category=bacteria]{cperf}{clostridium,perfringens}
\multiglossaryentry[category=bacteria]{ctet}{clostridium,tetani}

```

The result is the same as the previous example.

### 6.1.4 Example: Separators

The first example (Section 6.1.1) can be modified so that the species are also abbreviations. In this case, the separators are modified to suppress the space (`\relax`) if both the genus and species are abbreviated, or to use a non-breaking space `~` between the genus short form (shown on subsequent use) and the species long form (shown on first use). If the genus is showing the long form (first use) then a normal space is used.

Note that the separator attributes apply to the category of the element before the separator (not to the multi-entry category).

```

\glstsetcategoryattribute{genus}{combinedfirstsepfirst}{\space}
\glstsetcategoryattribute{genus}{combinedfirstsep}{\space}
\glstsetcategoryattribute{genus}{combinedsepfirst}{~}
\glstsetcategoryattribute{genus}{combinedsep}{\relax}

\setabbreviationstyle[species]{long-only-short-only-desc}

\newabbreviation[category=species,
  description={},parent=clostridium]{botulinum}{bot.}{botulinum}
\newabbreviation[category=species,
  description={},parent=clostridium]{perfringens}{per.}{perfringens}
\newabbreviation[,category=species,
  description={},parent=clostridium]{tetani}{tet.}{tetani}

```

This will cause a double dot at the end of the second sentence, which can be suppressed using the `discardperiod` and `retainfirstuseperiod` attributes.

```

\glstsetcategoriesattributes{species}{discardperiod,retainfirstuseperiod}{true}

```

This works because the final element's post-link hook is transferred to the multi-entry post-link hook, which can detect the sentence terminating period. If the post-link hook settings are changed, for example, to `postlinks=all,mpostlink=false` then the feature won't work as the final element's

post-link hook can't detect the period (because `\gls` is embedded too deeply inside the internal workings of `\mgls`).

The result is:

First use: Clostridium botulinum, C. perfringens, C. tetani.

Next use: C.bot., C.per., C.tet.

### 6.1.5 Example: Skipping Elements (Fragment Element)

This example is an alternative way of dealing with nested links (see Section 2.8).

```
\documentclass{article}

\usepackage[colorlinks]{hyperref}
\usepackage[stylemods,style=long]{glossaries-extra}

\makeglossaries

\setabbreviationstyle{long-short-sc}
\newabbreviation{ssi}{ssi}{server-side includes}
\newabbreviation{html}{html}{hypertext markup language}

\setabbreviationstyle[combinedabbrv]{long-only-short-sc-only}
\newabbreviation
  [category=combinedabbrv,
  description={\glsxtrshort{ssi} enabled \glsxtrshort{html}}]
  {shtml-frag}{shtml}{enabled}

\glssetcategoryattribute{combinedabbrv}{multioptions}
  {usedskipothers,firstsuffix={\glsxtrshort{\mglslastmainlabel}}}

\multiglossaryentry
  [category={combinedabbrv}]
  {shtml}[shtml-frag]{ssi,shtml-frag,html}

\begin{document}
Individual elements first use: \gls{ssi} and \gls{html}.

Individual elements next use: \gls{ssi} and \gls{html}.

Multi-entry first use: \mgls{shtml}.

Multi-entry next use: \mgls{shtml}.

Resetting all\glsresetall\mglsreset{shtml}:

Multi-entry first use: \mgls{shtml}.

Multi-entry next use: \mgls{shtml}.
```

```
Individual elements: \gls{ssi} and \gls{html}.
\printglossaries
\end{document}
```

This uses the **multioptions** attribute to skip “other” elements on subsequent use. The problematic abbreviation (SHTML) is defined as a fragment that simply expands to “enabled” on first use. Note that the description has to be supplied for the glossary.

The above produces (underlining added to mark the hyperlinks):

Individual elements first use: server-side includes (ssi) and hypertext markup language (HTML).

Individual elements next use: ssi and HTML.

Multi-entry first use: ssi enabled HTML (SHTML).

Multi-entry next use: SHTML.

Resetting all:

Multi-entry first use: server-side includes (ssi) enabled hypertext markup language (HTML) (SHTML).

Multi-entry next use: SHTML.

Individual elements: ssi and HTML.

The key difference here from the example using `\glsps` at the end of Section 2.8 is that the individual elements hyperlink to their respective entries in the glossary on first use of `\gls`.

The problem is that with the **colorlinks** package option, it’s not obvious where the hyperlinks start and end. The suffix (SHTML) will hyperlink to the “shtml” entry in the glossary, so the “enabled” hyperlink is redundant. The simplest fix for this is to add `hyper=notmainfirst` to the option list, which will prevent “enabled” from being a hyperlink.

Another problem occurs where `\gls` is used before the individual elements are used, which leads to their full expansion with a confusing amount of parentheses. A simple solution is to use the option `mglsopts=unsetothers`, which will unset the other (not-main) elements first. This can be localised with `presetlocal` but `\gls` will then unset the **first use flag** globally, which means that the other elements won’t show the full form when they are first used on their on after `\gls`. This can be switched to a local unset with `others=local`.

The complete set of options are now:

```
\glssetcategoryattribute{combinedabbrv}{multioptions}
{%
  hyper=notmainfirst,
  mglsopts={presetlocal,unsetothers,others={local}},
  usedskipothers,
  firstsuffix={\glsxtrshort{\mglslastmainlabel}}
}
```

This now produces (underlining added to mark the hyperlinks):

Individual elements first use: server-side includes (ssi) and hypertext markup language (HTML).

Individual elements next use: ssi and HTML.

Multi-entry first use: ssi enabled HTML (SHTML).

Multi-entry next use: SHTML.

Resetting all:

Multi-entry first use: ssi enabled HTML (SHTML).

Multi-entry next use: SHTML.

Individual elements: server-side includes (ssi) and hypertext markup language (HTML).

This method still has two main drawbacks: the description must be added manually and the long form can't be accessed with `\glsxtrlong`. The next example provides an alternative approach.

### 6.1.6 Example: Skipping Elements (Prefix and Post-Link Hooks)

This is a modified version of the previous example. In this case, the main element isn't a fragment and also happens to have the same label as the multi-entry set. (`\mgl{shtml}` references the multi-entry label and `\gls{shtml}` references the individual entry.)

In this case, the nested parts are marked up with custom commands:

```
\newrobustcmd{\combinedpre}[1]{\glsps{#1}}
\newrobustcmd{\combinedpost}[1]{\glsps{#1}}
```

```
\newabbreviation{shtml}{shtml}
{ }\combinedpre{ssi} enabled \combinedpost{html}}
```

This means that it's no longer necessary to manually insert the description and the long form can be accessed as usual with `\glsxtrshort{shtml}`. Note that it is necessary to define the custom commands robustly otherwise they will need to be protected against premature expansion:

```
\newcommand{\combinedpre}[1]{\glsps{#1}}
\newcommand{\combinedpost}[1]{\glsps{#1}}
```

```
\newabbreviation{shtml}{shtml}
{ }\protect\combinedpre{ssi} enabled \protect\combinedpost{html}}
```

In both cases, an initial empty group is added to guard against any first letter uppercase commands, such as `\Glsxtrlong`.

The abbreviations all use the `long-postshort-sc-user` style, which places the short form in the post-link hook on **first use**. The `\gls` post-link hook for the main element can be transferred to the `\mgl`s post-link using:

```
mpostlinkelement=main
```

All elements have their individual post-link hooks suppressed by default. As in the previous example, the other elements can be skipped on subsequent use:

```
usedskipothers
```

Within `\mgl`s, the nested content needs to be suppressed, which can be done by redefining the custom commands. This can be done in the multi-entry prefix. Since the entire content of `\mgl`s (except for the final multi-entry post-link hook) occurs inside a group, this redefinition will be localised.

The complete document is as follows:

```
\documentclass{article}

\usepackage[colorlinks]{hyperref}
\usepackage[stylemods,style=long]{glossaries-extra}

\makeglossaries

\setabbreviationstyle{long-postshort-sc-user}

\newabbreviation{ssi}{ssi}{server-side includes}
\newabbreviation{html}{html}{hypertext markup language}

\newrobustcmd{\combinedpre}[1]{\glsp{#1}}
\newrobustcmd{\combinedpost}[1]{\glsp{#1}}

\newabbreviation{shtml}{shtml}
{{}\combinedpre{ssi} enabled \combinedpost{html}}

\glssetcategoryattribute{combinedabbrv}{multioptions}
{%
  mpostlinkelement=main,
  usedskipothers
}

\multiglossaryentry
[category={combinedabbrv}]
{shtml}[shtml]{ssi,shtml,html}

\mgldefcategoryprefix{combinedabbrv}{%
  \renewcommand{\combinedpre}[1]{\ignorespaces}%
  \renewcommand{\combinedpost}[1]{\unskip}%
}

\begin{document}
Individual elements first use: \gls{ssi} and \gls{html}.

Individual elements next use: \gls{ssi} and \gls{html}.

Multi-entry first use: \mgl{shtml}.

Multi-entry next use: \mgl{shtml}.

Individual entry first use: \gls{shtml}.
```



```

Resetting all\glsresetall\mglresetall:
Multi-entry first use: \mgl{shtml}.
Multi-entry next use: \mgl{shtml}.
Individual elements: \gls{ssi} and \gls{html}.

```

```

Resetting all\glsresetall\mglresetall:
Individual entry first use: \gls{shtml}.
Multi-entry first use: \mgl{shtml}. (Wrong!)

```

```

\printglossaries
\end{document}

```

This now produces (underlining added to mark the hyperlinks):

Individual elements first use: server-side includes (ssi) and hypertext markup language (HTML).

Individual elements next use: ssi and HTML.

Multi-entry first use: ssi enabled HTML (SHTML).

Multi-entry next use: SHTML.

Individual entry first use: SHTML.

Resetting all:

Multi-entry first use: server-side includes enabled hypertext markup language (SHTML).

Multi-entry next use: SHTML.

Individual elements: ssi and HTML.

Resetting all:

Individual entry first use: ssi enabled HTML (SHTML).

Multi-entry first use: server-side includes SHTML hypertext markup language. (Wrong!)

Note the last two paragraphs, which highlights what happens if `\gls{shtml}` is used before `\mgl{shtml}` when neither of the other elements (ssi and html) have been used. The final instance of `\mgl` has produced the wrong result. This is because it's the first use of the multi-entry `shtml` but not the first use of the individual entry `shtml`.

One way around this is to modify the prefix to ensure that the main element's **first use flag** matches the multi-entry's first use flag:

```

\mgldefcategoryprefix{combinedabbrv}{%
\renewcommand{\combinedpre}[1]{\ignorespaces}%
\renewcommand{\combinedpost}[1]{\unskip}%

```

```

\mglisfirstuse
{\glslocalreset{\mglscurrentmainlabel}}%
{\glslocalunset{\mglscurrentmainlabel}}%
}

```

The `showtargets=annoteleft` option can be used to mark up the links with the targets. For example, the first instance of `\mgl{shtml}` will show as:

Multi-entry first use: `[glo:ssi]>SSI<` `[glo:shtml]>enabled<` `[glo:html]>HTML<` (SHTML).

Each entry has an individual hyperlink to its own glossary item, which may be confusing. This can be made clearer by suppressing the main element link on first use with:

```
hyper=notmainfirst
```

(as in the previous example), and adjusting the abbreviation style so that the parenthetical content in the post-link hook has a hyperlink:

```

\renewcommand*{\glxtruserparen}[2]{%
  \glxtrfullsep{#2}%
  \glxtrparen
  {\gls hyperlink[#1]{#2}%
   \ifglshasfield{\glxtruserfield}{#2}{, \glscurrentfieldvalue}{}}%
  }%
}

```

The remaining problem is how to deal with the possibility that `\mgl{shtml}` may come before the **first use** of the other elements. For example:

Multi-entry first use: `\mgl{shtml}`.

Individual elements: `\gls{ssi}` and `\gls{html}`.

This leads to:

Multi-entry first use: server-side includes enabled hypertext markup language (SHTML).

Individual elements: SSI and HTML.

This means that the abbreviations SSI and HTML aren't explained in the document text. One way around this is to only locally unset the other element **first use flags**:

```

\glssetcategoryattribute{combinedabbrv}{multioptions}
{%
  hyper=notmainfirst,
  mpostlinkelement=main,
  usedskipothers,
  mglsopts={others={local}}
}

```

With the above setting, the following:

```
\glsresetall\mglsresetall
```

Multi-entry first use: `\mgls{shtml}`.

Multi-entry next use: `\mgls{shtml}`.

Individual elements: `\gls{ssi}` and `\gls{html}`.

will now produce:

Multi-entry first use: server-side includes enabled hypertext markup language (SHTML).

Multi-entry next use: SHTML.

Individual elements: server-side includes (SSI) and hypertext markup language (HTML).

## 6.2 Main and Other Elements

The list of labels provided in the final argument of `\multiglossaryentry` consists of a main element and all the other elements. If the main element isn't identified in the optional argument, it's assumed to be the final element in the list.

The main element allows you to determine which target to use if you want the entire content of `\mgls` to be a single hyperlink. You can also use the settings described in Section 6.9 to only index the main element.

You can change the main element using:

```
\mglsSetMain{<multi-label>}{<new-main-label>}
```

The new main label provided in the second argument must be in the list corresponding to `<multi-label>`. This change is locally applied to the current scope. Note that if you are using `bib2gls`, this change in the document can't be detected.

The main element can also be used to identify which element should be displayed in the plural with `\mglsmainpl`. For example:

```
\newglossaryentry{great}{name={great},description={}}
\newglossaryentry{little}{name={little},description={}}
\newglossaryentry{grebe}{name={grebe},description={}}
```

```
\multiglossaryentry{greatgrebe}{great,grebe}
\multiglossaryentry{littlegrebe}{little,grebe}
```

In the above, two multi-entries are defined: `greatgrebe` and `littlegrebe`. In both cases the main element is `grebe` (the last element). Using `\mglspl` will show the plural for all elements, but using `\mglsmainpl` will only use the plural for the main element (`grebe`). For example:

```
Plural all: \mglspl{greatgrebe}, \mglspl{littlegrebe}.
Plural main: \mglsmainpl{greatgrebe}, \mglsmainpl{littlegrebe}.
```

produces:

Plural all: greats grebes, littles grebes.  
Plural main: great grebes, little grebes.

## 6.3 Prefixes and Suffixes

A multi-entry may have associated prefixes and suffixes. These are scoped and are placed outside of the hyperlinks and encapsulating commands. They are not affected by case-changing commands, such as `\Mgls`. If you want a prefix to obey case-changing, use the `\mpgls`-like commands instead (Section 6.11.4).

The prefix is inserted with:

```
\mglsprefix
```

The default definition is:

```
\newcommand*\mglsprefix{%  
  \ifdefempty\mglscurrentcategory  
  {\mglscurrentprefix}%  
  {%  
    \mglshascategoryprefix{\mglscurrentcategory}%  
    {\mglsusecategoryprefix{\mglscurrentcategory}}%  
    {\mglscurrentprefix}%  
  }%  
}
```

This will insert the current prefix unless there is prefix command associated with the current category.

The suffix is inserted with:

```
\mglssuffix
```

The command is defined as follows:

```
\newcommand*\mglssuffix{%  
  \ifdefempty\mglscurrentcategory  
  {\ifdefempty{\mglscurrentsuffix}{\space(\mglscurrentsuffix)}}%  
  {%  
    \mglshascategorysuffix{\mglscurrentcategory}%  
    {\mglsusecategorysuffix{\mglscurrentcategory}}%  
    {\ifdefempty{\mglscurrentsuffix}{\space(\mglscurrentsuffix)}}%  
  }%  
}
```

If there is a suffix associated with the current category, that will be used, otherwise if the current suffix isn't empty this inserts a space followed by the current suffix in parentheses. You can access the label of the last (non-skipped) element with `\mglslastelementlabel`.

Note that in both cases the category corresponds to the multi-entry category (see Section 6.8).

To define a category-dependent prefix, use:

```
\mglstdefcategoryprefix{<category>}{<definition>}
```

You can reference the current prefix with `\mglscurrentprefix`.

To define a category-dependent suffix, use:

```
\mglstdefcategorysuffix{<category>}{<definition>}
```

You can reference the current suffix with `\mglscurrentsuffix`.

The default definition of `\mglsprefix` tests if there is a category prefix using:

```
\glshascategoryprefix{<category>}{<true>}{<false>}
```

The category prefix is used with:

```
\glstusecategoryprefix{<category>}
```

The default definition of `\mglssuffix` tests if there is a category suffix using:

```
\glshascategorysuffix{<category>}{<true>}{<false>}
```

The category suffix is used with:

```
\glstusecategorysuffix{<category>}
```

The current prefix `\mglscurrentprefix` and `\mglscurrentsuffix` are obtained as follows:

- if this is the first use of the multi-entry (Section 6.7) then the *<prefix>* is set to the value of the *firstprefix* option and the *<suffix>* is set to the value of the *firstsuffix* option;
- otherwise the *<prefix>* is set to the value of the *usedprefix* option and the *<suffix>* is set to the value of the *usedsuffix* option.

The prefix and suffix (if set) are placed outside of the hyperlink and text formatting encapsulator. They are not affected by case-changing commands such as `\Mgls` or `\MGLS`.

For example:

```
\setabbreviationstyle{long-only-short-only}  
\newabbreviation{clostridium}{C.}{Clostridium}
```

```
\newglossaryentry{botulinum}{name=botulinum,description={}}
```

```
\multiglossaryentry[firstsuffix=botulism]  
{cbot}{clostridium,botulinum}
```

On first use, this produces (assuming the “clostridium” element hasn’t been used previously):

Clostridium botulinum (botulism).

On subsequent use, this produces:

C. botulinum.

## 6.4 Separators

The separators between each instance of `\gls` are given by the following commands, which all take two arguments. The first argument is the label of the previous element. The second argument is the label of the following element.

```
\glscombinedsep{<prev label>}{<next label>}
```

This is inserted between two entries that have both been marked as used. The default definition is:

```
\newcommand*{\glscombinedsep}[2]{%  
  \glsattribute{#1}{combinedsep}%  
  {\glsattribute{#1}{combinedsep}}%  
  { }%  
}
```

This will use the `combinedsep` attribute for the `<prev label>`’s category, if set. Otherwise this just does a space. Note that this ignores the second argument.

```
\glscombinedfirstsep{<prev label>}{<next label>}
```

This is inserted between two entries where only the next entry has been marked as used. The default definition is:

```
\newcommand*{\glscombinedfirstsep}[2]{%  
  \glsattribute{#1}{combinedfirstsep}%  
  {\glsattribute{#1}{combinedfirstsep}}%  
  {\glscombinedsep{#1}{#2}}%  
}
```

This will use the `combinedfirstsep` attribute for `<prev label>`’s category, if set. If that attribute isn’t set, `\glscombinedsep` is used.

```
\glscombinedsepprev{<prev label>}{<next label>}
```

This is inserted between two entries where only the previous entry has been marked as used. The default definition is:

```

\newcommand*\glscombinedsepfirst}[2]{%
  \glshasattribute{#1}{combinedsepfirst}%
  {\glsgetattribute{#1}{combinedsepfirst}}%
  {\glscombinedsep{#1}{#2}}%
}

```

This will use the **combinedsepfirst** attribute for *<prev label>*'s category, if set. If that attribute isn't set, `\glscombinedsep` is used.

```

\glscombinedfirstsepfirst{<prev label>}{<next label>}

```

This is inserted between two entries where both have been marked as used. The default definition is:

```

\newcommand*\glscombinedfirstsepfirst}[2]{%
  \glshasattribute{#1}{combinedfirstsepfirst}%
  {\glsgetattribute{#1}{combinedfirstsepfirst}}%
  {\glscombinedsep{#1}{#2}}%
}

```

This will use the **combinedfirstsepfirst** attribute for *<prev label>*'s category, if set. If that attribute isn't set, `\glscombinedsep` is used.

These commands may be redefined as required. For example, to have no space between two elements that have both been marked as used and are both abbreviations (disregarding category attributes):

```

\renewcommand*\glscombinedfirstsepfirst}[2]{%
  \ifglshasshort{#1}{\ifglshasshort{#2}{ }\space}{\space}%
}

```

There are some commands for redefining the above separators to common combinations.

```

\glssetcombinedsepabbrvnbsp

```

This does the following:

```

\renewcommand*\glscombinedsep}[2]{%
  \glshasattribute{#1}{combinedsep}%
  {\glsgetattribute{#1}{combinedsep}}%
  {\ifhasshort{#1}{~}{ }}%
}%
\renewcommand*\glscombinedsepfirst}[2]{%
  \glshasattribute{##1}{combinedsepfirst}%
  {\glsgetattribute{##1}{combinedsepfirst}}%
  {\ifhasshort{#1}{~}{ }}%
}%
\renewcommand*\glscombinedfirstsep}[2]{%
  \glshasattribute{#1}{combinedfirstsep}%
  {\glsgetattribute{#1}{combinedfirstsep}}%
}

```

```

{ }%
}%
\renewcommand*\glscombinedfirstsepfirst}[2]{%
  \glshasattribute{##1}{combinedfirstsepfirst}%
  {\glsgetattribute{##1}{combinedfirstsepfirst}}%
  { }%
}%

```

This uses a non-breakable space ~ following an abbreviation (that has already been marked as used). Note that if the associated attributes are set the commands will behave according to the attribute.

```
\glssetcombinedsepabbrvnone
```

This does the following:

```

\renewcommand*\glscombinedsep}[2]{%
  \glshasattribute{#1}{combinedsep}%
  {\glsgetattribute{#1}{combinedsep}}%
  {\ifhasshort{#1}{\ifhasshort{#2}{ { }}}}%
}%
\renewcommand*\glscombinedsepfirst}[2]{%
  \glshasattribute{#1}{combinedsepfirst}%
  {\glsgetattribute{#1}{combinedsepfirst}}%
  {\ifhasshort{#1}{ { }}}%
}%
\renewcommand*\glscombinedfirstsep}[2]{%
  \glshasattribute{##1}{combinedfirstsep}%
  {\glsgetattribute{##1}{combinedfirstsep}}%
  {\ifhasshort{##2}{ { }}}%
}%
\renewcommand*\glscombinedfirstsepfirst}[2]{%
  \glshasattribute{##1}{combinedfirstsepfirst}%
  {\glsgetattribute{##1}{combinedfirstsepfirst}}%
  { }%
}%

```

This does nothing if either element are abbreviations that have already been used. Note that if the associated attributes are set the commands will behave according to the attribute.

```
\glssetcombinedsepnarrow{<width>}{<narrow sep>}
```

This is rather more complicated as it measures a field value and uses *<narrow sep>* if the width is less than *<width>*. The field value is determined as follows:

- on **first use** the long field is used if it is set otherwise the first field is used;
- otherwise the short field is used if it is set otherwise the text field is used;

Note that this doesn't take into account fonts, hooks, abbreviation styles or plural forms (e.g. `\mglsp1`) or other field references (e.g. `\mglname`). If the associated attributes are set the commands will behave according to the attribute.



## 6.5 `\mgl`s Element Hooks

The `\mgl`s-like commands use the following hooks:

```
\mglselementprehook
```

This is done before each (non-skipped) element. (Default does nothing.)

```
\mglselementposthook
```

This is done after each (non-skipped) element. (Default does nothing.) Note that this is different from the normal entry post-link hook `\glspostlinkhook`. If the individual entry post-link hook is enabled (see the `postlinks` key in Section 6.9), this will go before `\mglselementposthook`.

The definitions of the following commands are scoped within the `\mgl`s-like commands so they can't be accessed elsewhere (including in the post-link hook, see Section 6.6). They may be used in the above hooks or in the separator commands (described in Section 6.4) or in the command used to encapsulate the entire content. They can also be used in the post-link hook (see Section 2.4) to determine if an entry is being used within a `\mgl`s-like command.

The multi-entry label is stored in:

```
\mglscurrentmultilabel
```

The label of the main element:

```
\mglscurrentmainlabel
```

The complete comma-separated list of elements:

```
\mglscurrentlist
```

Multi-entry options:

```
\mglscurrentoptions
```

These are the options that were used when defining the multi-entry. This doesn't include options set with `\multiglossaryentrysetup` or those passed to `\mgl`s (or whichever variant is being used).

The current multi-entry category in effect is stored in:

```
\mglscurrentcategory
```

The calling command control sequence name (e.g. “`mgl`s” or “`mgl`sp”) can be obtained with:

```
\glstrcurrentmglscsname
```

To test if the current multi-entry is the first use:

```
\mglsisfirstuse{<true>}{<false>}
```

This does *<true>* if this is the first use otherwise it does *<false>*. Note that this applies to the multi-entry first use flag not the **first use flags** of the individual elements.

At each iteration of the loop over the element list, the following commands are set, which can be accessed in hooks such as `\mglselementprehook` or in hooks used by the underlying `\gls` etc commands. For example, if `\mglscurrentlabel` is defined then `\gls` is being used inside `\mgl`.

The current element label:

```
\mglscurrentlabel
```

This is a count register that is set to the element index:

```
\mglselementindex
```

The current multi-entry prefix:

```
\mglscurrentprefix
```

The current multi-entry suffix:

```
\mglscurrentsuffix
```

```
\mglisiflast{<true>}{<false>}
```

If this is the last iteration, does *<true>* otherwise does *<false>*. This takes the skip options into account, so the last iteration may not necessarily be when the element index is equal to the total number of elements.

## 6.6 Post-Link Hook

There is a hook that occurs at the end the `\mgl`-like commands according to the `mpostlink` setting (see Section 6.9). The hook used depends on the `mpostlinkelement` option. These hooks can't access the commands described in Section 6.5 as the hook occurs outside of the scope in which they are defined.

The `mpostlinkelement=custom` option uses:

```
\mglscustompostlinkhook
```

This does nothing by default.

The `mpostlinkelement=last` option uses:

```
\mglslastelementpostlinkhook
```

which emulates the post-link hook of the last element.

The `mpostlinkelement=main` option uses:

```
\mglslastmainpostlinkhook
```

which emulates the post-link hook of the main element.

The default settings `postlinks=none`, `mpostlink=true`, `mpostlinkelementlast` will suppress the individual element post-link hooks (`\glspostlinkhook`) and do the multi-entry post-link hook for the last element (`\mglslastelementpostlinkhook`).

If you have the final element's post-link hook enabled and the multi-entry post-link hook enabled (for example, `postlinks=all`, `mpostlink=true`, `mpostlinkelement=last`), the final element's post-link hook will be done twice. Similarly for the main element with `postlinks=all`, `mpostlink=true`, `mpostlinkelement=main`.

The following commands are available for use in these hooks and may also be used in `\mglssuffix`.

The multi-entry label:

```
\mglslastmultilabel
```

The multi-entry category (Section 6.8):

```
\mglslastcategory
```

This will be empty if no category was assigned.

```
\mglswasfirstuse{<true>}{<false>}
```

If that was the first use of the multi-entry (Section 6.7) this does `<true>` otherwise it does `<false>`.

### 6.6.1 Last Element

The following commands relate to the last element.

The label of the last non-skipped element:

```
\mglslastelementlabel
```

If all elements were skipped or if the multi-entry wasn't defined, this will be empty.

Test if the last element was skipped:

```
\mgl@iflastelementskipped{<true>}{<false>}
```

If the last element was skipped this does *<true>* otherwise it does *<false>*. If all elements were skipped or if the multi-entry wasn't defined, this will do *<true>*.

Test if the last element was its first use:

```
\mgl@iflastelementwasfirstuse{<true>}{<false>}
```

If the last non-skipped element was used for the first time this does *<true>* otherwise it does *<false>*. (Corresponds to `\glxtrifwasfirstuse`.) If all elements were skipped or if the multi-entry wasn't defined, this will do *<true>*.

Test if the last element was plural:

```
\mgl@iflastelementwasplural{<true>}{<false>}
```

If the last non-skipped element had the plural form displayed, this does *<true>* otherwise it does *<false>*. (Corresponds to `\gl@ifplural`.) If all elements were skipped or if the multi-entry wasn't defined, this will do *<false>*.

Test if the last element was had any case-changing applied:

```
\mgl@iflastelementcapscase{<no-change>}{<firstuc>}{<all caps>}
```

Corresponds to `\glscaps` of the last non-skipped element. If all elements were skipped or if the multi-entry wasn't defined, this will do *<no-change>*.

## 6.6.2 Main Element

The following commands relate to the main element.

The label of the main element from the multi-entry that was just referenced:

```
\mgl@lastmainlabel
```

If the main element was skipped or if the multi-entry wasn't defined, this will be empty. If this is the same as `\mgl@lastelementlabel` then the main element was the last element.

Test if the main element was skipped:

```
\mgl@iflastmainskipped{<true>}{<false>}
```

If the main element from the multi-entry that was just referenced was skipped this does *<true>* otherwise it does *<false>*. If the multi-entry wasn't defined, this will do *<true>*.

Test if the main element was its first use:

```
\mgl@iflastmainwasfirstuse{<true>}{<false>}
```

If the main element was used for the first time this does *<true>* otherwise it does *<false>*. (Corre-

sponds to `\glxtrifwasfirstuse`.) If the main element was skipped or if the multi-entry wasn't defined, this will do `<true>`.

Test if the main element was plural:

```
\mglisiflastmainwasplural{<true>}{<false>}
```

If the main element from the multi-entry that was just referenced had its plural form displayed this does `<true>` otherwise it does `<false>`. (Corresponds to `\glisifplural`.) If the main element was skipped or if the multi-entry wasn't defined, this will do `<false>`.

Test if the main element was had any case-changing applied:

```
\mglisiflastmaincapscase{<no-change>}{<firstuc>}{<all caps>}
```

Corresponds to `\glscaps` of the main element from the multi-entry that was just referenced. If the main element was skipped or if the multi-entry wasn't defined, this will do `<no-change>`.

## 6.7 Multi-Entry First Use

Each multi-entry set has an associated first use flag. This is independent of the **first use flag** associated with the individual entries that make up the set. As with the `\gls`-like commands, `\mgl` unsets this flag. Unlike the `\glstext`-like commands, all the commands described in Section 6.11 (including commands like `\mglname`) unset this flag, even if the elements use commands like `\glsname` that don't unset the entry's first use flag.

You can determine whether or not a multi-entry set has been marked as used with:

```
\ifmglused{<multi-label>}{<true>}{<false>}
```

You can (globally) unset the flag (mark the set as having been referenced) with:

```
\mglunset{<multi-label>}
```

or reset it with:

```
\mglreset{<multi-label>}
```

There are also local versions of these commands:

```
\mgllocalunset{<multi-label>}
```

and

```
\mgllocalreset{<multi-label>}
```

To unset all multi-entries:

```
\mglunsetall
```

To reset all multi-entries:

```
\mglresetall
```

Note that unsetting or resetting any of the individual element **first use flags** doesn't affect the multi-entry flag. Similarly, unsetting or resetting the multi-entry flag doesn't affect the first use flags of the individual elements.

## 6.8 Multi-Entry Category

A multi-entry set may have an associated category set using the category key described in Section 6.9. This isn't set by default, but if it is set the category may have attributes set in the usual way. The multi-entry category is independent of the individual entry categories. The following attribute is recognised by commands like `\mgl`s:

**multioptions** default options to apply to any multi-entry set with the given category. These can be overridden by the first optional argument of `\multiglossaryentry` or by the setup key in the first optional argument of commands like `\mgl`s.

Note that you can't access the category or its attributes via the multi-entry label (for example, with `\glshasattribute`). If you need to access the current multi-entry's category within any of the `\mgl`s-like hooks (Section 6.5), you can obtain the category with `\mglscurrentcategory` and use commands like `\glshascategoryattribute`.

## 6.9 Multi-Entry Settings

The settings that govern all multi-entries can be set using:

```
\multiglossaryentrysetup{<options>}
```

The *<options>* are the same as for `\multiglossaryentry`. Options may also be set according to the multi-entry category attribute **multioptions**.

Whenever the `\mgl`s-like commands are used, options are applied in the following order:

1. general options identified by `\multiglossaryentrysetup`;
2. the category key is assigned if it's in the general options, `\multiglossaryentry` or setup key;
3. **multioptions** category attribute (if set);
4. any options provided in the first optional argument of `\multiglossaryentry`;

5. any options provided in the setup key in the first optional argument of the `\mgls`-like command.

These options are described below.

### 6.9.1 Indexing

**indexmain** This setting may take one of the following values:

**false** don't index the main entry;

**true** index the main entry;

**first** only index the main entry if it's the first use (of the main entry).

The default is true.

**indexothers** This setting may take one of the following values:

**false** don't index the other entries;

**true** index the other entries;

**first** only index the other entries if it's the first use (of the non-main entry).

The default is first.

### 6.9.2 Location Formats (Encaps)

**encapmain** This setting value should be the value to pass to format for the main entry. (The location encapsulator.) The default is `glsnumberformat`.

**encapothers** This setting value should be the value to pass to format for the other (not main) entries. (The location encapsulator.) The default is `glsnumberformat`.

### 6.9.3 Post-Link Hooks

**postlinks** This setting determines whether or not to enable the individual element's post-link hook (`\glspostlinkhook`). The value may be one of:

**none** suppress the post-link hook for all elements;

**all** don't suppress the post-link hook for all elements;

**notlast** only suppress the post-link hook for the last element;

**mainnotlast** suppress the post-link hook for all "other" (not main) elements and for the last element (so only the main element will have its post-link hook as long as it's not the last element);

**mainonly** suppress the post-link hook for all "other" (not main) elements;

**othernotlast** suppress the post-link hook for the main element and for the last element (so only the other elements will have their post-link hook as long as the element isn't the last one);

**otheronly** suppress the post-link hook for the main element.

The default is `postlinks=none`.

**mpostlink** This setting determines whether or not to enable the multi-entry post-link hook (Section 6.6). The value may be one of:

**false** suppress the multi-entry post-link hook;

**true** enable the multi-entry post-link hook;

**firstonly** enable the multi-entry post-link hook only for the first use of the multi-entry;

**usedonly** enable the multi-entry post-link hook only for the subsequent (not first) use of the multi-entry.

The default is `mpostlink=true`. If the value is omitted, `true` is assumed.

**mpostlinkelement** This setting indicates which post-link hook should be used if the multi-entry post-link hook has been enabled. Allowed values:

**last** use `\mglslastelementpostlinkhook` (that is, use the post-link hook for the last element);

**main** use `\mglslastmainpostlinkhook` (that is, use the post-link hook for the main element);

**custom** use `\mglslastcustompostlinkhook`.

Note that some combinations may cause a repeated hook.

#### 6.9.4 Prefixes and Suffixes

See Section 6.3 for more information on prefixes and suffixes. Note that the prefixes and suffixes are not affected by case-changing commands such as `\Mgls` or `\MGLS`. If you want a prefix to obey case-changing, use the `\mpgls`-like commands instead (Section 6.11.4).

**firstprefix** The prefix to use on first use of the multi-entry.

**usedprefix** The prefix to use on subsequent use of the multi-entry.

**firstsuffix** The suffix to use on first use of the multi-entry.

**usedsuffix** The suffix to use on subsequent use of the multi-entry.

#### 6.9.5 Skipping Elements

**firstskipmain** This is a boolean setting. If `true`, the main element will be omitted on (multi-entry) first use.

**firstskipothers** This is a boolean setting. If `true`, the other (non-main) elements will be omitted on (multi-entry) first use.



**usedskipmain** This is a boolean setting. If true, the main element will be omitted on (multi-entry) subsequent use.

**usedskipothers** This is a boolean setting. If true, the other (non-main) elements will be omitted on (multi-entry) subsequent use.

The skip options apply to the multi-entry first use flag not the individual element first use. See Section 6.7.

Note that it is technically possible to set the skip options so that both the main and the other elements are skipped. However, by default, this will generate a warning and only the final optional argument (the *<insert>*) will be displayed. There won't be a loop over all elements so the commands set at each iteration, such as `\mglscurrentlabel`, won't be defined.

The warning and the insertion of the *<insert>* is done by:

```
\glstrmglswarnallskipped{<message>}{<insert>}{<cs>}
```

where *<message>* is the warning message and *<cs>* is the control sequence that encapsulates the entire content (including hyperlink and the `textformat` setting, if enabled).

If, for some particular reason, you want this scenario, you can redefine this command to omit the warning.

### 6.9.6 General

**hyper** This setting may take one of the following values:

**none** no hyperlinks;

**allmain** encapsulate the entire content with a single hyperlink to the main entry's target;

**mainonly** only hyperlink the main entry;

**individual** hyperlink each entry individually;

**otheronly** only hyperlink the other entries;

**notmainfirst** don't hyperlink the main entry on multi-entry first use;

**nototherfirst** don't hyperlink the other entries on multi-entry first use;

**notfirst** don't hyperlink any entries on multi-entry first use.

The default is individual.

**textformat** This setting value should be the control sequence name (without the leading backslash) of the command used to encapsulate the entire content. The default is `@firstofone`.

**category** The category to apply to the multi-entry. This is independent of the categories of each of the elements. The default is no category. See Section 6.8.

**mglsopts** Default options to pass to `\mgl`s. Note that `setup` can't be used within this value.

## 6.10 `\mgl`s Options

The *options* for `\mgl`s (and similar commands) are listed below. Any additional options provided will be appended to the all value. For example:

```
\mgl[counter=chapter]{cbot}
```

is equivalent to:

```
\mgl[all={counter=chapter}]{cbot}
```

Whereas:

```
\mgl[counter=chapter,all={counter=section}]{cbot}
```

is treated as:

```
\mgl[all={counter=section,counter=chapter}]{cbot}
```

which has the same effect as:

```
\mgl[all={counter=chapter}]{cbot}
```

(The descriptions below reference `\gl`s which is used internally by `\mgl`s. Replace this with `\glspl` etc as applicable for the variants, such as `\mglspl`.)

**setup** The value should be a list of any options that can be passed to `\multiglossaryentrysetup`. These options will override any conflicting options that were supplied to `\multiglossaryentry` or `\multiglossaryentrysetup`. Note that `mgl`s can't be used within this value.

**all** The value should be a list of any options that can be passed to `\gl`s. These options will be passed to each instance of `\gl`s and will override any conflicting setting in `setup`.

**main** The value should be a list of any options that can be passed to `\gl`s. These options will be passed to the instance of `\gl`s used for the main label and will override any conflicting setting in `all`.

**others** The value should be a list of any options that can be passed to `\gl`s. These options will be passed to each instance of `\gl`s used for the other (not main) labels and will override any conflicting setting in `all`.

**hyper** a boolean option to determine whether or not to use hyperlinks (if supported). This may cause a conflict with other options, but is essentially provided to allow the starred version of `\mgl`s to switch off all hyperlinks.

**multiunset** This only applies to the multi-entry first use flag, described in Section 6.7, not the **first use flags** of the elements. The value may be one of:

global globally unset the flag (default);

local locally unset the flag;

none don't unset the flag.

**presetlocal** a boolean option that governs whether or not the following options should have a local or global effect. The default is `presetlocal=false` (global).

**resetall** a boolean option to determine whether or not to reset all entries in *<label list>* before using `\gls`. This option refers to the individual entry's first use flag not the multi-set flag.

**resetmain** a boolean option to determine whether or not to reset the main entry before using `\gls`. This option refers to the individual entry's **first use flag** not the multi-set flag.

**resetothers** a boolean option to determine whether or not to reset the other (not main) entries before using `\gls`. This option refers to the individual entry's first use flag not the multi-set flag.

**unsetall** a boolean option to determine whether or not to unset all entries in *<label list>* before using `\gls`. This option refers to the individual entry's first use flag not the multi-set flag.

**unsetmain** a boolean option to determine whether or not to unset the main entry before using `\gls`. This option refers to the individual entry's first use flag not the multi-set flag.

**unsetothers** a boolean option to determine whether or not to unset the other (not main) entries before using `\gls`. This option refers to the individual entry's first use flag not the multi-set flag.

The reset... options all use:

```
\mglselementreset{<label>}
```

The unset... options all use:

```
\mglselementunset{<label>}
```

These take the `presetlocal` into account.

An alternative way of resetting the other elements is to use:

```
\mglsunsetothers{<multi-label>}
```

or for a local reset:

```
\mglslocalunsetothers{<multi-label>}
```

## 6.11 Variants of `\mgl`

The commands listed in this section all behave like `\mgl`. These (including `\mgl` itself) are collectively referred to as the `\mgl`-like commands. All commands unset the multi-entry first use

flag (unless the `multiunset=none` option is applied). Only those commands that use the `\gls`-like commands (such as `\gls` or `\glspl`) will unset the individual entry first use flag.

### 6.11.1 `\gls`-like

```
\mglspl[<options>]{<multi-label>}[<insert>]
```

This uses `\glspl` instead of `\gls` for each entry.

```
\mglsmainpl[<options>]{<multi-label>}[<insert>]
```

This uses `\glspl` instead of `\gls` for the main entry and `\gls` for all the other entries.

```
\Mgls[<options>]{<multi-label>}[<insert>]
```

This uses `\Gls` for the first entry and `\gls` for the other entries.

```
\MGls[<options>]{<multi-label>}[<insert>]
```

This uses `\Gls` for all entries.

```
\Mglspl[<options>]{<multi-label>}[<insert>]
```

This uses `\Glspl` for the first entry and `\glspl` for the other entries.

```
\Mglsmainpl[<options>]{<multi-label>}[<insert>]
```

The first entry starts with an upper case. The plural form is used for the main entry.

```
\MGlspl[<options>]{<multi-label>}[<insert>]
```

This uses `\Glspl` for all entries.

```
\MGlsmainpl[<options>]{<multi-label>}[<insert>]
```

This uses `\Glspl` for the main entry and `\Gls` for all other entries.

```
\MGLS[<options>]{<multi-label>}[<insert>]
```

This uses `\GLS` instead of `\gls` for each entry.

```
\MGLSpl[<options>]{<multi-label>}[<insert>]
```

This uses `\GLSpl` instead of `\gls` for each entry.

```
\MGLSmainpl[<options>]{<multi-label>}[<insert>]
```

This uses all caps for all entries and \GLSp1 for the main entry.

### 6.11.2 Abbreviations

```
\mglsshort[<options>]{<multi-label>}[<insert>]
```

This will use \glxtrshort for any entries that have the short key set and will use \glstext otherwise.

```
\mglslong[<options>]{<multi-label>}[<insert>]
```

This will use \glxtrlong for any entries that have the long key set and will use \glstext otherwise.

```
\mglsfull[<options>]{<multi-label>}[<insert>]
```

This will use \glxtrfull for any entries that have the short key set and will use \glsfirst otherwise.

```
\Mglsshort[<options>]{<multi-label>}[<insert>]
```

As \mglsshort but with an initial capital on the first entry.

```
\Mglslong[<options>]{<multi-label>}[<insert>]
```

As \mglslong but with an initial capital on the first entry.

```
\Mglsfull[<options>]{<multi-label>}[<insert>]
```

As \mglsfull but with an initial capital on the first entry.

### 6.11.3 Other Fields

```
\mglsname[<options>]{<multi-label>}[<insert>]
```

This uses \glsname instead of \gls for each entry.

```
\MGLsname[<options>]{<multi-label>}[<insert>]
```

This uses \GLsname instead of \gls for each entry.

```
\Mglsname[<options>]{<multi-label>}[<insert>]
```

This uses \Glsname instead of \gls for the first entry and \glsname for all the other entries.

```
\mglssymbol[<options>]{<multi-label>}[<insert>]
```

This uses \glsymbol if the symbol key has been set otherwise it uses \gls for each element.

```
\MGLssymbol[<options>]{<multi-label>}[<insert>]
```

This uses \glsymbol if the symbol key has been set otherwise it uses \Gls for each element. (Note that no case change is applied to the symbol as this usually isn't appropriate.)

```
\Mglsymbol[<options>]{<multi-label>}[<insert>]
```

As above, but \Gls is only used for the first element (if it doesn't have the symbol key set).

```
\mglseusefield[<options>]{<multi-label>}[<insert>]
```

Use \glsdisp{*<label>*}{*<field value>**<insert>*} if the field given by:

```
\mglsefield
```

exists, otherwise use \gls. By default, this is user1 (corresponding to the user1 key). If you redefine \mglsefield, you will need to use the internal name.

```
\Mglseusefield[<options>]{<multi-label>}[<insert>]
```

As \mglseusefield but the first element starts with an initial uppercase.

```
\MGLseusefield[<options>]{<multi-label>}[<insert>]
```

As \mglseusefield but each element starts with an initial uppercase.

You can use the pre-element hook \mglselementprehook to locally redefine \mglsefirst. Examples:

1. if the multi-category is "sample" then use the user2 field otherwise use the user1 field:

```
\renewcommand{\mglselementprehook}{%
  \ifdefstring{\mglsecurrentcategory}{sample}%
  {\renewcommand{\mglsefield}{user2}}%
  {\renewcommand{\mglsefield}{user1}}%
}
```

2. if the element's category is "sample" then use the user2 field otherwise use the user1 field:

```

\renewcommand{\mglselementprehook}{%
  \glsifcategory{\mglscurrentlabel}{sample}%
  {\renewcommand{\mglsgfield}{userii}}%
  {\renewcommand{\mglsgfield}{useri}}%
}

```

3. if either the multi-entry’s category or the element’s category has the custom attribute “mglsgfield” set then use it otherwise use the user1 field:

```

\renewcommand{\mglselementprehook}{%
  \glsifcategoryattribute{\mglscurrentcategory}{mglsgfield}%
  {\renewcommand{\mglsgfield}{\glsgetcategoryattribute{\mglscurrentcategory}{mglsgfield}}}%
  {%
    \glsifattribute{\mglscurrentlabel}{mglsgfield}%
    {\renewcommand{\mglsgfield}{\glsgetattribute{\mglscurrentlabel}{mglsgfield}}}%
    {\renewcommand{\mglsgfield}{useri}}%
  }%
}

```

#### 6.11.4 Support for glossaries-prefix (\pgls)

If you load the glossaries-prefix package (either after glossaries-extra) or with the `prefix` package option, then the following commands will use one of the \pgls-like commands provided by that package. (See the glossaries user manual for further details.)

If the glossaries-prefix package hasn’t been loaded then \gls (or analogous case-changing variant) will be used instead and a warning is issued. The warning can be removed by redefining the following to do nothing:

```
\mpglsWarning
```

```
\mpgls[<options>]{<multi-label>}[<insert>]
```

Uses \pgls for the first element and \gls for the remaining elements.

```
\mpglspl[<options>]{<multi-label>}[<insert>]
```

Uses \pglspl for the first element and \glspl for the remaining elements.

```
\mpglsmainpl[<options>]{<multi-label>}[<insert>]
```

Only uses the plural form for the main element. The first element uses the prefixing command (\pgls or \pglspl, depending on whether the first element is the main element).

```
\Mpgls[<options>]{<multi-label>}[<insert>]
```

Uses \Ppgls for the first element and \gls for the remaining elements.

```
\Mpglsmainpl [options] {multi-label} [insert]
```

Only uses the plural form for the main element. The first element uses the first-letter uppercase prefixing command (`\Pgl`s or `\Pglsp`l, depending on whether the first element is the main element).

```
\MPGls [options] {multi-label} [insert]
```

Uses `\Pgl`s for the first element and `\G`l s for the remaining elements.

```
\MPGlspl [options] {multi-label} [insert]
```

Uses `\Pglsp`l for the first element and `\G`l spl for the remaining elements.

```
\MPGLsmainpl [options] {multi-label} [insert]
```

Only uses the plural form for the main element. The first element uses the prefixing command (`\Pgl`s or `\Pglsp`l, depending on whether the first element is the main element). All elements are converted to first letter uppercase.

```
\MPGLS [options] {multi-label} [insert]
```

Uses `\PGL`S for the first element and `\G`LS for the remaining elements.

```
\MPGLSpl [options] {multi-label} [insert]
```

Uses `\PGLSp`l for the first element and `\G`LSpl for the remaining elements.

```
\MPGLSmainpl [options] {multi-label} [insert]
```

Only uses the plural form for the main element. All elements are converted to uppercase. The first element uses the prefixing command (`\PGL`S or `\PGLSp`l, depending on whether the first element is the main element).

## 6.12 Cross-References

Multi-entry labels may be used in the cross-referencing keys `see` and `seealso`. The formatting command will use:

```
\mglsseefirstitem{label}
```

for the first item in the list (if it's a multi-entry) and



```
\mglseeitem{<label>}
```

for any subsequent items that are multi-entries. The default definition of `\mglseeitem` is:

```
\newcommand*{\mglseeitem}[1]{%
  \mglname[all={noindex},setup={hyper=allmain}]{#1}%
}
```

This switches off indexing, sets the hyperlink to encompass the entire multi-entry content and uses the name field. The default definition of `\mglseeirstitem` is simply `\mglseeitem`.

For example, to use the short or text fields:

```
\renewcommand*{\mglseeitem}[1]{%
  \mglshort[all={noindex},setup={hyper=allmain}]{#1}%
}
```

A multi-entry label may also be used in the alias key. The hyperlink target will be the target for the main entry. For example:

```
\multiglossaryentry{cbot}{clostridium,botulinum}
\newglossaryentry{botox}{name=botox,description={},alias={cbot}}
```

In this case `\gls{botox}` will hyperlink to the `botulinum` target.

Any multi-entries used in the cross-referencing keys must be defined before the glossary is displayed. There is some support for `docdef=true` but not for the other `docdef` settings.

## 6.13 Additional Commands

You can test if a label represents a multi-entry using:

```
\glxtrifmulti{<label>}{<true>}{<false>}
```

The following command will expand to the main entry label for the given multi-entry label:

```
\glxtrmultimain{<multi-label>}
```

This will expand to nothing if the supplied *<multi-label>* hasn't been defined as a multi-entry. Similarly, for the complete label list:

```
\glxtrmultilist{<multi-label>}
```

To iterate over all the list of all elements:

```
\mglstorelements{<multi-label>}{<cs>}{<body>}
```

This defines *<cs>* to the current element label on each iteration of the loop, which can be used to reference the label in *<body>*. This internally uses `\@for` (patched by the `xfor` package).

There is a similar command that skips the main element:

```
\mglsforotherelements{<multi-label>}{<cs>}{<body>}
```

The total number of elements can be obtained with:

```
\glxtrmultitotalelements{<multi-label>}
```

This expands to the number, if *<multi-label>* is defined, otherwise expands to nothing.

The index of the main element can be obtained with:

```
\glxtrmultimainindex{<multi-label>}
```

This expands to the index, if *<multi-label>* is defined, otherwise expands to nothing. Indexing starts from 1 for the first element. The index of the final non-main element can be obtained with:

```
\glxtrmultilastotherindex{<multi-label>}
```

The `\multiglossaryentry` command will write the label information to the aux file using:

```
\writemultiglossentry{<options>}{<multi-label>}{<main-label>}{<list>}
```

This will write the following line to the aux file:

```
\@glxtr@multientry{<options>}{<multi-label>}{<main-label>}{<list>}
```

This is provided to support `docdef=true` and also for the benefit of any tools that require the information (such as `bib2gls` or autocompletion tools). If it's not required and causes too much clutter, it can be disabled by redefining `\writemultiglossentry` to do nothing.

## 6.14 bib2gls

In the `bib2gls v2.9+` user manual, these multi-entry sets are referred to as “compound entries” or “compound sets” to differentiate them from `bib2gls`'s multi-entry types (such as `@dualentry`).

Each instance of one of the `\mgls`-like commands is written to the aux file and so can be picked up by `bib2gls` (at least version 2.9). The resource options can be used to determine whether or not to consider the other (non-main) elements to be dependent on the main element.

With `bib2gls`, you can either define the compound entries in the document with `\multiglossaryentry` (or `\providemultiglossaryentry`) or you can use the `@compoundset` entry type in a bib file. Whichever method you use, remember that the entries that form the elements of the set must be defined first. See the `bib2gls` manual (v2.9+) for further details.

You can use the resource option `compound-adjust-name` to replace the name field of the main entry to:

```
\glxtrmultientryadjustedname{<sublist1>}{<name>}{<sublist2>}{<label>}
```

where *label* is the label identifying the compound set, *name* was the value of the name before adjustment, *sublist1* is the sub-list of other element labels before the main element (empty if the main element is the first element in the list), and *sublist2* is the sub-list of other elements after the main element (empty if the main label is the final element).

This command is defined in `glossaries-extra-bib2gls`, which is automatically loaded with `record=only` and `record=nameref`. Case-changing versions of this command are also available. First letter uppercase:

```
\Glsxtrmultientryadjustedname{<sublist1>}{<name>}{<sublist2>}{<label>}
```

Title case:

```
\GlsXtrmultientryadjustedname{<sublist1>}{<name>}{<sublist2>}{<label>}
```

All uppercase:

```
\GLSxtrmultientryadjustedname{<sublist1>}{<name>}{<sublist2>}{<label>}
```

Note that this command doesn't take the prefix or suffix into account (see Section 6.3).

The separator between each element in the sub-lists is produced with:

```
\glxtrmultientryadjustednamesep{<pre label>}{<post label>}
```

The default definition just uses `\glscombinedfirstsepfirst`.

The separator between the last element of *sublist1* and the main element is produced with:

```
\glxtrmultientryadjustednamepresep{<pre label>}{<post label>}
```

Similarly for the separator between the main element and the first element of *sublist2*:

```
\glxtrmultientryadjustednamepostsep{<pre label>}{<post label>}
```

These both default to `\glxtrmultientryadjustednamesep`.

The *name* is encapsulated with:

```
\glxtrmultientryadjustednamefmt{<text>}
```

This just does its argument by default. If *sublist1* is empty for the first letter upper case version, then *name* is encapsulated with:

```
\Glsxtrmultientryadjustednamefmt{<text>}
```

This does `\makefirstuc{<text>}` by default. For the title case version, the name is encapsulated

with:

```
\GlsXtrmultientryadjustednamefmt{<text>}
```

This uses `\glscapitalisewords` (provided by `glossaries v4.48+`) if defined or `\capitalisewords` otherwise. The all uppercase version uses:

```
\GLSxtrmultientryadjustednamefmt{<text>}
```

This uses `\mfirstucMakeUppercase` by default.

Each element label in the sub-lists is encapsulated with:

```
\glsxtrmultientryadjustednameother{<label>}
```

This does `\glsentryname{<label>}` by default. For the first letter uppercase version (where `<sublist1>` isn't empty), then the element label is encapsulated with:

```
\Glsxtrmultientryadjustednameother{<label>}
```

This does `\Glsentryname{<label>}` by default. The title case version uses:

```
\GlsXtrmultientryadjustednameother{<label>}
```

This does `\glsentrytitlecase{<label>}{<name>}` by default. The all uppercase version uses:

```
\GLSxtrmultientryadjustednameother{<label>}
```

This is defined as:

```
\newcommand*{\GLSxtrmultientryadjustednameother}[1]{%  
  \mfirstucMakeUppercase{\glsentryname{#1}}}
```

## 7 Categories

Each entry defined by `\newglossaryentry` (or commands that internally use it such as `\newabbreviation`) is assigned a category through the `category` key. You may add any category that you like, but since the category is a label used in the creation of some control sequences, avoid problematic characters within the category label. (So take care if you have babel shorthands on that make some characters active.)

The use of categories can give you more control over the way entries are displayed in the text or glossary. Note that an entry’s category is independent of the glossary type. Be careful not to confuse category with type.

For multi-entry categories, see Section 6.8.

The default category assumed by `\newglossaryentry` is labelled `general`. Abbreviations defined with `\newabbreviation` have the category set to `abbreviation` by default. Abbreviations defined with `\newacronym` have the category set to `acronym` by default.

Additionally, if you have enabled `\newterm` with the `index` package option that command will set the category to `index` by default. If you have enabled `\glstrnewsymbol` with the `symbols` package option, that command will set the category to `symbol`. If you have enabled `\glstrnewnumber` with the `numbers` package option, that command will set the category to `number`.

You can obtain the category label for a given entry using

```
\glscategory{<label>}
```

This is equivalent to commands like `\glsenryname` and so may be used in an expandable context. No error is generated if the entry doesn’t exist.

You can test the category for a given entry using

```
\glstestcategory{<entry-label>}{<category-label>}{<true part>}{<false part>}
```

This is equivalent to

```
\ifglstestcategory{<entry-label>}{<category-label>}{<true part>}{<false part>}
```

so any restrictions that apply to `\ifglstestcategory` also apply to `\glstestcategory`.

Each category may have a set of attributes. For example, the `general` and `acronym` categories have the attribute `regular` set to “true” to indicate that all entries with either of those categories are regular entries (as opposed to abbreviations). This attribute is accessed by `\glsenryfmt` to determine whether to use `\glsgenentryfmt` or `\glstrgenabbrvfmt`.

Other attributes recognised by glossaries-extra are:

**nohyperfirst** When using commands like `\gls` this will automatically suppress the hyperlink on **first use** for entries with a category that has this attribute set to “true”. (This settings can be overridden by explicitly setting the hyper key on or off in the optional argument of commands like `\gls`.) As from version 1.07, `\glsfirst`, `\Glsfirst`, `\GLSfirst` and their plural versions (which should ideally behave in a similar way to the first use of `\gls` or `\glspl`) now honour this attribute (but not the package-wide `hyperfirst=false` option, which matches the behaviour of glossaries). If you want commands like `\glsfirst` to ignore the **nohyperfirst** attribute then just redefine

```
\glsxtrchecknohyperfirst{\label}
```

to do nothing.

**nohyper** When using commands like `\gls` this will automatically suppress the hyperlink for entries with a category that has this attribute set to “true”. (This settings can be overridden by explicitly setting the hyper key on or off in the optional argument of commands like `\gls`.)

**indexonlyfirst** This is similar to the **indexonlyfirst** package option but only for entries that have a category with this attribute set to “true”.

**wrgloss** When using commands like `\gls`, if this attribute is set to “after”, it will automatically implement `wrgloss=after`. (New to v1.14.)

**discardperiod** If set to “true”, the post-**link-text** hook will discard a full stop (period) that follows *non-plural* commands like `\gls` or `\glsstext`. (Provided for entries such as abbreviations that end with a full stop.) This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it’s using `\newabbreviation`.) This attribute doesn’t apply to the accessibility fields.

Note that this can cause a problem if you access a field that doesn’t end with a full stop. For example:

```
\newabbreviation
[user1={German Speaking \TeX\ User Group}]
{dante}{DANTE e.V.}{Deutschsprachige Anwendervereinigung \TeX\
e.V.}
```

Here the short and long fields end with a full stop, but the `user1` field doesn’t. The simplest solution in this situation is to put the sentence terminator in the final optional argument. For example:

```
\glsuseri{dante}[.]
```

This will bring the punctuation character inside the link-text and it won’t be discarded.

**pluraldiscardperiod** If this attribute is set to “true” and the **discardperiod** attribute is set to “true”, this will behave as above for the plural commands like `\glspl` or `\glsplural`. This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it’s using `\newabbreviation`.)

**retainfirstuseperiod** If this attribute is set to “true” then the full stop won’t be discarded for **first use** instances, even if **discardperiod** or **pluraldiscardperiod** are set. This is useful for *(short)* (*(long)*) abbreviation styles where only the short form has a trailing full stop. This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it’s using `\newabbreviation`.) This attribute doesn’t apply to the accessibility fields.

**markwords** If this attribute is set to “true” any entry defined using `\newabbreviation` will automatically have spaces in the long form replaced with

```
\glsxtrwordsep
```

and each word is encapsulated with

```
\glsxtrword{<word>}
```

For example:

```
\glssetcategoryattribute{abbreviation}{markwords}{true}  
\newabbreviation{ip}{IP}{Internet Protocol}
```

is essentially the same as

```
\newabbreviation{ip}{IP}  
{\glsxtrword{Internet}\glsxtrwordsep\glsxtrword{Protocol}}
```

The “hyphen” styles, such as **long-hyphen-short-hyphen**, take advantage of this markup. If the inserted material (provided in the final argument of commands like `\gls`) starts with a hyphen then `\glsxtrwordsep` is locally redefined to a hyphen. (The default value is a space). Note that this only applies to commands like `\gls` and not like `\glsxtrlong`. You can provide your own localised switch, if required. For example:

```
\newcommand{\hyplong}[2] [] {%  
  {\def\glsxtrwordsep{-}\glsxtrlong[#1]{#2}}}
```

This setting will also adjust the long plural. This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it’s using `\newabbreviation`.)

This setting may result in the `\glsxtrword` and `\glsxtrwordsep` markup ending up in the sort field, depending on the style in use.

**markshortwords** This is similar to **markwords** but applies to the short form. (Only useful for abbreviations that contain spaces.) This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it's using `\newabbreviation`.)

This setting will only adjust the short plural if the `shortplural` key isn't used. This setting will take precedence over **insertdots**.

This setting may result in the `\glxtrword` and `\glxtrwordsep` markup ending up in the sort field, depending on the style in use.

**insertdots** If this attribute is set to “true” any entry defined using `\newabbreviation` will automatically have full stops (periods) inserted after each letter. The entry will be defined with those dots present as though they had been present in the `<short>` argument of `\newabbreviation` (rather than inserting them every time the entry is used). The short plural form defaults to the new dotted version of the original `<short>` form with the plural suffix appended. *This setting is incompatible with **markshortwords**.* This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it's using `\newabbreviation`.)

If you explicitly override the short plural using the `shortplural` key, you must explicitly insert the dots yourself (since there's no way for the code to determine if the plural has a suffix that shouldn't be followed by a dot).

This attribute is best used with the **discardperiod** attribute set to “true”.

**aposplural** If this attribute is set to “true”, `\newabbreviation` will insert an apostrophe (') before the plural suffix for the *short* plural form (unless explicitly overridden with the `shortplural` key). The long plural form is unaffected by this setting. This setting overrides **noshortplural**. This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it's using `\newabbreviation`.) Check with your supervisor, publisher or editor if you want to use this attribute as this usage is controversial.

**noshortplural** If this attribute is set to “true”, `\newabbreviation` won't append the plural suffix for the short plural form. This means the short and `shortplural` values will be the same unless explicitly overridden. *This setting is incompatible with **aposplural**.* This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it's using `\newabbreviation`.)

**headuc** If this attribute is set to “true”, commands like `\glsfmtshort` will use the upper case version in the page headers.

**tagging** If this attribute is set to “true”, the tagging command defined by `\GlsXtrEnableInitialTagging` will be activated to use `\glxtrtagfont` in the glossary (see Section 4.1).



**entrycount** Unlike the above attributes, this attribute isn't boolean but instead must be an integer value and is used in combination with `\glsenableentrycount` (see Section 2.5). Leave blank or undefined for categories that shouldn't have this facility enabled. The value of this attribute is used by `\glsxtrifcounttrigger` to determine how commands such as `\gls` should behave.

With glossaries, commands like `\cgl`s use `\cglformat` only if the previous usage count for that entry was equal to 1. With `glossaries-extra` the test is now for entries that have the **entrycount** attribute set and where the previous usage count for that entry is less than or equal to the value of that attribute.

**linkcount** This attribute is set to `true` by `\GlsXtrEnableLinkCounting` (see Section 8.2).

**linkcountmaster** This attribute is set to the name of the master counter by `\GlsXtrEnableLinkCounting` if the optional argument is provided (see Section 8.2).

**glossdesc** The `\glossentrydesc` command (used in the predefined glossary styles) is modified by `glossaries-extra` to check for this attribute. The attribute may have one of the following values:

- **firstuc**: the first letter of the description will be converted to upper case (using `\Glsentrydesc`).
- **title**: the description will be used in the argument of the title casing command. If you have at least `glossaries v4.48`, the title casing is indirectly performed by `\glscapitalisewords`, which defaults to `\capitalisewords` (provided by `mfirstuc`). You can either redefine `\glscapitalisewords` if you want the change to also affect `\glsentrytitlecase` or if you only want the change to apply to the attribute case-changing then redefine:

```
\glsxtrfieldtitlecasecs{phrase cs}
```

For example:

```
\newcommand*\glsxtrfieldtitlecasecs[1]{\xcapitalisefmtwords*{#1}}
```

(Note that the argument to `\glsxtrfieldtitlecasecs` will be a control sequence whose replacement text is the entry's description, which is why `\xcapitalisefmtwords` is needed instead of `\capitalisefmtwords`.)

Any other values of this attribute are ignored. Remember that there are design limitations for both the first letter uppercasing and the title casing commands. See the `mfirstuc` user manual for further details.

**glossdescfont** (New to version 1.04) In addition to the above, the modified `\glossentrydesc` command also checks this attribute. If set, it should be the name of a control sequence (without the leading backslash) that takes one argument. This control sequence will be applied to the description text. For example:

```
\glssetcategoryattribute{general}{glossdescfont}{emph}
```

**glossname** As `glossdesc` but applies to `\glossentryname`. Additionally, if this attribute is set to “uc” the name is converted to all capitals.

**indexname** If set, the `\glstrpostnamehook` hook used at the end of `\glossentryname` will index the entry using `\index`. See Section 9 for further details.

**glossnamefont** (New to version 1.04) In addition to the above, the modified `\glossentryname` command also checks this attribute. If set, it should be the name of a control sequence (without the leading backslash) that takes one argument. This control sequence will be applied to the name text. For example:

```
\glsssetcategoryattribute{general}{glossnamefont}{emph}
```

Note that this overrides `\glsnamefont` which will only be used if this attribute hasn’t been set.

Remember that glossary styles may additionally apply a font change, such as the list styles which put the name in the optional argument of `\item`.

**glosssymbolfont** (New to version 1.42.) This is similar to `glossnamefont` and `glossdescfont` but is used by `\glossentrysymbol`.

**textformat** (New to version 1.21.) Commands like `\gls` and `\glstext` have the link text encapsulated in the argument of `\glstextformat` by default. If this attribute is set, the control sequence given by the attribute value will be used instead. As with the above, the attribute value should be the name (without the leading backslash) of a command that takes a single argument (the link text). Remember that the abbreviation styles may apply an additional font change.

**hyperoutside** (New to v1.21.) The attribute value may be `false`, `true` or `unset`. If `unset`, `true` is assumed. This indicates the default setting of the `hyperoutside` key, described in Section 2.2.

**dualindex** If set, whenever a glossary entry has information written to the external glossary file through commands like `\gls` and `\glsadd`, a corresponding line will be written to the indexing file using `\index`. See Section 9 for further details.

**targeturl** If set, the hyperlink generated by commands like `\gls` will be set to the URL provided by this attributes value. For example:

```
\glsssetcategoryattribute{general}{targeturl}{master-doc.pdf}
```

(See also the accompanying sample file `sample-external.tex`.) If the URL contains awkward characters (such as `%` or `~`) remember that the base glossaries package provides commands like `\glsperscentchar` and `\glstildechar` that expand to literal characters.

If you want to a named anchor within the target URL (notionally adding `#<name>` to the URL), then you also need to set `targetname` to the anchor `<name>`. You may use `\glslabel` within `<name>` which is set by commands like `\gls` to the entry’s label.

All the predefined glossary styles start each entry listing with `\glstarget` which sets the anchor to `\glolinkprefix\glslabel`, so if you want entries to link to glossaries in the URL given by `targeturl`, you can just do:

```
\glsssetcategoryattribute{general}{targetname}{\glolinkprefix\glslabel}
```

(If the target document changed `\glolinkprefix` then you will need to adjust the above as appropriate.)

If the anchor is in the form `<name1>.<name2>` then use `targetname` for the `<name2>` part and `targetcategory` for the `<name1>` part.

For example:

```
\glsssetcategoryattribute{general}{targeturl}{master-doc.pdf}
\glsssetcategoryattribute{general}{targetcategory}{page}
\glsssetcategoryattribute{general}{targetname}{7}
```

will cause all link text for `general` entries to link to `master-doc.pdf#page.7` (page 7 of that PDF).

If you want a mixture in your document of entries that link to an internal glossary and entries that link to an external URL then you can use the starred form of `\newignoredglossary` for the external list. For example:

```
\newignoredglossary*{external}

\glsssetcategoryattribute{external}{targeturl}{master-doc.pdf}
\glsssetcategoryattribute{general}{targetname}{\glolinkprefix\glslabel}

\newglossaryentry{sample}{name={sample},description={local example}}

\newglossaryentry{sample2}{name={sample2},
  type=external,
  category=external,
  description={external example}}
```

**externallocation** The value should be the file name of the target document when manually indexing an external location (see Section 2.2). In general, it's better to use `bib2gls` v1.7+ which can handle multiple external sources and doesn't require this attribute.

If a term is defined using `\newabbreviation` and accessibility support has been supplied via the `accsupp` package option then the following attributes are also available. If `shortaccess` isn't set its value will be obtained from:

```
\glsdefaultshortaccess{<short>}{<long>}
```

This is defined by `glossaries-accsupp` to just do `<long>` but `glossaries-extra` redefines it to do `<long>` (`<short>`). The `accessinsertdots`, `accessaposplural` and `accessnoshortplural` attributes below refer to the `<short>` form that's passed to this command.

The following attributes are only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it's using `\newabbreviation`). They have no effect if the `accsupp` package option hasn't been used.

**accessinsertdots** If this attribute is set to “true” and the glossaries-accsupp package has been loaded (with the `accsupp` option), then this behaves like `insertdots` but for the *short* part used in the `shortaccess` field instead of the `short` field. This setting will be overridden by an explicit use of the `shortaccess` key in the optional argument of `\newabbreviation` (or `\newacronym`).

**accessaposplural** This boolean attribute overrides `aposplural` for the `shortpluralaccess` key. Has no effect if there's no accessibility support or if the `shortaccess` key hasn't been set or if the `shortpluralaccess` key is explicitly set. If the `aposplural` is set and this attribute isn't set and the `shortaccess` key is set, then the `aposplural` setting governs the default `shortpluralaccess` setting. If you want `aposplural` but don't want it applied to the accessibility support, set the `accessaposplural` attribute to “false”. This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it's using `\newabbreviation`.)

**accessnoshortplural** This boolean attribute overrides `noshortplural` for the `shortpluralaccess` key. The same conditions apply as for `accessaposplural`. This attribute is only applicable to entries defined using `\newabbreviation` (or `\newacronym` if it's using `\newabbreviation`.)

**nameshortaccess** If this attribute is set to “true”, the `access` field (used for the name field's accessibility support) automatically assigned if it's not provided.

**textshortaccess** Like `nameshortaccess` but applies to the `textaccess` field automatically assigned if it's not provided.

**firstshortaccess** Like `nameshortaccess` but applies to the `firstaccess` field automatically assigned if it's not provided.

**combinedfirstsep** The separator to use for `\glscombinefirstsep`.

**combinedfirstsepfirst** The separator to use for `\glscombinedfirstsepfirst`.

**combinedsepfirst** The separator to use for `\glscombinesepfirst`.

**combinedsep** The separator to use for `\glscombinedsep`.

An attribute can be set using:

```
\glssetcategoryattribute{<category-label>}{<attribute-label>}{<value>}
```

where *<category-label>* is the category label, *<attribute-label>* is the attribute label and *<value>* is the new value for the attribute. *This will be localised to the current scope*. If you want a global definition use the following command instead.

If you want to apply the same attribute to multiple categories then use:

```
\glsssetcategoriesattribute{<category-label list>}{<attribute-label>}{<value>}
```

*This has a global effect.*

If you also want to set multiple attributes to the same value, then you can use:

```
\glsssetcategoriesattributes{<category-label list>}{<attribute-label list>}{<value>}
```

*This has a global effect.*

For example:

```
\newcommand{<latinname>}[1]{\emph{#1}}  
\glsssetcategoriesattributes{genus,species}{textformat,glossnamefont}{<latinname>}
```

There is a shortcut version to set the **regular** attribute to “true”:

```
\glsssetregularcategory{<category-label>}
```

This internally uses `\glsssetcategoryattribute` so it has a local effect.

If you need to lookup the category label for a particular entry, you can use the shortcut command:

```
\glsssetattribute{<entry-label>}{<attribute-label>}{<value>}
```

This uses `\glsssetcategoryattribute` with `\glsscategor`y to set the attribute. Note that this will affect all other entries that share this entry’s category.

The above use local assignments so they can be placed inside a group to limit their definition. As from v1.47, the value can be unset using:

```
\glssunsetcategoryattribute{<category-label>}{<attribute-label>}
```

You can fetch the value of an attribute for a particular category using:

```
\glssgetcategoryattribute{<category-label>}{<attribute-label>}
```

Again there is a shortcut if you need to lookup the category label for a given entry:

```
\glssgetattribute{<entry-label>}{<attribute-label>}
```

You can test if an attribute has been assigned to a given category using:

```
\glshascategoryattribute{<category-label>}{<attribute-label>}{<true code>}{<false code>}
```

This uses etoolbox’s `\ifcvoid` and does *<true code>* if the attribute has been set and isn’t blank and isn’t `\relax`. The shortcut if you need to lookup the category label from an entry is:

```
\glshasattribute{<entry-label>}{<attribute-label>}{<true code>}{<false code>}
```

You can test the value of an attribute for a particular category using:

```
\gl@ifcategoryattribute{<category-label>}{<attribute-label>}{<value>}{<true-part>}{<false-part>}
```

This tests if the attribute (given by *<attribute-label>*) for the category (given by *<category-label>*) is set and equal to *<value>*. If true, *<true-part>* is done. If the attribute isn’t set or is set but isn’t equal to *<value>*, *<false part>* is done.

For example:

```
\gl@ifcategoryattribute{general}{nohyper}{true}{NO HYPER}{HYPER}
```

This does “NO HYPER” if the general category has the **nohyper** attribute set to true otherwise it does “HYPER”.

With boolean-style attributes like **nohyper**, make sure you always test for true not false in case the attribute hasn’t been set.

Again there’s a shortcut if you need to lookup the category label from a particular entry:

```
\gl@ifattribute{<entry-label>}{<attribute-label>}{<value>}{<true-part>}{<false-part>}
```

There’s also a shortcut to determine if a particular category has the **regular** attribute set to “true”:

```
\gl@ifregularcategory{<category-label>}{<true-part>}{<false-part>}
```

Alternatively, if you need to lookup the category for a particular entry:

```
\gl@ifregular{<entry-label>}{<true-part>}{<false-part>}
```

Note that if the **regular** attribute hasn’t be set, the above do *<false-part>*. There are also reverse commands that test if the **regular** attribute has been set to “false”:

```
\gl@ifnotregularcategory{<category-label>}{<true-part>}{<false-part>}
```

or for a particular entry:

```
\glsifnotregular{<entry-label>}{<true-part>}{<>false-part>}
```

Again, if the `regular` attribute hasn't been set, the above do *<>false-part>*, so these reverse commands aren't logically opposite in the strict sense.

You can iterate through all entries with a given category using:

```
\glsforeachincategory[<glossary-labels>]{<category-label>}{<glossary-cs>}{<label-cs>}{<body>}
```

This iterates through all entries in the glossaries identified by the comma-separated list *<glossary-labels>* that have the category given by *<category-label>* and performs *<body>* for each match. Within *<body>*, you can use *<glossary-cs>* and *<label-cs>* (which much be control sequences) to access the current glossary and entry label. If *<glossary-labels>* is omitted, all glossaries are assumed.

Similarly, you can iterate through all entries that have a category with a given attribute using:

```
\glsforeachwithattribute[<glossary-labels>]{<attribute-label>}{<attribute-value>}{<glossary-cs>}{<label-cs>}{<body>}
```

This will do *<body>* for each entry that has a category with the attribute *<attribute-label>* set to *<attribute-value>*. The remaining arguments are as the previous command.

You can change the category for a particular entry using the standard glossary field changing commands, such as `\glsfielddef`. Alternatively, you can use

```
\glxtrsetcategory{<entry-labels>}{<category-label>}
```

This will change the category to *<category-label>* for each entry listed in the comma-separated list *<entry-labels>*. This command uses `\glsfieldxdef` so it will expand *<category-label>* and make the change global.

You can also change the category for all entries with a glossary or glossaries using:

```
\glxtrsetcategoryforall{<glossary-labels>}{<category-label>}
```

where *<glossary-labels>* is a comma-separated list of glossary labels.

## 8 Counting References

There are three basic ways of counting entry references:

1. Counting the total number of times `\glsunset` is used (`\glsreset` resets the count and is best avoided). This is provided by the base glossaries package and is intended for documents where the term should be displayed differently if it's only been used a certain number of times. The information has to be written to the `.aux` file so that it's available on the next  $\LaTeX$  run.  
This method is extended by `glossaries-extra` and is described in Section 8.1.
2. Counting the total number of records. This method is only available with `bib2gls` and is intended for documents where the term should be displayed differently if it's only been recorded (indexed) a certain number of times. See Section 10.5 for further details.
3. Counting the number of times the `\gls`-like or `\glstext`-like commands are used. (That is, those commands that internally use `\@gls@link`.) Unlike the other two methods, this just provides a running total rather than the total from the previous  $\LaTeX$  run. This method is intended to make it more convenient to work with hooks like `\glslinkcheckfirsthyperhook`, `\glslinkpostsetkeys` or `\glslinkpresetkeys`. See Section 8.2 for further details.

### 8.1 Entry Counting (First Use Flag)

As mentioned in Section 2.5, `glossaries-extra` modifies the `\glsenableentrycount` command to allow for the `entrycount` attribute. This means that you not only need to enable entry counting with `\glsenableentrycount`, but you also need to set the appropriate attribute (see Section 7).

Remember that entry counting only counts the number of times an entry is used by commands that change the `first use flag`. (That is, all those commands that mark the entry as having been used.) There are many commands that don't modify this flag and they won't contribute to the entry use count.

With `glossaries-extra`, you may use `\cgl`s instead of `\gls` even if you haven't enabled entry counting. You will only get a warning if you use `\glsenableentrycount` without setting the `entrycount` attribute. (With `glossaries`, commands like `\cgl`s will generate a warning if `\glsenableentrycount` hasn't been used.) The abbreviation shortcut `\ab` uses `\cgl`s (see Section 4.3). The acronym shortcut `\ac` uses `\cgl`s if it's been defined with `shortcuts=ac` (or `shortcuts=all`) but uses `\gls` if it's been defined with `shortcuts=acronyms` (or `shortcuts=acro`).



All upper case versions (not provided by glossaries) are also available:

```
\cGLS[<options>]{<label>}[<insert>]
```

and

```
\cGLSpl[<options>]{<label>}[<insert>]
```

These are analogous to `\cgl`s and `\cgl`spl but they use

```
\cGLSformat{<label>}{<insert>}
```

and

```
\cGLSplformat{<label>}{<insert>}
```

which convert the analogous `\cgl`sformat and `\cgl`splformat to upper case.

Just using glossaries:

```
\documentclass{article}
```

```
\usepackage{glossaries}
```

```
\makeglossaries
```

```
\glsenableentrycount
```

```
\newacronym{html}{HTML}{hypertext markup language}
```

```
\newacronym{xml}{XML}{extensible markup language}
```

```
\begin{document}
```

Used once: `\cgl`s{html}.

Used twice: `\cgl`s{xml} and `\cgl`s{xml}.

```
\printglossaries
```

```
\end{document}
```

If you switch to `glossaries-extra` you must set the `entrycount` attribute:

```
\documentclass{article}
```

```
\usepackage{glossaries-extra}
```

```
\makeglossaries
```

```
\glsenableentrycount
```

```

\glssetcategoryattribute{abbreviation}{entrycount}{1}

\newabbreviation{html}{HTML}{hypertext markup language}
\newabbreviation{xml}{XML}{extensible markup language}

\begin{document}

Used once: \cglshtml}.

Used twice: \cglsexml} and \cglsexml}.

\printglossaries

\end{document}

```

When activated with `\glsenableentrycount`, commands such as `\cglsh` now use

```
\glsxtrifcounttrigger{<label>}{<trigger code>}{<normal code>}
```

to determine if the entry trips the entry count trigger. The *<trigger code>* uses commands like `\cglshformat` and unsets the **first use flag**. The *<normal code>* is the code that would ordinarily be performed by whatever the equivalent command is (for example, `\cglsh` will use `\cglshformat` in *<trigger code>* but the usual `\gls` behaviour in *<normal code>*).

The default definition is:

```

\newcommand*{\glsxtrifcounttrigger}[3]{%
  \glsattribute{#1}{entrycount}%
  {%
    \ifnum\glsentryprevcount{#1}>\glsattribute{#1}{entrycount}\relax
    #3%
    \else
    #2%
    \fi
  }%
  {#3}%
}

```

This means that if an entry is assigned to a category that has the **entrycount** attribute then the *<trigger code>* will be used if the previous count value (the number of times the entry was used on the last run) is greater than the value of the attribute.

For example, to trigger normal use if the previous count value is greater than four:

```
\glssetcategoryattribute{abbreviation}{entrycount}{4}
```

There is a convenient command provided to enable entry counting, set the **entrycount** attribute and redefine `\gls`, etc to use `\cglsh` etc:

```
\GlsXtrEnableEntryCounting{<categories>}{<value>}
```

The first argument *<categories>* is a comma-separated list of categories. For each category, the **entrycount** attribute is set to *<value>*. In addition, this does:

```
\renewcommand*\gls{\cglsl}%  
\renewcommand*\Gls{\cGls}%  
\renewcommand*\glspl{\cglspl}%  
\renewcommand*\Glspl{\cGlspl}%  
\renewcommand*\GLS{\cGLS}%  
\renewcommand*\GLSpl{\cGLSpl}%
```

This makes it easier to enable entry-counting on existing documents.

If you use `\GlsXtrEnableEntryCounting` more than once, subsequent uses will just set the **entrycount** attribute for each listed category.

The above example document can then become:

```
\documentclass{article}  
  
\usepackage{glossaries-extra}  
  
\makeglossaries  
  
\GlsXtrEnableEntryCounting{abbreviation}{1}  
  
\newabbreviation{html}{HTML}{hypertext markup language}  
\newabbreviation{xml}{XML}{extensible markup language}  
  
\begin{document}  
  
Used once: \gls{html}.  
  
Used twice: \gls{xml} and \gls{xml}.  
  
\printglossaries  
  
\end{document}
```

The standard entry-counting function describe above counts the number of times an entry has been marked as used throughout the document. (The reset commands will reset the total back to zero.) If you prefer to count per sectional-unit, you can use

```
\GlsXtrEnableEntryUnitCounting{<categories>}{<value>}{<counter-name>}
```

where *<categories>* is a comma-separated list of categories to which this feature should be applied, *<value>* is the trigger value and *<counter-name>* is the name of the counter used by the sectional unit.

Due to the asynchronous nature of T<sub>E</sub>X's output routine, discrepancies will occur in page spanning paragraphs if you use the page counter.

Note that you can't use both the document-wide counting and the per-unit counting in the same document.

The counter value is used as part of a label, which means that `\the<counter-name>` needs to be expandable. Since `hyperref` also has a similar requirement and provides `\theH<counter-name>` as an expandable alternative, `glossaries-extra` will use `\theH<counter-name>` if it exists otherwise it will use `\the<counter-name>`.

The per-unit counting function uses two attributes: `entrycount` (as before) and `unitcount` (the name of the counter).

Both the original document-wide counting mechanism and the per-unit counting mechanism provide a command that can be used to access the current count value for this run:

```
\glentrycurrcount{<label>}
```

and the final value from the previous run:

```
\glentryprevcount{<label>}
```

In the case of the per-unit counting, this is the final value *for the current unit*. In both commands `<label>` is the entry's label.

The per-unit counting mechanism additionally provides:

```
\glentryprevtotalcount{<label>}
```

which gives the sum of all the per-unit totals from the previous run for the entry given by `<label>`, and

```
\glentryprevmaxcount{<label>}
```

which gives the maximum per-unit total from the previous run.

The above two commands are unavailable for the document-wide counting.

Example of per-unit counting, where the unit is the chapter:

```
\documentclass{report}
\usepackage{glossaries-extra}

\GlsXtrEnableEntryUnitCounting{abbreviation}{2}{chapter}

\makeglossaries

\newabbreviation{html}{HTML}{hypertext markup language}
\newabbreviation{css}{CSS}{cascading style sheet}

\newglossaryentry{sample}{name={sample},description={sample}}
```

```
\begin{document}
\chapter{Sample}
```

Used once: `\gls{html}`.

Used three times: `\gls{css}` and `\gls{css}` and `\gls{css}`.

Used once: `\gls{sample}`.

```
\chapter{Another Sample}
```

Used once: `\gls{css}`.

Used twice: `\gls{html}` and `\gls{html}`.

```
\printglossaries
\end{document}
```

In this document, the `css` entry is used three times in the first chapter. This is more than the trigger value of 2, so `\gls{css}` is expanded on **first use** with the short form used on subsequent use, and the `css` entries in that chapter are added to the glossary. In the second chapter, the `css` entry is only used once, which trips the suppression trigger, so in that chapter, the long form is used and `\gls{css}` doesn't get a line added to the glossary file.

The `html` is used a total of three times, but the expansion and indexing suppression trigger is tripped in both chapters because the per-unit total (1 for the first chapter and 2 for the second chapter) is less than or equal to the trigger value.

The `sample` entry has only been used once, but it doesn't trip the indexing suppression because it's in the general category, which hasn't been listed in `\GlsXtrEnableEntryUnitCounting`.

The per-unit entry counting can be used for other purposes. In the following example document the trigger value is set to zero, which means the index suppression won't be triggered, but the unit entry count is used to automatically suppress the hyperlink for commands like `\gls` by modifying the hook

```
\glslinkcheckfirsthyperhook
```

which is used at the end of the macro to determine whether or not to suppress the hyperlink.

```
\documentclass{article}
```

```
\usepackage[colorlinks]{hyperref}
```

```
\usepackage{glossaries-extra}
```

```
\makeglossaries
```

```
\GlsXtrEnableEntryUnitCounting{general}{0}{page}
```

```
\newglossaryentry{sample}{name={sample},description={an example}}
```

```

\renewcommand*{\glslinkcheckfirsthyperhook}{%
  \ifnum\glstextcurrcount\glslabel>0
    \setkeys{glslink}{hyper=false}%
  \fi
}

\begin{document}

A \gls{sample} entry.
Next use: \gls{sample}.

\newpage

Next page: \gls{sample}.
Again: \gls{sample}.

\printglossaries

\end{document}

```

This only produces a hyperlink for the first instance of `\gls{sample}` on each page.

The earlier warning about using the page counter still applies. If the first instance of `\gls` occurs at the top of the page within a paragraph that started on the previous page, then the count will continue from the previous page.

## 8.2 Link Counting

As from version 1.26, an alternative method of entry counting is to count the number of times the `\gls`-like or `\glstext`-like commands are used. (The “link” in this method’s name refers to the use of the internal command `\@gls@link` not to `\hyperlink` although `\@gls@link` may use `\hyperlink` when displaying the [link-text](#).)

To enable link counting use the preamble-only command:

```
\GlsXtrEnableLinkCounting[<master counter>]{<categories>}
```

where *<categories>* is a list of category labels. The optional argument *<master counter>* may be used to identify a master counter (which must be defined). If present, the associated link counter will be reset when the master counter is incremented. This command automatically sets the [linkcount](#) attribute for the given categories. If the optional argument is present, it also sets the [linkcountmaster](#) attribute.

When enabled, commands like `\gls` and `\glstext` increment the associated counter using

```
\glsxtrinlinkcounter{<counter name>}
```

This just does `\stepcounter{<counter name>}` by default but if you need `\refstepcounter`

instead, just redefine this command:

```
\renewcommand*{\glxtrinlinkcounter}[1]{\refstepcounter{#1}}
```

You can access the internal count register using

```
\GlsXtrLinkCounterValue{<label>}
```

where *<label>* is the entry's label. This will expand to 0 if the counter hasn't been defined.

It's also possible to access the display value (`\the<counter>`) using

```
\GlsXtrTheLinkCounter{<counter>}
```

(This will expand to 0 if the counter hasn't been defined.)

In order to conserve resources, the counter is only defined when it first needs to be incremented so terms that have been defined but haven't been used in the document won't have the associated count register allocated.

You can test if the counter has been defined using:

```
\GlsXtrIfLinkCounterDef{<label>}{<true>}{<false>}
```

where *<label>* is the entry's label.

The counter name can be obtained using

```
\GlsXtrLinkCounterName{<label>}
```

This simply expands to the counter name associated with the entry given by *<label>* without any check for existence. For example, to change the display command (`\the<counter>`) using `etoolbox`:

```
\csdef{the\GlsXtrLinkCounterName{duck}}{\Roman{\GlsXtrLinkCounterName{duck}}}
```

This is useful if you just want to change the display for specific entries but isn't convenient if you want to change the display for all entries. Instead, it's simpler to redefine `\GlsXtrTheLinkCounter`. For example:

```
\renewcommand*{\GlsXtrTheLinkCounter}[1]{%
  \GlsXtrIfLinkCounterDef{#1}%
  {\Roman{\GlsXtrLinkCounterName{#1}}}%
  {0}%
}
```

In both cases, the redefinition should be implemented after `\GlsXtrEnableLinkCounting`.

Here's an example document that uses link counting to disable the hyperlink after the first reference. This redefines `\glslinkpresetkeys` (which is used by both `\gls` and `\gls{text}`) instead of `\glslinkcheckfirsthyperhook` (which is used by `\gls` but not by `\gls{text}`).

```

\documentclass{article}

\usepackage[colorlinks]{hyperref}
\usepackage{glossaries-extra}

\makeglossaries

\renewcommand*{\glslinkpresetkeys}{%
  \ifnum\GlsXtrLinkCounterValue{\glslabel}>1
    \setkeys{glslink}{hyper=false}%
  \fi
}

\GlsXtrEnableLinkCounting{general}

\newglossaryentry{sample1}{name={sample1},description={an example}}
\newglossaryentry{sample2}{name={sample2},description={another example}}

\newabbreviation{ex}{ex}{example}

\begin{document}

\section{Sample Section}

\Gls{sample1}, \gls{sample2} and \gls{ex}.
\Glstext{sample1} and \gls{ex} again.

\section{Another Sample Section}

\Gls{sample1}, \gls{sample2} and \gls{ex}.

\printglossaries

\end{document}

```

The use of `\glslinkpresetkeys` means that the options can override this. For example

```
\gls[hyper=true]{sample1}
```

will override the `hyper=false` setting in `\glslinkpresetkeys`. If `\glslinkpostsetkeys` is used instead, the `hyper=false` setting will override the setting provided in the optional argument.

The abbreviation category doesn't have the `linkcount` attribute set (since it's not listed in the argument of `\GlsXtrEnableLinkCounting`). This means that `\GlsXtrLinkCounterValue` always expands to 0 for the abbreviation (ex), so the inequality test

```
\ifnum\GlsXtrLinkCounterValue{\glslabel}>1
```

will always be false. This means that the abbreviation won't have `hyper=false` applied. If the test is changed to



```
\ifnum\GlsXtrLinkCounterValue{\glslabel}=1
\else
\setkeys{glslink}{hyper=false}%
\fi
```

Then the abbreviation will always have `hyper=false` applied.

To reset the counter every section use the optional argument to set the master counter:

```
\GlsXtrEnableLinkCounting[section]{general}
```

## 9 Auto-Indexing

It's possible that you may also want a normal index as well as the glossary, and you may want entries to automatically be added to the index (as in this document). There are two attributes that govern this: `indexname` and `dualindex`.

The auto-indexing is designed for `makeindex` syntax. If you've used the `xindy` package option, the automatic escaping of `xindy` special characters in the sort field may result in an incorrect sort value for the `\index` command used by the auto-indexing. Note also that `texindy` has a fixed set of special characters (corresponding to `makeindex`'s defaults) that can't be customized. You may want to consider using `bib2gls` and its dual entries as an alternative approach.

The `\glstrpostnamehook` macro, used at the end of `\glossentryname` and `\Glossentryname`, checks the `indexname` attribute for the category associated with that entry. Since `\glossentryname` is used in the default glossary styles, this makes a convenient way of automatically indexing each entry name at its location in the glossary without fiddling around with the value of the name key.

The internal macro used by the `glossaries` package to write the information to the external glossary file is modified to check for the `dualindex` attribute.

In both cases, the indexing is done through

```
\glstrdoautoindexname{<label>}{<attribute-label>}
```

This uses the standard `\index` command with the sort value taken from the entry's sort key and the actual value set to `\glssentryname{<label>}`. As from v1.16, there are user-level commands available to change the sort and actual value used by the automated index.

The actual value is given by

```
\glstrautoindexentry{<label>}
```

where `<label>` is the entry's label. The default definition is:

```
\newcommand*{\glstrautoindexentry}[1]{\string\glssentryname{#1}}
```

Note the use of `\string` to prevent `\glssentryname` from being expanded as it's written to the index file.

The sort value is assigned using:

```
\glsextrautoindexassignsort{<cs>}{<label>}
```

where *<label>* is the entry label and *<cs>* is the command which needs to be set to the sort value. The default definition is:

```
\newcommand*\glsextrautoindexassignsort}[2]{%
  \glsletentryfield{#1}{#2}{sort}%
}
```

After this macro is called, *<cs>* is then processed to escape any of `makeindex`'s special characters. Note that this escaping is only performed on the sort not on the actual value. The escaping of the sort value is performed by

```
\glsextrautoindexesc
```

You can redefine this to do nothing if you want to omit the escaping. You may want to consider providing another field to obtain the appropriate sort value if the one provided in the sort field isn't suitable (because it may already have had special characters escaped or it may be a numeric value in the case of sort by use or definition).

The command used to perform the actual indexing is:

```
\glsextrautoindex{<text>}
```

This just does `\index{<text>}` by default.

The entry's parent field isn't referenced in this automated indexing.

For example, to index the value of the first key, instead of the name key:

```
\renewcommand*\glsextrautoindexentry}[1]{\string\glsentryfirst{#1}}
```

and if the sort value also needs to be set to the long field, if present, otherwise the sort field:

```
\renewcommand*\glsextrautoindexassignsort}[2]{%
  \ifglshaslong{#2}%
  {\glsletentryfield{#1}{#2}{long}}%
  {\glsletentryfield{#1}{#2}{sort}}%
}
```

If the value of the attribute given by *<attribute-label>* is "true", no encap will be added, otherwise the encap will be the attribute value. For example:

```
\glssetcategoryattribute{general}{indexname}{textbf}
```

will set the encap to `textbf` which will display the relevant page number in bold whereas

```
\glssetcategoryattribute{general}{dualindex}{true}
```

won't apply any formatting to the page number in the index.

The location used in the index will always be the page number not the counter used in the glossary. (Unless some other loaded package has modified the definition of `\index` to use some thing else.)

By default the format key won't be used with the `dualindex` attribute. You can allow the format key to override the attribute value by using the preamble-only command:

```
\GlsXtrEnableIndexFormatOverride
```

If you use this command and `hyperref` has been loaded, then the `theindex` environment will be modified to redefine `\glshypernumber` to allow formats that use that command.

The `dualindex` attribute will still be used on subsequent use even if the `indexonlyfirst` attribute (or `indexonlyfirst` package option) is set. However, the `dualindex` attribute will honour the `noindex` key.

The `\glsxtrdoautoindexname` command will attempt to escape any of `\makeindex`'s special characters, but there may be special cases where it fails, so take care. This assumes the default `makeindex` `actual`, `level`, `quote` and `encap` values (unless any of the commands `\actualchar`, `\levelchar`, `\quotechar` or `\encapchar` have been defined before `glossaries-extra` is loaded).

If this isn't the case, you can use the following preamble-only commands to set the correct characters.

Be very careful of possible shifting category codes!

```
\GlsXtrSetActualChar{<char>}
```

Set the actual character to `<char>`.

```
\GlsXtrSetLevelChar{<char>}
```

Set the level character to `<char>`.

```
\GlsXtrSetEscChar{<char>}
```

Set the escape (quote) character to `<char>`.

```
\GlsXtrSetEncapChar{<char>}
```

Set the encap character to `<char>`.

## 10 bib2gls: Managing Reference Databases

There is a new command line application called `bib2gls`, which works in much the same way as a combination of `bibtex` and `makeindex/xindy`. Instead of storing all your entry definitions in a `.tex` and loading them using `\input` or `\loadglsentries`, the entries can instead be stored in a `.bib` file and `bib2gls` can selectively write the appropriate commands to a `.gls.tex` file which is loaded using `\glstrresourcefile` (or `\GlsXtrLoadResources`).

This means that you can use a reference managing system, such as JabRef, to maintain the database and it reduces the  $\TeX$  overhead by only defining the entries that are actually required in the document. If you currently have a `.tex` file that contains hundreds of definitions, but you only use a dozen or so in your document, then the build time is needlessly slowed by the unrequired definitions that occur when the file is input. (You can convert an existing `.tex` file containing glossary definitions to a `.bib` file using `convertgls2bib`, supplied with `bib2gls`.)

There are some new commands and options added to `glossaries-extra` to help assist the integration of `bib2gls` into the document build process.

This chapter just provides a general overview of `bib2gls`. The full details and some sample documents are provided in the `bib2gls` [manual](#).

An example of the contents of `.bib` file that stores glossary entries that can be extracted with `bib2gls`:

```
@entry{bird,
  name={bird},
  description = {feathered animal},
  see=[see also]{duck,goose}
}

@entry{duck,
  name={duck},
  description = {a waterbird with short legs}
}

@entry{goose,
  name="goose",
  plural="geese",
  description={a waterbird with a long neck}
}
```

The follow provides some abbreviations:

```
@string{ssi={server-side includes}}
```

```

@string{html={hypertext markup language}}

@abbreviation{shtml,
  short="shtml",
  long= ssi # " enabled " # html,
  description={a combination of \gls{html} and \gls{ssi}}
}

@abbreviation{html,
  short = "html",
  long = html,
  description={a markup language for creating web pages}
}

@abbreviation{ssi,
  short="ssi",
  long = ssi,
  description={a simple interpreted server-side scripting language}
}

```

Here are some symbols:

```
preamble{"\providecommand{\mtx}[1]{\boldsymbol{#1}}"}

```

```

@symbol{M,
  name={\mathcal{M}},
  text={\mathcal{M}},
  description={a matrix}
}

```

```

@symbol{v,
  name={\vec{v}},
  text={\vec{v}},
  description={a vector}
}

```

```

@symbol{S,
  name={\mathcal{S}},
  text={\mathcal{S}},
  description={a set}
}

```

To ensure that `bib2gls` can find out which entries have been used in the document, you need the `record` package option:

```
\usepackage[record]{glossaries-extra}
```

If this option's value is omitted (as above), the normal indexing will be switched off, since `bib2gls` can also sort the entries and collate the locations.

If you still want to use an indexing application (for example, you need a custom `xindy` rule), then just use `record=hybrid` and continue to use `\makeglossaries` and `\printglossary` (or

`\printglossaries`), but you also need to instruct `bib2gls` to omit sorting to save time and to prevent the sort key from being set.

The `.glstex` file created by `bib2gls` is loaded using:

```
\glxtrresourcefile[<options>]{<filename>}
```

(Don't include the file extension in `<filename>`.) There's a shortcut version (recommended over the above) that sets `<filename>` to use `\jobname`:

```
\GlsXtrLoadResources[<options>]
```

On the first use, this command is a shortcut for

```
\glxtrresourcefile[<options>]{\jobname}
```

On subsequent use,<sup>1</sup> this command is a shortcut for

```
\glxtrresourcefile[<options>]{\jobname-<n>}
```

where `<n>` is the current value of

```
\glxtrresourcecount
```

which is incremented at the end of `\GlsXtrLoadResources`. Any advisory notes regarding `\glxtrresourcefile` also apply to `\GlsXtrLoadResources`.

The `\glxtrresourcefile` command writes the line

```
\glxtr@resource{<options>}{<filename>}
```

to the `.aux` file and will input `<filename>.glstex` if it exists.<sup>2</sup>

Since the `.glstex` file won't exist on the first L<sup>A</sup>T<sub>E</sub>X run, the `record` package option additionally switches on `undefaction=warn`. Any use of commands like `\gls` or `\glsnext` will produce ?? in the document, since the entries are undefined at this point. Once `bib2gls` has created the `.glstex` file the references should be resolved. This may cause a shift in the locations if the actual text produced once the entry is defined is significantly larger than the placeholder ?? (as this can alter the page breaking).

Note that as from v1.12, `\glxtrresourcefile` temporarily switches the category code of `@` to `11` (letter) while it reads the file to allow for any internal commands stored in the location field.

## 10.1 Selection

The default behaviour is for `bib2gls` to select all entries that have a record in the `.aux` file, and any dependent entries (including parent and cross-references). The `glsignore` format (for example,

<sup>1</sup>Version 1.11 only allowed one use of `\GlsXtrLoadResources` per document.

<sup>2</sup>v1.08 assumed `<filename>.tex` but that's potentially dangerous if, for example, `<filename>` happens to be the same as `\jobname`. The `.glstex` extension was enforced by version 1.11.

`\gls[format=glsignore]{duck}`) is recognised by `bib2gls` as a special ignored record. This means that it will match the selection criteria but the record won't be added to the location list. This means that you won't get spurious commas in the location list (as can happen with the other indexing methods), so you can do, for example,

```
\GlsXtrSetDefaultNumberFormat{glsignore}
```

at the start of the front matter and

```
\GlsXtrSetDefaultNumberFormat{glsnumberformat}
```

at the start of the main matter to prevent any records in the front matter from occurring in the location lists.

Note that commands like `\glsaddall` and `\glsaddallunused` don't work with `bib2gls` as the command has to iterate over the internal lists of defined entry labels, which will be empty on the first run and on subsequent runs will only contain those entries that have been selected by `bib2gls`.

If you want to add all entries to the glossary, you need to tell `bib2gls` this in the options list. For example:

```
\GlsXtrLoadResources[src={terms},selection={all}]
```

This will add all entries, regardless of whether or not they have any records in the `.aux` file. Those that don't have any records will have an empty location list. See the `bib2gls` user manual for more details of this option.

## 10.2 Sorting and Displaying the Glossary

There are many sorting options provided by `bib2gls`. The default is to sort according to the system locale. If the document has a language setting, you can use `sort=doc` to instruct `bib2gls` to sort according to that. (The language tag obtained from `tracklang`'s interface is written to the `.aux` file.) For a multilingual document you need to explicitly set the locale using a well-formed language tag. For example:

```
\GlsXtrLoadResources[
  src=terms, % data in terms.bib
  sort=de-DE-1996 % sort according to this locale
]
```

The locale-sensitive sort methods usually ignore most punctuation so for lists of symbols you may find it more appropriate to use one of the letter-base sort methods that sort according to the Unicode value of each character. Alternatively you can provide a custom rule. See the `bib2gls` manual for full details of all the available sort methods.

Since the `.gls.tex` file only defines those references required within the document (selected according to the `selection` option) and the definitions have been written in the order corresponding



to bib2gls's sorted list, the glossaries can simply be displayed using `\printunsrtglossary` (or `\printunsrtglossaries`), described in Section 11.2.

Suppose the .bib examples shown above have been stored in the files `terms.bib`, `abbrvs.bib` and `symbols.bib` which may either be in the current directory or on T<sub>E</sub>X's path. Then the document might look like:

```
\documentclass{article}

\usepackage[record]{glossaries-extra}

\setabbreviationstyle{long-short-desc}

\GlsXtrLoadResources[src={terms,abbrvs,symbols}]

\begin{document}
\gls{bird}

\gls{shtml}

\gls{M}

\printunsrtglossaries
\end{document}
```

The document build process (assuming the document is called `mydoc`) is:

```
pdflatex mydoc
bib2gls mydoc
pdflatex mydoc
```

This creates a single glossary containing the entries: `bird`, `duck`, `goose`, `html`, `M`, `shtml` and `ssi` (in that order). The `bird`, `shtml` and `M` entries were added because `bib2gls` detected (from the .aux file) that they had been used in the document. The other entries were added because `bib2gls` detected (from the .bib files) that they are referenced by the used entries. In the case of `duck` and `goose`, they are in the `see` field for `bird`. In the case of `ssi` and `html`, they are referenced in the `description` field of `shtml`. These cross-referenced entries won't have a location list when the glossary is first displayed, but depending on how they are referenced, they may pick up a location list on the next document build.

The entries can be separated into different glossaries with different sort methods:

```
\documentclass{article}

\usepackage[record,abbreviations,symbols]{glossaries-extra}

\setabbreviationstyle{long-short-desc}

\GlsXtrLoadResources[src={terms},sort={en-GB},type=main]

\GlsXtrLoadResources
```

```

[src={abbrvs},sort={letter-nocase},type=abbreviations]

\GlsXtrLoadResources
[src={symbols},sort={use},type={symbols}]

\begin{document}
\gls{bird}

\gls{shtml}

\gls{M}

\printunsrtglossaries
\end{document}

```

Or you can have multiple instance of `\GlsXtrLoadResources` with the same type, which will produce a glossary with ordered sub-blocks. For example:

```

\documentclass{article}

\usepackage[record,style=indexgroup]{glossaries-extra}

\setabbreviationstyle{long-short-desc}

\GlsXtrLoadResources
[src={abbrvs},sort={letter-nocase},type=main,
group={Abbreviations}]

\GlsXtrLoadResources
[src={symbols},sort={use},type=main,
group={Symbols}]

\GlsXtrLoadResources[src={terms},sort={en-GB},type=main]

\begin{document}
\gls{bird}

\gls{shtml}

\gls{M}

\printunsrtglossaries
\end{document}

```

This will result in a glossary where the first group has the title “Abbreviations”, the second group has the title “Symbols” and then follow the usual letter groups. Note that for this example to work, you must run `bib2gls` with the `--group` (or `-g`) switch. For example, if the document is called `myDoc.tex`:

```
pdflatex myDoc
```

```
bib2gls -g myDoc
pdflatex myDoc
```

The value of the group field must always be a label. You can set the corresponding title with `\glstrsetgrouptitle` (see Section 2.11). If no title is set then the label is used as the group title.

You can provide your own custom sort rule. For example, if you are using  $\text{Xe}\LaTeX$  or  $\text{Lua}\LaTeX$ :

```
\GlsXtrLoadResources[
  src=terms, % entries in terms.bib
  sort=custom, % custom sort rule
  sort-rule={% required with sort=custom
    < æ;Æ < a;á;â;ã;ä;Å;Á;Ă;Ä < b,B
    < c;ć,C;Ĉ < d,D < e;é,E;É < f,F < g,G
    < h,H < i;í,I;Î < j,J < l;ł,L;Ł < m,M < n,N
    < o;ö;ø,O;Û;Ü < p,P < q,Q < r,R < s;ś,S;Ś
    < t,T < u;ú,U;Ū < v,V < w,W < x,X < y,Y <
    z;ż,Z;Ż
  }
]
```

Remember that if you are using `inputenc` then extended characters, such as `é` or `ø`, are active and will expand when written to the `.aux` file. So with  $\text{PDF}\LaTeX$  the above would have to be changed to protect against expansion. Some of the options, including `sort-rule`, allow Unicode characters to be indicated in the format `\u<hex>` (or `\u <hex>`) **in the .aux file**. `bib2gls` will recognise this as the character given by the hexadecimal value `<hex>`. The `\u` also needs protection from expansion, so with a non-Unicode aware engine, the character `æ` needs to be written as `\string\uE6` and so on. This is quite cumbersome, but you can use the shortcut `\glshex E6` instead, so the above needs to be written as:

```
\GlsXtrLoadResources[
  src=terms, % entries in terms.bib
  sort=custom, % custom sort rule
  sort-rule={% required with sort=custom
    < \glshex E6;\glshex C6
    < a;\glshex E1;\glshex E5,\glshex E4,A;\glshex C1;\glshex C5;\glshex C4
    < b,B < c;\glshex 0107,C;\glshex 0106 < d,D
    < e;\glshex E9,E;\glshex C9 < f,F < g,G
    < h,H < i;\glshex ED,I;\glshex CD < j,J
    < l;\glshex 0142,L;\glshex 0141 < m,M < n,N
    < o;\glshex F6;\glshex F8,0;\glshex D6;\glshex D8
    < p,P < q,Q < r,R < s;\glshex 013F,S;\glshex 015A
    < t,T < u;\glshex FA,U;\glshex DA < v,V < w,W < x,X < y,Y
    < z;\glshex 017C,Z;\glshex 017B
  }]
]
```

## 10.3 The glossaries-extra-bib2gls package

The package option `record=only` (or simply `record`) automatically loads the supplementary package `glossaries-extra-bib2gls`, which provides some commands that are specific to `bib2gls`. The package isn't loaded by `record=hybrid` as that option is intended for sorting with `makeindex` or `xindy` and it is expected that the sorting will be switched off (with the resource option `sort=none`).

If `glossaries-extra-bib2gls` is loaded via the `record` package option then the check for associated language resource files (see Section 15) will also search for the existence of `glossariesxtr-⟨script⟩.ldf` for each document dialect (where `⟨script⟩` is the four letter script identifier, such as `Latn`).

This package provides some shortcut commands that use `\printunsrtglossary` if the relevant package option has defined the associated glossary: `\printunsrtabbreviations`, `\printunsrtacronyms`, `\printunsrtsymbols`, `\printunsrtnumbers` and `\printunsrtindex`.

The `savenumberlist` package option doesn't have any effect with `bib2gls`. The location lists are saved by default, so `glossaries-extra-bib2gls` patches `\glsentrynumberlist` and `\glsdisplaynumberlist` to work with the location field

```
\glsxtrprovidecommand{⟨cs⟩}[⟨n⟩][⟨default⟩]{⟨definition⟩}
```

This command is intended for use in `@preamble`. It's simply defined to `\providecommand` in `glossaries-extra-bib2gls` but `bib2gls`'s interpreter treats it as `\renewcommand`. This means that you can override `bib2gls`'s internal definition of a command without overriding the command definition in the document (if it's already defined before the resource file is input). For example

```
@preamble{"\glsxtrprovidecommand{\int}{integral}"}
```

This will force `bib2gls` to treat `\int` as the word "integral" to assist sorting but if this preamble code is written to the `.gls.tex` file (as it is by default) then it won't override the current definition (provided by the kernel or redefined by a package).

The helper commands in the resource files are defined using `\providecommand`. For many of them, if you want to provide an alternative definition then you need to define the command before the resource file is loaded. There are a few that may be redefined afterwards but if you use `\renewcommand` then you will get an error on the first  $\LaTeX$  run when the `.gls.tex` file doesn't exist. In this case, you may prefer to use:

```
\glsrenewcommand{⟨cs⟩}[⟨n⟩][⟨default⟩]{⟨definition⟩}
```

This behaves like `\renewcommand` but only generates a warning rather than an error if the command isn't already defined so it won't interrupt the document build.

```
\GlsXtrIndexCounterLink{⟨text⟩}{⟨label⟩}
```

If the `\hyperref` command has been defined (that is, `hyperref` has been loaded before `glossaries-extra`) then this command checks for the existence of the `indexcounter` field. If this field is set for the entry given by `⟨label⟩`, this command does `\hyperref[wrglossary.⟨value⟩]{⟨text⟩}`, where `⟨value⟩` is the value of the `indexcounter` field. If the field isn't set or if `\hyperref` hasn't

been defined, this just does *text*. This command is provided for use with the `indexcounter` package option combined with `bib2gls`'s `save-index-counter` resource option. See the `bib2gls` manual for further details (at least version 1.4).

If you use the `set-widest` resource option, `bib2gls` v1.8+ will now use:

```
\glxtrSetWidest{<type>}{<level>}{<text>}
```

(if it has been defined) to set the widest name for the given glossary type and level. This allows for both the `almtree` style and the styles provided by `glossary-longextra`, which need to know the widest name.

If `bib2gls` can't determine the widest name (typically because the name field consists of commands that aren't recognised by the interpreter) then `bib2gls` v1.8+ will now use:

```
\glxtrSetWidestFallback{<max depth>}{<list>}
```

(if defined). Currently the maximum hierarchical depth *max depth* may only be 0 or 2. This command requires commands provided by the `glossaries-extra-stylemods` package with the `almtree` style enabled. In this case, it may be simpler to just use `\glissetwidest`.

### 10.3.1 Supplemental Locations

```
\glxtrdisplaysupplc{<prefix>}{<counter>}{<format>}{<src>}{<location>}
```

This is used by `bib2gls` version 1.7+ for supplemental locations, instead of using `\glxtrsupphypernumber` with the `externallocation` attribute. This command sets up the location counter and prefix (used in the formation of hyperlinks) and then uses

```
\glxtrmultisupplocation{<location>}{<src>}{<format>}
```

to format the actual location (with an external hyperlink, if supported).

### 10.3.2 Nameref Record

Normally locations are recorded in the `.aux` file in the form:

```
\glxtr@record{<label>}{<prefix>}{<counter>}{<format>}{<location>}
```

The `record=nameref` option, which requires at least `bib2gls` v1.8, instead uses:

```
\glxtr@record@nameref{<label>}{<prefix>}{<counter>}{<format>}{<location>}{<title>}{<href>}{<hcounter>}
```

where *title* is obtained from `\@currentlabelname` and *href* is obtained from `\@currentHref`. These commands require `hyperref`. If they are undefined, *title* and *href* will be left empty and

bib2gls will treat it as a regular record.

Be careful with this option as  $\langle href \rangle$  will globally change on every instance of  $\backslash refstepcounter$  but  $\langle title \rangle$  won't necessarily change. It can therefore cause unexpected behaviour.

The final argument  $\langle hcounter \rangle$  is obtained from  $\backslash theH\langle counter \rangle$  which provides the partial target name associated with the indexing counter. With the original `makeindex/xindy` approach, it's not possible to include this information in the location, so the base glossaries package attempts to derive a prefix from which the  $\langle hcounter \rangle$  value can be reconstituted by appending the prefix. Unfortunately, not all definitions of  $\backslash theH\langle counter \rangle$  are in the form  $\langle prefix \rangle \backslash the\langle counter \rangle$  (most notably the equation counter with chapters) so this can fail.

Since `bib2gls` is customized specifically for use with `glossaries-extra`, it's now possible to save  $\langle hcounter \rangle$ , so the `record=nameref` option does this. By providing both  $\langle href \rangle$  and  $\langle hcounter \rangle$ , you can determine which target you would rather use. The default is to use  $\langle hcounter \rangle$ , which will take you to the place where the corresponding counter was incremented with  $\backslash refstepcounter$ . However, you may choose to switch to using the  $\langle href \rangle$  target, which will take you to the nearest target before the indexing took place.

With `bib2gls` v1.8+, normal locations are displayed using:

```
\glsnoidxdisplayloc{\langle prefix \rangle}{\langle counter \rangle}{\langle format \rangle}{\langle location \rangle}
```

This is provided by the base `glossaries` package and is simply defined to do:

```
\setentrycounter[\langle prefix \rangle]{\langle counter \rangle}\csuse{\langle format \rangle}{\langle location \rangle}
```

Earlier versions of `bib2gls` only used this in the `loclist` field and explicitly used  $\backslash setentrycounter$  in the location field followed by  $\backslash \langle format \rangle \langle location \rangle$ , which follows the code that's created with the default `makeindex` setting. The  $\backslash setentrycounter$  command sets up the prefix needed for  $\backslash glshypernumber$  to reform the target name from the given location.

The locations identified by  $\backslash glsxtr@record@nameref$  are written by `bib2gls` to the location list using:

```
\glsxtrdisplaylocnameref{\langle prefix \rangle}{\langle counter \rangle}{\langle format \rangle}{\langle location \rangle}  
{\langle title \rangle}{\langle href \rangle}{\langle hcounter \rangle}{\langle file \rangle}
```

With normal internal locations,  $\langle file \rangle$  will always be empty. With supplemental locations,  $\langle file \rangle$  will be the external file reference.

The default definition is:

```
\newcommand*\glsxtrdisplaylocnameref}[8]{%  
  \ifstrequal{#2}{equation}%  
  {\glsxtrnameref link{#3}{( #4 )}{#2.#7}{#8}}%  
  {%  
    \ifstreempty{#5}%
```

```

    {%
      \glstrnamereflink{#3}{#4}{#2.#7}{#8}%
    }%
    {%
      \ifstrequal{#2}{page}%
        {\glstrnamereflink{#3}{#4}{#2.#7}{#8}}%
        {\glstrnamereflink{#3}{#5}{#2.#7}{#8}}%
    }%
  }%
}

```

which uses:

```
\glstrnamereflink{<format>}{<title>}{<target>}{<file>}
```

This ignores the *<prefix>*, *<counter>* and *{<location>}* arguments and instead creates a hyperlink with the target name obtained from *<target>* (and *<file>*, if not empty).

Since pages and equations typically don't have titles, the default definition of `\glstrdisplaylocnameref` checks the counter was used as the location. If it's page or if *<title>* is empty, then just the location is used as the hyperlink text. If the counter equation, then the text is the location in parentheses. Otherwise the text is obtained from *<title>*.

If *<file>* is empty an internal link is created with:

```
\glstrfmtinternalnameref{<target>}{<format>}{<title>}
```

otherwise an external link is created with:

```
\glstrfmtexternalnameref{<target>}{<format>}{<title>}{<file>}
```

The *<file>* argument is set by `bib2gls` for supplemental locations.

Here's alternative definition that uses the *<prefix>* and *<counter>* to reform the target name (as `\glsnoidxdisplayloc`) but uses the *<title>* as the hyperlink text:

```

\renewcommand*{\glstrdisplaylocnameref}[7]{%
  \glstrnamereflink{#3}{#5}{#6}{#7}%
}

```

which uses:

```
\glstrnamecloclink{<prefix>}{<counter>}{<format>}{<location>}{<title>}{<file>}
```

This uses the same commands as `\glstrnamereflink` to produce the hyperlinks.

In both cases, the link is encapsulated with the text-block command whose name is given by *<format>*, but `\glshypernumber` is first locally redefined to `\@firstofone` to prevent a conflict with the usual location hyperlink formation. This means that if the *<format>* is `hyperbf` then it will simply behave like `textbf`.

For compactness, `bib2gls` merges normal records if the `<prefix>`, `<counter>` and `<location>` all match. (An order of precedence can be provided for format conflicts.) With `nameref` records, you can use the `--merge-nameref-on` switch provided by `bib2gls v1.8+` to determine how to merge `nameref` records. This switch must be followed by one of the following keywords: `hcounter` (merge on `<hcounter>`, default) `href` (merge on `<href>`), `title` (merge on `<title>`) and `location` (merge on `<location>`, as regular records). In all cases, the `<counter>` must also match.

### 10.3.3 Helper Commands for Resource Options

```
\glshex
```

This is just defined as `\string\u`, which is required when you need to indicate a Unicode character in the form `\u{hex}` in some of the resource options (as illustrated above).

```
\glscapturedgroup
```

This is just defined as `\string\%` and is used for the captured group reference in a replacement part of a regular expression substitution (requires at least `bib2gls` version 1.5). For example:

```
sort-replace={{([a-zA-Z])\string\.\}\glscapturedgroup1}}
```

This only removes a full stop that follows any of the characters `a,...,z` or `A,...,Z`.

If you use the `save-child-count` resource option, you can test if the `childcount` field is non-zero using:

```
\GlsXtrIfHasNonZeroChildCount{<label>}{<>true>}{<>false>}
```

This internally uses `\GlsXtrIfFieldNonZero` and will do `<>false>` if the field isn't set. Within `<>true>` and `<>false>` you can use `\glscurrentfieldvalue` to access the value. (It will be 0 in `<>false>` if the field isn't set.) As from v1.47, there is also a starred version which uses `\GlsXtrIfFieldNonZero*` (don't add grouping).

A convenient shortcut for use in the `entry-type-aliases` setting:

```
\GlsXtrBibTeXEntryAliases
```

This provides aliases for Bib<sub>T</sub>E<sub>X</sub>'s standard entry types to `bib2gls`'s `@bibtexentry` entry type (requires at least `bib2gls` version 1.4).

You may also want to provide storage keys for Bib<sub>T</sub>E<sub>X</sub>'s standard fields rather than having to alias them all. This can be done with:

```
\GlsXtrProvideBibTeXFields
```

Note that Bib<sub>T</sub>E<sub>X</sub>'s `type` field clashes with the `glossaries` package's `type` key, so this command provides the key `bibtextype` instead. You can alias it with `field-aliases=type=bibtextype` in the resource options. Each storage key is provided with a convenient command to access the value



in the form `\glxtrbib<field>`. For example, `\glxtrbibaddress`. The `bibtex` type field can be accessed with `\glxtrbibtype`. Each of these commands takes the entry label as the sole argument.

The `glossaries-extra-bib2gls` package also provides definitions of the missing mathematical Greek commands: `\Alpha`, `\Beta`, `\Epsilon`, `\Zeta`, `\Eta`, `\Iota`, `\Kappa`, `\Mu`, `\Nu`, `\Omicron`, `\Rho`, `\Tau`, `\Chi`, `\Digamma`, `\omicron`. These are all defined with `\providecommand`, so they won't override any definitions provided by any package loaded before `glossaries-extra`. Since `bib2gls`'s interpreter recognises these commands, using them instead of explicitly using the Latin characters with the same shape helps to keep the Greek symbols together when sorting. Similarly, if `upgreek` has been loaded, the missing upright Greek commands are also provided.

The remaining commands provide common rule blocks for use in the `sort-rule` resource option. If you want a rule for a specific locale, you can provide similar commands in a file called `glossariesxtr-<tag>.ldf`, where `<tag>` identifies the dialect, locale, region or root language. See the description of `\IfTrackedLanguageFileExists` in the `tracklang` documentation for further details. If this file is on  $\TeX$ 's path and the `tracklang` package (automatically loaded by `glossaries`) detects that the document has requested that language or locale, then the file will automatically be loaded. For example, if you want to provide a rule block for Welsh, then create a file called `glossariesxtr-welsh.ldf` that contains:

```
\ProvidesGlossariesExtraLang{welsh}[2018/02/23 v1.0]

\@ifpackageloaded{glossaries-extra-bib2gls}
{
  \newcommand{\glxtrWelshRules}{%
    \glxtrLatinA
    \string<b,B
    \string<c,C
    \string<ch,CH
    \string<d,D
    \string<dd,DD
    \string<\glxtrLatinE
    \string<f,F
    \string<ff,FF
    \string<g,G
    \string<ng,NG
    \string<\glxtrLatinH
    \string<\glxtrLatinI
    \string<j,J
    \string<\glxtrLatinL
    \string<ll,LL
    \string<\glxtrLatinM
    \string<\glxtrLatinN
    \string<\glxtrLatinO
    \string<\glxtrLatinP
    \string<ph,PH
    \string<r,R
    \string<rh,RH
    \string<\glxtrLatinS
```

```

\string<\glxtrLatinT
\string<th,TH
\string<u,U
\string<w,W
\string<y,Y
}
}
{}% glossaries-extra-bib2gls.sty not loaded

```

(The use of `\string` is in case the `<` character has been made active.) You can provide more than one rule-block per local, to allow for loanwords or foreign words. For example, you could provide `\glxtrWelshIRules`, `\glxtrWelshIIRules` etc.

If the rules are for a particular script (independent of language or region) then they can be provided in a file given by `glossariesxtr-⟨script⟩.ldf` instead. For example, the file `glossariesxtr-Cyrl.ldf` could contain:

```

\ProvidesGlossariesExtraLang{Cyrl}[2018/02/23 v1.0]
\newcommand*{\glxtrGeneralCyrillicIRules}{%
  % Cyrillic rules
}
\newcommand*{\glxtrGeneralCyrillicIIRules}{%
  % an alternative set of Cyrillic rules
}

```

(Remember that the required document language scripts need to be tracked through the `tracklang` package, in order for these files to be automatically loaded. This essentially means ensuring you load the appropriate language package before `tracklang` is loaded by the base `glossaries` package or any other package that uses it. See the `tracklang` documentation for further details.)

Alternatively, if the rules are specific to a subject rather than a region or language, then you can provide a supplementary package. For example, if you have a package called, say, `mapsymbols` that provides map symbols, then the file `mapsymbols.sty` might contain:

```

\NeedsTeXFormat{LaTeX2e}
\ProvidesPackage{mapsymbols}
  some package or font loading stuff here to provide
  the appropriate symbols
\newcommand{\Stadium}{...}
\newcommand{\Battlefield}{...}
\newcommand{\Harbour}{...}
  etc

```

```

Provide a rule block:
\newcommand{\MapSymbolOrder}{%
  \glshex 2694 % crossed-swords 0x2694
  \string< \glshex 2693 % anchor 0x2693
  \string< \glshex 26BD % football 0x26BD
}

```

and the supplementary file `mapsymbols.bib` can provide the appropriate definitions for `bib2gls`:

```
@preamble{"\glsxtrprovidecommand{\Harbour}{\char"2693}
\glsxtrprovidecommand{\Battlefield}{\char"2694}
\glsxtrprovidecommand{\Stadium}{\char"26BD}"}

```

Now both the preamble and rule block can be used in the resource set:

```
\usepackage{mapsymbols}% my custom package
\usepackage[record]{glossaries-extra}

\GlsXtrLoadResources[
  src={mapsymbols,% <--- my custom mapsymbols.bib
  entries% data in entries.bib
  },
  sort={custom},
  sort-rule={\glsxtrcontrolrules % control codes
; \glsxtrspacerules % space characters
; \glsxtrnonprintablerules % non-printable characters
; \glsxtrcombiningdiacriticrules % combining diacritics
, \glsxtrhyphenrules % hyphens
< \glsxtrgeneralpuncrules % general punctuation
< \glsxtrdigitrules % 0, ..., 9
< \glsxtrfractionrules % fraction symbols
< \MapSymbolOrder % <--- custom map symbols
< \glsxtrMathItalicGreekIrules % math-greek symbols
< \glsxtrGeneralLatinIrules % Latin letters
}
]

```

The following commands are provided by `glossaries-extra-bib2gls`. They should be separated by the rule separator characters `;` (semi-colon) or `,` (comma) or `&` (ampersand) or `<` (less than). See Java's [RuleBasedCollator](#) documentation for details of the rule syntax.

For example, the following will place the mathematical Greek symbols (`\alpha`, `\Alpha`, `\beta`, `\Beta` etc) in a block before Latin characters:

```
sort-rule={\glsxtrcontrolrules
; \glsxtrspacerules
; \glsxtrnonprintablerules
; \glsxtrcombiningdiacriticrules
, \glsxtrhyphenrules
< \glsxtrgeneralpuncrules
< \glsxtrdigitrules
< \glsxtrfractionrules
< \glsxtrMathItalicGreekIrules
< \glsxtrGeneralLatinIVrules
< \glsxtrLatinAA
< \glsxtrLatinOslash
}

```

<code>\glsxtrcontrolrules</code>
----------------------------------

These are control characters that are usually placed at the start of a rule in the ignored section.

They typically won't occur in any sort values, but if they do they should normally be ignored.

`\glxtrspacerules`

These are space characters. They typically come after the control characters with the two blocks separated by a ; (semi-colon).

`\glxtrnonprintablerules`

These are non-printable characters (BOM, tabs, line feed and carriage return). They typically come after the spaces separated by a ; (semi-colon). These characters aren't checked for by `bib2gls` when it determines whether or not to use the interpreter, so a TAB or newline character may end up in the sort value if it wasn't interpreted.

`\glxtrcombiningdiacriticrules`

These are combining diacritic marks which typically follow the space and non-printable blocks (separated by a semi-colon). This command is defined in terms of sub-block commands:

```
\newcommand*{\glxtrcombiningdiacriticrules}{%
  \glxtrcombiningdiacriticIrules\string;
  \glxtrcombiningdiacriticIIrules\string;
  \glxtrcombiningdiacriticIIIrules\string;
  \glxtrcombiningdiacriticIVrules
}
```

If you prefer, you can use the sub-blocks directly in your required ordered.

`\glxtrcombiningdiacriticIrules`

This contains the combining diacritics: acute, grave, breve, circumflex, caron, ring, vertical line above, diaeresis (umlaut), double acute, tilde, dot above, combining macron.

`\glxtrcombiningdiacriticIIrules`

This contains the combining diacritics: short solidus overlay, cedilla, ogonek, dot below, low line, overline, hook above, double vertical line above, double grave accent, candrabindu, inverted breve, turned comma above, comma above, reversed comma above, comma above right, grave accent below, acute accent below.

`\glxtrcombiningdiacriticIIIrules`

This contains the combining diacritics: left tack below, right tack below, left angle above, horn, left half ring below, up tack below, down tack below, plus sign below, minus sign below, palatalized hook below, retroflex hook below, diaeresis below, ring below, comma below, vertical line below, bridge below, inverted double arch below, caron below, circumflex accent below, breve below,

inverted breve below, tilde below, macron below, double low line, tilde overlay, short stroke overlay, long stroke overlay, long solidus overlay, right half ring below, inverted bridge below, square below, seagull below, x above, vertical tilde, double overline, Greek perispomeni, Greek dialytika tonos, Greek ypogegrammeni, double tilde, double inverted breve, Cyrillic titlo, Cyrillic palatalization, Cyrillic dasia pneumata, Cyrillic psili pneumata.

```
\glxtrcombiningsdiacriticIVrules
```

This contains the combining diacritics: left harpoon above, right harpoon above, long vertical line overlay, short vertical line overlay, anticlockwise arrow above, clockwise arrow above, left arrow above, right arrow above, ring overlay, clockwise ring overlay, anticlockwise ring overlay, three dots above, four dots above, enclosing circle, enclosing square, enclosing diamond, enclosing circle backslash, left right arrow above.

```
\glxtrhyphenrules
```

This contains hyphens (including the minus sign 0x2212). This rule block typically comes after the diacritic rules separated by a comma.

```
\glxtrgeneralpuncrules
```

This contains punctuation characters. This rule block typically comes after the hyphen rules separated by a less than (<). As with the combining diacritics, this command is defined in terms of sub-blocks which may be used directly instead if a different order is required:

```
\newcommand*{\glxtrgeneralpuncrules}{%  
  \glxtrgeneralpuncIrules  
  \string<\glxtrcurrencyrules  
  \string<\glxtrgeneralpuncIIrules  
}
```

```
\glxtrgeneralpuncIrules
```

This is the first punctuation sub-block containing: underscore, macron, comma, semi-colon, colon, exclamation mark, inverted exclamation mark, question mark, inverted question mark, solidus, full stop, acute accent, grave accent, circumflex accent, diaeresis, tilde, middle dot, cedilla, straight apostrophe, straight double quote, left guillemet, right guillemet, left parenthesis, right parenthesis, left square bracket, right square bracket, left curly bracket, right curly bracket, section sign, pilcrow sign, copyright sign, registered sign, at sign.

```
\glxtrcurrencyrules
```

This sub-block contains some currency symbols: currency sign, Thai currency symbol baht, cent sign, colon sign, cruzeiro sign, dollar sign, dong sign, euro sign, French franc sign, lira sign, mill sign, naira sign, peseta sign, pound sign, rupee sign, new sheqel sign, won sign, yen sign.

```
\glxtrgeneralpuncIIrules
```

This sub-block contains some other punctuation symbols: asterisk, backslash, ampersand, hash sign, percent sign, plus sign, plus-minus sign, division sign, multiplication sign, less-than sign, equals sign, greater-than sign, not sign, vertical bar (pipe), broken bar, degree sign, micron sign.

```
\glxtrdigitrules
```

This rule block contains the Basic Latin digits (0, ..., 9) and the subscript and superscript digits (0<sup>0</sup> etc) made equivalent to the corresponding Basic Latin digit. The digit block typically comes after the punctuation rules separated by a less than (<).

```
\glxtrBasicDigitrules
```

This rule block contains just the Basic Latin digits (0, ..., 9).

```
\glxtrSubScriptDigitrules
```

This rule block contains just the subscript digits (0 ... 9).

```
\glxtrSuperScriptDigitrules
```

This rule block contains just the superscript digits (0<sup>0</sup> ... 9<sup>9</sup>).

```
\glxtrfractionrules
```

This rule block contains vulgar fraction characters. The digit block typically comes after the digit rules separated by a less than (<).

There are a number of Latin rule blocks. Some of these included extended characters or ligatures (such as ß or œ) but they don't include accented characters. If you require a Latin rule block that includes accented characters, digraphs, trigraphs or other extended characters, then it's best to provide similar commands in a `glossariesxtr-⟨tag⟩.ldf` file for the particular language or region.

```
\glxtrGeneralLatinIrules
```

This is just the basic (non-extended) Latin alphabet with the superscript and subscript Latin letters (a<sup>a</sup> etc) treated as the equivalent basic Latin letter. (If you don't want the subscripts and superscripts included you can redefine `\glxtrLatinA` etc to omit them.)

```
\glxtrGeneralLatinIIrules
```

This is like `\glxtrGeneralLatinIrules` but it includes eth (Ð) between 'D' and 'E' and eszett (ß) treated as 'ss'.

```
\glxtrGeneralLatinIIIrules
```

This is like `\glxtrGeneralLatinIrules` but it includes eth (Ð) between ‘D’ and ‘E’ and eszett (ß) treated as ‘sz’.

```
\glxtrGeneralLatinIVrules
```

This is like `\glxtrGeneralLatinIrules` but it includes eth (Ð) between ‘D’ and ‘E’, ae-ligature (æ) is treated as ‘æ’, oe-ligature (œ) is treated as ‘oe’, eszett (ß) treated as ‘ss’ and thorn (þ) is treated as ‘th’.

```
\glxtrGeneralLatinVrules
```

This is like `\glxtrGeneralLatinIrules` but it includes eth (Ð) between ‘D’ and ‘E’, eszett (ß) treated as ‘ss’ and thorn (þ) treated as ‘th’.

```
\glxtrGeneralLatinVIrules
```

This is like `\glxtrGeneralLatinIrules` but it includes eth (Ð) between ‘D’ and ‘E’, eszett (ß) treated as ‘sz’ and thorn (þ) treated as ‘th’.

```
\glxtrGeneralLatinVIIrules
```

This is like `\glxtrGeneralLatinIrules` but it includes ae-ligature (æ) between ‘A’ and ‘B’, eth (Ð) between ‘D’ and ‘E’, insular G (Ƿ) instead of ‘G’, oe-ligature between ‘O’ and ‘P’, long s (ſ) equivalent to ‘s’, thorn (þ) between ‘T’ and ‘U’ andwynn (ƿ) instead of W.

```
\glxtrGeneralLatinVIIIrules
```

This is like `\glxtrGeneralLatinIrules` but ae-ligature (æ) is treated as ‘æ’, oe-ligature (œ) is treated as ‘oe’, eszett (ß) treated as ‘ss’, thorn (þ) is treated as ‘th’, Ø is treated as ‘O’ and Ʒ is treated as ‘L’.

```
\glxtrLatinA
```

A mini-rule that just covers ‘A’ but includes the sub- and superscript A.

```
\glxtrLatinE
```

A mini-rule that just covers ‘E’ but includes the subscript E.

```
\glxtrLatinH
```

A mini-rule that just covers ‘H’ but includes the subscript H.

```
\glxtrLatinK
```

A mini-rule that just covers 'K' but includes the subscript K.

```
\glxtrLatinI
```

A mini-rule that just covers 'I' but includes the superscript I.

```
\glxtrLatinL
```

A mini-rule that just covers 'L' but includes the subscript L.

```
\glxtrLatinM
```

A mini-rule that just covers 'M' but includes the subscript M.

```
\glxtrLatinN
```

A mini-rule that just covers 'N' but includes the sub- and superscript N.

```
\glxtrLatinO
```

A mini-rule that just covers 'O' but includes the sub- and superscript O.

```
\glxtrLatinP
```

A mini-rule that just covers 'P' but includes the subscript P.

```
\glxtrLatinS
```

A mini-rule that just covers 'S' but includes the subscript S.

```
\glxtrLatinT
```

A mini-rule that just covers 'T' but includes the subscript T.

```
\glxtrLatinX
```

A mini-rule that just covers 'X' but includes the subscript X.

```
\glxtrLatinEszettSs
```

A mini-rule that just covers eszett (ß) and makes long s (ſ) followed by short 's' equivalent to 'ß'.  
(This is used in the above blocks that treat 'ß' as 'ss'.)



```
\glxtrLatinEszettSz
```

A mini-rule that just covers eszett (ß) and makes long s (ſ) followed by ‘z’ equivalent to ‘ß’. (This is used in the above blocks that treat ‘ß’ as ‘sz’.)

```
\glxtrLatinEth
```

A mini-rule for eth (Ð) so you don’t need to remember the Unicode values.

```
\glxtrLatinThorn
```

A mini-rule for thorn (þ) so you don’t need to remember the Unicode values.

```
\glxtrLatinAELigature
```

A mini-rule for ae-ligature (æ) so you don’t need to remember the Unicode values.

```
\glxtrLatinOELigature
```

A mini-rule for oe-ligature (œ) so you don’t need to remember the Unicode values.

```
\glxtrLatinOslash
```

A mini-rule for ‘Ø’ so you don’t need to remember the Unicode values.

```
\glxtrLatinLslash
```

A mini-rule for ‘Ł’ so you don’t need to remember the Unicode values.

```
\glxtrLatinWynn
```

A mini-rule for wynn (ƿ) so you don’t need to remember the Unicode values.

```
\glxtrLatinInsularG
```

A mini-rule for insular G (ḡ) so you don’t need to remember the Unicode values.

```
\glxtrLatinSchwa
```

A mini-rule that just covers schwa (ə) but includes the subscript schwa. (Not used in any of the provided Latin rule blocks described above.)

```
\glxtrLatinAA
```

A mini-rule for ‘Å’ so you don’t need to remember the Unicode values. (Not used in any of the

provided Latin rule blocks described above.)

```
\glstrMathGreekIrules
```

A rule block for mathematical Greek (`\alpha`, `\beta` etc) and upright Greek (`\upalpha`, etc, from the `upgreek` package) characters that includes digamma (`\digamma` and `\Digamma`) between epsilon and zeta. The upright and italic versions are gathered together into the same letter group.

```
\glstrMathGreekIIrules
```

As `\glstrMathGreekIrules` but doesn't include digamma.

```
\glstrMathUpGreekIrules
```

A rule block for upright Greek (`\upalpha`, etc, from the `upgreek` package) characters that includes digamma (`\digamma` and `\Digamma`) between epsilon and zeta.

```
\glstrMathUpGreekIIrules
```

A rule block for upright Greek (`\upalpha`, etc, from the `upgreek` package) that doesn't include digamma.

```
\glstrMathItalicGreekIrules
```

A rule block for mathematical Greek (`\alpha`, `\Alpha`, etc) characters that includes digamma (`\diagamma` and `\Digamma`) between epsilon and zeta. Note that even though the upper case `\Delta` etc are actually rendered upright by `LATEX`, `bib2gls`'s interpreter treats them as italic to help keep them close to the lower case versions.

```
\glstrMathItalicGreekIIrules
```

A rule block for mathematical Greek (`\alpha`, `\Alpha`, etc) characters that doesn't include digamma.

```
\glstrMathItalicUpperGreekIrules
```

A rule block for upper case mathematical Greek (`\Alpha`, `\Beta`, etc) characters that includes digamma (`\Digamma`) between epsilon and zeta.

```
\glstrMathItalicUpperGreekIIrules
```

A rule block for upper case mathematical Greek (`\Alpha`, `\Beta`, etc) characters that doesn't include digamma.

```
\glxtrMathItalicLowerGreekIrules
```

A rule block for lower case mathematical Greek (`\alpha`, `\beta`, etc) characters that includes digamma (`\digamma`) between epsilon and zeta.

```
\glxtrMathItalicLowerGreekIIrules
```

A rule block for lower case mathematical Greek (`\alpha`, `\beta`, etc) characters that doesn't include digamma.

Additionally, there are commands in the form `\glxtrUpAlpha`, `\glxtrUpBeta` etc and `\glxtrMathItalicAlpha`, `\glxtrMathItalicBeta` etc that just cover the upper and lower case forms of a special Greek character (`\Upalpha`, `\upalpha` etc and `\Alpha`, `\alpha` etc) as well as the following:

```
\glxtrMathItalicPartial
```

The partial derivative symbol ( $\partial$ ).

```
\glxtrMathItalicNabla
```

The nabla symbol ( $\nabla$ ).

## 10.4 Supplementary Commands

These commands are provided by `glossaries-extra` for use with `bib2gls`.

The information provided with `\GlsXtrLoadResources` is written to the `.aux` file using

```
\protected@write\@auxout{\glxtrresourceinit}{\langle information \rangle}
```

where `\langle information \rangle` is the information to pass to `bib2gls`. The command in the second argument

```
\glxtrresourceinit
```

may be used to temporarily redefine commands before the information is written to the file. This does nothing by default, but may be redefined to allow the use of short commands for convenience. For example, with:

```
\renewcommand{\glxtrresourceinit}{\let\u\glshex}
```

you can just use, for example, `\u E6` instead of `\string\uE6` in the custom rule. This redefinition of `\u` is scoped so its original definition is restored after the write operation.

If you have multiple resource commands and you want a default set of options you can supply them in the definition of:

```
\GlsXtrDefaultResourceOptions
```

For example:

```
\renewcommand{\GlsXtrDefaultResourceOptions}{selection=all}
```

This should be done before the resource commands.

It's possible to specify label prefixes. For example, modifying the earlier example:

```
\documentclass{article}

\usepackage[record,style=indexgroup]{glossaries-extra}

\setabbreviationstyle{long-short-desc}

\GlsXtrLoadResources
[src={abbrvs},sort={letter-nocase},type=main,
label-prefix={abr.},
group={Abbreviations}]

\GlsXtrLoadResources
[src={symbols},sort={use},type=main,
label-prefix={sym.},
group={Symbols}]

\GlsXtrLoadResources[src={terms},sort={en-GB},type=main
label-prefix={trm.}]

\begin{document}
\gls{trm.bird}

\gls{abr.shtml}

\gls{sym.M}

\printunsrtglossaries
\end{document}
```

If you do something like this, you may find it more convenient to define custom commands that set the prefix. For example:

```
\newcommand*{\sym}[2] [] {\gls[#1]{sym.#2}}
```

The problem with this is that the custom command `\sym` doesn't allow for modifiers (such as `\gls*` or `\gls+`). Instead you can use:

```
\glsxtrnewgls[<default options>]{<prefix>}{<cs>}
```

which defines the command `<cs>` that behaves like

```
\gls<modifier>[<default options>,<options>]{<prefix><label>}[<insert>]
```

For example:

```
\glstrnewgls{sym.}{\sym}
```

or (to default to no hyperlinks)

```
\glstrnewgls[hyper=false]{sym.}{\sym}
```

now you can use `\sym+{M}` to behave like `\gls+{sym.M}`.

If you also want the plural and first letter upper case versions you can use

```
\glstrnewglslike[<default options>]{<prefix>}{<gls-like cs>}
  {<glspl-like cs>}{<Gls-like cs>}{<Glspl-like cs>}
```

For example:

```
\glstrnewglslike[hyper=false]{idx.}{\idx}{\idxpl}{\Idx}{\Idxpl}
```

For the all caps versions:

```
\glstrnewGLSlike[<default options>]{<prefix>}{<GLS-like cs>}
  {<GLSpl-like cs>}
```

For example:

```
\glstrnewGLSlike[hyper=false]{idx.}{\IDX}{\IDXpl}
```

There's an analogous command for `\rgls`:

```
\glstrnewrgls[<default options>]{<prefix>}{<cs>}
```

and for `\rgls`, `\rglspl`, `\rGls` and `\rGlspl`:

```
\glstrnewrglslike[<default options>]{<prefix>}{<rgls-like cs>}
  {<rglspl-like cs>}{<rGls-like cs>}{<rGlspl-like cs>}
```

and for the all caps:

```
\glstrnewrGLSlike[<default options>]{<prefix>}{<rGLS-like cs>}
  {<rGLSpl-like cs>}
```

If you provide your own custom command with just `\newcommand` that has syntax that starts with `[<options>]{<label>}`, then you can notify `bib2gls` using:

```
\glstridentifyglslike{<prefix>}{<command>}
```

This writes information to the `.aux` file so that `bib2gls` can search for the given command when looking for dependencies.

Another possibility is to set up known label prefixes, with each one identified by:

```
\glxtraddlabelprefix{<prefix>
```

These should be listed in order of precedence. Since no entries are defined on the first L<sup>A</sup>T<sub>E</sub>X run, the final prefix should be the fallback. You can prepend a prefix to the list using:

```
\glxtrprependlabelprefix{<prefix>
```

which gives it the highest order of precedence.

The *<prefix>* argument may be empty. You can clear the list with:

```
\glxtrclearlabelprefixes
```

You can test if a prefix is already in the list with:

```
\glxtrifinlabelprefixlist{<prefix>}{<true>}{<false>
```

In general it's best to avoid adding multiple instances of the same prefix, so you can check with this command before adding a prefix to the list. However, it can be useful to repeat a prefix at the end of the list so that it can be used as a fallback for entries that haven't yet been defined.

With the list of possible prefixes set up (including an empty prefix if necessary), you can use:

```
\dgl[s][<options>]{<label>}[<insert>]
```

which behaves like

```
\gl[s][<options>]{<prefix><label>}[<insert>]
```

where *<prefix>* is the first prefix in the list such that *<prefix><label>* matches a defined entry (or the last entry in the prefix list if none match).

There are also analogous commands for the plural and case-changing versions:

```
\dglspl[<options>]{<label>}[<insert>]
```

(uses `\glspl`),

```
\dGls[<options>]{<label>}[<insert>]
```

(uses `\Gls`),

```
\dGlspl[<options>]{<label>}[<insert>]
```

(uses `\Glspl`),

```
\dGLS[<options>]{<label>}[<insert>]
```

(uses \GLS),

```
\dGLSp1[<options>]{<label>}[<insert>]
```

(uses \GLSp1),

```
\dglslink[<options>]{<label>}[<insert>]
```

(uses \glslink),

```
\dglsdisp[<options>]{<label>}[<insert>]
```

(uses \glsdisp).

These commands are essentially provided for a mixture of single and dual entries. Suppose the file `entries.bib` contains:

```
@index{duck}
@dualindexabbreviation{svm,
  short={SVM},
  long={support vector machine}
}
@dualindexsymbol{pi,
  symbol={\ensuremath{\pi}},
  description={ratio of a circle's circumference to its
    diameter}
}
```

and suppose the document code is:

```
\documentclass{article}
\usepackage{hyperref}
\usepackage[record,abbreviations,symbols]{glossaries-extra}

\newcommand{\bibglsnewdualindexsymbolsecondary}[5]{%
  \longnewglossaryentry*{#1}{name={#3},category={symbol},
    type={symbols},symbol={#4},#2}{#5}%
}

\GlsXtrLoadResources[src=entries]

\begin{document}
First use: \gls{duck}, \gls{svm}, \gls{pi}.
Next use: \gls{duck}, \gls{svm}, \gls{pi}.
\printunsrtglossaries
\end{document}
```

This uses the default empty primary prefix and `dual.` for the dual prefix, so `\gls{svm}` is referencing the primary entry, which is (essentially) an `@index` type not an abbreviation. It therefore doesn't follow the abbreviation style, and it also hyperlinks to the index not to the list of abbreviations. Similarly for `\gls{pi}`, which references the primary `@index` entry rather than the symbol.

What's really needed is:

```
\gls{duck}, \gls{dual.svm}, \gls{dual.pi}.
```

or with

```
\GlsXtrLoadResources[src=entries,
  label-prefix={idx.},
  dual-prefix={}
]
```

then only the entries without a dual need a prefix:

```
\gls{idx.duck}, \gls{svm}, \gls{pi}.
```

Using `\glsxtrnewglslike`, as earlier, this can be simplified to:

```
\idx{duck}, \gls{svm}, \gls{pi}.
```

but this requires remembering which terms have duals.

An alternative is to use `\dgl` instead:

```
\documentclass{article}
\usepackage{hyperref}
\usepackage[record,abbreviations,symbols]{glossaries-extra}

\newcommand{\bibglsnewdualindexsymbolsecondary}[5]{%
  \longnewglossaryentry*{#1}{name={#3},category={symbol},
    type={symbols},symbol={#4},#2}{#5}%
}

\GlsXtrLoadResources[src=entries]

\glsxtraddlabelprefix{dual.}
\glsxtraddlabelprefix{}

\begin{document}
First use: \dgl{duck}, \dgl{svm}, \dgl{pi}.
Next use: \dgl{duck}, \dgl{svm}, \dgl{pi}.
\printunsrtglossaries
\end{document}
```

On the first  $\LaTeX$  call (when the `.gls.tex` file doesn't exist), neither `dual.svm` nor `svm` exists, so `\dgl` uses the last prefix (which is empty in this case). This means that on the first  $\LaTeX$  run, `\dgl{svm}` behaves like `\gls{svm}`, which adds a record for the primary `svm` entry. The default primary-dual dependency means that this will cause both the primary (`svm`) and dual (`dual.svm`)



entry to be selected. The location will be added to the primary entry’s location list, unless overridden by resource options, such as `combine-dual-locations`.

Once `bib2gls` has been run and the `.gls.tex` file exists, then `dual.svm` exists. So `\dgl{s}{svm}` will again first try `dual.svm` (as `dual.` is the first in the list of label prefixes). That now exists, so `\dgl{s}{svm}` now behaves like `\gls{dual.svm}`, which follows the abbreviation style and hyperlinks to the list of abbreviations.

Similarly for the index-symbol combination `dual.pi` and `pi`. In the case of `\dgl{s}{duck}`, the label `dual.duck` never exists, so that’s never selected. The empty prefix is the only one that matches, so `\dgl{s}{duck}` always behaves like `\gls{duck}`.

If you haven’t used `combine-dual-locations` an extra `bib2gls+LATEX` run may be required to correct the location lists.

If you change the label prefixes, remember to update the corresponding `\glsxtraddlabelprefix{<prefix>}`. If no prefixes have been added to the list (or if the list is cleared), just an empty prefix is assumed.

As from version 1.8, `bib2gls` provides hooks that identify the label prefixes in the `.gls.tex` file:

```
\bibglstertiaryprefixlabel{<prefix>}
\bibglsdualprefixlabel{<prefix>}
\bibglsprefixlabel{<prefix>}
```

These do nothing by default, but they can be defined before the resource file is loaded to set up the prefix list. For example:

```
\newcommand{\bibglsprefixlabel}[1]{\glsxtraddlabelprefix{#1}}
\newcommand{\bibglsdualprefixlabel}[1]{\glsxtrprependlabelprefix{#1}}
\GlsXtrLoadResources[src=entries]
```

Remember that this will only have an effect once the `.gls.tex` file has been created. The prefix list will be empty on the first run (which is treated as a single empty prefix). If this isn’t a suitable fallback, it may be necessary to add one after all the resource commands:

```
\newcommand{\bibglsprefixlabel}[1]{\glsxtraddlabelprefix{#1}}
\newcommand{\bibglsdualprefixlabel}[1]{\glsxtrprependlabelprefix{#1}}
\GlsXtrLoadResources[src=entries,label-prefix={idx.}]
\glsxtraddlabelprefix{idx.}
```

Although this rather defeats the purpose of using the hooks as you still have to keep track of the fallback prefix.

## 10.5 Record Counting

As from version 1.1 of `bib2gls`, you can save the total record count for each entry by invoking `bib2gls` with the `--record-count` or `--record-count-unit` switches. These options will ensure that when each entry is written to the `.gls.tex` file `bib2gls` will additionally set the following internal fields for that entry:

- `recordcount`: set to the total number of records found for the entry;
- `recordcount.<counter>`: set to the total number of records found for the entry for the given counter.

If `--record-count-unit` is used then additionally:

- `recordcount.<counter>.<location>`: set to the total number of records found for the entry for the given counter with the given location.

Only use the unit counting option if the locations don't contain any special characters. If you really need it with locations that may contain formatting commands, then you can try redefining:

```
\glstrdetoklocation{<location>}
```

so that it detokenizes *<location>* but take care when using `\GlsXtrLocationRecordCount` with commands like `\thepage` as they can end up becoming detokenized too early.

Note that the record count includes locations that `bib2gls` discards, such as ignored records, duplicates and partial duplicates. It doesn't include cross-reference records. For example, if `\gls{bird}` is used twice on page 1, once on page 2 and four times on page 3, and `\gls[counter=section]{bird}` is used once in section 3, then the total record count (stored in the `recordcount` field) is  $2 + 1 + 4 + 1 = 8$ , the total for the page counter (stored in the `recordcount.page` field) is  $2 + 1 + 4 = 7$ , and the total for the section counter (stored in the `recordcount.section` field) is 1.

With the unit counting on as well, the field `recordcount.page.1` is set to 2, `recordcount.page.2` is set to 1, `recordcount.page.3` is set to 4 and `recordcount.section.3` is set to 1.

You can access these fields using the following commands which will expand to the field value if set or to 0 if unset:

```
\GlsXtrTotalRecordCount{<label>}
```

This expands to the total record count for the entry given by *<label>*.

```
\GlsXtrTotalRecordCount{bird}
```

expands to 8.

```
\GlsXtrRecordCount{<label>}{<counter>}
```

This expands to the counter total for the entry given by *<label>* where *<counter>* is the counter name. For example:

```
\GlsXtrRecordCount{bird}{page}
```

expands to 7 and

```
\GlsXtrRecordCount{bird}{section}
```

expands to 1.

```
\GlsXtrLocationRecordCount{<label>}{<counter>}{<location>}
```

This expands to the total for the given location. For example

```
\GlsXtrLocationRecordCount{bird}{page}{3}
```

expands to 4. Be careful about using `\thepage` in the `<location>` part. Remember that due to  $\TeX$ 's asynchronous output routine, `\thepage` may not be correct.

There are commands analogous to the entry counting commands like `\cgl`s and `\cgl`sformat that are triggered by the record count. These are listed below.

```
\rgls<modifier>[<options>]{<label>}[<insert>]
```

```
\rglsp1<modifier>[<options>]{<label>}[<insert>]
```

```
\rGls<modifier>[<options>]{<label>}[<insert>]
```

```
\rGlspl<modifier>[<options>]{<label>}[<insert>]
```

```
\rGLS<modifier>[<options>]{<label>}[<insert>]
```

```
\rGLSpl<modifier>[<options>]{<label>}[<insert>]
```

These commands check the `recordcount` attribute which, if set, should be a number. For example:

```
\glissetcategoryattribute{abbreviation}{recordcount}{1}
```

For convenience, you can use

```
\GlsXtrSetRecordCountAttribute{<category list>}{<n>}
```

to set the `recordcount` attribute to `<n>` for all the categories listed in `<category list>`.

The `\rgls`-like commands use

```
\glxtrifrecordtrigger{<label>}{<trigger code>}{<normal>}
```

to determine whether the `\rgls`-like command should behave like its `\gls` counterpart (`<normal>`) or whether it should instead use `<trigger code>`.

This command checks if the `recordcount` attribute is set. If not is just does *normal*, otherwise it tests if

```
\glxtrrecordtriggervalue{<label>}
```

is greater than the value given in the `recordcount` attribute for that entry's category. If true, this does *normal* otherwise it does *trigger code*. The default definition of the trigger value command is:

```
\newcommand*\glxtrrecordtriggervalue[1]{%
  \GlsXtrTotalRecordCount{#1}%
}
```

The *trigger code* part writes a record with the format set to `glstriggerrecordformat` (which `bib2gls` v1.1+ recognises as a special type of ignored location format) and does *trigger format*. Then it unsets the `first use flag`. Note that it doesn't implement the post-link hook. This ensures that the record count is correct on the next run.

The *trigger format* depends on the `\rgls`-like command used and will be one of the following:

```
\rglsformat{<label>}{<insert>}
```

```
\rglspformat{<label>}{<insert>}
```

```
\rGlsformat{<label>}{<insert>}
```

```
\rGlspformat{<label>}{<insert>}
```

```
\rGLSformat{<label>}{<insert>}
```

```
\rGLSpformat{<label>}{<insert>}
```

These all behave much like their `\cglformat` counterparts. If the entry's `regular` attribute is set or if the entry doesn't have a long form, the first or first plural is used, otherwise the long or long plural form is used.

You can use

```
\glxtrenablerecordcount
```

to redefine `\gls`, `\glsp`, `\Gls`, `\Glsp`, `\GLS`, `\GLSp` to `\rgls`, `\rglsp`, `\rGls`, `\rGlsp`, `\rGLS`, `\rGLSp`, respectively, for convenience.

If you don't want the entries that use *trigger code* to appear in the glossary, you need to use the resource option `trigger-type` to assign them to another glossary. For example:

```
\documentclass{article}

\usepackage[record]{glossaries-extra}

\newignoredglossary{ignored}

\GlsXtrLoadResources[
  src=example-glossaries-acronym,
  trigger-type=ignored,
  category=abbreviation
]

\glstrenablerecordcount
\GlsXtrSetRecordCountAttribute{abbreviation}{1}

\begin{document}
\gls{lid}. \gls{stc}. \gls{lid}. \gls{aeu}.
\gls{upa}. \gls{aeu}.

\printunsrtglossaries
\end{document}
```

In the above, `stc` and `upa` both only have one record, so they are assigned to the ignored glossary instead of the main one.

# 11 Miscellaneous New Commands

The glossaries package provides `\glsrefentry` entry to cross-reference entries when used with the `entrycounter` or `subentrycounter` options. The glossaries-extra package provides a supplementary command

```
\glsxtrpageref{<label>}
```

that works in the same way except that it uses `\pageref` instead of `\ref`.

You can copy an entry to another glossary using

```
\glsxtrcopytoglossary{<entry-label>}{<glossary-type>}
```

This appends `<entry-label>` to the end of the internal list for the glossary given by `<glossary-type>`. Be careful if you use the `hyperref` package as this may cause duplicate hypertargets. You will need to change `\glolinkprefix` to another value or disable hyperlinks when you display the duplicate. Alternatively, use the new `target` key to switch off the targets:

```
\printunsrtglossary[target=false]
```

The glossaries package allows you to set preamble code for a given glossary type using `\setglossarypreamble`. This overrides any previous setting. With `glossaries-extra` (as from v1.12) you can instead append to the preamble using

```
\apptoglossarypreamble[<type>]{<code>}
```

or prepend using

```
\pretoglossarypreamble[<type>]{<code>}
```

## 11.1 Entry Fields

A field may now be used to store the name of a text-block command that takes a single argument. The field is given by

```
\GlsXtrFmtField
```

The default value is `useri`. Note that the value must be the control sequence name *without the initial backslash*.

For example:

```
\newcommand*\mtx}[1]{\boldsymbol{#1}}
\newcommand*\mtxinv}[1]{\mtx{#1}\sp{-1}}

\newglossaryentry{matrix}{%
  name={matrix},
  symbol={\ensuremath{\mtx{M}}},
  plural={matrices},
  user1={mtx},
  description={rectangular array of values}
}

\newglossaryentry{identitymatrix}{%
  name={identity matrix},
  symbol={\ensuremath{\mtx{I}}},
  plural={identity matrices},
  description={a diagonal matrix with all diagonal elements equal to
1 and all other elements equal to 0}
}

\newglossaryentry{matrixinv}{%
  name={matrix inverse},
  symbol={\ensuremath{\mtxinv{M}}},
  user1={mtxinv},
  description={a square \gls{matrix} such that
   $\mtx{M}\mtxinv{M}=\glssymbol{identitymatrix}$ }
}
```

There are two commands provided that allow you to apply the command to an argument:

```
\glsxtrfmt [options] {label} {text}
```

This effectively does

```
\glslink [default-options], options] {label} {\glsxtrfmtdisplay {cs name} {text} {}}
```

where *cs name* is the control sequence name supplied in the provided field, which must be defined to take a single required argument. Although it effectively acts like `\glslink` it misses out the post-link hook.

The default *default-options* are given by

```
\GlsXtrFmtDefaultOptions
```

This is defined as `noindex` but may be redefined as appropriate. Note that the replacement text of `\GlsXtrFmtDefaultOptions` is prepended to the optional argument of `\glslink`.

As from version 1.23, there's also a starred version of this command that has a final optional argument:

```
\glsxtrfmt*[\langle options \rangle]{\langle label \rangle}{\langle text \rangle}[\langle insert \rangle]
```

Both the starred and unstarred versions use:

```
\glsxtrfmtdisplay{\langle cs name \rangle}{\langle text \rangle}{\langle insert \rangle}
```

within the link text. In the case of the unstarred version  $\langle insert \rangle$  will be empty. It will also be empty if the final option argument is missing from the starred form. If the entry given by  $\langle label \rangle$  is undefined  $\glsxtrfmt$  and  $\glsxtrfmt*$  will issue an error (or warning if `undefaction=warn`). There won't be a warning or error if the entry is defined by the given field is missing. In either case, (the entry is undefined or the field is missing)  $\langle cs name \rangle$  will be `@firstofone` otherwise it will be the field value. The default definition is:

```
\newcommand{\glsxtrfmtdisplay}[3]{\csuse{#1}{#2}#3}
```

which puts  $\langle text \rangle$  inside the argument of the control sequence and  $\langle insert \rangle$  outside it (but it will still be inside the link text).

Remember that nested links cause a problem so avoid using commands like  $\gls$  or  $\glsxtrfmt$  within  $\langle text \rangle$ .

For example:

```
\[
  \glsxtrfmt{matrix}{A}
  \glsxtrfmt{matrixinv}{A}
  =
  \glsymbol{identitymatrix}
\]
```

If the default options are set to `noindex` then  $\glsxtrfmt$  won't index, but will create a hyperlink (if `hyperref` has been loaded). This can be changed so that it also suppresses the hyperlink:

```
\renewcommand{\GlsXtrFmtDefaultOptions}{hyper=false,noindex}
```

Note that  $\glsxtrfmt$  won't work with PDF bookmarks. Instead you can use

```
\glsxtrentryfmt{\langle label \rangle}{\langle text \rangle}
```

If `hyperref` is used, this uses `\texorpdfstring` and will expand to

```
\glsxtrpdfentryfmt{\langle label \rangle}{\langle text \rangle}
```

within the PDF bookmarks, but in the document it will do  $\langle cs \rangle \langle text \rangle$  if a control sequence name has been provided or just  $\langle text \rangle$  otherwise. The PDF bookmark version simply does  $\langle text \rangle$ . It may be redefined, but remember that it needs to expand fully.



The glossaries package provides `\glsaddstoragekey` to add new keys. This command will cause an error if the key has already been defined. The glossaries-extra package provides a supplementary command that will only define the key if it doesn't already exist:

```
\glsxtrprovidestoragekey{<key>}{<default>}{<cs>}
```

If the key has already been defined, it will still provide the command given in the third argument `<cs>` (if it hasn't already been defined). Unlike `\glsaddstoragekey`, `<cs>` may be left empty if you're happy to just use `\glsfieldfetch` to fetch the value of this new key.

You can test if a key has been provided with:

```
\glsxtrifkeydefined{<key>}{<true>}{<false>}
```

This tests if `<key>` is available for use in the `<key>=` list in the second argument of `\newglossaryentry` (or the optional argument of commands like `\newabbreviation`). The corresponding field may not have been set for any of the entries if no default was provided.

There are now commands provided to set individual fields. Note that these only change the specified field, not any related values. For example, changing the value of the text field won't update the plural field. There are also some fields that should really only be set when entries are defined (such as the parent field). Unexpected results may occur if they are subsequently changed.

```
\GlsXtrSetField{<label>}{<field>}{<value>}
```

Sets the field given by `<field>` to `<value>` for the entry given by `<label>`. No expansion is performed. It's not necessary for the field to have been defined as a key. You can access the value later with `\glsxtrusefield`. Note that `\glsxtrifkeydefined` only tests if a key has been defined for use with commands like `\newglossaryentry`. If a field without a corresponding key is assigned a value, the key remains undefined. This command is robust.

`\GlsXtrSetField` uses

```
\glsxtrsetfieldifexists{<label>}{<field>}{<code>}
```

where `<label>` is the entry label and `<code>` is the assignment code.

This command just uses `\glsdoifexists{<label>}{<code>}` (ignoring the `<field>` argument), so by default it causes an error if the entry doesn't exist. This can be changed to a warning with `undefaction=warn`. You can redefine `\glsxtrsetfieldifexists` to simply do `<code>` if you want to skip the existence check. Alternatively you can instead use

```
\glsxtrdeffield{<label>}{<field>}{<arguments>}{<replacement text>}
```

This simply uses etoolbox's `\csdef` without any checks. This command isn't robust. There is also a version that uses `\protected@csdef` instead:<sup>1</sup>

---

<sup>1</sup>Pre version 1.28 used `\csdef`.

```
\glstxreffield{⟨label⟩}{⟨field⟩}{⟨arguments⟩}{⟨replacement text⟩}
```

The following command was added to glossaries-extra v1.47 primarily for the convenience of `bib2gls`:

```
\glstxtrapptocsvfield{⟨label⟩}{⟨field⟩}{⟨value⟩}
```

There's no check for the existence of either the entry or the field. If the entry identified by `⟨label⟩` has the given field set then this command will append a comma followed by `⟨value⟩` to the existing value, otherwise it will set the field to just `⟨value⟩`. This uses `\csdef` or `\csappto` so the effect can be localised.

```
\GlsXtrSetField{⟨label⟩}{⟨field⟩}{⟨value⟩}
```

As `\GlsXtrSetField` but globally.

```
\eGlsXtrSetField{⟨label⟩}{⟨field⟩}{⟨value⟩}
```

As `\GlsXtrSetField` but uses protected expansion.

```
\xGlsXtrSetField{⟨label⟩}{⟨field⟩}{⟨value⟩}
```

As `\gGlsXtrSetField` but uses protected expansion.

```
\GlsXtrLetField{⟨label⟩}{⟨field⟩}{⟨cs⟩}
```

Sets the field given by `⟨field⟩` to the replacement text of `⟨cs⟩` for the entry given by `⟨label⟩` (using `\let`).

```
\csGlsXtrLetField{⟨label⟩}{⟨field⟩}{⟨cs name⟩}
```

As `\GlsXtrLetField` but the control sequence name is supplied instead.

```
\GlsXtrLetFieldToField{⟨label-1⟩}{⟨field-1⟩}{⟨label-2⟩}{⟨field-2⟩}
```

Sets the field given by `⟨field-1⟩` for the entry given by `⟨label-1⟩` to the field given by `⟨field-2⟩` for the entry given by `⟨label-2⟩`. There's no check for the existence of `⟨label-2⟩`, but `\glstxrsetfieldifexists{⟨label-1⟩}{⟨field-1⟩}{⟨code⟩}` is still used, as for `\GlsXtrSetField`.

The glossaries package provides `\ifglshasfield` to determine if a field has been set. The glossaries-extra package provides a simpler version:

```
\glstxtrifhasfield{⟨field⟩}{⟨label⟩}{⟨true⟩}{⟨false⟩}
```

(New to v1.19.) Note that in this case the `⟨field⟩` must be the *internal* field label (for example, `user1` rather than `user1`). Unlike `\ifglshasfield`, this version doesn't complain if the entry

(given by *label*) or the field don't exist and will simply do *false*. If the field does exist for the given entry and it's not empty, the *true* part is done otherwise it does *false*. Within *true* you may use

```
\glscurrentfieldvalue
```

to access the field value. This command includes grouping which scopes the *true* and *false* parts. The starred version

```
\glxtrifhasfield*{<field>}{<label>}{<>true>}{<>false>}
```

omits the implicit grouping.

Be careful of keys that use `\relax` as the default value (such as the symbol). Use `\ifglshassymbol` instead.

There is also a version that simply uses `\ifcsundef`. It doesn't save the field value, but can be used if you only need to check if the field is defined without accessing it:

```
\GlsXtrIfFieldUndef{<field>}{<label>}{<>true>}{<>false>}
```

There's a difference between an undefined field and an unset field. An undefined field hasn't been assigned any value (no associated internal control sequence has been defined). If a defined field has been defined to empty, then it's considered unset. `\GlsXtrIfFieldUndef` implement *false* for a defined but empty field whereas `\glxtrifhasfield` and `\ifglshasfield` will implement *false* a defined but empty field. Remember that any keys that may be used in `\newglossaryentry` will have a default value if not provided. In many cases, the default value is empty, so only use `\GlsXtrIfFieldUndef` for fields that can only be defined through commands like `\GlsXtrSetField`.

You can test if a field value equals a string using

```
\GlsXtrIfFieldEqStr{<field>}{<label>}{<text>}{<>true>}{<>false>}
```

If the entry exists and has the given field set to the given text then this does *true* otherwise it does *false*. This uses `\glxtrifhasfield` to test if the field exists and then compares the replacement text of `\glscurrentfieldvalue` with *text* using etoolbox's `\ifdefstring`. Version 1.39 introduced a starred form of this command, which uses the starred form of `\glxtrifhasfield`.

As from version 1.31, there's a similar command:

```
\GlsXtrIfFieldEqXpStr{<field>}{<label>}{<text>}{<true>}{<false>}
```

This is like `\GlsXtrIfFieldEqStr` but first (protected) fully expands `<text>` (but not the field value). If you want to compare the (protected) full expansion of both the field value and `<text>` use:

```
\GlsXtrIfXpFieldEqXpStr{<field>}{<label>}{<text>}{<true>}{<false>}
```

Again, version 1.39 introduced a starred form of these commands, which use the starred form of `\glxtrifhasfield`.

As from v1.42, you can test if the field value is contained in a comma-separated list with:

```
\GlsXtrIfFieldValueInCsvList{<label>}{<field>}{<list>}{<true>}{<false>}
```

The unstarred version uses the unstarred form of `\glxtrifhasfield` (which adds grouping so `<true>` and `<false>` will be localised). The starred version uses `\glxtrifhasfield*`. If the field value (without expansion) is contained in `<list>` then `<true>` is done otherwise `<false>` is done. If the field hasn't been set `<false>` is done. This internally uses `\DTLifinlist` provided by `datatool`-base which performs a one level expansion on `<list>`. See the `datatool` documentation for further details.

This command is intended for fields that contain a label. For example, to test if the category is one of a set of labels:

```
\GlsXtrIfFieldValueInCsvList{examplelabel}{category}%  
{abbreviation,acronym}% set of labels  
{true part}{false part}
```

As from v1.31, if a field represents a numeric (integer) value, you can use the following two numeric tests. If the field is set, it must expand to an integer. You may use `\glscurrentfieldvalue` within `<true>` or `<false>` to access the actual value. Both `<true>` and `<false>` are scoped. If the field is undefined or empty, the value is assumed to be 0, and `\glscurrentfieldvalue` is set accordingly. As from version 1.39, these numeric tests have starred versions. The unstarred versions add implicit grouping. The starred versions don't.

As from v1.47 there's a similar command:

```
\GlsXtrIfValueInFieldCsvList{<label>}{<field>}{<value>}{<true>}{<false>}
```

This is essentially the opposite situation where the list is stored in the given field and `<value>` is the element to find in the list. Again the unstarred versions add implicit grouping. Note that the `<value>` isn't expanded. If you need it to be fully expanded before searching for it use:

```
\xGlsXtrIfValueInFieldCsvList{<label>}{<field>}{<value>}{<true>}{<false>}
```

(To add a value to a field containing a comma-separated list, use `\glxtrapptocsvfield`. To iterate over the field use `\glxtrforcsvfield`.)

To test if the value is non-zero:

```
\GlsXtrIfFieldNonZero{<field>}{<label>}{<true>}{<false>}
```

Alternatively, you can test if the field expands to a specific number using:

```
\GlsXtrIfFieldEqNum{<field>}{<label>}{<n>}{<true>}{<false>}
```

This does *<true>* if the field value equals *<n>* (using `\ifnum` for the comparison) otherwise it does *<false>*. For a more general numeric comparison you can use:

```
\GlsXtrIfFieldCmpNum{<field>}{<label>}{<comparison>}{<n>}{<true>}{<false>}
```

where *<comparison>* is one of =, < or >.

The glossaries package provides `\glsfieldfetch` which can be used to fetch the value of the given field and store it in a control sequence. The glossaries-extra package provides another way of accessing the field value:

```
\glsxtrusefield{<entry-label>}{<field-label>}
```

This works in the same way as commands like `\glsentrytext` but the field label is specified in the first argument. Note that the *<field-label>* corresponds to the internal field tag, which isn't always the same as the key name. See Table 4.1 of the glossaries manual. No error occurs if the entry or field haven't been defined. This command is not robust.

There is also a version that converts the first letter to uppercase (analogous to `\Glsentrytext`):

```
\Glsxtrusefield{<entry-label>}{<field-label>}
```

and, as from v1.37, a command that converts the entire value to upper case:

```
\GLSxtrusefield{<entry-label>}{<field-label>}
```

If you want to use a field to store a list that can be used as an etoolbox internal list, you can use the following command that adds an item to the field using etoolbox's `\listcsadd`:

```
\glsxtrfieldlistadd{<label>}{<field>}{<item>}
```

where *<label>* is the entry's label, *<field>* is the entry's field and *<item>* is the item to add. There are analogous commands that use `\listgadd`, `\listeadd` and `\listxadd`:

```
\glxtrfieldlistgadd{<label>}{<field>}{<item>}
```

```
\glxtrfieldliststeadd{<label>}{<field>}{<item>}
```

```
\glxtrfieldlistxadd{<label>}{<field>}{<item>}
```

You can then iterate over the list using:

```
\glxtrfielddolistloop{<label>}{<field>}
```

or

```
\glxtrfieldforlistloop{<label>}{<field>}{<handler>}
```

that internally use `\dolistcsloop` and `\forlistloop`, respectively. You can use `\listbreak` to break out of the loop (see the `etoolbox` manual for further details).

For fields that contain comma-separated lists use `\glxtrforcsvfield` instead.

New to v1.42:

```
\glxtrfieldformatlist{<label>}{<field>}
```

Like `datatool-base's \DTLformatlist`, this iterates over an (`etoolbox`) internal list and formats each item. Uses all the same helper commands as `\DTLformatlist` (the same list handler macro is used). Unlike the `datatool-base` command, this command has no starred version. Grouping is automatically applied.

For example, with `bib2gls's save-child-count` resource option:

```
\newcommand*{\listchildren}[1]{%
  \GlsXtrIfFieldNonZero{childcount}{#1}%
  {child count: \glscurrentfieldvalue; children:
    \let\DTLlistformatitem\glsfmtname
    \glxtrfieldformatlist{#1}{childlist}%
  }%
  {no children}%
}
```

For fields that contain a comma-separated list use `\glxtrfieldformatcsvlist` instead.

There are also commands that use `\ifinlistcs`:

```
\glxtrfieldifinlist{<label>}{<field>}{<item>}{<true>}{<false>}
```

and `\xifinlistcs`

```
\glxtrfieldxifinlist{<label>}{<field>}{<item>}{<true>}{<false>}
```

See the etoolbox’s user manual for further details of these commands, in particular the limitations of `\ifinlist`.

If the field has a comma-separated list value instead, you can iterate over it using:

```
\glxtrforcsvfield{<label>}{<field>}{<handler>}
```

where again *<handler>* is a control sequence that takes a single argument. Unlike the etoolbox loops, this doesn’t ignore empty elements nor does it discard leading / trailing spaces. Internally it uses `\@for` (modified by `xfor` which is automatically loaded by glossaries). The `xfor` package modifies the behaviour of `\@for` to allow the loop to be broken prematurely using `\@endfortrue`. The `\glxtrforcsvfield` command locally defines a user level command:

```
\glxtrendfor
```

which is just a synonym for `\@endfortrue`.

The loop is performed within the true part of `\glxtrifhasfield` so scoping is automatically applied. If you don’t want scoping use `\glxtrforcsvfield*` which will use `\glxtrifhasfield*` instead but take care if you nest these starred commands as unexpected results can occur without the scoping.

New to v1.42:

```
\glxtrfieldformatcsvlist{<label>}{<field>}
```

Like `\glxtrfieldformatcsvlist` but for fields that contain comma-separated lists.

As from version 1.32, if the field given by

```
\GlsXtrForeignTextField
```

(which defaults to `userii`) contains a locale tag, then

```
\GlsXtrForeignText{<entry label>}{<text>}
```

can be used to encapsulate *<text>* in `\foreignlanguage{<dialect>}{<text>}` where *<dialect>* is obtained from the locale tag through tracklang’s `\GetTrackedDialectFromLanguageTag` command. You need at least tracklang v1.3.6 for this to work properly. The *<dialect>* must be one that’s tracked (which typically means that `babel` or `polyglossia` has been loaded with the appropriate setting for that language). If `\foreignlanguage` hasn’t been defined, this just does *<text>*. For example:

```
\documentclass{article}
```

```
\usepackage[main=british,brazilian,ngerman]{babel}
```

```
\usepackage{glossaries-extra}
```

```

\setabbreviationstyle{long-short-user}
\newabbreviation
[user1={Associa\c{c}\~ao Brasileria de Normas T\'ecnicas},
 user2= {pt-BR}
]
{abnt}{ABNT}{Brazilian National Standards Organization}

\newabbreviation
[user1={Deutsches Institut f\"ur Normung e.V.},
 user2={de-DE-1996}]
{din}{DIN}{German Institute for Standardization}

\renewcommand*{\glxtruserparen}[2]{%
 \glxtrfullsep{#2}%
 \glxtrparen
 {#1%
 \ifglshasfield{\glxtruserfield}{#2}%
 {, \emph{\GlsXtrForeignText{#2}{\glscurrentfieldvalue}}}%
 }%
 }%
}

\begin{document}
\gls{abnt}, \gls{din}.
\end{document}

```

When using the **record** option, in addition to recording the usual location, you can also record the current value of another counter at the same time using the preamble-only command:

```
\GlsXtrRecordCounter{<counter name>}
```

For example:

```
\usepackage[record]{glossaries-extra}
\GlsXtrRecordCounter{section}
```

Each time an entry is referenced with commands like `\gls` or `\glstext`, the `.aux` file will not only contain the `\glxtr@record` command but also

```
\glxtr@counterrecord{<label>}{section}{<n>}
```

where `<n>` is the current expansion of `\thesection` and `<label>` is the entry's label. On the next run, when the `.aux` file is run, this command will do

```
\glxtrfieldlistgadd{<label>}{record.<counter>}{<n>}
```

In the above example, if `\gls{bird}` is used in section 1.2 this would be

```
\glxtrfieldlistgadd{bird}{record.section}{1.2}
```



Note that there's no key corresponding to this new record .section field, but its value can be accessed with `\glstrfielduse` or the list can be iterated over with `\glstrfielddolistloop` etc.

## 11.2 Display All Entries Without Sorting or Indexing

```
\printunsrtglossary[<options>]
```

This behaves like `\printnoidxglossary` but never sorts the entries and always lists all the defined entries for the given glossary (and doesn't require `\makenoidxglossaries`). If you want to use one of the tabular-like styles with `\printunsrtglossary`, make sure you load `glossaries-extra-stylemods` which modifies the definition of `\glsgroupskip` to avoid the "Incomplete `\iftrue`" error that may otherwise occur.

There's also a starred form

```
\printunsrtglossary*[<options>]{<code>}
```

which is equivalent to

```
\begingroup
  <code>\printunsrtglossary[<options>]%
\endgroup
```

Note that unlike `\glossary preamble`, the supplied *<code>* is done before the glossary header.

This means you now have the option to simply list all entries on the first L<sup>A</sup>T<sub>E</sub>X run without the need for a post-processor, however there will be no **number list** in this case, as that has to be set by a post-processor such as `bib2gls` (see Section 10).

No attempt is made to gather hierarchical elements. If child entries aren't defined immediately after their parent entry, they won't be together in the glossary when using `\printunsrtglossary`.

There's a difference in behaviour depending on whether or not the `group` key is defined. If not defined (default), the group label will be formed from the first letter of the name field. The corresponding group title will be obtained as discussed in Section 2.11. This can lead to an odd effect if you are using a style that separates letter groups when the ordering isn't alphabetical.

If the `group` key is defined (which it is with the `record` option) then the group label will be obtained from the value of that field. If the field is empty, *no grouping is performed*, even if the style supports it. (That is, there won't be a header or a vertical separation.) If the group field is non-empty, then the corresponding title is obtained as described earlier.

In either case, if the `groups` option is set to `false` then no group formation will be performed.

If you want to use a different field for the group label, you can redefine

```
\glstrgroupfield
```

to the relevant internal field label, but the group *key* must still be defined (through the `record` option or with commands like `\glsaddstoragekey`) to ensure that `\printunsrtglossary` uses `\glstrgroupfield`. (This method is used by `bib2gls` for secondary entries, which have the group label stored in the `secondarygroup` internal field.)

If you have any entries with the see key set, you will need the `glossaries` package option `seenoin-index=ignore` or `seenoin-index=warn` to prevent an error occurring from the automated `\glssee` normally triggered by this key. The `record=only` package option will automatically deal with this.

For example:

```
\documentclass{article}

\usepackage{glossaries-extra}

\newglossaryentry{zebra}{name={zebra},description={stripy animal}}
\newglossaryentry{ant}{name={ant},description={an insect}}

\begin{document}
\gls{ant} and \gls{zebra}

\printunsrtglossaries
\end{document}
```

In the above, `zebra` will be listed before `ant` as it was defined first.

If you allow document definitions with the `docdefs` option, the document will require a second  $\LaTeX$  run if the entries are defined after `\printunsrtglossary`.

The optional argument is as for `\printnoidxglossary` (except for the sort key, which isn't available).

All glossaries may be displayed in the order of their definition using:

```
\printunsrtglossaries
```

which is analogous to `\printnoidxglossaries`. This just iterates over all defined glossaries (that aren't on the ignored list) and does `\printunsrtglossary[type=<type>]`.

### 11.2.1 Hooks

To avoid complications caused by tabular-like glossary styles, `\printunsrtglossary` iterates over all entries in the selected glossary and appends the appropriate code to an internal command. Once the construction of this command is complete, then it's performed to display the glossary. This puts the loop outside the style code. For convenience, there's a hook used within the loop:

```
\printunsrtglossaryentryprocesshook{<label>}
```

This hook should not display any content, but may be used to perform calculations. For example, to calculate widths. Within this hook you can use:

```
\printunsrtglossaryskipentry
```

to skip the current entry. This will prevent the entry from being added to the internal command.

There's another hook immediately before the internal command containing the glossary code is performed:

```
\printunsrtglossarypredoglossary
```

The internal command uses

```
\printunsrtglossaryhandler{<label>}
```

to display each item in the list, where *<label>* is the current label.

By default the handler just does

```
\glstrunsrtdo{<label>}
```

which determines whether to use `\glossentry` or `\subglossentry` and checks the location and loclist fields for the **number list**. If you want to use a different field to be used instead of location then redefine:

```
\GlsXtrLocationField
```

to the internal name of the desired field. For example:

```
\renewcommand{\GlsXtrLocationField}{primarylocation}
```

Note that if the given location field is undefined or unset, the handler will fallback on the loclist field.

You can instruct `bib2gls` to omit setting the loclist field with the resource option `--save-loclist=false` to prevent it from being used as a fallback.

### 11.2.2 Filtering

You can redefine the handler used by `\printunsrtglossary` if required. For example, you may want to filter entries according to the category label. You can test if a label is contained in a comma-separated list of labels using:

```
\glstriflabelinlist{<label>}{<label list>}{<true>}{<false>}
```

The *<label>* and *<label list>* will be fully expanded.

If you redefine the handler to exclude entries, you may end up with an empty glossary. This could cause a problem for the list-based styles.

For example, if the preamble includes:

```
\usepackage[record,style=index]{glossaries-extra}
\GlsXtrRecordCounter{section}
```

then you can print the glossary but first redefine the handler to only select entries that include the current section number in the `record.section` field:

```
\renewcommand{\printunsrtglossaryhandler}[1]{%
  \glstrfieldxifinlist{#1}{record.section}{\thesection}
  {\glstrunsrtdo{#1}}%
  }%
}
```

Alternatively you can use the starred form of `\printunsrtglossary` which will localise the change:

```
\printunsrtglossary*{%
  \renewcommand{\printunsrtglossaryhandler}[1]{%
    \glstrfieldxifinlist{#1}{record.section}{\thesection}
    {\glstrunsrtdo{#1}}%
    }%
  }%
}
```

If you are using the `hyperref` package and want to display the same glossary more than once, you can also add a temporary redefinition of `\glolinkprefix` to avoid duplicate hypertarget names. For example:

```
\printunsrtglossary*{%
  \renewcommand{\printunsrtglossaryhandler}[1]{%
    \glstrfieldxifinlist{#1}{record.section}{\thesection}
    {\glstrunsrtdo{#1}}%
    }%
  }%
  \ifcsundef{theHsection}%
  {%
    \renewcommand*{\glolinkprefix}{record.\csuse{thesection}.}%
  }%
  {%
    \renewcommand*{\glolinkprefix}{record.\csuse{theHsection}.}%
  }%
}
```

Note that this will cause a problem if your descriptions contain commands like `\gls` that need to link an entry that doesn't appear in the summary. In this case, it's a better approach to use:

```
\printunsrtglossary*{%
  \renewcommand{\printunsrtglossaryhandler}[1]{%
    \glstrfieldxifinlist{#1}{record.section}{\thesection}
```

```

    {\glxtrunsrtdo{#1}}%
    {}%
  }%
  \ifcsundef{theHsection}%
  {%
    \setkeys{printgloss}{targetnameprefix={record.\csuse{thesection}.}}%
  }%
  {%
    \setkeys{printgloss}{targetnameprefix={record.\csuse{theHsection}.}}%
  }%
}

```

If it's a short summary at the start of a section, you might also want to suppress the glossary header and add some vertical space afterwards:

```

\printunsrtglossary*{%
  \renewcommand{\printunsrtglossaryhandler}[1]{%
    \glxtrfieldxifinlist{#1}{record.section}{\thesection}
    {\glxtrunsrtdo{#1}}%
    {}%
  }%
  \ifcsundef{theHsection}%
  {%
    \renewcommand*\glolinkprefix{record.\csuse{thesection}.}%
  }%
  {%
    \renewcommand*\glolinkprefix{record.\csuse{theHsection}.}%
  }%
  \renewcommand*\glossarysection[2][{}]{%
    \appto\glossarypostamble{\glspar\medskip\glspar}%
  }
}

```

There's a shortcut command that essentially does this:

```
\printunsrtglossaryunit[<options>]{<counter name>}
```

The above example can simply be replaced with:

```
\printunsrtglossaryunit{section}
```

This shortcut command is actually defined to use `\printunsrtglossary*` with

```
\printunsrtglossaryunitsetup{<counter name>}
```

so if you want to just make some minor modifications you can do

```

\printunsrtglossary*\printunsrtglossaryunitsetup{section}%
  \renewcommand*\glossarysection[2][{}]{\subsection*{Summary}}%
}

```

which will start the list with a subsection header with the title “Summary” (overriding the glossary’s title).

Note that this shortcut command is only available with the `record` (or `record=hybrid`) package option.

This temporary change in the hypertarget prefix means you need to explicitly use `\hyperlink` to create a link to it as commands like `\gls` will try to link to the target created with the default definition of `\gloslinkprefix`. This isn’t a problem if you want a primary glossary of all terms produced using just `\printunsrtglossary` (in the front or back matter) which can be the target for all glossary references and then just use `\printunsrtglossaryunit` for a quick summary at the start of a section etc.

## 11.3 Partial Glossaries

It’s possible that you may require greater customisation over the way the glossary is displayed that can’t be simply achieved with the hooks or glossary styles. This section describes a command and environment provided to assist with this, but note that they aren’t compatible with tabular-like glossary styles, such as `long` or `super`, due to their complexity and internal scoping that interferes with alignment. You will also need to take care with list styles (provided in the `glossary-list` package).

To get a better understanding of how this works, it’s useful to consider how a glossary with `makeindex` works. Here’s a simple example document:

```
\documentclass{article}

\usepackage{glossaries}

\makeglossaries

\newglossaryentry{cabbage}{name={cabbage},
  description={vegetable with thick green or purple leaves}}

\newglossaryentry{broccoli}{name={broccoli},
  description={vegetable with heads of small green or purple flower buds}}

\begin{document}
\Gls{cabbage} and \gls{broccoli}.

\printglossary
\end{document}
```

When the document is built, `makeindex` creates a file that contains:

```
\glossarysection[\glossarytoctitle]{\glossarytitle}\glossarypreamble
\begin{theglossary}\glossaryheader
\glsgroupheading{B}\relax \glsresetentrylist
\glossentry{broccoli}{\langle location list \rangle}\glsgroupskip
\glsgroupheading{C}\relax \glsresetentrylist
```

```
\glossentry{cabbage}{\langle location list \rangle}%
\end{theglossary}\glossarypostamble
```

The `\printglossary` command defines the commands shown above after it's detected the glossary type, the title and style. It then inputs the file.

The `\printunsrtglossary` command performs the same preliminary setup but there's no file to input. Instead it then does the section heading (`\glossarysection`) and preamble (`\glossarypreamble`) and constructs a control sequence that contains `\begin{theglossary}` *<content>* `\end{theglossary}`.

The letter group markup (`\glsgroupheading` and `\glsgroupskip`) is inserted whenever the group label changes between top-level entries. In this case, *<content>* doesn't explicitly contain `\glossentry` but uses a handler function instead. For example, instead of:

```
\glossentry{broccoli}{\langle location list \rangle}
```

the *<content>* will contain:

```
\langle internal handler \rangle{broccoli}
```

This internal handler uses `\printunsrtglossaryhandler` to determine the required information (location list, hierarchical level) that's needed to typeset the entry (using `\glossentry` or `\subglossentry`).

```
\begin{printunsrtglossarywrap}[\langle options \rangle]
\langle content \rangle \end{printunsrtglossarywrap}
```

The `printunsrtglossarywrap` environment provides a wrapper in which you can place the actual glossary code. The optional argument is the same as for `\printunsrtglossary`, but note that in this case the type key simply provides the glossary title and doesn't identify the content.

This environment essentially does:

```
\langle initial setup \rangle
\glossarysection[\glossarytoctitle]{\glossarytitle}\glossarypreamble
\begin{theglossary}\glossaryheader\glsresetentrylist
\langle content \rangle
\end{theglossary}\glossarypreamble
```

where *<initial setup>* is much the same code as used by `\printglossary` and `\printunsrtglossary`. Most importantly, *<initial setup>* sets the current glossary style, which determines the definition of `theglossary`, `glossentry` and `subglossentry`.

Whilst it is possible to explicitly use the commands that create letter group headings and the handler within *<content>*, it would be quite laborious and prone to error to do so for anything other than a very short list. This can be illustrated with the following silly example:

```
\begin{printunsrtglossarywrap}[style=indexgroup]%
\glsgroupheading{W}%
\gdef\glscurrententrylabel{cabbage}%
```

```

\printunsrtglossaryhandler\glscurrententrylabel
\glsgroupskip
\glsgroupheading{Z}%
\gdef\glscurrententrylabel{broccoli}%
\printunsrtglossaryhandler\glscurrententrylabel
\end{printunsrtglossarywrap}

```

This trivial example will work with a tabular-like style, such as long (although the group headings will be ignored). A more practical example that uses a loop within *content* won't.

```

\printunsrtinnerglossary[options]{pre-code}{post-code}

```

This command is provided for use within `printunsrtglossarywrap`. The optional argument *options* is similar to `\printunsrtglossary` but the following keys are unavailable: `title`, `toctitle`, `style`, `numberedsection` and `label`.

This will do:

```

\begingroup
  initial setup
  pre-code
  content
  post-code
\endgroup

```

where *initial setup* processes the options and assigns `\currentglossary`, *pre-code* is some preliminary code and *post-code* is some final code before the end of the scoping. The *content* is the sequence of code that `\printunsrtglossary` would normally insert within the `theglossary` environment.

For example:

```

\begin{printunsrtglossarywrap}[style=indexgroup]
\printunsrtinnerglossary[type=main]{}{}
\end{printunsrtglossarywrap}

```

This produces a result very similar to that obtained with just:

```

\printunsrtglossary[style=indexgroup,type=main]

```

The first case is unsuitable for use with a tabular-style. It will also cause a problem with a list style when used with `bib2gls` (where the inner content will be empty on the first  $\LaTeX$  run which will cause a missing `\item` error).

This partial glossary command is more useful when you need to apply filtering (which can be set up in the *pre-code* argument as in `\printunsrtglossary*`) or if you have multiple glossaries. For example:

```

\begin{printunsrtglossarywrap}[style=list]
\item[Animals]
\printunsrtinnerglossary[type=animal]{}{}

```



```

\item[Vegetables]
\printunsrtinnerglossary[type=vegetable]{}{}
\item[Minerals]
\printunsrtinnerglossary[type=mineral]{}{}
\end{printunsrtglossarywrap}

```

In this case, the list style doesn't cause a problem as there will be three instances of `\item` on the first  $\LaTeX$  run.

Here's another example:

```

\begin{printunsrtglossarywrap}[style=indexgroup]
\glsgroupheading{animal}%
\printunsrtinnerglossary[type=animal]{}{}
\glsgroupskip
\glsgroupheading{vegetable}%
\printunsrtinnerglossary[type=vegetable]{}{}
\glsgroupskip
\glsgroupheading{mineral}%
\printunsrtinnerglossary[type=mineral]{}{}
\end{printunsrtglossarywrap}

```

Note that in both of the above cases, the inner glossaries have been arranged manually (animal, then vegetable and then mineral).

It's also possible to use `\printunsrtinnerglossary` within the handler function used by `\printunsrtglossary`. The internal scoping within `\printunsrtinnerglossary` helps to reduce interference.

This is a rather more complicated example that requires `bib2gls`. Suppose I have a file called `topictitles.bib` that contains:

```

@indexplural{animal}
@indexplural{mineral}
@indexplural{vegetable}

```

And also a file called `topics.bib` that contains entries like:

```

@entry{zebra,
  name={zebra},
  description={striped African horse},
  category={animal}
}

@entry{broccoli,
  name={broccoli},
  description={vegetable with heads of small green or purple flower buds},
  category={vegetable}
}

@entry{quartz,
  name={quartz},
  description={hard mineral consisting of silica},

```

```

    category={mineral}
}

```

Note that the category labels in the second file match the entry labels in the first file.

The simplest way of creating a hierarchical glossary from this data is to input both files and copy the category field to the parent field:

```

\GlsXtrLoadResources[src={topictitles,topics},
  replicate-fields={category=parent}]

```

The glossary can then simply be displayed with:

```

\printunsrtglossary[style=indexgroup]

```

This will now be ordered: animal (followed by animal child entries), mineral (followed by mineral child entries), vegetable (followed by vegetable child entries).

Suppose (for some strange reason) that I now need the ordering to be vegetable, mineral, animal (that is, reverse alphabetical) but the child entries still need to be in the normal alphabetical order.

It's not possible to use different sort methods for different hierarchical levels with `bib2gls`, but it is possible to simulate it.

Instead of making the entries within `topics.bib` children of the entries defined in `topictitles.bib`, I'm now going to create separate glossaries for each type:

```

\newignoredglossary*{animal}
\newignoredglossary*{mineral}
\newignoredglossary*{vegetable}

```

The entries in `topictitles.bib` go in the default main glossary and are sorted in reverse:

```

\GlsXtrLoadResources[src=topictitles,type=main,selection=all,
  sort=en-GB-reverse]

```

Note that I've selected all entries in this example. It becomes more complicated with the default selection criteria. (See the `sample-nested.tex` example provided with `bib2gls v2.3+`.)

Now the entries in `topics.bib` are selected but the `type` field is set to the category field:

```

\GlsXtrLoadResources[src=topics,type={same as category},selection=all,
  sort=en-GB]

```

The aim here is to use `\printunsrtglossary` to list all the entries in the main glossary (that is, all the topic titles) and use a handler that tests if there is a glossary that has the same label as the current entry label. If one exists, it's then listed using `\printunsrtinnerglassary` with the level offset shifted to give a hierarchical appearance:

```

\newcommand{\nestedhandler}[1]{%
  \glstrunsrtdo{#1}%
  \ifglossaryexists*{#1}%
  {%
    \printunsrtinnerglassary[type={#1},leveloffset=++1]{}%
  }%
}

```

```

    {}%
}

\printunsrtglossary*[type=main,style=index]{%
  \let\printunsrtglossaryhandler\nestedhandler
}

```

I've used `\newignoredglossary*` as I don't need to specify a title for any of those glossaries nor do I need to use those glossaries with `\printunsrtglossaries`. With `bib2gls` v2.3+, I can omit the three `\newignoredglossary*` lines and use the `--provide-glossaries` switch which will make `bib2gls` automatically provide any unknown glossaries (with `\provideignoredglossary`) in the `.gls.tex` file.

## 11.4 Standalone Entry Items

It may be that you don't want a list but would rather display entry details throughout the document. You can simply do `\glsentryname` followed by `\glsentrydesc`. (Remember that if you don't want a sorted list, use `sort=none` to skip the construction of the sort field.) For example, in the preamble provide a custom command:

```

\newcommand{\displayterm}[1]{%
  \par\medskip\par\noindent
  Definition: \glsentryname{#1}.\par
  \glsentrydesc{#1}
  \par\medskip
}

```

define your entries

```

\newglossaryentry{function}{name={function},
  description={a relation or expression involving variables}
}

```

and then later in the text:

```
\displayterm{function}
```

However, it may be that you want to use `hyperref` and have commands like `\gls` link back to the place where the term is described. Instead of using `\glsentryname` use

```
\glstrglossentry{<label>}
```

where *<label>* is the entry's label.

This is designed to behave much like the way the name is displayed in the glossary. It performs the following:

- Defines `\glscurrententrylabel` to the entry's label. This is usually done at the start of the glossary style commands `\glossentry` and `\subglossentry` and may be used by hooks, such as the post-name hooks. Here the definition is localised so that it's only available for use in `\glossentryname`.

- Defines `\currentglossary` to the entry's glossary type. This is usually done at the start of commands like `\printglossary` and may be used by style hooks. Here the definition is localised so that it's only available for use in `\glsentryitem` and `\glssubentryitem`. The value is obtained by fully expanding:

```
\GlsXtrStandaloneGlossaryType
```

which defaults to the value of the type field for the current entry.

- Increments and display the entry counters if the `entrycounter` or `subentrycounter` package options are set. If the entry doesn't have a parent, then this does

– `\glsentryitem{<label>}`

otherwise it does (as from v1.31)

– `\GlsXtrStandaloneSubEntryItem{<label>}` which defaults to `\glssubentryitem{<label>}` if the entry has a parent but not a grandparent.

This reflects the behaviour of the predefined hierarchical styles. A bug in pre-version 1.31 used `\glsentryitem` for all child levels, which doesn't match the hierarchical glossary styles. If you want to restore this behaviour, just do:

```
\renewcommand*{\GlsXtrStandaloneSubEntryItem}[1]{\glssubentryitem{#1}}
```

- Sets the hyper-target if supported (using `\glstarget`) and displays the entry name using:

```
\GlsXtrStandaloneEntryName{<label>}
```

which uses `\glstarget{<label>}{\glossentryname{<label>}}` by default. Remember that `\glossentryname` uses `\glsnamefont` or picks up the style from category attributes such as `glossnamefont`.

If you have used `\nopostdesc` or `\glxtrnopostpunc` in any of your description fields, you can use

```
\glsextractivatenopost
```

to make these commands behave as they normally do within a glossary. This needs to be placed before

```
\glossentrydesc{<label>}\glspostdescription
```

and scoped. Note that `\glsnonextpages` and `\glsnextpages` have no effect outside of the glossary and are not intended for use in a standalone context.

It's also possible to select a different field (rather than using name):

```
\glxtrglossentryother{<header>}{<label>}{<field>}
```

The *<field>* must be given using its internal field label which may not be the same as the key used to set the field. See the key to field mappings table in the glossaries user manual. The *<header>* argument is the code to pass to the third argument of `\glxtrtitleorpdforheading`. It may be left empty in which case the default is determined as follows:

- If `\glxtrhead<field>` is defined, then *<header>* is `\glxtrhead<field>{<label>}`.
- Otherwise *<header>* is simply the field value.

The `\glxtrglossentryother` command internally uses

```
\GlsXtrStandaloneEntryOther{<label>}{<field>}
```

instead of `\GlsXtrStandaloneEntryName`, which uses `\glossentrynameother{<label>}{<field>}` instead of `\glossentryname{<label>}`.

If you have loaded the glossaries-accsupp package (through the `accsupp` option) then accessibility support will be provided if there's a corresponding command

```
\gls<field>accessdisplay{<text>}{<label>}
```

(for example, `\glsymbolaccessdisplay`).

This means that my custom command can be changed to:

```
\newcommand{\displayterm}[1]{%
  \par\medskip\par\noindent
  Definition: \glxtrglossentry{#1}.\par
  \glentrydesc{#1}
  \par\medskip
}
```

If I want numbered definitions, then I can use the package options `entrycounter` or `subentrycounter` and remove the colon:

```
\newcommand{\displayterm}[1]{%
  \par\medskip\par\noindent
  Definition \glxtrglossentry{#1}.\par
  \glentrydesc{#1}
  \par\medskip
}
```

The counter label uses a dot after the number by default but this can be changed to a colon:

```
\renewcommand*{\glentrycounterlabel}{\theglossaryentry:\space}
```

It's now possible to not only use `\gls` to link back to the definition but also use `\glsrefentry` to reference the counter and `\glxtrpageref` to reference the page number.

If I want the description to behave more like it does in a glossary in need to make the following modification:

```

\newcommand{\displayterm}[1]{%
  \par\medskip\par\noindent
  Definition \glstrglossentry{#1}.\par
  \begingroup
  \glsextractivatenopost
  \glossentrydesc{#1}\glspostdescription
  \endgroup
  \par\medskip
}

```

(Note the grouping to localise `\glsextractivatenopost`.)

You can also use `\glstrglossentry` within section headings. For example:

```
\section{\glstrglossentry{function}}
```

This will use `\glstentryname` in PDF bookmarks (if `\texorpdfstring` is defined) and will use `\glstrheadname` in page headers and table of contents. (If you're using a page style or table of contents that doesn't use `\markright` or `\markbook` or `\@starttoc` then you need to insert `\glstrmarkhook` and `\@glstrinmark` at the start of the header or table of contents either scoped or afterwards cancelled with `\@glstrnotinmark` and `\glstrrestoremarkhook`.)

## 11.5 Entry Aliases

An entry can be made an alias of another entry using the alias key. The value should be the label of the other term. There's no check for the other's existence when the aliased entry is defined. This is to allow the possibility of defining the other entry after the aliased entry. (For example, when used with `bib2gls`.)

If an entry `<entry-1>` is made an alias of `<entry-2>` then:

- If the `see` field wasn't provided when `<entry-1>` was defined, the alias key will automatically trigger

```
\glssee{<entry-1>}{<entry-2>}
```

- If the `hyperref` package has been loaded then `\gls{<entry-1>}` will link to `<entry-2>`'s target. (Unless the `targeturl` attribute has been set for `<entry-1>`'s category.)
- With `record=off` or `record=hybrid`, the `noindex` setting will automatically be triggered when referencing `<entry-1>` with commands like `\gls` or `\glstext`. This prevents `<entry-1>` from having a **location list** (aside from the cross-reference added with `\glssee`) unless it's been explicitly indexed with `\glsadd` or if the indexing has been explicitly set using `noindex=false`.

Note that with `record=only`, the location list for aliased entries is controlled with `bib2gls`'s settings.

The index suppression trigger is performed by

```
\glxtrsetaliasnoindex
```

This is performed after the default options provided by `\GlsXtrSetDefaultGlsOpts` have been set. With `record=only`, `\glxtrsetaliasnoindex` will default to do nothing.

Within the definition of `\glxtrsetaliasnoindex` you can use

```
\glxtrindexaliased
```

to index `<entry-2>`.

The index suppression command can be redefined to index the main term instead. For example:

```
\renewcommand{\glxtrsetaliasnoindex}{%  
  \glxtrindexaliased  
  \setkeys{glslink}{noindex}%  
}
```

The value of the alias field can be accessed using

```
\glxtralias{<label>}
```

## 12 On-the-Fly Document Definitions

The commands described here may superficially look like `\index{<word>}`, but they behave rather differently. If you want to use `\index` then just use `\index`.

The glossaries package advises against defining entries in the document environment. As mentioned in Section 1.2 above, this ability is disabled by default with `glossaries-extra` but can be enabled using the `docdefs` package options.

Although this can be problematic, the `glossaries-extra` package provides a way of defining and using entries within the document environment without the tricks used with the `docdefs` option. *There are limitations with this approach, so take care with it.* This function is disabled by default, but can be enabled using the preamble-only command:

```
\GlsXtrEnableOnTheFly
```

When used, this defines the commands described below.

The commands `\glsxtr`, `\glsxtrpl`, `\Glsxtr` and `\Glsxtrpl` can't be used after the glossaries have been displayed (through `\printglossary` etc). It's best not to mix these commands with the standard glossary commands, such as `\gls` or there may be unexpected results.

```
\glsxtr[<gls-options>][<dfn-options>]{<label>}
```

If an entry with the label `<label>` has already been defined, this just does `\gls[<gls-options>]{<label>}`. If `<label>` hasn't been defined, this will define the entry using:

```
\newglossaryentry{<label>}{name={<label>},  
category=\glsxtrcat,  
description={\nopostdesc},  
<dfn-options>}
```

The `<label>` must contain any non-expandable commands, such as formatting commands or problematic characters. If the term requires any of these, they must be omitted from the `<label>` and placed in the name key must be provided in the optional argument `<dfn-options>`.



The second optional argument  $\langle dfn-options \rangle$  should be empty if the entry has already been defined, since it's too late for them. If it's not empty, a warning will be generated with

```
\GlsXtrWarning{ $\langle dfn-options \rangle$ }{ $\langle label \rangle$ }
```

For example, this warning will be generated on the second instance of  $\backslash glsxtr$  below:

```
\glsxtr[] [plural=geese]{goose}
... later
\glsxtr[] [plural=geese]{goose}
```

If you are considering doing something like:

```
\newcommand*{\goose}{\glsxtr[] [plural=geese]{goose}}
\renewcommand*{\GlsXtrWarning}[2]{ }
... later
\goose\ some more text here
```

then don't bother. It's simpler and less problematic to just define the entries in the preamble with  $\backslash newglossaryentry$  and then use  $\backslash gls$  in the document.

There are plural and case-changing alternatives to  $\backslash glsxtr$ :

```
\glsxtrpl[ $\langle gls-options \rangle$ ] [ $\langle dfn-options \rangle$ ]{ $\langle label \rangle$ }
```

This is like  $\backslash glsxtr$  but uses  $\backslash glspl$  instead of  $\backslash gls$ .

```
\Glsxtr[ $\langle gls-options \rangle$ ] [ $\langle dfn-options \rangle$ ]{ $\langle label \rangle$ }
```

This is like  $\backslash glsxtr$  but uses  $\backslash Gls$  instead of  $\backslash gls$ .

```
\Glsxtrpl[ $\langle gls-options \rangle$ ] [ $\langle dfn-options \rangle$ ]{ $\langle label \rangle$ }
```

This is like  $\backslash glsxtr$  but uses  $\backslash Glspl$  instead of  $\backslash gls$ .

If you use UTF-8 and don't want the inconvenient of needing to use an ASCII-only label, then it's better to use Xe $\LaTeX$  or Lua $\LaTeX$  instead of  $\LaTeX$  (or pdf $\LaTeX$ ). If you really desperately want to use UTF-8 entry labels without switching to Xe $\LaTeX$  or Lua $\LaTeX$  then there is a starred version of  $\backslash GlsXtrEnableOnTheFly$  that allows you to use UTF-8 characters in  $\langle label \rangle$ , but it's experimental and may not work in some cases.

If you use the starred version of  $\backslash GlsXtrEnableOnTheFly$  don't use any commands in the  $\langle label \rangle$ , even if they expand to just text.

## 13 Supplemental Packages

The glossaries bundle provides additional support packages `glossaries-prefix` (for prefixing) and `glossaries-accsupp` (for accessibility support). These packages aren't automatically loaded.

### 13.1 Prefixes or Determiners

If prefixing is required, you can simply load `glossaries-prefix` after `glossaries-extra`. For example:

```
\documentclass{article}

\usepackage{glossaries-extra}
\usepackage{glossaries-prefix}

\makeglossaries

\newabbreviation
  [prefix={an\space},
  prefixfirst={a~}]
  {svm}{SVM}{support vector machine}

\begin{document}

First use: \pgls{svm}.
Next use: \pgls{svm}.

\printglossaries

\end{document}
```

### 13.2 Accessibility Support

The `glossaries-accsupp` package is still experimental and so accessibility features are liable to change.

The `glossaries-accsupp` package needs to be loaded before `glossaries-extra` or through the `accsupp` package option:

```
\usepackage[accsupp]{glossaries-extra}
```

If you don't load `glossaries-accsupp` or you load `glossaries-accsupp` after `glossaries-extra` the new `\glsaccess<xxx>` commands described below will simply be equivalent to the corresponding `\glsentry<xxx>` commands. Other accessibility features, such as the attributes used by `\newabbreviation` also won't work if `glossaries-accsupp` is loaded too late.

The following `\glsaccess<xxx>` commands add accessibility information wrapped around the corresponding `\glsentry<xxx>` commands. There is no check for existence of the entry nor do any of these commands add formatting, hyperlinks or indexing information.

```
\glsaccessname{<label>}
```

This displays the value of the name field for the entry identified by `<label>`.

If the `glossaries-accsupp` package isn't loaded, this is simply defined as:

```
\newcommand*\glsaccessname[1]{\glsentryname{#1}}
```

otherwise it's defined as:

```
\newcommand*\glsaccessname[1]{%
  \glsnameaccessdisplay
  {%
    \glsentryname{#1}%
  }%
  {#1}%
}
```

(`\glsnameaccessdisplay` is defined by the `glossaries-accsupp` package.) The first letter upper case version is:

```
\Glsaccessname{<label>}
```

Without the `glossaries-accsupp` package this is just defined as:

```
\newcommand*\Glsaccessname[1]{\Glsentryname{#1}}
```

With the `glossaries-accsupp` package this is defined as:

```
\newcommand*\Glsaccessname[1]{%
  \glsnameaccessdisplay
  {%
    \Glsentryname{#1}%
  }%
  {#1}%
}
```

The following commands are all defined in an analogous manner.

```
\glsaccesstext{<label>}
```

This displays the value of the text field.

```
\Glsaccessstext{\<label>}
```

This displays the value of the text field with the first letter converted to upper case.

```
\glsaccessplural{\<label>}
```

This displays the value of the plural field.

```
\Glsaccessplural{\<label>}
```

This displays the value of the plural field with the first letter converted to upper case.

```
\glsaccessfirst{\<label>}
```

This displays the value of the first field.

```
\Glsaccessfirst{\<label>}
```

This displays the value of the first field with the first letter converted to upper case.

```
\glsaccessfirstplural{\<label>}
```

This displays the value of the firstplural field.

```
\Glsaccessfirstplural{\<label>}
```

This displays the value of the firstplural field with the first letter converted to upper case.

```
\glsaccesssymbol{\<label>}
```

This displays the value of the symbol field.

```
\Glsaccesssymbol{\<label>}
```

This displays the value of the symbol field with the first letter converted to upper case.

```
\glsaccesssymbolplural{\<label>}
```

This displays the value of the symbolplural field.

```
\Glsaccesssymbolplural{\<label>}
```

This displays the value of the symbolplural field with the first letter converted to upper case.

```
\glsaccessdesc{<label>}
```

This displays the value of the description field.

```
\Glsaccessdesc{<label>}
```

This displays the value of the description field with the first letter converted to upper case.

```
\glsaccessdescplural{<label>}
```

This displays the value of the descriptionplural field.

```
\Glsaccessdescplural{<label>}
```

This displays the value of the descriptionplural field with the first letter converted to upper case.

```
\glsaccessshort{<label>}
```

This displays the value of the short field.

```
\Glsaccessshort{<label>}
```

This displays the value of the short field with the first letter converted to upper case.

```
\glsaccessshortpl{<label>}
```

This displays the value of the shortplural field.

```
\Glsaccessshortpl{<label>}
```

This displays the value of the shortplural field with the first letter converted to upper case.

```
\glsaccesslong{<label>}
```

This displays the value of the long field.

```
\Glsaccesslong{<label>}
```

This displays the value of the long field with the first letter converted to upper case.

```
\glsaccesslongpl{<label>}
```

This displays the value of the longplural field.

```
\Glsaccesslongpl{<label>}
```

This displays the value of the longplural field with the first letter converted to upper case.

## 14 Sample Files

The following sample files are provided with this package:

**sample.tex** Simple sample file that uses one of the dummy files provided by the glossaries package for testing.

**sample-abbr-styles.tex** Demonstrates all predefined abbreviation styles.

**sample-mixture.tex** General entries, acronyms and initialisms all treated differently.

**sample-name-font** Categories and attributes are used to customize the way different entries appear.

**sample-abbrev.tex** General abbreviations.

**sample-acronym.tex** Acronyms aren't initialisms and don't expand on **first use**.

**sample-acronym-desc.tex** Acronyms that have a separate long form and description.

**sample-crossref.tex** Unused entries that have been cross-referenced automatically are added at the end of the document.

**sample-indexhook.tex** Use the index hook to track which entries have been indexed (and therefore find out which ones haven't been indexed).

**sample-footnote.tex** Footnote abbreviation style that moves the footnote marker outside of the hyperlink generated by `\gls` and moves it after certain punctuation characters for neatness.

**sample-undef.tex** Warn on undefined entries instead of generating an error.

**sample-mixed-abbrev-styles.tex** Different abbreviation styles for different entries.

**sample-initialisms.tex** Automatically insert dots into initialisms.

**sample-postdot.tex** Another initialisms example.

**sample-postlink.tex** Automatically inserting text after the **link-text** produced by commands like `\gls` (outside of hyperlink, if present).

**sample-header.tex** Using entries in section/chapter headings.

**sample-autoindex.tex** Using the **dualindex** and **indexname** attributes to automatically add glossary entries to the index (in addition to the glossary **location list**).

**sample-autoindex-hyp.tex** As previous but uses hyperref.

**sample-nested.tex** Using `\gls` within the value of the name key.

**sample-entrycount.tex** Enable entry-use counting (only index if used more than  $n$  times, see Section 8.1).

**sample-unitentrycount.tex** Enable use of per-unit entry-use counting (Section 8.1).

**sample-onelink.tex** Using the per-unit entry counting (Section 8.1) to only have one hyperlink per entry per page.

**sample-linkcount.tex** Using link counting (Section 8.2) to only have one hyperlink per entry.

**sample-pages.tex** Insert “page” or “pages” before the location list.

**sample-altmodifier.tex** Set the default options for commands like `\gls` and add an alternative modifier.

**sample-mixedsort.tex** Uses the optional argument of `\makeglossaries` to allow a mixture of `\printglossary` and `\printnoidxglossary`.

**sample-external.tex** Uses the `targeturl` attribute to allow for entries that should link to an external URL rather than to an internal glossary.

**sample-fmt.tex** Provides text-block commands associated with entries in order to use `\glsxtrfmt`.

**sample-alias.tex** Uses the alias key. (See Section 11.5.)

**sample-alttree.tex** Uses the `glossaries-extra-stylemods` package with the `alttree` style (see Section 2.11.3).

**sample-alttree-sym.tex** Another `alttree` example that measures the symbol widths.

**sample-alttree-marginpar.tex** Another `alttree` example that puts the `number list` in the margin.

**sample-onthefly.tex** Using on-the-fly commands. Terms with accents must have the name key explicitly set.

**sample-onthefly-xetex.tex** Using on-the-fly commands with  $X_{\LaTeX}$ . Terms with UTF-8 characters don’t need to have the name key explicitly set. Terms that contain commands must have the name key explicitly set with the commands removed from the label.

**sample-onthefly-utf8.tex** Tries to emulate the previous sample file for use with  $\LaTeX$  through the starred version of `\GlsXtrEnableOnTheFly`. This is a bit iffy and may not always work. Terms that contain commands must have the name key explicitly set with the commands removed from the label.

**sample-accsupp.tex** Integrate `glossaries-accsupp`.

**sample-prefix.tex** Integrate `glossaries-prefix`.



**sample-suppl-main.tex** Uses thevalue to reference a location in the supplementary file `sample-suppl.tex`.

**sample-suppl-main-hyp.tex** A more complicated version to the above that uses the `hyperref` package to reference a location in the supplementary file `sample-suppl-hyp.tex`.

## 15 Multi-Lingual Support

There's only one command provided by `glossaries-extra` that you're likely to want to change in your document and that's `\abbreviationsname` (Section 1.2) if you use the `abbreviations` package option to automatically create the glossary labelled abbreviations. If this command doesn't already exist, it will be defined to "Abbreviations" if `babel` hasn't been loaded, otherwise it will be defined as `\acronymname` (provided by `glossaries`).

You can redefine it in the usual way. For example:

```
\renewcommand*{\abbreviationsname}{List of Abbreviations}
```

Or using `babel` or `polyglossia` captions hook:

```
\appto\captionenglish{%  
  \renewcommand*{\abbreviationsname}{List of Abbreviations}%  
}
```

Alternatively you can use the `title` key when you print the list of abbreviations. For example:

```
\printabbreviations[title={List of Abbreviations}]
```

or

```
\printglossary[type=abbreviations,title={List of Abbreviations}]
```

The other fixed text commands are the diagnostic messages, which shouldn't appear in the final draft of your document.

The `glossaries-extra` package has the facility to load language modules (whose filename is in the form `glossariesxtr-⟨language⟩.ldf`) if they exist, but won't warn if they don't. If `glossaries-extra-bib2gls` is loaded via the `record` package option then the check for language resource files will additionally search for an associated language script file given by `glossariesxtr-⟨script⟩.ldf` where `⟨script⟩` is the four letter script identifier, such as `Latn`, associated with the given dialect. There's no warning if the associated file isn't found. The script file is loaded after the dialect file.

If you want to write your own language module, you just need to create a file called `glossariesxtr-⟨lang⟩.ldf`, where `⟨lang⟩` identifies the language or dialect (see the `tracklang` package). For example, `glossariesxtr-french.ldf`.

The simplest code for this file is:

```
\ProvidesGlossariesExtraLang{french}[2015/12/09 v1.0]  
  
\newcommand*{\glossariesxtrcaptionsfrench}{%  
  \def\abbreviationsname{Abr'eviations}%  
}  
\glossariesxtrcaptionsfrench
```

```

\ifcsdef{captions\CurrentTrackedDialect}
{%
  \csappto{captions\CurrentTrackedDialect}%
  {%
    \glossariesxtrcaptionsfrench
  }%
}%
\ifcsdef{captions\CurrentTrackedLanguage}
{%
  \csappto{captions\CurrentTrackedLanguage}%
  {%
    \glossariesxtrcaptionsfrench
  }%
}%
{}%
}

```

You can adapt this for other languages by replacing all instances of the language identifier `french` and the translated text `Abr\ 'eviations` as appropriate. You can also use the `.ldf` file to provide rule blocks for a particular language for use with `bib2gls`'s custom sort rule. See Section 10.3 for further details.

This `.ldf` file then needs to be put somewhere on `TeX`'s path so that it can be found by `glossaries-extra`. You might also want to consider uploading it to CTAN so that it can be useful to others. (Please don't send it to me. I already have more packages than I am able to maintain.)

If you additionally want to provide translations for the diagnostic messages used when a glossary is missing, you need to redefine the following commands:

```
\GlsXtrNoGlsWarningHead{\label}{\file}
```

This produces the following text in English:

This document is incomplete. The external file associated with the glossary '`label`' (which should be called `file`) hasn't been created.

```
\GlsXtrNoGlsWarningEmptyStart
```

This produces the following text in English:

This has probably happened because there are no entries defined in this glossary.

```
\GlsXtrNoGlsWarningEmptyMain
```

This produces the following text in English:

If you don't want this glossary, add `nomain` to your package option list when you load `glossaries-extra.sty`. For example:

```
\GlsXtrNoGlsWarningEmptyNotMain{<label>}
```

This produces the following text in English:

Did you forget to use `type=<label>` when you defined your entries? If you tried to load entries into this glossary with `\loadglsentries` did you remember to use `[<label>]` as the optional argument? If you did, check that the definitions in the file you loaded all had the type set to `\glsdefaulttype`.

```
\GlsXtrNoGlsWarningCheckFile{<file>}
```

This produces the following text in English:

Check the contents of the file `<file>`. If it's empty, that means you haven't indexed any of your entries in this glossary (using commands like `\gls` or `\glsadd`) so this list can't be generated. If the file isn't empty, the document build process hasn't been completed.

```
\GlsXtrNoGlsWarningMismatch
```

This produces the following text in English:

You need to either replace `\makenoidglossaries` with `\makeglossaries` or replace `\printglossary` (or `\printglossaries`) with `\printnoidglossary` (or `\printnoidglossaries`) and then rebuild this document.

```
\GlsXtrNoGlsWarningNoOut{<file>}
```

This produces the following text in English:

The file `<file>` doesn't exist. This most likely means you haven't used `\makeglossaries` or you have used `\nofiles`. If this is just a draft version of the document, you can suppress this message using the `nomissinggls` package option.

```
\GlsXtrNoGlsWarningTail
```

This produces the following text in English:

This message will be removed once the problem has been fixed.

```
\GlsXtrNoGlsWarningBuildInfo
```

This is advice on how to generate the glossary files.

```
\GlsXtrNoGlsWarningAutoMake{\label}
```

This is the message produced when the **automake** option is used, but the document needs a rerun or the shell escape setting doesn't permit the execution of the external application. This command also generates a warning in the transcript file.

See the documented code (`glossaries-extra-code.pdf`) for further details.

# Glossary

**bib2gls** A command line Java application that selects entries from a .bib file and converts them to glossary definitions (like `bibtex` but also performs hierarchical sorting and collation, thus omitting the need for `xindy` or `makeindex`). Further details at: <http://www.dickimaw-books.com/software/bib2gls/>.

**entry location** The location of the entry in the document. This defaults to the page number on which the entry appears. An entry may have multiple locations.

**first use** The first time a glossary entry is used (from the start of the document or after a reset) with one of the following commands: `\gls`, `\Gls`, `\GLS`, `\glspl`, `\Glspl`, `\GLSpl` or `\glsdisp`.

**first use flag** A conditional that determines whether or not the entry has been used according to the rules of **first use**.

**first use text** The text that is displayed on first use, which is governed by the `first` and `firstplural` keys of `\newglossaryentry`. (May be overridden by `\glsdisp`.)

**link-text** The text produced by commands such as `\gls`. It may or may not have a hyperlink to the glossary.

**location list** A list of **entry locations**. See **number list**.

**makeglossaries** A custom designed Perl script interface provided with the `glossaries` package to run `xindy` or `makeindex` according to the document settings.

**makeglossaries-lite** A custom designed Lua script interface to `xindy` and `makeindex` provided with the `glossaries` package. This is a cut-down alternative to the Perl `makeglossaries` script. If you have Perl installed, use the Perl script instead. This script is distributed in the source code on CTAN with the file name `makeglossaries-lite.lua` but TeX Live on Unix-like systems creates a symbolic link called `makeglossaries-lite` (without the `.lua` extension) to the actual `makeglossaries-lite.lua` script, and TeX distributions on Windows convert the script to an executable `makeglossaries-lite.exe`.

**makeindex** An indexing application.

**number list** A list of entry locations (also called a location list). The number list can be suppressed using the `nonumberlist` package option.

**xindy** An flexible indexing application with multilingual support written in Perl.

# Index

## A

\AB	91	long-noshort-noreg	105
\Ab	91	long-noshort-sc	97, 101
\ab	91, 176	long-noshort-sc-desc	101, 117
abbreviation styles (deprecated):		long-noshort-sm	101
footnote-em	109	long-noshort-sm-desc	101
footnote-sc	108	long-only-short-only	95, 102, 103
footnote-sm	109	long-only-short-only-desc	103
long-desc-em	101	long-only-short-sc-only	96, 103
long-desc-sc	101	long-only-short-sc-only-desc	103
long-desc-sm	101	long-postshort-sc-user	96, 110, 135
long-em	101	long-postshort-sc-user-desc	111
long-sc	101	long-postshort-user	110
long-sm	101	long-postshort-user-desc	110, 111
postfootnote-em	110	long-short	46, 50, 51, 86, 92, 102–104, 111, 115, 120
postfootnote-sc	110	long-short-desc	50, 105, 106, 120
postfootnote-sm	110	long-short-em	94, 97, 102
abbreviation styles:		long-short-em-desc	105
footnote	108	long-short-sc	50, 93, 102, 105
footnote-desc	109	long-short-sc-desc	50, 105
long	101	long-short-sm	50, 93, 102
long-desc	101	long-short-sm-desc	50, 105
long-em-noshort-em	98, 102, 103	long-short-user	98, 102–104, 106, 110
long-em-noshort-em-desc	101, 105	long-short-user-desc	106
long-em-noshort-em-desc-noreg	105	nolong-short	99, 106
long-em-noshort-em-noreg	98, 102, 103	nolong-short-em	100
long-em-short-em	94, 97, 102, 115	nolong-short-noreg	106
long-em-short-em-desc	105	nolong-short-sc	99
long-hyphen-long-hyphen	113	nolong-short-sm	99
long-hyphen-noshort-desc-noreg	112	postfootnote	85, 109
long-hyphen-noshort-noreg	98, 112	postfootnote-desc	110
long-hyphen-postshort-hyphen	98, 112–114	short	99
long-hyphen-postshort-hyphen-desc	113	short-desc	100
long-hyphen-short-hyphen	111–113, 167	short-em	100
long-hyphen-short-hyphen-desc	112	short-em-desc	100
long-noshort	50, 88, 101, 102, 105	short-em-footnote	98, 109
long-noshort-desc	46, 50, 100, 101, 105	short-em-footnote-desc	98, 109
long-noshort-desc-noreg	105	short-em-long	94, 106
long-noshort-em	101	short-em-long-desc	107
long-noshort-em-desc	101	short-em-long-em	94, 106

short-em-long-em-desc	107	\Ac	91
short-em-nolong	99, 100	\ac	49, 91, 176
short-em-nolong-desc	100	\ACF	91
short-em-postfootnote	110	\Acf	91
short-em-postfootnote-desc	110	\acf	91
short-footnote	50, 86, 98, 107–109, 115	\ACFP	91
short-footnote-desc	50, 109, 110	\Acfp	91
short-hyphen-long-hyphen	113, 114	\acfp	91
short-hyphen-long-hyphen-desc	114	\ACL	91
short-hyphen-postlong-hyphen	114	\Acl	91
short-hyphen-postlong-hyphen-desc	114	\acl	91
short-long	50, 86, 92, 96, 98, 106, 119, 120	\ACLP	91
short-long-desc	50, 98, 107	\Aclp	91
short-long-user	104, 106, 107, 110	\aclp	91
short-long-user-desc	107	\ACP	91
short-nolong	7, 86, 88, 89, 99, 100, 106	\Acp	91
short-nolong-desc	100, 107	\acp	91
short-nolong-desc-noreg	107	\acrfull	49, 89
short-nolong-noreg	106	\acrlong	46, 49, 89
short-postfootnote	38, 109, 110	acronym styles (glossaries):	
short-postfootnote-desc	110	dua	50
short-postlong-user	110	dua-desc	50
short-postlong-user-desc	110	footnote	50
short-sc	99	footnote-desc	50
short-sc-desc	100	footnote-sc	50
short-sc-footnote	50, 108, 109	footnote-sc-desc	50
short-sc-footnote-desc	50, 109	footnote-sm	50
short-sc-long	50, 93, 106, 120	footnote-sm-desc	50
short-sc-long-desc	50, 107	long-sc-short	50
short-sc-nolong	99	long-sc-short-desc	50
short-sc-nolong-desc	100	long-short-desc	50
short-sc-postfootnote	98, 110	long-sm-short	50
short-sc-postfootnote-desc	110	long-sm-short-desc	50
short-sm	99	long-sp-short	50, 51
short-sm-desc	100	long-sp-short-desc	50
short-sm-footnote	50	sc-short-long	50
short-sm-footnote-desc	50, 109	sc-short-long-desc	50
short-sm-long	50, 93, 106	short-long	50
short-sm-long-desc	50, 107	short-long-desc	50
short-sm-nolong	99	sm-short-long	50
short-sm-nolong-desc	100	sm-short-long-desc	50
short-sm-postfootnote	110	\acronymfont	88
short-sm-postfootnote-desc	110	\acronymtype	19, 20
\abbreviationsname	19, 258	\acrpluralsuffix	42
\abbrvpluralsuffix	42, 117	\acrshort	46, 49, 88
\ABP	91	\ACS	91
\Abp	91	\Acs	91
\abp	91	\acs	49, 91
\AC	91	\ACSP	91



<code>\Acsp</code>	91	<code>symbol</code>	37, 165
<code>\acsp</code>	91	category attributes:	
<code>\actualchar</code>	188	<code>accessaposplural</code>	171, 172
<code>\AF</code>	91	<code>accessinsertdots</code>	171, 172
<code>\Af</code>	91	<code>accessnoshortplural</code>	171, 172
<code>\af</code>	91	<code>aposplural</code>	43, 93, 168, 172
<code>\AFP</code>	91	<code>combinedfirstsep</code>	142, 172
<code>\Afp</code>	91	<code>combinedfirstsefirst</code>	143, 172
<code>\afp</code>	91	<code>combinedsep</code>	142, 172
<code>\AL</code>	91	<code>combinedsefirst</code>	143, 172
<code>\Al</code>	91	<code>discardperiod</code>	36, 132, 166–168
<code>\al</code>	91	<code>dualindex</code>	170, 186, 188, 255
<code>align (environment)</code>	15	<code>entrycount</code>	38, 169, 176–180
<code>\ALP</code>	91	<code>externallocation</code>	29, 30, 171, 197
<code>\Alp</code>	91	<code>firstshortaccess</code>	172
<code>\alp</code>	91	<code>glossdesc</code>	53, 169, 170
<code>\Alpha</code>	201, 203, 210	<code>glossdescfont</code>	53, 169, 170
<code>\alpha</code>	203, 210, 211	<code>glossname</code>	53, 54, 170
<code>\alsoname</code>	34	<code>glossnamefont</code>	53, 54, 170, 244
<code>amsgen package</code>	1	<code>glosssymbolfont</code>	53, 170
<code>amsmath package</code>	16	<code>headuc</code>	47, 122, 123, 168
<code>\apptoglossarypreamble</code>	222	<code>hyperoutside</code>	26, 170
<code>\AS</code>	91	<code>indexname</code>	54, 170, 186, 255
<code>\As</code>	91	<code>indexonlyfirst</code>	25, 166, 188
<code>\as</code>	91	<code>insertdots</code>	86, 168, 172
<code>\ASP</code>	91	<code>linkcount</code>	169, 182, 184
<code>\Asp</code>	91	<code>linkcountmaster</code>	169, 182
<code>\asp</code>	91	<code>markshortwords</code>	168
		<code>markwords</code>	111, 112, 116, 167, 168
		<code>multioptions</code>	134, 150
		<code>nameshortaccess</code>	172
		<code>nohyper</code>	166, 174
		<code>nohyperfirst</code>	107, 116, 166
		<code>noshortplural</code>	43, 86, 93, 168, 172
		<code>pluraldiscardperiod</code>	167
		<code>recordcount</code>	219, 220
		<code>regular</code>	35, 88, 91, 92, 98, 99, 102, 103, 105–107, 116, 118, 165, 173–175, 220
		<code>retainfirstuseperiod</code>	132, 167
		<code>tagging</code>	87, 88, 168
		<code>targetcategory</code>	171
		<code>targetname</code>	170, 171
		<code>targeturl</code>	51, 170, 171, 246, 256
		<code>textformat</code>	26, 35, 41, 170
		<code>textshortaccess</code>	172
		<code>unitcount</code>	180
		<code>wrgloss</code>	25, 166
		<code>\cGLS</code>	91, 177
		<code>\cgls</code>	91, 169, 176, 178
<b>B</b>			
<code>babel package</code>	6, 19, 165, 231, 258		
<code>\Beta</code>	201, 203, 210		
<code>\beta</code>	203, 210, 211		
<code>bib2gls</code>	1, 10, 12–18, 22, 29, 30, 38, 39, 54, 57, 64, 67–70, 73, 74, 82, 139, 162, 171, 176, 186, 189– 202, 204, 210, 211, 213, 217, 218, 220, 226, 230, 233–235, 240–243, 246, 259, 262		
<code>\bibglsdualprefixlabel</code>	217		
<code>\bibglsprimaryprefixlabel</code>	217		
<code>\bibgls tertiaryprefixlabel</code>	217		
<b>C</b>			
<code>\capitalisewords</code>	169		
categories:			
<code>abbreviation</code>	39, 86, 87, 165, 184		
<code>acronym</code>	8, 55, 86, 87, 165		
<code>general</code>	37, 38, 55, 56, 165, 174, 181		
<code>index</code>	23, 165		
<code>number</code>	165		

<code>\cGLSformat</code> .....	177	<code>equation (counter)</code> .....	15, 16, 28, 198, 199
<code>\cGLSpl</code> .....	91, 177	<code>equation (environment)</code> .....	15, 16
<code>\cglspl</code> .....	91	<code>\Eta</code> .....	201
<code>\cGLSplformat</code> .....	177	<code>etoolbox package</code>	1, 174, 183, 225, 227, 229–231
<code>\Chi</code> .....	201	<b>F</b>	
<code>convertgls2bib</code> .....	189	<code>\false options</code>	
<code>\csGlsXtrLetField</code> .....	226	<code>groups</code> .....	53
<code>\currentglossary</code> .....	240	<code>fancyhdr package</code> .....	71
<code>\CustomAbbreviationFields</code> .....	115	<code>figure (environment)</code> .....	15
<b>D</b>		<code>file types</code>	
<code>datatool package</code> .....	228	<code>aux</code> .....	129, 162
<code>datatool-base package</code> .....	1, 228, 230	<code>bib</code> .....	15, 162
<code>\descriptionname</code> .....	73	<code>glg-abr</code> .....	18
<code>\dGLS</code> .....	215	<code>glo-abr</code> .....	18
<code>\dGls</code> .....	214	<code>gls-abr</code> .....	18
<code>\dgl</code> .....	214	<code>first use</code>	7, 25, 35, 37, 38, 43–46, 51, 85, 86, 89, 91, 92, 99, 102, 105–109, 117, 118, 127, 135, 138, 144, 166, 167, 181, 255, 262, 262
<code>\dglsgl</code> .....	215	<code>first use flag</code> .....	38, 39, 121, 134, 137, 138, 146, 149, 150, 154–156, 176, 178, 220, 262
<code>\dGLSpl</code> .....	215	<code>first use text</code> .....	262, 279
<code>\dGlspl</code> .....	214	<code>fontenc package</code> .....	92
<code>\dglspl</code> .....	214	<code>\footnote</code> .....	85, 98, 108
<code>\diagamma</code> .....	210	<code>\forall abbreviationlists</code> .....	87
<code>\Digamma</code> .....	201, 210	<code>\forall acronyms</code> .....	87
<code>\digamma</code> .....	210, 211	<code>\forall gls entries</code> .....	12
<code>document (environment)</code> .....	17, 18, 30, 248	<b>G</b>	
<code>\DTLformatlist</code> .....	230	<code>\GetTrackedDialectFromLanguageTag</code>	231
<b>E</b>		<code>\glssetwidest</code> .....	63
<code>\eglssetwidest</code> .....	63	<code>\glsupdatewidest</code> .....	63
<code>\eglsupdatewidest</code> .....	63	<code>\glsXtrSetField</code> .....	226
<code>\eGlsXtrSetField</code> .....	226	<code>\glo link prefix</code> .....	26
<code>\encapchar</code> .....	188	<code>glossaries package</code> .....	18, 23, 31, 34, 42, 53, 166, 198, 200, 202, 229, 231, 234
<code>entry location</code> .....	262, 262	<code>glossaries-accsupp package</code> .....	12, 54, 119, 171, 172, 245, 250, 251, 256
<code>entrycounter package</code> .....	245	<code>glossaries-extra package</code>	23, 31, 32, 53, 171, 201
<code>\entryname</code> .....	72	<code>glossaries-extra-bib2gls package</code> .....	14, 15, 18–20, 163, 196, 201, 203, 258
<code>environments:</code>		<code>glossaries-extra-stylemods package</code> .....	11, 12, 53, 58, 60, 61, 197, 233, 256
<code>align</code> .....	15	<code>glossaries-prefix package</code> .....	12, 159, 250, 256
<code>document</code> .....	17, 18, 30, 248	<code>\glossariesextrasetup</code> .....	12, 21
<code>equation</code> .....	15, 16	<code>glossary styles:</code>	
<code>figure</code> .....	15	<code>altlist</code> .....	59, 60
<code>longtable</code> .....	72, 77–80	<code>almtree</code> .....	61–66, 73, 81, 197, 256
<code>multicols</code> .....	67, 81	<code>bookindex</code> .....	67, 70
<code>multicols*</code> .....	67	<code>index</code> .....	61
<code>printunstrtglossarywrap</code> .....	239, 240		
<code>table</code> .....	15		
<code>tabular</code> .....	59, 72, 77–80, 233, 234		
<code>theglossary</code> .....	6, 239, 240		
<code>theindex</code> .....	188		
<code>\Epsilon</code> .....	201		

inline	59	<code>\gls</code>	26, 27, 35,
list	59, 60, 241		38, 43, 45, 48, 86, 88, 91, 92, 100, 102,
listdotted	59, 60		118, 166, 167, 170, 176, 178, 181, 256, 262
listhypergroup	52	<code>\glsabbrvdefaultfont</code>	92, 93
long	59, 238, 240	<code>\glsabbrvemfont</code>	94, 99–102, 105–107, 109, 110
long-desc-name	77	<code>\glsabbrvfont</code>	46, 51, 117
long-desc-sym-name	80	<code>\glsabbrvhyphenfont</code>	95
long-loc-desc-name	78	<code>\glsabbrvonlyfont</code>	95
long-loc-desc-sym-name	80	<code>\glsabbrvscfont</code>	93, 96, 99–102, 105–110
long-loc-sym-desc-name	80	<code>\glsabbrvsconlyfont</code>	96, 96
long-name-desc	76, 77	<code>\glsabbrvscuserfont</code>	96, 96
long-name-desc-loc	77	<code>\glsabbrvsmfont</code>	93, 99–102, 105–107, 109, 110
long-name-desc-sym	78, 79	<code>\glsabbrvuserfont</code>	94, 104
long-name-desc-sym-loc	78, 79	<code>\Glsaccessdesc</code>	253
long-name-sym-desc	79	<code>\glsaccessdesc</code>	253
long-name-sym-desc-loc	79	<code>\Glsaccessdescplural</code>	253
long-sym-desc-name	79	<code>\glsaccessdescplural</code>	253
long3col	58	<code>\Glsaccessfirst</code>	252
longragged-booktabs	76	<code>\glsaccessfirst</code>	252
mcolindexgroup	67	<code>\Glsaccessfirstplural</code>	252
super	238	<code>\glsaccessfirstplural</code>	252
topic	81	<code>\Glsaccesslong</code>	253
topicmcols	81	<code>\glsaccesslong</code>	253
tree	61, 62, 81	<code>\Glsaccesslongpl</code>	254
treenoname	62	<code>\glsaccesslongpl</code>	253
glossary-bookindex package	67, 71	<code>\Glsaccessname</code>	251
glossary-inline package	59	<code>\glsaccessname</code>	251
glossary-list package	238	<code>\Glsaccessplural</code>	252
glossary-long package	73	<code>\glsaccessplural</code>	252
glossary-longextra package	72, 197	<code>\Glsaccessshort</code>	253
glossary-topic package	81, 82	<code>\glsaccessshort</code>	253
glossary-tree package	60, 61, 63, 64, 70, 81	<code>\Glsaccessshortpl</code>	253
<code>\glossaryheader</code>	238, 239	<code>\glsaccessshortpl</code>	253
<code>\glossarypostamble</code>	239	<code>\Glsaccesssymbol</code>	252
<code>\glossarypreamble</code>	238, 239	<code>\glsaccesssymbol</code>	252
<code>\glossarysection</code>	238, 239	<code>\Glsaccesssymbolplural</code>	252
<code>\glossarytitle</code>	238, 239	<code>\glsaccesssymbolplural</code>	252
<code>\glossarytoctitle</code>	238, 239	<code>\Glsaccesstext</code>	252
<code>\glossentry</code>	238, 239	<code>\glsaccesstext</code>	12, 251
<code>\glossentrydesc</code>	53, 169	<code>\glsacspace</code>	51
<code>\Glossentryname</code>	54, 186	<code>\glsacspacemax</code>	51
<code>\glossentryname</code>	53, 54, 170, 186	<code>\glsadd</code>	25, 170
<code>\glossentrynameother</code>	54	<code>\glsadd options</code>	
<code>\glossentrysymbol</code>	53, 54, 170	format	27
<code>\glossxtrsetpopts</code>	47	theHvalue	28, 30
<code>\GLS</code>	43, 262	thevalue	28, 29, 257
<code>\Gls</code>	43, 48, 118, 262	<code>\glsaddall</code>	12, 25

<code>\glsaddeach</code>	24	<code>\glsFindWidestAnyNameSymbol</code>	65
<code>\glsaddpostsetkeys</code>	28	<code>\glsFindWidestAnyNameSymbolLocation</code>	65
<code>\glsaddpresetkeys</code>	28	<code>\glsFindWidestLevelTwo</code>	65
<code>\glsaltlistitem</code>	60	<code>\glsFindWidestTopLevelName</code>	64
<code>\glsalttreechildpredesc</code>	61	<code>\glsFindWidestUsedAnyName</code>	64
<code>\glsalttreepredesc</code>	61	<code>\glsFindWidestUsedAnyNameLocation</code>	65
<code>\glsapturedgroup</code>	200	<code>\glsFindWidestUsedAnyNameSymbol</code>	65
<code>\glscategory</code>	165	<code>\glsFindWidestUsedAnyNameSymbolLocation</code>	65
<code>\glscategorylabel</code>	117	<code>\glsFindWidestUsedLevelTwo</code>	64
<code>\glscombinedfirstsep</code>	142	<code>\glsFindWidestUsedTopLevelName</code>	64
<code>\glscombinedfirstsepfirst</code>	143, 172	<code>\GLSfirst</code>	85
<code>\glscombinedsep</code>	142, 172	<code>\Glsfirst</code>	85
<code>\glscombinedsepfirst</code>	142	<code>\glsfirst</code>	35, 38, 85, 89, 92
<code>\glscombinefirstsep</code>	172	<code>\glsfirstabbrvdefaultfont</code>	92
<code>\glscombinesepfirst</code>	172	<code>\glsfirstabbrvemfont</code>	94
<code>\glscurrententrylabel</code>	55, 56	<code>\glsfirstabbrvfont</code>	51, 117
<code>\glscurrentfieldvalue</code>	227	<code>\glsfirstabbrvhyphenfont</code>	95
<code>\glsdefaultshortaccess</code>	171	<code>\glsfirstabbrvonlyfont</code>	95
<code>\glsdefpostdesc</code>	55	<code>\glsfirstabbrvsconlyfont</code>	96
<code>\glsdefpostlink</code>	37	<code>\glsfirstabbrvscuserfont</code>	96
<code>\glsdefpostname</code>	55	<code>\glsfirstabbrvsmfont</code>	93
<code>\glsdesc</code>	45	<code>\glsfirstabbrvuserfont</code>	94
<code>\glsdescwidth</code>	73	<code>\glsfirstlongdefaultfont</code>	93
<code>\glsdisp</code>	262	<code>\glsfirstlongemfont</code>	94, 101, 102, 105–107
<code>\glsdisplaynumberlist</code>	196	<code>\glsfirstlongfont</code>	117
<code>\glsdoifexists</code>	22, 225	<code>\glsfirstlongfootnotefont</code>	108
<code>\glsenableentrycount</code>	38, 169, 176	<code>\glsfirstlonghyphenfont</code>	95
<code>\glsentrycurrcount</code>	180	<code>\glsfirstlongonlyfont</code>	95
<code>\Glsentrydesc</code>	169	<code>\glsfirstlonguserfont</code>	95
<code>\glsentryfmt</code>	35	<code>\GLSfmtfirst</code>	126
<code>\Glsentryfull</code>	118	<code>\Glsfmtfirst</code>	126
<code>\glsentryfull</code>	118	<code>\glsfmtfirst</code>	126
<code>\Glsentryfullpl</code>	118	<code>\GLSfmtfirstpl</code>	126
<code>\glsentryfullpl</code>	118	<code>\Glsfmtfirstpl</code>	126
<code>\glsentrylong</code>	43, 46	<code>\glsfmtfirstpl</code>	126
<code>\glsentrynumberlist</code>	65, 196	<code>\GLSfmtfull</code>	125
<code>\glsentrypdfsymbol</code>	54	<code>\Glsfmtfull</code>	124
<code>\glsentryprevcount</code>	180	<code>\glsfmtfull</code>	124
<code>\glsentryprevmaxcount</code>	180	<code>\Glsfmtfullpl</code>	125
<code>\glsentryprevtotalcount</code>	180	<code>\Glsfmtfullpl</code>	125
<code>\glsentryshort</code>	43, 45, 46, 121	<code>\glsfmtfullpl</code>	124
<code>\glsentrytext</code>	12, 45, 121	<code>\GLSfmtlong</code>	124
<code>\glsentrytitlecase</code>	164, 169	<code>\Glsfmtlong</code>	124
<code>\glsextrapostnamehook</code>	55	<code>\glsfmtlong</code>	123
<code>\glsfielddef</code>	175	<code>\GLSfmtlongpl</code>	124
<code>\glsfieldfetch</code>	229	<code>\Glsfmtlongpl</code>	124
<code>\glsfieldxdef</code>	175	<code>\GLSfmtlongpl</code>	123
<code>\glsFindWidestAnyName</code>	64	<code>\GLSfmtname</code>	126
<code>\glsFindWidestAnyNameLocation</code>	65		

<code>\Glsfmtname</code>	126	<code>\glslinkpostsetkeys</code>	28, 184
<code>\glsfmtname</code>	125	<code>\glslinkpresetkeys</code>	28, 183, 184
<code>\GLSfmtplural</code>	125	<code>\glslistchildpostlocation</code>	60
<code>\Glsfmtplural</code>	125	<code>\glslistchildprelocation</code>	59
<code>\glsfmtplural</code>	125	<code>\glslistdesc</code>	59
<code>\GLSfmtshort</code>	123	<code>\glslistdottedwidth</code>	60
<code>\Glsfmtshort</code>	123	<code>\glslistgroupafterheader</code>	60
<code>\glsfmtshort</code>	51, 123, 168	<code>\glslistgroupheaderitem</code>	60
<code>\Glsfmtshortpl</code>	123	<code>\glslistgroupskip</code>	60
<code>\glsfmtshortpl</code>	123	<code>\glslistitem</code>	59
<code>\GLSfmtttext</code>	125	<code>\glslistprelocation</code>	59
<code>\Glsfmtttext</code>	125	<code>\glslocalreaseteach</code>	39
<code>\glsfmtttext</code>	85, 125	<code>\glslocalunseteach</code>	39
<code>\glsforeachwithattribute</code>	175	<code>\glslongdefaultfont</code>	92
<code>\glsgenentry</code>	35	<code>\glslongemfont</code>	94, 101
<code>\glsgenentryfmt</code>	35, 91	<code>\glslongextraDescAlign</code>	73
<code>\glsgetattribute</code>	173	<code>\glslongextraDescFmt</code>	75
<code>\glsgetcategoryattribute</code>	173	<code>\glslongextraDescNameHeader</code>	77
<code>\glsgetwidestname</code>	64	<code>\glslongextraDescNameTabularFooter</code>	77
<code>\glsgetwidestsubname</code>	64	<code>\glslongextraDescNameTabularHeader</code>	77
<code>\glsgroupheading</code>	238	<code>\glslongextraDescSymNameHeader</code>	80
<code>\glsgroupskip</code>	238	<code>\glslongextraDescSymNameTabularFooter</code>	80
<code>\glshasattribute</code>	174	<code>\glslongextraDescSymNameTabularHeader</code>	80
<code>\glshascategoryattribute</code>	174	<code>\glslongextraDescSymNameTabularHeader</code>	80
<code>\glshex</code>	195, 200	<code>\glslongextraGroupHeading</code>	76
<code>\glshypernumber</code>	188	<code>\glslongextraHeaderFmt</code>	72
<code>\glsifattribute</code>	174	<code>\glslongextraLocationAlign</code>	73
<code>\glsifcategory</code>	165	<code>\glslongextraLocationDescNameHeader</code>	78
<code>\glsifcategoryattribute</code>	174	<code>\glslongextraLocationDescNameTabularFooter</code>	78
<code>\glsifnotregular</code>	175	<code>\glslongextraLocationDescNameTabularHeader</code>	78
<code>\glsifnotregularcategory</code>	174	<code>\glslongextraLocationDescSymNameHeader</code>	80
<code>\glsifregular</code>	174	<code>\glslongextraLocationDescSymNameTabularFooter</code>	81
<code>\glsifregularcategory</code>	174	<code>\glslongextraLocationDescSymNameTabularHeader</code>	80
<code>\glskeylisttok</code>	117	<code>\glslongextraLocationFmt</code>	75, 76
<code>\glslabeltok</code>	117	<code>\glslongextraLocationSymDescNameHeader</code>	80
<code>\glslink</code>	26, 35	<code>\glslongextraLocationSymDescNameTabularFooter</code>	80
<code>\glslink options</code>		<code>\glslongextraLocationSymDescNameTabularHeader</code>	80
<code>counter</code>	15	<code>\glslongextraLocationSetDescWidth</code>	74
<code>format</code>	29, 151, 188, 220	<code>\glslongextraNameAlign</code>	72
<code>hyper</code>	47, 166	<code>\glslongextraNameDescHeader</code>	76
<code>hyper=false</code>	122		
<code>hyperoutside</code>	25, 170		
<code>noindex</code>	25, 47, 122, 188, 246		
<code>prefix</code>	26, 52		
<code>textformat</code>	26, 41		
<code>theHvalue</code>	26, 28		
<code>thevalue</code>	26, 28		
<code>wrgloss</code>	25, 27, 166		
<code>\glslinkcheckfirsthyperhook</code>	181		

<code>\glslongextraNameDescLocationHeader</code>	77	<code>\glslongfootnotefont</code>	108
<code>\glslongextraNameDescLocationTabularFooter</code>	77	<code>\glslonghyphenfont</code>	95
<code>\glslongextraNameDescLocationTabularHeader</code>	77	<code>\glslongonlyfont</code>	95
<code>\glslongextraNameDescSymHeader</code>	78	<code>\glslongpltok</code>	116
<code>\glslongextraNameDescSymLocationHeader</code>	78	<code>\glslongtok</code>	116
<code>\glslongextraNameDescSymLocationTabularFooter</code>	79	<code>\glslonguserfont</code>	94
<code>\glslongextraNameDescSymLocationTabularHeader</code>	78	<code>\glsnameaccessdisplay</code>	251
<code>\glslongextraNameDescSymTabularFooter</code>	78	<code>\glsnavhyperlinkname</code>	52
<code>\glslongextraNameDescSymTabularHeader</code>	78	<code>\glsnoidxdisplayloc</code>	28, 57
<code>\glslongextraNameDescTabularFooter</code>	77	<code>\glspagelistwidth</code>	73
<code>\glslongextraNameDescTabularHeader</code>	76	<code>\glspdfmftfull</code>	124
<code>\glslongextraNameFmt</code>	75	<code>\glspdfmftfullpl</code>	124
<code>\glslongextraNameSymDescHeader</code>	79	<code>\glspercentchar</code>	170
<code>\glslongextraNameSymDescLocationHeader</code>	79	<code>\GLSpl</code>	262
<code>\glslongextraNameSymDescLocationTabularFooter</code>	79	<code>\GLspl</code>	118, 262
<code>\glslongextraNameSymDescLocationTabularHeader</code>	79	<code>\glspl</code>	118, 262
<code>\glslongextraNameSymDescTabularFooter</code>	79	<code>\glspluralsuffix</code>	42, 93
<code>\glslongextraNameSymDescTabularHeader</code>	79	<code>\glspostlinkhook</code>	145, 147, 151
<code>\glslongextraSetDescWidth</code>	73	<code>\glsps</code>	46
<code>\glslongextraSetWidest</code>	73	<code>\glspt</code>	46
<code>\glslongextraSubDescFmt</code>	75	<code>\glsrefentry</code>	222
<code>\glslongextraSubNameFmt</code>	75	<code>\glsrenewcommand</code>	196
<code>\glslongextraSubSymbolFmt</code>	75	<code>\glsresetentrylist</code>	238
<code>\glslongextraSymbolAlign</code>	72	<code>\glsseeitem</code>	34
<code>\glslongextraSymbolFmt</code>	75	<code>\glsseeitem</code>	31
<code>\glslongextraSymDescNameHeader</code>	79	<code>\glsseeitemformat</code>	31, 31
<code>\glslongextraSymDescNameTabularFooter</code>	80	<code>\glsseelastoxfordsep</code>	34
<code>\glslongextraSymDescNameTabularHeader</code>	79	<code>\glsseelist</code>	31, 34
<code>\glslongextraSymLocSetDescWidth</code>	75	<code>\glsseelistformat</code>	85
<code>\glslongextraSymSetDescWidth</code>	74	<code>\glssetattribute</code>	173
<code>\glslongextraTabularVAlign</code>	72	<code>\glssetcategoriesattribute</code>	173
<code>\glslongextraUpdateWidest</code>	73	<code>\glssetcategoriesattributes</code>	173
<code>\glslongextraUpdateWidestChild</code>	74	<code>\glssetcategoryattribute</code>	172
<code>\GlsLongExtraUseTabulartrue</code>	72	<code>\glssetcombinedsepabbrvnbs</code>	143
<code>\glslongfont</code>	118	<code>\glssetcombinedsepabbrvnone</code>	144
		<code>\glssetcombinedsepabbrvnone</code>	144
		<code>\glssetcombinedsepnarrow</code>	144
		<code>\glssetregularcategory</code>	173
		<code>\glssetwidest</code>	197
		<code>\glsshortpltok</code>	116
		<code>\glsshorttok</code>	92, 116
		<code>\glsshowtargetouter</code>	10
		<code>\Glstext</code>	48
		<code>\glstext</code>	45, 48, 85
		<code>\glstextformat</code>	35
		<code>\glstextup</code>	93
		<code>\glstopicAssignSubIndent</code>	83
		<code>\glstopicAssignWidest</code>	83
		<code>\glstopicCols</code>	81
		<code>\glstopicColsEnv</code>	81

<code>\glstopicDesc</code> .....	83	<code>\glxtrabbrvfootnote</code> .....	108
<code>\glstopicGroupHeading</code> .....	82	<code>\glxtrabbrvpluralsuffix</code> .....	42, 93
<code>\glstopicInit</code> .....	82	<code>\glxtrabbrvtype</code> .....	19
<code>\glstopicItem</code> .....	82	<code>\glxtractivatenopost</code> .....	244
<code>\glstopicLoc</code> .....	83	<code>\glxtraddallcrossrefs</code> .....	30
<code>\glstopicMarker</code> .....	82	<code>\glxtraddlabelprefix</code> .....	214
<code>\glstopicMidSkip</code> .....	83	<code>\glxtralias</code> .....	247
<code>\glstopicParIndent</code> .....	81	<code>\glxtrAltTreeIndent</code> .....	66
<code>\glstopicPostSkip</code> .....	83	<code>\glxtralttreeInit</code> .....	66
<code>\glstopicPreSkip</code> .....	82	<code>\glxtralttreeSubSymbolDescLocation</code> .....	65
<code>\glstopicSubIndent</code> .....	81	<code>\glxtralttreeSymbolDescLocation</code> ..	65
<code>\glstopicSubItem</code> .....	83	<code>\glxtrapptocsvfield</code> .....	226
<code>\glstopicSubItemBox</code> .....	84	<code>\GlsXtrAutoAddOnFormat</code> .....	24
<code>\glstopicSubItemParIndent</code> .....	82	<code>\glxtrautoindex</code> .....	187
<code>\glstopicSubItemSep</code> .....	84	<code>\glxtrautoindexassignsort</code> .....	187
<code>\glstopicSubLoc</code> .....	84	<code>\glxtrautoindexentry</code> .....	186
<code>\glstopicSubNameFont</code> .....	83	<code>\glxtrautoindexesc</code> .....	187
<code>\glstopicSubPreLocSep</code> .....	84	<code>\glxtrBasicDigitrules</code> .....	206
<code>\glstopicTitle</code> .....	82	<code>\GlsXtrBibTeXEntryAliases</code> .....	200
<code>\glstopicTitleFont</code> .....	83	<code>\glxtrbookindexatendgroup</code> .....	69
<code>\glstreechilddesc</code> .....	62	<code>\glxtrbookindexbetween</code> .....	69
<code>\glstreechildDescLoc</code> .....	63	<code>\glxtrbookindexbookmark</code> .....	70
<code>\glstreechildpredesc</code> .....	61	<code>\glxtrbookindexcols</code> .....	67
<code>\glstreechildprelocation</code> .....	62	<code>\glxtrbookindexcolspread</code> .....	67
<code>\glstreechildsymbol</code> .....	62	<code>\glxtrbookindexfirstmark</code> .....	71
<code>\glstreedefaultnamefmt</code> .....	60	<code>\glxtrbookindexfirstmarkfmt</code> .....	71
<code>\glstreedesc</code> .....	62	<code>\glxtrbookindexformatheader</code> .....	70
<code>\glstreeDescLoc</code> .....	62	<code>\glxtrbookindexlastmark</code> .....	71
<code>\glstreegroupheaderfmt</code> .....	60	<code>\glxtrbookindexlastmarkfmt</code> .....	71
<code>\glstreegroupskip</code> .....	61	<code>\glxtrbookindexlocation</code> .....	68
<code>\glstreeheadergroupskip</code> .....	61	<code>\glxtrbookindexmarkentry</code> .....	71
<code>\glstreenamefmt</code> .....	60	<code>\glxtrbookindexmulticolenv</code> .....	67
<code>\glstreenavigationfmt</code> .....	60	<code>\glxtrbookindexname</code> .....	68
<code>\glstreeNoDescSymbolPreLocation</code> ..	63	<code>\glxtrbookindexparentchildsep</code> ..	69
<code>\glstreenonamechilddesc</code> .....	62	<code>\glxtrbookindexparentschildsep</code> ..	69
<code>\glstreenonamedesc</code> .....	62	<code>\glxtrbookindexprelocation</code> .....	68
<code>\glstreenonamesymbol</code> .....	62	<code>\glxtrbookindexsubatendgroup</code> .....	69
<code>\glstreepredesc</code> .....	61	<code>\glxtrbookindexsubbetween</code> .....	69
<code>\glstreePreHeader</code> .....	61	<code>\glxtrbookindexsublocation</code> .....	69
<code>\glstreeprelocation</code> .....	62	<code>\glxtrbookindexsubname</code> .....	68
<code>\glstreesymbol</code> .....	62	<code>\glxtrbookindexsubprelocation</code> ..	68
<code>\glunsetcategoryattribute</code> .....	173	<code>\glxtrbookindexsubsubatendgroup</code> ..	69
<code>\glupdatewidest</code> .....	63	<code>\glxtrbookindexsubsubbetween</code> .....	69
<code>\gluseabbrvfont</code> .....	87	<code>\glxtrchecknohyperfirst</code> .....	166
<code>\gluselongfont</code> .....	87	<code>\glxtrclearlabelprefixes</code> .....	214
<code>\gluserdescription</code> .....	104	<code>\glxtrcombiningdiacriticIIIrules</code> ..	204
<code>\Glsxtr</code> .....	249	<code>\glxtrcombiningdiacriticIIrules</code> ..	204
<code>\glxtr</code> .....	248	<code>\glxtrcombiningdiacriticIrules</code> ..	204
<code>\glxtrabbreviationfont</code> .....	36	<code>\glxtrcombiningdiacriticIVrules</code> ..	205

<code>\glxtrcombingdiacriticrules</code>	204	<code>\glxtrfootnotedesname</code>	109
<code>\glxtrcontrolrules</code>	203	<code>\glxtrfootnotedesort</code>	109
<code>\glxtrcopytoglossary</code>	222	<code>\glxtrfootnotename</code>	108
<code>\glxtrcurrencyrules</code>	205	<code>\glxtrforcsvfield</code>	231
<code>\glxtrcurrentmglsname</code>	146	<code>\GlsXtrForeignText</code>	231
<code>\GlsXtrDefaultResourceOptions</code>	212	<code>\GlsXtrForeignTextField</code>	231
<code>\glxtrdeffield</code>	225	<code>\GlsXtrFormatLocationList</code>	56
<code>\glxtrdetoklocation</code>	218	<code>\GlsXtrForUnsetBufferedList</code>	40
<code>\glxtrdigitrules</code>	206	<code>\glxtrfractionrules</code>	206
<code>\GlsXtrDiscardUnsetBuffering</code>	41	<code>\GLSxtrfull</code>	90, 91, 118
<code>\glxtrdisplayendloc</code>	57	<code>\Glsxtrfull</code>	89, 91, 118
<code>\glxtrdisplayendloohook</code>	57	<code>\glxtrfull</code>	35, 38, 49, 86, 89, 90, 91, 118
<code>\glxtrdisplaylocnameref</code>	198	<code>\Glsxtrfullformat</code>	118
<code>\glxtrdisplaysingleloc</code>	57	<code>\glxtrfullformat</code>	92, 118
<code>\glxtrdisplaystartloc</code>	57	<code>\GLSxtrfullpl</code>	90, 91, 118
<code>\glxtrdisplaysuploc</code>	197	<code>\Glsxtrfullpl</code>	90, 91, 118
<code>\glxtrdoautoindexname</code>	55, 186	<code>\glxtrfullpl</code>	90, 91, 118
<code>\glxtrdownrglossaryhook</code>	27	<code>\Glsxtrfullplformat</code>	118
<code>\glxtredeffield</code>	226	<code>\glxtrfullplformat</code>	118
<code>\glxtremsuffix</code>	94	<code>\glxtrfullsep</code>	51, 97
<code>\GlsXtrEnableEntryCounting</code>	179	<code>\glxtrgenabbrfmt</code>	35, 91
<code>\GlsXtrEnableEntryUnitCounting</code>	179	<code>\glxtrGeneralLatinIIrules</code>	207
<code>\GlsXtrEnableIndexFormatOverride</code>	188	<code>\glxtrGeneralLatinIrules</code>	206
<code>\GlsXtrEnableInitialTagging</code>	87, 168	<code>\glxtrGeneralLatinIrules</code>	206
<code>\GlsXtrEnableLinkCounting</code>	169, 182	<code>\glxtrGeneralLatinIVrules</code>	207
<code>\GlsXtrEnableOnTheFly</code>	248, 256	<code>\glxtrGeneralLatinVIIrules</code>	207
<code>\GlsXtrEnablePreLocationTag</code>	56	<code>\glxtrGeneralLatinVIrules</code>	207
<code>\glxtrenablerecordcount</code>	220	<code>\glxtrGeneralLatinVrules</code>	207
<code>\glxtrendfor</code>	231	<code>\glxtrGeneralLatinVrules</code>	207
<code>\glxtrentryfmt</code>	224	<code>\glxtrgeneralpuncIrules</code>	206
<code>\GlsXtrExpandedFmt</code>	41	<code>\glxtrgeneralpuncIrules</code>	205
<code>\glxtrfielddolistloop</code>	230	<code>\glxtrgeneralpuncrules</code>	205
<code>\glxtrfieldforlistloop</code>	230	<code>\glxtrglossentry</code>	243
<code>\glxtrfieldformatcsvlist</code>	231	<code>\glxtrglossentryother</code>	245
<code>\glxtrfieldformatlist</code>	230	<code>\glxtrgroupfield</code>	234
<code>\glxtrfieldifinlist</code>	230	<code>\GLSxtrhiername</code>	33
<code>\glxtrfieldlistadd</code>	229	<code>\GLSxtrhiername</code>	33
<code>\glxtrfieldliststeadd</code>	230	<code>\GlsXtrhiername</code>	32
<code>\glxtrfieldlistgadd</code>	230	<code>\Glsxtrhiername</code>	32
<code>\glxtrfieldlistxadd</code>	230	<code>\glxtrhiername</code>	32, 32
<code>\glxtrfieldtitlecasecs</code>	169	<code>\glxtrhiernamesep</code>	32
<code>\glxtrfieldxifinlist</code>	231	<code>\glxtrhyphenrules</code>	205
<code>\glxtrfmt</code>	223	<code>\glxtrhyphensuffix</code>	95
<code>\glxtrfmt*</code>	224	<code>\glxtridentifyglslike</code>	213
<code>\GlsXtrFmtDefaultOptions</code>	223	<code>\glxtrifcounttrigger</code>	169, 178
<code>\glxtrfmtdisplay</code>	224	<code>\glxtrifcustomdiscardperiod</code>	36
<code>\glxtrfmtexternalnameref</code>	199	<code>\GlsXtrIfFieldCmpNum</code>	229
<code>\GlsXtrFmtField</code>	222	<code>\GlsXtrIfFieldEqNum</code>	229
<code>\glxtrfmtinternalnameref</code>	199	<code>\GlsXtrIfFieldEqStr</code>	227



<code>\GlsXtrIfFieldEqXpStr</code>	228	<code>\glsxtrLatinT</code>	208
<code>\GlsXtrIfFieldNonZero</code>	229	<code>\glsxtrLatinThorn</code>	209
<code>\GlsXtrIfFieldUndef</code>	227	<code>\glsxtrLatinWynn</code>	209
<code>\GlsXtrIfFieldValueInCsvList</code>	228	<code>\glsxtrLatinX</code>	208
<code>\glsxtrifhasfield</code>	226	<code>\GlsXtrLetField</code>	226
<code>\glsxtrifhasfield*</code>	227	<code>\GlsXtrLetFieldToField</code>	226
<code>\GlsXtrIfHasNonZeroChildCount</code>	200	<code>\GlsXtrLinkCounterName</code>	183
<code>\glsxtrifinlabelprefixlist</code>	214	<code>\GlsXtrLinkCounterValue</code>	183
<code>\glsxtrifkeydefined</code>	225	<code>\GlsXtrLoadResources</code>	191
<code>\glsxtriflabelinlist</code>	235	<code>\glsxtrlocalsetgrouptitle</code>	53
<code>\GlsXtrIfLinkCounterDef</code>	183	<code>\GlsXtrLocationField</code>	235
<code>\glsxtrifmulti</code>	161	<code>\GlsXtrLocationRecordCount</code>	219
<code>\glsxtrifnextpunc</code>	109	<code>\glsxtrlocrangefmt</code>	57
<code>\glsxtrifrecordtrigger</code>	219	<code>\GLSxtrlong</code>	91
<code>\GlsXtrIfUnusedOrUndefined</code>	39	<code>\Glsxtrlong</code>	89, 91
<code>\GlsXtrIfValueInFieldCsvList</code>	228	<code>\glsxtrlong</code>	35, 46, 49, 86, 89, 91, 99
<code>\glsxtrifwasfirstuse</code>	38, 39	<code>\glsxtrlonghyphen</code>	113
<code>\GlsXtrIfXpFieldEqXpStr</code>	228	<code>\glsxtrlonghyphenshort</code>	111
<code>\glsxtrinlinkcounter</code>	182	<code>\glsxtrlongnoshortdescname</code>	100
<code>\glsxtrinindexaliased</code>	247	<code>\glsxtrlongnoshortname</code>	101
<code>\GlsXtrIndexCounterLink</code>	196	<code>\GLSxtrlongpl</code>	90, 91
<code>\glsxtrinindexseealso</code>	34	<code>\Glsxtrlongpl</code>	90, 91
<code>\glsxtrinittwrgloss</code>	25, 27	<code>\glsxtrlongpl</code>	90, 91
<code>\Glsxtrinilinefullformat</code>	118	<code>\glsxtrlongshortdescname</code>	105
<code>\glsxtrinilinefullformat</code>	118	<code>\glsxtrlongshortdescsort</code>	105
<code>\Glsxtrinilinefullplformat</code>	118	<code>\glsxtrlongshortname</code>	102
<code>\glsxtrinilinefullplformat</code>	118	<code>\glsxtrlongshortuserdescname</code>	106
<code>\glsxtrininsertinsidettrue</code>	96	<code>\glsxtrMathGreekIIrules</code>	210
<code>\glsxtrLatinA</code>	207	<code>\glsxtrMathGreekIrules</code>	210
<code>\glsxtrLatinAA</code>	209	<code>\glsxtrMathItalicGreekIIrules</code>	210
<code>\glsxtrLatinAELigature</code>	209	<code>\glsxtrMathItalicGreekIrules</code>	210
<code>\glsxtrLatinE</code>	207	<code>\glsxtrMathItalicLowerGreekIIrules</code>	211
<code>\glsxtrLatinEszettSs</code>	208	<code>\glsxtrMathItalicLowerGreekIrules</code>	211
<code>\glsxtrLatinEszettSz</code>	209	<code>\glsxtrMathItalicNabla</code>	211
<code>\glsxtrLatinEth</code>	209	<code>\glsxtrMathItalicPartial</code>	211
<code>\glsxtrLatinH</code>	207	<code>\glsxtrMathItalicUpperGreekIIrules</code>	210
<code>\glsxtrLatinI</code>	208	<code>\glsxtrMathItalicUpperGreekIrules</code>	210
<code>\glsxtrLatinInsularG</code>	209	<code>\glsxtrMathUpGreekIIrules</code>	210
<code>\glsxtrLatinK</code>	208	<code>\glsxtrMathUpGreekIrules</code>	210
<code>\glsxtrLatinL</code>	208	<code>\GlsXtrMglsOrGls</code>	130
<code>\glsxtrLatinLslash</code>	209	<code>\glsxtrmglsWarnAllSkipped</code>	153
<code>\glsxtrLatinM</code>	208	<code>\GLSxtrmultientryadjustedname</code>	163
<code>\glsxtrLatinN</code>	208	<code>\GlsXtrmultientryadjustedname</code>	163
<code>\glsxtrLatinO</code>	208	<code>\Glsxtrmultientryadjustedname</code>	163
<code>\glsxtrLatinOELigature</code>	209	<code>\glsxtrmultientryadjustedname</code>	163
<code>\glsxtrLatinOslash</code>	209	<code>\GLSxtrmultientryadjustednamefmt</code>	164
<code>\glsxtrLatinP</code>	208	<code>\GlsXtrmultientryadjustednamefmt</code>	164
<code>\glsxtrLatinS</code>	208	<code>\Glsxtrmultientryadjustednamefmt</code>	163
<code>\glsxtrLatinSchwa</code>	209	<code>\glsxtrmultientryadjustednamefmt</code>	163

<code>\GLSxtrmultientryadjustednameother</code>	164	<code>\glsxtrpl</code>	249
<code>\GlsXtrmultientryadjustednameother</code>	164	<code>\glsxtrpostdescription</code>	55
<code>\Glsxtrmultientryadjustednameother</code>	164	<code>\glsxtrposthyphenlong</code>	114
<code>\glsxtrmultientryadjustednameother</code>	164	<code>\glsxtrposthyphenshort</code>	113
<code>\glsxtrmultientryadjustednamepostsep</code>		<code>\glsxtrpostlink</code>	36
.....	163	<code>\glsxtrpostlinkAddDescOnFirstUse</code>	37
<code>\glsxtrmultientryadjustednamepresep</code>	163	<code>\glsxtrpostlinkAddSymbolDescOnFirstUse</code>	
<code>\glsxtrmultientryadjustednamesep</code>	163	.....	38
<code>\glsxtrmultilastotherindex</code>	162	<code>\glsxtrpostlinkAddSymbolOnFirstUse</code>	38
<code>\glsxtrmultilist</code>	161	<code>\glsxtrpostlink&lt;category&gt;</code>	37, 109
<code>\glsxtrmultimain</code>	161	<code>\glsxtrpostlinkendsentence</code>	36
<code>\glsxtrmultimainindex</code>	162	<code>\glsxtrpostlinkhook</code>	36
<code>\glsxtrmultisupplocation</code>	197	<code>\glsxtrpostlongdescription</code>	23
<code>\glsxtrmultitotalelements</code>	162	<code>\glsxtrpostnamehook</code>	54, 186
<code>\glsxtrnameloclink</code>	199	<code>\GlsXtrPostNewAbbreviation</code>	115
<code>\glsxtrnamereflink</code>	199	<code>\glsxtrprelocation</code>	59
<code>\glsxtrnewgls</code>	212	<code>\glsxtrprependlabelprefix</code>	214
<code>\glsxtrnewGLSlike</code>	213	<code>\GlsXtrProvideBibTeXFields</code>	200
<code>\glsxtrnewglslike</code>	213	<code>\glsxtrprovidecommand</code>	196
<code>\glsxtrnewnumber</code>	20, 21, 165	<code>\glsxtrprovidestoragekey</code>	225
<code>\glsxtrnewrgls</code>	213	<code>\GlsXtrRecordCount</code>	218
<code>\glsxtrnewrglslike</code>	213	<code>\GlsXtrRecordCounter</code>	232
<code>\glsxtrnewrglslike</code>	213	<code>\glsxtrrecordtriggervalue</code>	220
<code>\glsxtrnewsymbol</code>	19, 21, 165	<code>\glsxtrregularfont</code>	35
<code>\GlsXtrNoGlsWarningAutoMake</code>	261	<code>\glsxtrresourcefile</code>	191
<code>\GlsXtrNoGlsWarningBuildInfo</code>	261	<code>\glsxtrresourceinit</code>	211
<code>\GlsXtrNoGlsWarningCheckFile</code>	260	<code>\glsxtrrestorepostpunc</code>	22
<code>\GlsXtrNoGlsWarningEmptyMain</code>	259	<code>\glsxtrRevertMarks</code>	122
<code>\GlsXtrNoGlsWarningEmptyNotMain</code>	260	<code>\glsxtrRevertTocMarks</code>	122
<code>\GlsXtrNoGlsWarningEmptyStart</code>	259	<code>\glsxtrsconlydescname</code>	103
<code>\GlsXtrNoGlsWarningHead</code>	259	<code>\glsxtrsconlydescsort</code>	103
<code>\GlsXtrNoGlsWarningMisMatch</code>	260	<code>\glsxtrsconlyname</code>	103
<code>\GlsXtrNoGlsWarningNoOut</code>	260	<code>\glsxtrsconlysuffix</code>	96
<code>\GlsXtrNoGlsWarningTail</code>	260	<code>\glsxtrscsuffix</code>	93, 96
<code>\glsxtrnonprintablerules</code>	204	<code>\glsxtrscusersuffix</code>	96
<code>\glsxtrnopostpunc</code>	22, 244	<code>\glsxtrseealsolabels</code>	34
<code>\glsxtronlydescname</code>	103	<code>\glsxtrseelist</code>	34
<code>\glsxtronlydescsort</code>	103	<code>\GlsXtrSetActualChar</code>	188
<code>\glsxtronlyname</code>	102	<code>\glsxtrsetaliasnoindex</code>	247
<code>\glsxtronlysuffix</code>	96	<code>\GlsXtrSetAltModifier</code>	27, 130
<code>\glsxtrorglong</code>	116	<code>\glsxtrsetcategory</code>	175
<code>\glsxtrorgshort</code>	116	<code>\glsxtrsetcategoryforall</code>	175
<code>\GLSxtrp</code>	48	<code>\GlsXtrSetDefaultGlsOpts</code>	25, 26, 247
<code>\Glsxtrp</code>	48	<code>\GlsXtrSetEncapChar</code>	188
<code>\glsxtrp</code>	46	<code>\GlsXtrSetEscChar</code>	188
<code>\glsxtrpageref</code>	222	<code>\GlsXtrSetField</code>	225
<code>\glsxtrparen</code>	92, 104	<code>\glsxtrsetfieldifexists</code>	225
<code>\glsxtrpdfentryfmt</code>	224	<code>\glsxtrsetglossarylabel</code>	52
<code>\Glsxtrpl</code>	249	<code>\glsxtrsetgrouptitle</code>	53



memoir class	7, 8	\Mglslong	157
mfistuc package	1, 169	\mglslong	157
\MGLS	156	\MGLSmainpl	157
\MGLs	156	\MGLsmainpl	156
\Mgls	156	\Mglsmainpl	156
\mgls	128	\mglsmainpl	156
\mglscurrentcategory	145	\MGLsname	157
\mglscurrentlabel	146	\Mglsname	158
\mglscurrentlist	145	\mglsname	157
\mglscurrentmainlabel	145	\MGLSpl	156
\mglscurrentmultilabel	145	\MGLspl	156
\mglscurrentoptions	145	\Mglspl	156
\mglscurrentprefix	146	\mglspl	156
\mglscurrentsuffix	146	\mglsprefix	140
\mglscustompostlinkhook	147	\mglsreset	149
\mglsdefcategoryprefix	141	\mglsresetall	150
\mglsdefcategorysuffix	141	\mglsseefirstitem	160
\mglselementindex	146	\mglsseeitem	161
\mglselementposthook	145	\mglsSetMain	139
\mglselementprehook	145	\mglsSetOptions	129
\mglselementreset	155	\Mglsshort	157
\mglselementunset	155	\mglsshort	157
\mglsfield	158	\mglsuffix	140, 147
\mglsforelements	161	\MGLssymbol	158
\mglsforotherelements	162	\Mglsymbol	158
\Mglsfull	157	\mglsymbol	158
\mglsfull	157	\mglsunset	149
\mglschascategoryprefix	141	\mglsunsetall	150
\mglschascategorysuffix	141	\mglsunsetothers	155
\mglsiflast	146	\mglsusecategoryprefix	141
\mglsiflastelementcapscase	148	\mglsusecategorysuffix	141
\mglsiflastelementskipped	148	\MGLsusefield	158
\mglsiflastelementwasfirstuse	148	\Mglsusefield	158
\mglsiflastelementwasplural	148	\mglsusefield	158
\mglsiflastmaincapscase	149	\mglswasfirstuse	147
\mglsiflastmainskipped	148	\MPGLS	160
\mglsiflastmainwasfirstuse	148	\MPGLs	160
\mglsiflastmainwasplural	149	\Mpgls	159
\mglsisfirstuse	146	\mpgls	159
\mglslastcategory	147	\MPGLSmainpl	160
\mglslastcustompostlinkhook	152	\MPGLsmainpl	160
\mglslastelementlabel	141, 147	\Mpglsmainpl	160
\mglslastelementpostlinkhook	147, 152	\mpglsmainpl	159
\mglslastmainlabel	148	\MPGLSpl	160
\mglslastmainpostlinkhook	147, 152	\MPGLspl	160
\mglslastmultilabel	147	\mpglspl	159
\mglslocalreset	149	\mpglsWarning	159
\mglslocalunset	149	\Mu	201
\mglslocalunsetothers	155	multicols (environment)	67, 81

multicols package	81	sort	17, 19, 43, 46, 92, 100–102, 105, 106, 109, 110, 115, 116, 167, 168, 186, 187, 191, 243
multicols* (environment)	67	symbol	23, 54, 158, 227, 252
\multiglossaryentry	128	symbolaccess	54
\multiglossaryentryglobalfalse	129	symbolplural	252
\multiglossaryentryglobaltrue	129	text	31, 32, 35, 42, 43, 92, 115, 125, 144, 161, 225, 251, 252
\multiglossaryentrysetup	150	textaccess	172
<b>N</b>			
\newabbr	91	type	50, 165, 200, 242, 244
\newabbreviation	86, 91, 116, 117, 165, 167, 168, 171, 251	user1	54, 97, 98, 131, 158, 159, 166
\newabbreviationstyle	51, 114	user2	158
\newacronym	7, 19, 23, 49, 51, 86, 86, 115	\newignoredglossary	51, 171
\newacronymstyle	51, 114	\newnum	21
\newentry	21	\newsym	21
\newglossaryentry	17, 21, 165, 249, 262	\newterm	23, 165
\newglossaryentry options		\nopostdesc	22, 244
access	172	\Nu	201
alias	22, 33, 129, 161, 246, 247, 256	number list	11, 12, 16, 17, 26, 31, 33, 56, 59–61, 65, 131, 233, 235, 256, 262, 262
category	22, 26, 86, 165, 242	<b>O</b>	
counter	28	\Omicron	201
description	22, 23, 98–102, 104–110, 115, 193, 253	\omicron	201
descriptionplural	23, 253	<b>P</b>	
first	35, 42, 43, 91, 92, 115, 126, 144, 187, 252, 262	package options:	
firstaccess	172	abbreviations	18, 19, 21, 258
firstplural	35, 42, 115, 252, 262	accsupp	12, 171, 172, 245, 250
group	52, 195, 233, 234	acronym	19, 20
location	68, 196, 198, 235	acronymlists	19, 87
loclist	198, 235	acronyms	20
long	23, 42, 86, 92, 144, 157, 166, 187, 253	automake	24, 261
longplural	42, 86, 116, 253, 254	autoseeindex	13
name	31, 32, 42, 43, 54, 92, 99–115, 125, 161– 163, 172, 186, 187, 233, 244, 248, 251, 256	false	13
nameshortaccess	172	colorlinks	134
parent	64, 129, 187, 225, 242	counter	
plural	35, 42, 115, 225, 252	chapter	14
prefix	52	equation	14
see	13, 14, 22, 30, 31, 33, 34, 129, 160, 193, 234, 246	section	14
seealso	13, 22, 33–35, 129, 160	wrglossary	16
short	23, 32, 35, 42, 43, 86, 92, 144, 157, 161, 166, 168, 172, 253	debug	10
shortaccess	171, 172	all	10
shortplural	42, 43, 86, 93, 116, 117, 168, 253	showtargets	10
shortpluralaccess	172	showwrgloss	10
		true	10
		docdef	17, 21, 24, 161
		atom	18
		false	17
		restricted	17, 18

true	17, 18, 129, 161, 162
docdefs	234, 248
true	17
entrycounter	222, 244
equations	15, 28
true	14
floats	15
hyperfirst	
false	166
index	20, 23, 165
indexcounter	14, 16, 197
indexcrossrefs	12, 13, 30
false	13
indexonlyfirst	25, 166, 188
makeindex	198
nogroupskip	59–61, 81
nomain	9
nomissinggglstext	18
nonumberlist	33, 56, 76, 262
nopostdot	11, 56, 59
false	6, 11, 55
true	6
noredefwarn	
false	6
true	6
notree	63
numbers	20, 21, 165
postdot	6, 11
postpunc	11
comma	11
dot	11
none	11
prefix	12, 159
record	13,
39, 67, 190, 191, 196, 232–234, 238, 258	
hybrid	10, 15, 23, 190, 196, 238, 246
nameref	13, 15, 163, 197, 198
off	23, 246
only	13–15, 23, 163, 196, 234, 246, 247
savenumberlist	196
section	
chapter	70
seeautonumberlist	33
seenoindex	30
ignore	30, 234
warn	234
shortcuts	20, 21, 49
abbr	21, 91
abbreviations	21, 91
ac	20, 21, 49, 91, 176
acro	20, 176
acronyms	20, 176
all	21, 176
false	21
none	21
other	21
true	21
showtargets	10
annoteleft	138
sort	
none	14, 243
stylemods	12, 53, 58, 67
all	12
default	12
subentrycounter	222, 244
symbols	19, 21, 165
toc	
false	6
true	6
translate	
babel	6
true	6
undefaction	12, 22
error	12, 14, 39
warn	12, 14, 17, 39, 191, 224, 225
writetgllabelnames	18
writetgllabels	18
xindy	34, 186
page (counter)	14, 16, 180, 182, 199
\pagelistname	72
\pageref	222
\parindent	82
polyglossia package	231, 258
\pretoglossarypreamble	222
\printabbreviations	18
\printglossaries	8, 9
\printglossary	8, 14, 52, 248
\printglossary options	
label	52, 240
nogroupskip	59
numberedsection	240
prefix	52
style	240
target	52, 222
targetnameprefix	52
title	240, 258
toctitle	240
type	239

<code>\printnoidxglossary</code> .....	52		
<code>\printnoidxglossary options</code>			
<code>sort</code> .....	234		
<code>\printunsrtabbreviations</code> .....	19, 196		
<code>\printunsrtacronyms</code> .....	20, 196		
<code>\printunsrtglossaries</code> .....	234		
<code>\printunsrtglossary</code> ....	19, 20, 196, 233		
<code>\printunsrtglossary options</code>			
<code>groups</code> .....	52, 233		
<code>leveloffset</code> .....	52		
<code>\printunsrtglossary*</code> .....	233		
<code>\printunsrtglossaryentryprocesshook</code>	234		
<code>\printunsrtglossaryhandler</code> ...	235, 239		
<code>\printunsrtglossarypredoglossary</code> ..	235		
<code>\printunsrtglossaryskipentry</code> .....	235		
<code>\printunsrtglossaryunit</code> .....	237		
<code>\printunsrtglossaryunitsetup</code> .....	237		
<code>printunsrtglossarywrap (environment)</code> .			
.....	239, 240		
<code>\printunsrtindex</code> .....	20, 196		
<code>\printunsrtinnerglossary</code> .....	240		
<code>\printunsrtnumbers</code> .....	20, 196		
<code>\printunsrtsymbols</code> .....	19, 196		
<code>\provideignoredglossary</code> .....	52		
<code>\providemultiglossaryentry</code> .....	128		
		<b>Q</b>	
<code>\quotechar</code> .....	188		
		<b>R</b>	
<code>\ref</code> .....	222		
<code>relsize package</code> .....	93		
<code>\RestoreAcronyms</code> .....	50, 88, 115		
<code>\rGLS</code> .....	219		
<code>\rGls</code> .....	219		
<code>\rgls</code> .....	219		
<code>\rGLSformat</code> .....	220		
<code>\rGlsformat</code> .....	220		
<code>\rglsformat</code> .....	220		
<code>\rGLSpl</code> .....	219		
<code>\rGlspl</code> .....	219		
<code>\rglspl</code> .....	219		
<code>\rGLSplformat</code> .....	220		
<code>\rGlsplformat</code> .....	220		
<code>\rglsplformat</code> .....	220		
<code>\Rho</code> .....	201		
		<b>S</b>	
<code>\seealsoname</code> .....	34		
<code>\setabbreviationstyle</code> .....	88, 114		
<code>\setacronymstyle</code> .....	88		
<code>\setupglossaries</code> .....	10		
<code>slantsc package</code> .....	123		
<code>soul package</code> .....	26, 39		
<code>style package</code> .....	67		
<code>subentrycounter package</code> .....	245		
<code>\symbolname</code> .....	72		
		<b>T</b>	
<code>table (environment)</code> .....	15		
<code>tabular (environment)</code> .....	59, 72, 77–80, 233, 234		
<code>\Tau</code> .....	201		
<code>texindy</code> .....	186		
<code>\texorpdfstring</code> .....	54, 122		
<code>textcase package</code> .....	1		
<code>\textsc</code> .....	92, 121, 123		
<code>\textsmaller</code> .....	44		
<code>\the</code> .....	92		
<code>theglossary (environment)</code> .....	6, 239, 240		
<code>theindex (environment)</code> .....	188		
<code>tracklang package</code> ...	1, 192, 201, 202, 231, 258		
<code>translator package</code> .....	6		
		<b>U</b>	
<code>\underline</code> .....	87		
<code>\upalpha</code> .....	210		
<code>upgreek package</code> .....	201, 210		
		<b>W</b>	
<code>wrglossary (counter)</code> .....	16, 17		
<code>\writemultiglossentry</code> .....	162		
		<b>X</b>	
<code>xfor package</code> .....	1, 161, 231		
<code>\xglsetwidest</code> .....	63		
<code>\xglupdatewidest</code> .....	64		
<code>\xGlsXtrIfValueInFieldCsvList</code> .....	228		
<code>\xGlsXtrSetField</code> .....	226		
<code>xindy</code> 8, 10, 14–18, 186, 190, 196, 198, 262, 262			
<code>xindy</code> .....	29		
<code>xkeyval package</code> .....	1		
		<b>Z</b>	
<code>\Zeta</code> .....	201		