

# Package ‘GenomicDataCommons’

April 15, 2020

**Type** Package

**Title** NIH / NCI Genomic Data Commons Access

**Description** Programmatically access the NIH / NCI Genomic Data Commons RESTful service.

**Version** 1.10.0

**Date** 2018-11-08

**License** Artistic-2.0

**Depends** R (>= 3.4.0), magrittr

**Imports** stats, httr, xml2, jsonlite, utils, rlang, readr,  
GenomicRanges, IRanges, dplyr, rappdirs, SummarizedExperiment,  
S4Vectors, tibble

**Suggests** BiocStyle, knitr, rmarkdown, DT, testthat, listviewer,  
ggplot2, GenomicAlignments, Rsamtools

**biocViews** DataImport, Sequencing

**URL** <https://bioconductor.org/packages/GenomicDataCommons>,  
<http://github.com/Bioconductor/GenomicDataCommons>

**BugReports** <https://github.com/Bioconductor/GenomicDataCommons/issues/new>

**VignetteBuilder** knitr

**RoxygenNote** 6.1.0

**git\_url** <https://git.bioconductor.org/packages/GenomicDataCommons>

**git\_branch** RELEASE\_3\_10

**git\_last\_commit** 75d565f

**git\_last\_commit\_date** 2019-10-29

**Date/Publication** 2020-04-14

**Author** Martin Morgan [aut],  
Sean Davis [aut, cre]

**Maintainer** Sean Davis <seandavi@gmail.com>

**R topics documented:**

.htseq_importer . . . . .	2
aggregations . . . . .	3
available_expand . . . . .	3
available_fields . . . . .	4
available_rnaseq_workflows . . . . .	5
available_values . . . . .	6
count . . . . .	7
default_fields . . . . .	7
entity_name . . . . .	8
expand . . . . .	9
facet . . . . .	10
filtering . . . . .	11
gdcdata . . . . .	12
gdc_cache . . . . .	14
gdc_client . . . . .	15
gdc_clinical . . . . .	15
gdc_token . . . . .	16
GenomicDataCommons . . . . .	17
grep_fields . . . . .	18
ids . . . . .	19
id_field . . . . .	19
make_filter . . . . .	20
manifest . . . . .	21
mapping . . . . .	22
query . . . . .	22
readDNACopy . . . . .	24
readHTSeqFile . . . . .	24
response . . . . .	25
results . . . . .	26
results_all . . . . .	27
select . . . . .	27
slicing . . . . .	28
status . . . . .	29
transfer . . . . .	30
write_manifest . . . . .	31

<b>Index</b>	<b>32</b>
--------------	-----------

---

.htseq_importer	<i>Import multiple files of HTSeq-counts format</i>
-----------------	---

---

**Description**

Import multiple files of HTSeq-counts format

**Usage**

```
.htseq_importer(fnames)
```

---

aggregations	<i>aggregations</i>
--------------	---------------------

---

### Description

aggregations

### Usage

```
aggregations(x)
```

```
## S3 method for class 'GDCQuery'
aggregations(x)
```

```
## S3 method for class 'GDCResponse'
aggregations(x)
```

### Arguments

x                    a [GDCQuery](#) object

### Value

a list of data.frame with one member for each requested facet. The data frames each have two columns, key and doc\_count.

### Methods (by class)

- GDCQuery:
- GDCResponse:

### Examples

```
library(magrittr)
# Number of each file type
res = files() %>% facet(c('type','data_type')) %>% aggregations()
res$type
```

---

available_expand	<i>Return valid values for "expand"</i>
------------------	---

---

### Description

The GDC allows a shorthand for specifying groups of fields to be returned by the metadata queries. These can be specified in a [select](#) method call to easily supply groups of fields.

**Usage**

```
available_expand(entity)

## S3 method for class 'character'
available_expand(entity)

## S3 method for class 'GDCQuery'
available_expand(entity)
```

**Arguments**

entity Either a [GDCQuery](#) object or a character(1) specifying a GDC entity ('cases', 'files', 'annotations', 'projects')

**Value**

A character vector

**See Also**

See [https://docs.gdc.cancer.gov/API/Users\\_Guide/Search\\_and\\_Retrieval/#expand](https://docs.gdc.cancer.gov/API/Users_Guide/Search_and_Retrieval/#expand) for details

**Examples**

```
head(available_expand('files'))
```

---

available_fields	<i>S3 Generic to return all GDC fields</i>
------------------	--

---

**Description**

S3 Generic to return all GDC fields

**Usage**

```
available_fields(x)

## S3 method for class 'GDCQuery'
available_fields(x)

## S3 method for class 'character'
available_fields(x)
```

**Arguments**

x A character(1) string ('cases', 'files', 'projects', 'annotations') or an subclass of [GDCQuery](#).

**Value**

a character vector of the default fields

**Methods (by class)**

- GDCQuery: GDCQuery method
- character: character method

**Examples**

```
available_fields('projects')
projQuery = query('projects')
available_fields(projQuery)
```

---

available\_rnaseq\_workflows

*Get RNA-seq quantification from the NCI GDC.*

---

**Description**

gdc\_rnaseq is a high-level function for accessing the NCI GDC RNA-seq data and summarizing as a [SummarizedExperiment](#).

**Usage**

```
available_rnaseq_workflows()

gdc_rnaseq(project_id, workflow_type)
```

**Arguments**

project_id	character() vector with one or more project ids. Available project_ids can be found using <code>ids(projects())</code> . Note that not all projects contain RNA-seq data.
workflow_type	character(1) with the workflow type. Possible values can be accessed using <code>available_rnaseq_workflows</code>

**Details**

The RNA-seq data are downloaded using [gdcdata](#) with caching used as available. The resulting files are read and combined without any transformation. It is up to the user to perform further normalization or transformation if needed.

Clinical information for each file (see [gdc\\_clinical](#) for details) is loaded into the `colData` slot. Quality control mapping information is also stored in the `colData` with column names beginning with "qc\_\_".

**Value**

a `SummarizedExperiment` object, populated with the expression values, the gene ids in the `rowData`, and the clinical data associated with each sample in the `colData`.

## Functions

- available\_rnaseq\_workflows: Show possible RNA-seq workflow types

## References

See [https://docs.gdc.cancer.gov/Data/Bioinformatics\\_Pipelines/Expression\\_mRNA\\_Pipeline/](https://docs.gdc.cancer.gov/Data/Bioinformatics_Pipelines/Expression_mRNA_Pipeline/) for details of data processing that occurs at the GDC.

## Examples

```
available_rnaseq_workflows()

## Not run:
tcga_se = gdc_rnaseq('TCGA-ACC', 'HTSeq - Counts')
tcga_se

## End(Not run)
```

---

available_values	<i>Find common values for a GDC field</i>
------------------	---

---

## Description

Find common values for a GDC field

## Usage

```
available_values(entity, field, legacy = FALSE)
```

## Arguments

entity	character(1), a GDC entity ("cases", "files", "annotations", "projects")
field	character(1), a field that is present in the entity record
legacy	logical(1), use the legacy endpoint or not.

## Value

character vector of the top 100 (or fewer) most frequent values for a the given field

## Examples

```
available_values('files', 'cases.project.project_id')[1:5]
```

---

count	<i>provide count of records in a <a href="#">GDCQuery</a></i>
-------	---

---

### Description

provide count of records in a [GDCQuery](#)

### Usage

```
count(x, ...)
```

```
## S3 method for class 'GDCQuery'  
count(x, ...)
```

```
## S3 method for class 'GDCResponse'  
count(x, ...)
```

### Arguments

x	a <a href="#">GDCQuery</a> object
...	passed to htrr (good for passing config info, etc.)

### Value

integer(1) representing the count of records that will be returned by the current query

### Methods (by class)

- [GDCQuery](#):
- [GDCResponse](#):

### Examples

```
# total number of projects  
projects() %>% count()
```

```
# total number of cases  
cases() %>% count()
```

---

default_fields	<i>S3 Generic to return default GDC fields</i>
----------------	--

---

### Description

S3 Generic to return default GDC fields

**Usage**

```
default_fields(x)

## S3 method for class 'character'
default_fields(x)

## S3 method for class 'GDCQuery'
default_fields(x)
```

**Arguments**

x                    A character string ('cases', 'files', 'projects', 'annotations') or an subclass of [GDCQuery](#).

**Value**

a character vector of the default fields

**Methods (by class)**

- character: character method
- GDCQuery: GDCQuery method

**Examples**

```
default_fields('projects')
projQuery = query('projects')
default_fields(projQuery)
```

---

entity\_name

*Get the entity name from a GDCQuery object*

---

**Description**

An "entity" is simply one of the four metadata endpoints.

- cases
- projects
- files
- annotations

All [GDCQuery](#) objects will have an entity name. This S3 method is simply a utility accessor for those names.

**Usage**

```
entity_name(x)

## S3 method for class 'GDCQuery'
entity_name(x)

## S3 method for class 'GDCResults'
entity_name(x)
```



**Arguments**

x                    a [GDCQuery](#) object

**Value**

character(1) name of an associated entity; one of "cases", "files", "projects", "annotations".

**Examples**

```

qcases = cases()
qprojects = projects()

entity_name(qcases)
entity_name(qprojects)

```

---

expand	<i>Set the expand parameter</i>
--------	---------------------------------

---

**Description**

S3 generic to set GDCQuery expand parameter

**Usage**

```

expand(x, expand)

## S3 method for class 'GDCQuery'
expand(x, expand)

```

**Arguments**

x                    the objects on which to set fields  
expand                a character vector specifying the fields

**Value**

A [GDCQuery](#) object, with the expand member altered.

**Methods (by class)**

- GDCQuery: set expand fields on a GDCQuery object

**Examples**

```

gProj = projects()
gProj$fields
head(available_fields(gProj))
default_fields(gProj)

gProj %>%
  select(default_fields(gProj)[1:2]) %>%
  response() %>%

```

```
str(max_level=2)
```

---

facet

*Set facets for a [GDCQuery](#)*

---

## Description

Set facets for a [GDCQuery](#)

Get facets for a [GDCQuery](#)

## Usage

```
facet(x, facets)
```

```
get_facets(x)
```

```
## S3 method for class 'GDCQuery'  
get_facets(x)
```

## Arguments

x a [GDCQuery](#) object

facets a character vector of fields that will be used for forming aggregations (facets). Default is to set facets for all default fields. See [default\\_fields](#) for details

## Value

returns a [GDCQuery](#) object, with facets field updated.

## Examples

```
# create a new GDCQuery against the projects endpoint  
gProj = projects()  
  
# default facets are NULL  
get_facets(gProj)  
  
# set facets and save result  
gProjFacet = facet(gProj)  
  
# check facets  
get_facets(gProjFacet)  
  
# and get a response, noting that  
# the aggregations list member contains  
# tibbles for each facet  
str(response(gProjFacet, size=2), max.level=2)
```

---

filtering

*Manipulating GDCQuery filters*

---

## Description

Manipulating GDCQuery filters

The filter is simply a safe accessor for the filter element in [GDCQuery](#) objects.

The `get_filter` is simply a safe accessor for the filter element in [GDCQuery](#) objects.

## Usage

```
filter(x, expr)
```

```
## S3 method for class 'GDCQuery'
```

```
filter(x, expr)
```

```
get_filter(x)
```

```
## S3 method for class 'GDCQuery'
```

```
get_filter(x)
```

## Arguments

`x` the object on which to set the filter list member

`expr` a filter expression in the form of the right hand side of a formula, where bare names (without quotes) are allowed if they are available fields associated with the GDCQuery object, `x`

## Value

A [GDCQuery](#) object with the filter field replaced by specified filter expression

## Examples

```
# make a GDCQuery object to start
#
# Projects
#
pQuery = projects()

# check for the default fields
# so that we can use one of them to build a filter
default_fields(pQuery)
pQuery = filter(pQuery, ~ project_id == 'TCGA-LUAC')
get_filter(pQuery)

#
# Files
#
fQuery = files()
default_fields(fQuery)
```

```

fQuery = filter(fQuery, ~ data_format == 'VCF')
# OR
# with recent GenomicDataCommons versions:
# no "~" needed
fQuery = filter(fQuery, data_format == 'VCF')

get_filter(fQuery)

fQuery = filter(fQuery, ~ data_format == 'VCF'
                & experimental_strategy == 'WXS'
                & type == 'simple_somatic_mutation')

files() %>% filter(~ data_format == 'VCF'
                  & experimental_strategy == 'WXS'
                  & type == 'simple_somatic_mutation') %>% count()

files() %>% filter( data_format == 'VCF'
                   & experimental_strategy == 'WXS'
                   & type == 'simple_somatic_mutation') %>% count()

# Filters may be chained for the
# equivalent query
#
# When chained, filters are combined with logical AND

files() %>%
  filter(~ data_format == 'VCF') %>%
  filter(~ experimental_strategy == 'WXS') %>%
  filter(~ type == 'simple_somatic_mutation') %>%
  count()

# OR

files() %>%
  filter( data_format == 'VCF') %>%
  filter( experimental_strategy == 'WXS') %>%
  filter( type == 'simple_somatic_mutation') %>%
  count()

# Use str() to get a cleaner picture
str(get_filter(fQuery))

```

---

gdcdata

[Download GDC files](#)


---

## Description

Download one or more files from GDC. Files are downloaded using the UUID and renamed to the file name on the remote system. By default, neither the uuid nor the file name on the remote system can exist.

## Usage

```

gdcdata(uuids, use_cached = TRUE, progress = interactive(),
        token = NULL, access_method = "api", transfer_args = character())

```

**Arguments**

uuids	character() of GDC file UUIDs.
use_cached	logical(1) default TRUE indicating that, if found in the cache, the file will not be downloaded again. If FALSE, all supplied uuids will be re-downloaded.
progress	logical(1) default TRUE in interactive sessions, FALSE otherwise indicating whether a progress bar should be produced for each file download.
token	(optional) character(1) security token allowing access to restricted data. See <a href="https://gdc-docs.nci.nih.gov/API/Users_Guide/Authentication_and_Authorization/">https://gdc-docs.nci.nih.gov/API/Users_Guide/Authentication_and_Authorization/</a> .
access_method	character(1), either 'api' or 'client'. See details.
transfer_args	character(1), additional arguments to pass to the gdc-client command line. See <a href="#">gdc_client</a> and <a href="#">transfer_help</a> for details.

**Details**

This function is appropriate for one or several files; for large downloads use [manifest](#) to create a manifest for and the GDC Data Transfer Tool.

When `access_method` is "api", the GDC "data" endpoint is the transfer mechanism used. The alternative `access_method`, "client", will utilize the `gdc-client` transfer tool, which must be downloaded separately and available. See [gdc\\_client](#) for details on specifying the location of the `gdc-client` executable.

**Value**

a named vector with file uuids as the names and paths as the value

**See Also**

[manifest](#) for downloading large data.

**Examples**

```
# get some example file uuids
uuids <- files() %>%
  filter(~ access == 'open' & file_size < 100000) %>%
  results(size = 3) %>%
  ids()

# and get the data, placing it into the gdc_cache() directory
fpaths <- gdcdata(uuids, use_cached=TRUE)

fpaths
```

---

`gdc_cache`*Work with gdc cache directory*

---

## Description

The GenomicDataCommons package will cache downloaded files to minimize network and allow for offline work. These functions are used to create a cache directory if one does not exist, set a global option, and query that option. The cache directory will default to the user "cache" directory according to specifications in `app_dir`. However, the user may want to set this to another directory with more or higher performance storage.

## Usage

```
gdc_cache()
```

```
gdc_set_cache(directory = rappdirs::app_dir(appname =  
  "GenomicDataCommons")$cache(), verbose = TRUE,  
  create_without_asking = !interactive())
```

## Arguments

<code>directory</code>	character(1) directory path, will be created recursively if not present.
<code>verbose</code>	logical(1) whether or not to message the location of the cache directory after creation.
<code>create_without_asking</code>	logical(1) specifying whether to allow the function to create the cache directory without asking the user first. In an interactive session, if the cache directory does not exist, the user will be prompted before creation.

## Details

The cache structure is currently just a directory with each file being represented by a path constructed as: CACHEDIR/UUID/FILENAME. The cached files can be manipulated using standard file system commands (removing, finding, etc.). In this sense, the cache system is minimalist in design.

## Value

character(1) directory path that serves as the base directory for GenomicDataCommons downloads.  
the created directory (invisibly)

## Functions

- `gdc_set_cache`: (Re)set the GenomicDataCommons cache directory

## Examples

```
gdc_cache()  
## Not run:  
gdc_set_cache(getwd())  
  
## End(Not run)
```

---

gdc_client	<i>return gdc-client executable path</i>
------------	--

---

### Description

This function is a convenience function to find and return the path to the GDC Data Transfer Tool executable assumed to be named 'gdc-client'. The assumption is that the appropriate version of the GDC Data Transfer Tool is a separate download available from <https://gdc.cancer.gov/access-data/gdc-data-transfer-tool> and as a backup from <https://github.com/NCI-GDC/gdc-client>.

### Usage

```
gdc_client()
```

### Details

The path is checked in the following order:

1. an R option("gdc\_client")
2. an environment variable GDC\_CLIENT
3. from the search PATH
4. in the current working directory

### Value

character(1) the path to the gdc-client executable.

### Examples

```
# this cannot run without first
# downloading the GDC Data Transfer Tool
gdc_client = try(gdc_client(),silent=TRUE)
```

---

gdc_clinical	<i>Get clinical information from GDC</i>
--------------	--

---

### Description

The NCI GDC has a complex data model that allows various studies to supply numerous clinical and demographic data elements. However, across all projects that enter the GDC, there are similarities. This function returns four data.frames associated with case\_ids from the GDC.

### Usage

```
gdc_clinical(case_ids, include_list_cols = FALSE)
```

**Arguments**

`case_ids` a character() vector of `case_ids`, typically from "cases" query.

`include_list_cols` logical(1), whether to include list columns in the "main" data.frame. These list columns have values for aliquots, samples, etc. While these may be useful for some situations, they are generally not that useful as clinical annotations.

**Details**

Note that these data.frames can, in general, have different numbers of rows (or even no rows at all). If one wishes to combine to produce a single data.frame, using the approach of left joining to the "main" data.frame will yield a useful combined data.frame. We do not do that directly given the potential for 1:many relationships. It is up to the user to determine what the best approach is for any given dataset.

**Value**

A list of four data.frames:

1. main, representing basic case identification and metadata (update date, etc.)
2. diagnoses
3. esposures
4. demographic

**Examples**

```
case_ids = cases() %>% results(size=10) %>% ids()
clinical_data = gdc_clinical(case_ids)

# overview of clinical results
class(clinical_data)
names(clinical_data)
sapply(clinical_data, class)
sapply(clinical_data, nrow)

# available data
head(clinical_data$main)
head(clinical_data$demographic)
head(clinical_data$diagnoses)
head(clinical_data$exposures)
```



## Description

The GDC requires an auth token for downloading data that are "controlled access". For example, BAM files for human datasets, germline variant calls, and SNP array raw data all are protected as "controlled access". For these files, a GDC access token is required. See the [https://docs.gdc.cancer.gov/Data\\_Portal/Users\\_authentication-tokens](https://docs.gdc.cancer.gov/Data_Portal/Users_authentication-tokens). Note that this function simply returns a string value. It is possible to keep the GDC token in a variable in R or to pass a string directly to the appropriate parameter. This function is simply a convenience function for alternative approaches to get a token from an environment variable or a file.

## Usage

```
gdc_token()
```

## Details

This function will resolve locations of the GDC token in the following order:

- from the environment variable, GDC\_TOKEN, expected to contain the token downloaded from the GDC as a string
- using `readLines` to read a file named in the environment variable, GDC\_TOKEN\_FILE
- using `readLines` to read from a file called `.gdc_token` in the user's home directory

If all of these fail, this function will return an error.

## Value

character(1) (invisibly, to protect against inadvertently printing) the GDC token.

## References

[https://docs.gdc.cancer.gov/Data\\_Portal/Users\\_Guide/Authentication/#gdc-authentication-tokens](https://docs.gdc.cancer.gov/Data_Portal/Users_Guide/Authentication/#gdc-authentication-tokens)

## Examples

```
# This will not run before a GDC token  
# is in place.  
token = try(gdc_token(), silent=TRUE)
```

## Description

Cool package for interfacing with NCI GDC

**finding data**

- [query](#)
- [cases](#)
- [projects](#)
- [files](#)
- [annotations](#)
- [mapping](#)

**downloading data**

data

---

grep_fields	<i>Find matching field names</i>
-------------	----------------------------------

---

**Description**

This utility function allows quick text-based search of available fields for using [grep](#)

**Usage**

```
grep_fields(entity, pattern, ..., value = TRUE)
```

**Arguments**

entity	one of "files", "cases", "annotations", "projects" against which to gather available fields for matching
pattern	A regular expression that will be used in a call to <a href="#">grep</a>
...	passed on to grep
value	logical(1) whether to return values as opposed to indices (passed along to grep)

**Value**

character() vector of field names matching pattern

**Examples**

```
grep_fields('files', 'analysis')
```

---

ids	<i>Get the ids associated with a GDC query or response</i>
-----	--

---

### Description

The GDC assigns ids (in the form of uuids) to objects in its database. Those ids can be used for relationships, searching on the website, and as unique ids. All

### Usage

```
ids(x)

## S3 method for class 'GDCManifest'
ids(x)

## S3 method for class 'GDCQuery'
ids(x)

## S3 method for class 'GDCResults'
ids(x)

## S3 method for class 'GDCResponse'
ids(x)
```

### Arguments

x                    A [GDCQuery](#) or [GDCResponse](#) object

### Value

a character vector of all the entity ids

### Examples

```
# use with a GDC query, in this case for "cases"
ids(cases() %>% filter(~ project.project_id == "TCGA-CHOL"))
# also works for responses
ids(response(files()))
# and results
ids(results(cases()))
```

---

id_field	<i>get the name of the id field</i>
----------	-------------------------------------

---

### Description

In many places in the GenomicDataCommons package, the entity ids are stored in a column or a vector with a specific name that corresponds to the field name at the GDC. The format is the entity name (singular) "\_id". This generic simply returns that name from a given object.

**Usage**

```
id_field(x)

## S3 method for class 'GDCQuery'
id_field(x)

## S3 method for class 'GDCResults'
id_field(x)
```

**Arguments**

x                    An object representing the query or results of an entity from the GDC ("cases", "files", "annotations", "projects")

**Value**

character(1) such as "case\_id", "file\_id", etc.

**Methods (by class)**

- GDCQuery: GDCQuery method
- GDCResults: GDCResults method

**Examples**

```
id_field(cases())
```

---

make\_filter

*Create NCI GDC filters for limiting GDC query results*

---

**Description**

Searching the NCI GDC allows for complex filtering based on logical operations and simple comparisons. This function facilitates writing such filter expressions in R-like syntax with R code evaluation.

**Usage**

```
make_filter(expr, available_fields)
```

**Arguments**

expr                    a lazy-wrapped expression or a formula RHS equivalent

available\_fields        a character vector of the additional names that will be injected into the filter evaluation environment

**Details**

If used with available\_fields, "bare" fields that are named in the available\_fields character vector can be used in the filter expression without quotes.

**Value**

a list that represents an R version of the JSON that will ultimately be used in an NCI GDC search or other query.

---

manifest	<i>Prepare GDC manifest file for bulk download</i>
----------	--

---

**Description**

The manifest function/method creates a manifest of files to be downloaded using the GDC Data Transfer Tool. There are methods for creating manifest data frames from [GDCQuery](#) objects that contain file information ("cases" and "files" queries).

**Usage**

```
manifest(x, from = 0, size = count(x), ...)
```

```
## S3 method for class 'gdc_files'
manifest(x, from = 0, size = count(x), ...)
```

```
## S3 method for class 'GDCfilesResponse'
manifest(x, from = 0, size = count(x), ...)
```

```
## S3 method for class 'GDCcasesResponse'
manifest(x, from = 0, size = count(x), ...)
```

**Arguments**

x	An <a href="#">GDCQuery</a> object of subclass "gdc_files" or "gdc_cases".
from	Record number from which to start when returning the manifest.
size	The total number of records to return. Default will return the usually desirable full set of records.
...	passed to <a href="#">PUT</a> .

**Value**

A [tibble](#), also of type "gdc\_manifest", with five columns:

- id
- filename
- md5
- size
- state

**Methods (by class)**

- gdc\_files:
- GDCfilesResponse:
- GDCcasesResponse:

**Examples**

```
gFiles = files()
shortManifest = gFiles %>% manifest(size=10)
head(shortManifest,n=3)
```

---

mapping

*Query GDC for available endpoint fields*


---

**Description**

Query GDC for available endpoint fields

**Usage**

```
mapping(endpoint)
```

**Arguments**

`endpoint` character(1) corresponding to endpoints for which users may specify additional or alternative fields. Endpoints include “projects”, “cases”, “files”, and “annotations”.

**Value**

A data frame describing the field (field name), full (full data model name), type (data type), and four additional columns describing the “set” to which the fields belong—“default”, “expand”, “multi”, and “nested”.

**Examples**

```
map <- mapping("projects")
head(map)
# get only the "default" fields
subset(map,defaults)
# And get just the text names of the "default" fields
subset(map,defaults)$field
```

---

query

*Start a query of GDC metadata*


---

**Description**

The basis for all functionality in this package starts with constructing a query in R. The `GDCQuery` object contains the filters, facets, and other parameters that define the returned results. A token is required for accessing certain datasets.

## Usage

```
query(entity, filters = NULL, facets = NULL, legacy = FALSE,  
      expand = NULL, fields = default_fields(entity))
```

```
cases(...)
```

```
files(...)
```

```
projects(...)
```

```
annotations(...)
```

## Arguments

entity	character vector of 'cases', 'files', 'annotations', or 'projects'
filters	a filter list, typically created using <code>make_filter</code> , or added to an existing GDCQuery object using <code>filter</code> .
facets	a character vector of
legacy	logical(1) whether to use the "legacy" archive or not. See <a href="https://docs.gdc.cancer.gov/Data_Portal/Users_Guide/Legacy_Archive/">https://docs.gdc.cancer.gov/Data_Portal/Users_Guide/Legacy_Archive/</a> and <a href="https://gdc-portal.nci.nih.gov/legacy-archive/search/f">https://gdc-portal.nci.nih.gov/legacy-archive/search/f</a> for details.
expand	a character vector of "expands" to include in returned data
fields	a character vector of fields to return
...	passed through to <code>query</code>

## Value

An S3 object, the GDCQuery object. This is a list with the following members.

- filters
- facets
- fields
- expand
- archive
- token

## Functions

- `cases`: convenience constructor for a GDCQuery for cases
- `files`: convenience constructor for a GDCQuery for files
- `projects`: convenience constructor for a GDCQuery for projects
- `annotations`: convenience constructor for a GDCQuery for annotations

## Examples

```
qcases = query('cases')  
# equivalent to:  
qcases = cases()
```

---

readDNACopy	<i>Read DNACopy results into GRanges object</i>
-------------	---

---

**Description**

Read DNACopy results into GRanges object

**Usage**

```
readDNACopy(fname, ...)
```

**Arguments**

fname	The path to a DNACopy-like file.
...	passed to <code>read_tsv</code>

**Value**

a `GRanges` object

**Examples**

```
fname = system.file(package='GenomicDataCommons',
                    'extdata/dnacopy.tsv.gz')
dnac = readDNACopy(fname)
class(dnac)
length(dnac)
```

---

readHTSeqFile	<i>Read a single htseq-counts result file.</i>
---------------	--

---

**Description**

The htseq package is used extensively to count reads relative to regions (see <http://www-huber.embl.de/HTSeq/doc/counting.html>). The output of htseq-count is a simple two-column table that includes features in column 1 and counts in column 2. This function simply reads in the data from one such file and assigns column names.

**Usage**

```
readHTSeqFile(fname, samplename = "sample", ...)
```

**Arguments**

fname	character(1), the path of the htseq-count file.
samplename	character(1), the name of the sample. This will become the name of the second column on the resulting data.frame, making for easier merging if necessary.
...	passed to <code>read_tsv</code>



**Value**

a two-column data frame

**Examples**

```
fname = system.file(package='GenomicDataCommons',
                    'extdata/example.htseq.counts.gz')
dat = readHTSeqFile(fname)
head(dat)
```

---

response

*Fetch [GDCQuery](#) metadata from GDC*

---

**Description**

Fetch [GDCQuery](#) metadata from GDC

**Usage**

```
response(x, ...)

## S3 method for class 'GDCQuery'
response(x, from = 0, size = 10, ...,
        response_handler = jsonlite::fromJSON)

response_all(x, ...)
```

**Arguments**

**x** a [GDCQuery](#) object

**...** passed to `httr` (good for passing config info, etc.)

**from** integer index from which to start returning data

**size** number of records to return

**response\_handler** a function that processes JSON (as text) and returns an R object. Default is [fromJSON](#).

**Value**

A `GDCResponse` object which is a list with the following members:

- results
- query
- aggregations
- pages

**Examples**

```
# basic class stuff
gCases = cases()
resp = response(gCases)
class(resp)
names(resp)

# And results from query
resp$results[[1]]
```

---

 results

*results*


---

**Description**

results

**Usage**

```
results(x, ...)

## S3 method for class 'GDCQuery'
results(x, ...)

## S3 method for class 'GDCResponse'
results(x, ...)
```

**Arguments**

x                    a [GDCQuery](#) object  
 ...                  passed on to [response](#)

**Value**

A (typically nested) list of GDC records

**Methods (by class)**

- GDCQuery:
- GDCResponse:

**Examples**

```
qcases = cases() %>% results()
length(qcases)
```

---

results_all	<i>results_all</i>
-------------	--------------------

---

**Description**

results\_all

**Usage**

```
results_all(x)

## S3 method for class 'GDCQuery'
results_all(x)

## S3 method for class 'GDCResponse'
results_all(x)
```

**Arguments**

x                    a [GDCQuery](#) object

**Value**

A (typically nested) list of GDC records

**Methods (by class)**

- GDCQuery:
- GDCResponse:

**Examples**

```
# details of all available projects
projResults = projects() %>% results_all()
length(projResults)
count(projects())
```

---

select	<i>S3 generic to set GDCQuery fields</i>
--------	--

---

**Description**

S3 generic to set GDCQuery fields

**Usage**

```
select(x, fields)

## S3 method for class 'GDCQuery'
select(x, fields)
```

**Arguments**

x	the objects on which to set fields
fields	a character vector specifying the fields

**Value**

A `GDCQuery` object, with the `fields` member altered.

**Methods (by class)**

- `GDCQuery`: set fields on a `GDCQuery` object

**Examples**

```
gProj = projects()
gProj$fields
head(available_fields(gProj))
default_fields(gProj)

gProj %>%
  select(default_fields(gProj)[1:2]) %>%
  response() %>%
  str(max_level=2)
```

---

slicing

*Query GDC for data slices*


---

**Description**

This function returns a BAM file representing reads overlapping regions specified either as chromosomal regions or as gencode gene symbols.

**Usage**

```
slicing(uuid, regions, symbols, destination = tempfile(),
  overwrite = FALSE, progress = interactive(), token = NULL,
  legacy = FALSE)
```

**Arguments**

uuid	character(1) identifying the BAM file resource
regions	character() vector describing chromosomal regions, e.g., <code>c("chr1", "chr2:10000", "chr3:10000-20000")</code> (all of chromosome 1, chromosome 2 from position 10000 to the end, chromosome 3 from 10000 to 20000).
symbols	character() vector of gencode gene symbols, e.g., <code>c("BRCA1", "PTEN")</code>
destination	character(1) default <code>tempfile()</code> file path for BAM file slice
overwrite	logical(1) default FALSE can destination be overwritten?
progress	logical(1) default <code>interactive()</code> should a progress bar be used?

token	character(1) security token allowing access to restricted data. Almost all BAM data is restricted, so a token is usually required. See <a href="https://gdc-docs.nci.nih.gov/API/Users_Guide/Authentication_and_Authorization/">https://gdc-docs.nci.nih.gov/API/Users_Guide/Authentication_and_Authorization/</a> .
legacy	logical(1) whether or not to use the "legacy" archive, containing older, non-harmonized data.

**Value**

character(1) destination to the downloaded BAM file

**Examples**

```
slicing("df80679e-c4d3-487b-934c-fcc782e5d46e",
        regions="chr17:75000000-76000000",
        token=gdc_token())
```

---

status

*Query the GDC for current status*

---

**Description**

Query the GDC for current status

**Usage**

```
status(version = NULL)
```

**Arguments**

version (optional) character(1) version of GDC

**Value**

List describing current status.

**Examples**

```
status()
```

---

transfer	<i>Bulk data download</i>
----------	---------------------------

---

### Description

The GDC maintains a special tool, [https://docs.gdc.cancer.gov/Data\\_Transfer\\_Tool/Users\\_Guide/Getting\\_Started/](https://docs.gdc.cancer.gov/Data_Transfer_Tool/Users_Guide/Getting_Started/), that enables high-performance, potentially parallel, and resumable downloads. The Data Transfer Tool is an external program that requires separate download. #' @param gdc\_client character(1) name or path to gdc-client executable. The executable that is used is found through the [gdc\\_client](#). See [gdc\\_client](#) for details on how to set the executable path.

### Usage

```
transfer(uuids, args = character(), token = NULL, overwrite = FALSE)
```

```
transfer_help()
```

### Arguments

uuids	character() vector of GDC file UUIDs
args	character() vector specifying command-line arguments to be passed to gdc-client. See <a href="#">transfer_help</a> for possible values. The arguments --manifest, --dir, and --token-file are determined by manifest, destination_dir, and token, respectively, and should NOT be provided as elements of args.
token	character(1) containing security token allowing access to restricted data. See <a href="https://gdc-docs.nci.nih.gov/API/Users_Guide/Authentication_and_Authorization/">https://gdc-docs.nci.nih.gov/API/Users_Guide/Authentication_and_Authorization/</a> . Note that the GDC transfer tool requires a file for data transfer. Therefore, this token will be written to a temporary file (with appropriate permissions set).
overwrite	logical(1) default FALSE indicating whether existing files with identical name should be over-written.

### Value

character(1) directory path to which the files were downloaded.

### Functions

- [transfer\\_help](#):

### Examples

```
file_manifest = files() %>% filter(~ access == "open") %>% manifest(size=10)
manifest_file = tempfile()
write.table(file_manifest,file=manifest_file,col.names=TRUE,row.names=FALSE,quote=FALSE)
destination <- transfer(manifest_file)
dir(destination)
# and with authentication
destination <- transfer(manifest_file,token=gdc_token)
```

---

write_manifest	<i>write a manifest data.frame to disk</i>
----------------	--

---

### Description

The `manifest` method creates a `data.frame` that represents the data for a manifest file needed by the GDC Data Transfer Tool. While the file format is nothing special, this is a simple helper function to write a manifest `data.frame` to disk. It returns the path to which the file is written, so it can be used "in-line" in a call to `transfer`.

### Usage

```
write_manifest(manifest, destfile = tempfile())
```

### Arguments

<code>manifest</code>	A <code>data.frame</code> with five columns, typically created by a call to <code>manifest</code>
<code>destfile</code>	The filename for saving the manifest.

### Value

character(1) the destination file name.

### Examples

```
mf = files() %>% manifest(size=10)
write_manifest(mf)
```

# Index

.htseq\_importer, 2

aggregations, 3

annotations, 18

annotations (query), 22

app\_dir, 14

available\_expand, 3

available\_fields, 4

available\_rnaseq\_workflows, 5

available\_values, 6

cases, 18

cases (query), 22

count, 7

default\_fields, 7, 10

entity\_name, 8

expand, 9

facet, 10

files, 18

files (query), 22

filter, 23

filter (filtering), 11

filtering, 11

fromJSON, 25

gdc\_cache, 14

gdc\_client, 13, 15, 30

gdc\_clinical, 5, 15

gdc\_rnaseq  
(available\_rnaseq\_workflows), 5

gdc\_set\_cache (gdc\_cache), 14

gdc\_token, 16

gdcdata, 5, 12

GDCQuery, 3, 4, 7–11, 19, 21, 25–28

GDCQuery (query), 22

GDCResponse, 19

GDCResponse (response), 25

GenomicDataCommons, 17

GenomicDataCommons-package  
(GenomicDataCommons), 17

get\_facets (facet), 10

get\_filter (filtering), 11

GRanges, 24

grep, 18

grep\_fields, 18

id\_field, 19

ids, 19

make\_filter, 20, 23

manifest, 13, 21, 31

mapping, 18, 22

projects, 18

projects (query), 22

PUT, 21

query, 18, 22, 23

read\_tsv, 24

readDNACopy, 24

readHTSeqFile, 24

response, 25, 26

response\_all (response), 25

results, 26

results\_all, 27

select, 3, 27

slicing, 28

status, 29

SummarizedExperiment, 5

tibble, 21

transfer, 30, 31

transfer\_help, 13, 30

transfer\_help (transfer), 30

write\_manifest, 31