

10 things (maybe) you didn't know about GenomicRanges, Biostrings, and Rsamtools

Hervé Pagès
hpages.on.github@gmail.com

June 2016

1. Inner vs outer metadata columns

```
> mcols(gr1)$id <- paste0("ID", seq_along(gr1))
> gr1
```

GRangesList object of length 3:

\$gr1

GRanges object with 1 range and 2 metadata columns:

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom2	3-6	+	5	0.45

seqinfo: 2 sequences from an unspecified genome; no seqlengths

\$gr2

GRanges object with 2 ranges and 2 metadata columns:

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom1	7-9	+	3	0.3
[2]	Chrom1	13-15	-	4	0.5

seqinfo: 2 sequences from an unspecified genome; no seqlengths

\$gr3

GRanges object with 2 ranges and 2 metadata columns:

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom1	1-3	-	6	0.4

1. Inner vs outer metadata columns

```
> mcols(gr1) # outer mcols
```

```
DataFrame with 3 rows and 1 column
```

```
      id  
  <character>  
gr1      ID1  
gr2      ID2  
gr3      ID3
```

```
> mcols(unlist(gr1, use.names=FALSE)) # inner mcols
```

```
DataFrame with 5 rows and 2 columns
```

```
      score      GC  
  <integer> <numeric>  
1           5      0.45  
2           3      0.30  
3           4      0.50  
4           6      0.40  
5           2      0.10
```

2. invertStrand()

Works out-of-the-box on any object that has a strand() getter and setter ==>
no need to implement specific methods.

```
> gr
```

```
GRanges object with 10 ranges and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
a	chr2	1-10	-	1	1.000000
b	chr2	2-10	+	2	0.888889
c	chr2	3-10	+	3	0.777778
.
h	chr3	8-10	+	8	0.222222
i	chr3	9-10	-	9	0.111111
j	chr3	10	-	10	0.000000

```
-----
```

```
seqinfo: 3 sequences from an unspecified genome; no seqlengths
```

2. invertStrand()

```
> invertStrand(gr)
```

```
GRanges object with 10 ranges and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
a	chr2	1-10	+	1	1.000000
b	chr2	2-10	-	2	0.888889
c	chr2	3-10	-	3	0.777778
.
h	chr3	8-10	-	8	0.222222
i	chr3	9-10	+	9	0.111111
j	chr3	10	+	10	0.000000

```
-----
```

```
seqinfo: 3 sequences from an unspecified genome; no seqlengths
```

2. invertStrand()

```
> gr1
```

```
GRangesList object of length 3:
```

```
$gr1
```

```
GRanges object with 1 range and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom2	3-6	+	5	0.45

```
-----
```

```
seqinfo: 2 sequences from an unspecified genome; no seqlengths
```

```
$gr2
```

```
GRanges object with 2 ranges and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom1	7-9	+	3	0.3
[2]	Chrom1	13-15	-	4	0.5

```
-----
```

```
seqinfo: 2 sequences from an unspecified genome; no seqlengths
```

```
$gr3
```

```
GRanges object with 2 ranges and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom1	1-3	-	6	0.4
[2]	Chrom2	4-9	-	2	0.1

2. invertStrand()

```
> invertStrand(gr1)
```

```
GRangesList object of length 3:
```

```
$gr1
```

```
GRanges object with 1 range and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom2	3-6	-	5	0.45

```
-----
```

```
seqinfo: 2 sequences from an unspecified genome; no seqlengths
```

```
$gr2
```

```
GRanges object with 2 ranges and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom1	7-9	-	3	0.3
[2]	Chrom1	13-15	+	4	0.5

```
-----
```

```
seqinfo: 2 sequences from an unspecified genome; no seqlengths
```

```
$gr3
```

```
GRanges object with 2 ranges and 2 metadata columns:
```

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
[1]	Chrom1	1-3	+	6	0.4
[2]	Chrom2	4-9	+	2	0.1

3. extractList()

Extract groups of elements from a vector-like object and return them in a list-like object.

```
> cvg <- Rle(c(0L, 2L, 5L, 1L, 0L), c(10, 6, 3, 4, 15))  
> cvg
```

```
integer-Rle of length 38 with 5 runs
```

```
Lengths: 10 6 3 4 15
```

```
Values : 0 2 5 1 0
```

```
> i <- IRanges(c(16, 19, 9), width=5, names=letters[1:3])  
> i
```

```
IRanges object with 3 ranges and 0 metadata columns:
```

	start	end	width
	<integer>	<integer>	<integer>
a	16	20	5
b	19	23	5
c	9	13	5

3. extractList()

```
> extractList(cvg, i)
RleList of length 3
$a
integer-Rle of length 5 with 3 runs
  Lengths: 1 3 1
  Values : 2 5 1

$b
integer-Rle of length 5 with 2 runs
  Lengths: 1 4
  Values : 5 1

$c
integer-Rle of length 5 with 2 runs
  Lengths: 2 3
  Values : 0 2
```

3. extractList()

`i` can be an `IntegerList` object:

```
> i <- IntegerList(c(25:20), NULL, seq(from=2, to=length(cvg), by=2))
> i
```

```
IntegerList of length 3
```

```
[[1]] 25 24 23 22 21 20
```

```
[[2]] integer(0)
```

```
[[3]] 2 4 6 8 10 12 14 16 18 20 22 24 26 28 30 32 34 36 38
```

```
> extractList(cvg, i)
```

```
RleList of length 3
```

```
[[1]]
```

```
integer-Rle of length 6 with 2 runs
```

```
Lengths: 2 4
```

```
Values : 0 1
```

```
[[2]]
```

```
integer-Rle of length 0 with 0 runs
```

```
Lengths:
```

```
Values :
```

```
[[3]]
```

```
integer-Rle of length 19 with 5 runs
```

```
Lengths: 5 3 1 2 8
```

```
Values : 0 2 5 1 0
```

4. 'with.revmap' arg for reduce() and (now) disjoint()

```
> ir
```

IRanges object with 6 ranges and 2 metadata columns:

	start	end	width		id	score
	<integer>	<integer>	<integer>		<character>	<integer>
[1]	11	13	3		a	3
[2]	12	14	3		b	2
[3]	13	15	3		c	1
[4]	2	4	3		d	0
[5]	7	9	3		e	-1
[6]	6	8	3		f	-2

```
> ir2 <- reduce(ir, with.revmap=TRUE)
```

```
> ir2
```

IRanges object with 3 ranges and 1 metadata column:

	start	end	width		revmap
	<integer>	<integer>	<integer>		<IntegerList>
[1]	2	4	3		4
[2]	6	9	4		6,5
[3]	11	15	5		1,2,3

4. 'with.revmap' arg for reduce() and disjoint()

```
> revmap <- mcols(ir2)$revmap  
> extractList(mcols(ir)$id, revmap)
```

CharacterList of length 3

```
[[1]] d  
[[2]] f e  
[[3]] a b c
```

```
> extractList(mcols(ir)$score, revmap)
```

IntegerList of length 3

```
[[1]] 0  
[[2]] -2 -1  
[[3]] 3 2 1
```

```
> mcols(ir2) <- DataFrame(id=extractList(mcols(ir)$id, revmap),  
+                          score=extractList(mcols(ir)$score, revmap))  
> ir2
```

IRanges object with 3 ranges and 2 metadata columns:

	start	end	width		id	score
	<integer>	<integer>	<integer>		<CharacterList>	<IntegerList>
[1]	2	4	3		d	0
[2]	6	9	4		f,e	-2,-1
[3]	11	15	5		a,b,c	3,2,1

5. Zero-width ranges

`findOverlaps/countOverlaps` support zero-width ranges.

```
> sliding_query <- IRanges(1:6, width=0)
> sliding_query
```

IRanges object with 6 ranges and 0 metadata columns:

	start	end	width
	<integer>	<integer>	<integer>
[1]	1	0	0
[2]	2	1	0
[3]	3	2	0
[4]	4	3	0
[5]	5	4	0
[6]	6	5	0

```
> countOverlaps(sliding_query, IRanges(3, 4))
```

```
[1] 0 0 0 1 0 0
```

But you have to specify `minoverlap=0` for this to work (default is 1).

```
> countOverlaps(sliding_query, IRanges(3, 4), minoverlap=0)
```

```
[1] 0 0 0 1 0 0
```

6. Biostrings::replaceAt()

Perform multiple substitutions at arbitrary positions in a set of sequences.

```
> library(Biostrings)
> library(hgu95av2probe)
> probes <- DNASTringSet(hgu95av2probe)
> probes
```

DNASTringSet object of length 201800:

```
      width seq
[1]      25 TGGCTCCTGCTGAGGTCCCCTTTCC
[2]      25 GGCTGTGAATTCCTGTACATATTTTC
[3]      25 GCTTCAATTCATTATGTTTTAATG
...      ...
[201798] 25 TTCTGTCAAAGCATCATCTCAACAA
[201799] 25 CAAAGCATCATCTCAACAAGCCCTC
[201800] 25 GTGCTCCTTGTC AACAGCGCACCCA
```

6. Biostrings::replaceAt()

Replace 3rd and 4th nucleotides by pattern -++-.

```
> replaceAt(probes, at=IRanges(3, 4), value="-++-")
```

DNASTringSet object of length 201800:

```
      width seq
[1]      27 TG-++-TCCTGCTGAGGTCCCCTTTCC
[2]      27 GG-++-GTGAATTCCTGTACATATTTC
[3]      27 GC-++-CAATTCATTATGTTTTAATG
...      ...
[201798] 27 TT-++-GTCAAAGCATCATCTCAACAA
[201799] 27 CA-++-GCATCATCTCAACAAGCCCTC
[201800] 27 GT-++-TCCTTGTC AACAGCGCACCCA
```

6. Biostrings::replaceAt()

If supplied pattern is empty, then performs deletions.

```
> replaceAt(probes, at=IRanges(3, 4), value="")
```

DNASTringSet object of length 201800:

```
      width seq
[1]     23 TGCCTGCTGAGGTCCCCTTCC
[2]     23 GGGTGAATTCCTGTACATATTC
[3]     23 GCCAATTCCATTATGTTTAAATG
...     ...
[201798] 23 TTGTCAAAGCATCATCTCAACAA
[201799] 23 CAGCATCATCTCAACAAGCCCTC
[201800] 23 GTTCCTTGTC AACAGCGCACCCA
```


6. Biostrings::replaceAt()

If `at` is a zero-width range, then performs insertions.

```
> replaceAt(probes, at=IRanges(4, 3), value="--+-")
```

DNASTringSet object of length 201800:

```
      width seq
 [1]    29 TGG--+-CTCCTGCTGAGGTCCCCTTTCC
 [2]    29 GGC--+-TGTGAATTCCTGTACATATTTCC
 [3]    29 GCT--+-TCAATTCATTATGTTTTAATG
 ...    ...
[201798] 29 TTC--+-TGTCAAAGCATCATCTCAACAA
[201799] 29 CAA--+-AGCATCATCTCAACAAGCCCTC
[201800] 29 GTG--+-CTCCTTGTC AACAGCGCACCCA
```

6. Biostrings::replaceAt()

Use it in combination with `vmatchPattern` to replace all the occurrences of a given pattern with another pattern:

```
> midx <- vmatchPattern("VCGTT", probes, fixed=FALSE)
> replaceAt(probes, at=midx, value="-++-")
```

DNASTringSet object of length 201800:

```
      width seq
 [1]     25 TGGCTCCTGCTGAGGTCCCCTTTCC
 [2]     25 GGCTGTGAATTCCTGTACATATTTC
 [3]     25 GCTTCAATTCCATTATGTTTTAATG
 ...     ...
[201798] 25 TTCTGTCAAAGCATCATCTCAACAA
[201799] 25 CAAAGCATCATCTCAACAAGCCCTC
[201800] 25 GTGCTCCTTGTC AACAGCGCACCCA
```

7. GRanges as a subscript

```
> cvg <- RleList(chr1=101:120, chr2=2:-8, chr3=31:40)
> gr
```

GRanges object with 10 ranges and 2 metadata columns:

	seqnames	ranges	strand	score	GC
	<Rle>	<IRanges>	<Rle>	<integer>	<numeric>
a	chr2	1-10	-	1	1.000000
b	chr2	2-10	+	2	0.888889
c	chr2	3-10	+	3	0.777778
.
h	chr3	8-10	+	8	0.222222
i	chr3	9-10	-	9	0.111111
j	chr3	10	-	10	0.000000

seqinfo: 3 sequences from an unspecified genome; no seqlengths

7. GRanges as a subscript

```
> cvg[gr]
RleList of length 10
$chr2
integer-Rle of length 10 with 10 runs
  Lengths: 1 1 1 1 1 1 1 1 1 1
  Values : 2 1 0 -1 -2 -3 -4 -5 -6 -7

$chr2
integer-Rle of length 9 with 9 runs
  Lengths: 1 1 1 1 1 1 1 1 1
  Values : 1 0 -1 -2 -3 -4 -5 -6 -7

$chr2
integer-Rle of length 8 with 8 runs
  Lengths: 1 1 1 1 1 1 1 1
  Values : 0 -1 -2 -3 -4 -5 -6 -7

$chr2
integer-Rle of length 7 with 7 runs
  Lengths: 1 1 1 1 1 1 1
  Values : -1 -2 -3 -4 -5 -6 -7

$chr1
integer-Rle of length 6 with 6 runs
  Lengths: 1 1 1 1 1 1
  Values : 105 106 107 108 109 110

...
<5 more elements>
```

8. BSgenomeViews objects

```
> library(BSgenome.Mmusculus.UCSC.mm10)
> genome <- BSgenome.Mmusculus.UCSC.mm10
> library(TxDb.Mmusculus.UCSC.mm10.knownGene)
> txdb <- TxDb.Mmusculus.UCSC.mm10.knownGene
> ex <- exons(txdb, columns=c("exon_id", "tx_name", "gene_id"))
> v <- Views(genome, ex)
```

8. BSgenomeViews objects

```
> v
```

```
BSgenomeViews object with 447558 views and 3 metadata columns:
```

```
      seqnames      ranges strand      dna |
      <Rle>        <IRanges> <Rle>    <DNASet> |
[1]      chr1 3073253-3074322      + [AAGGAAAGAG...TAGAGAAATG] |
[2]      chr1 3102016-3102125      + [GTGCTTGCTT...ACAAAATAT] |
[3]      chr1 3252757-3253236      + [TTCTTCTGTG...TACCTTCAAT] |
...
[447556] chrUn_JH584304      58564-58835      - [CTGTGTCCT...CAGAGAAATG] |
[447557] chrUn_JH584304      58564-59690      - [CTCTCTGCTG...CAGAGAAATG] |
[447558] chrUn_JH584304      59592-59667      - [AGCTGTCCCG...GCCTTCTCAG] |
      exon_id      tx_name      gene_id
      <integer>    <CharacterList> <CharacterList>
[1]      1 ENSMUST00000193812.1
[2]      2 ENSMUST00000082908.1
[3]      3 ENSMUST00000192857.1
...
[447556] 447556 ENSMUST00000179505.7      66776
[447557] 447557 ENSMUST00000178343.1      66776
[447558] 447558 ENSMUST00000179505.7      66776
```

```
-----
seqinfo: 66 sequences (1 circular) from mm10 genome
```

8. BSgenomeViews objects

```
> af <- alphabetFrequency(v, baseOnly=TRUE)
> head(af)
```

	A	C	G	T	other
[1,]	376	160	206	328	0
[2,]	45	20	20	25	0
[3,]	138	105	86	151	0
[4,]	28	14	30	29	0
[5,]	57	39	20	33	0
[6,]	208	258	204	256	0

9. Pile-up statistics on a BAM file with Rsamtools::pileup()

```
> library(Rsamtools)
> library(RNAseqData.HNRNPC.bam.chr14)
> fl <- RNAseqData.HNRNPC.bam.chr14_BAMFILES[1]
> sbp <- ScanBamParam(which=GRanges("chr14", IRanges(1, 53674770)))
> pp <- PileupParam(distinguish_nucleotides=FALSE,
+                  distinguish_strands=FALSE,
+                  min_mapq=13,
+                  min_base_quality=10,
+                  min_nucleotide_depth=4)
> res <- pileup(fl, scanBamParam=sbp, pileupParam=pp)
```


9. Pile-up statistics on a BAM file with Rsamtools::pileup()

```
> dim(res)
```

```
[1] 248409      4
```

```
> head(res)
```

	seqnames	pos	count	which_label
1	chr14	19681651	4	chr14:1-53674770
2	chr14	19681655	4	chr14:1-53674770
3	chr14	19681657	4	chr14:1-53674770
4	chr14	19681658	4	chr14:1-53674770
5	chr14	19681661	4	chr14:1-53674770
6	chr14	19681662	4	chr14:1-53674770

10. Merging 2 GRanges objects (added this week)

```
> x
```

```
GRanges object with 2 ranges and 3 metadata columns:
```

	seqnames	ranges	strand	score	a1	a2
	<Rle>	<IRanges>	<Rle>	<numeric>	<integer>	<numeric>
[1]	chr1	1-1000	*	0.45	5	6
[2]	chr2	2000-3000	*	NA	7	8

```
-----  
seqinfo: 2 sequences from an unspecified genome; no seqlengths
```

```
> y
```

```
GRanges object with 3 ranges and 3 metadata columns:
```

	seqnames	ranges	strand	score	b1	b2
	<Rle>	<IRanges>	<Rle>	<numeric>	<integer>	<numeric>
[1]	chr2	150-151	*	0.70	0	1
[2]	chr1	1-10	*	0.82	5	-2
[3]	chr2	2000-3000	*	0.10	1	1

```
-----  
seqinfo: 2 sequences from an unspecified genome; no seqlengths
```

10. Merging 2 GRanges objects

```
> merge(x, y)
```

```
GRanges object with 1 range and 5 metadata columns:
```

	seqnames	ranges	strand	score	a1	a2	b1
	<Rle>	<IRanges>	<Rle>	<numeric>	<integer>	<numeric>	<integer>
[1]	chr2	2000-3000	*	0.1	7	8	1
		b2					
		<numeric>					
[1]		1					

```
-----  
seqinfo: 2 sequences from an unspecified genome; no seqlengths
```

10. Merging 2 GRanges objects

```
> merge(x, y, all=TRUE)
```

```
GRanges object with 4 ranges and 5 metadata columns:
```

	seqnames	ranges	strand	score	a1	a2	b1
	<Rle>	<IRanges>	<Rle>	<numeric>	<integer>	<numeric>	<integer>
[1]	chr1	1-10	*	0.82	<NA>	NA	5
[2]	chr1	1-1000	*	0.45	5	6	<NA>
[3]	chr2	150-151	*	0.70	<NA>	NA	0
[4]	chr2	2000-3000	*	0.10	7	8	1

b2

<numeric>

[1]	-2
[2]	NA
[3]	1
[4]	1

seqinfo: 2 sequences from an unspecified genome; no seqlengths