

Package ‘treeio’

December 21, 2024

Title Base Classes and Functions for Phylogenetic Tree Input and Output

Version 1.31.0

Description 'treeio' is an R package to make it easier to import and store phylogenetic tree with associated data; and to link external data from different sources to phylogeny. It also supports exporting phylogenetic tree with heterogeneous associated data to a single tree file and can be served as a platform for merging tree with associated data and converting file formats.

Depends R ($\geq 3.6.0$)

Imports ape, dplyr, jsonlite, magrittr, methods, rlang, stats, tibble, tidytree ($\geq 0.4.5$), utils, yulab.utils ($\geq 0.1.6$)

Suggests Biostrings, cli, ggplot2, ggtree, igraph, knitr, rmarkdown, phangorn, prettydoc, purrr, testthat, tidyr, vroom, xml2, yaml

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

Encoding UTF-8

URL <https://yulab-smu.top/contribution-tree-data/>

BugReports <https://github.com/YuLab-SMU/treeio/issues>

biocViews Software, Annotation, Clustering, DataImport, DataRepresentation, Alignment, MultipleSequenceAlignment, Phylogenetics

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/treeio>

git_branch devel

git_last_commit 79e207c

git_last_commit_date 2024-10-29

Repository Bioconductor 3.21

Date/Publication 2024-12-20

Author Guangchuang Yu [aut, cre] (ORCID:
<https://orcid.org/0000-0002-6485-8781>),
 Tommy Tsan-Yuk Lam [ctb, ths],
 Shuangbin Xu [ctb] (ORCID: <https://orcid.org/0000-0003-3513-5362>),
 Bradley Jones [ctb],
 Casey Dunn [ctb],
 Tyler Bradley [ctb],
 Konstantinos Geles [ctb]

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Contents

treeio-package	3
as.treedata.phylo	4
find.hclust	4
get.placements	5
get.tree	6
get.treetext	6
getNodeNum	7
is.gtree	7
jplace-class	8
label_branch_paml	8
mask	9
merge_tree	10
print.treedataList	10
raxml2nwk	11
read.astral	11
read.beast	12
read.codeml	13
read.codeml_mlc	14
read.fasta	14
read.hyphy	15
read.hyphy.seq	16
read.iqtree	16
read.jplace	17
read.jtree	17
read.mcmctree	18
read.mega_tabular	19
read.newick	19
read.nextstrain.json	20
read.nhx	20
read.paml_rst	21
read.phylip	22
read.phylip.seq	22
read.phylip.tree	23
read.phyloxml	23
read.r8s	24

read.raxml	25
read.treeqza	25
read.treetime	26
reexports	27
rename_taxa	27
rescale_tree	28
spt	28
write.beast	29
write.beast.newick	30
write.jplace	31
write.jtree	31

Index	33
--------------	-----------

treeio-package	<i>treeio: Base Classes and Functions for Phylogenetic Tree Input and Output</i>
----------------	--

Description

'treeio' is an R package to make it easier to import and store phylogenetic tree with associated data; and to link external data from different sources to phylogeny. It also supports exporting phylogenetic tree with heterogeneous associated data to a single tree file and can be served as a platform for merging tree with associated data and converting file formats.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com> ([ORCID](#))

Other contributors:

- Tommy Tsan-Yuk Lam <tylam.tommy@gmail.com> [contributor, thesis advisor]
- Shuangbin Xu <xshuangbin@163.com> ([ORCID](#)) [contributor]
- Bradley Jones <brj1@sfu.ca> [contributor]
- Casey Dunn <casey_dunn@brown.edu> [contributor]
- Tyler Bradley <tcb85@drexel.edu> [contributor]
- Konstantinos Geles <konstantinos.geles@studenti.unicz.it> [contributor]

See Also

Useful links:

- <https://yulab-smu.top/contribution-tree-data/>
- Report bugs at <https://github.com/YuLab-SMU/treeio/issues>

as.treedata.phylo	<i>as.treedata</i>
-------------------	--------------------

Description

convert phylo to treedata

Usage

```
## S3 method for class 'phylo'  
as.treedata(tree, boot = NULL, ...)
```

Arguments

tree	input tree, a phylo object
boot	optional, can be bootstrap value from ape::boot.phylo
...	additional parameters

Details

converting phylo object to treedata object

Author(s)

Guangchuang Yu

find.hclust	<i>find the hierarchical cluster analysis among the nodes of graph based on the length of all the shortest paths in the graph.</i>
-------------	--

Description

find the hierarchical cluster analysis among the nodes of graph based on the length of all the shortest paths in the graph.

Usage

```
find.hclust(  
  x,  
  graph.mst = FALSE,  
  weights = NULL,  
  hclust.method = "average",  
  ...  
)
```

Arguments

x	a igraph object
graph.mst	logical whether obtain the minimum spanning tree first then find.hclust, default is FALSE.
weights	a numeric vector giving edge weights or a character. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used even if the graph has a weight attribute. If this is a character, the graph has the edge attribute which is numeric, then it will be used, default is NULL.
hclust.method	the agglomeration method to be used, This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC).
...	additional parameters

Value

hclust object

Examples

```
library(igraph)
set.seed(123)
g <- igraph::sample_gnp(100, .1) %>%
  set_edge_attr(name='weight', value=abs(rnorm(E(.),3)))
tr1 <- find.hclust(g, weights = NA)
tr2 <- find.hclust(g)
tr3 <- find.hclust(g, graph.mst = TRUE)
```

get.placements *get.placements*

Description

access placement information

Usage

```
get.placements(tree, ...)

## S3 method for class 'jplace'
get.placements(tree, by = "best", ...)
```

Arguments

tree	tree object
...	additional parameters
by	one of 'best' and 'all'

Value

placement tibble

get.tree	<i>get.tree</i>
----------	-----------------

Description

access phylo slot

Usage

```
get.tree(x, ...)
```

Arguments

x	tree object
...	additional parameters

Value

phylo object

Author(s)

Guangchuang Yu

get.treetext	<i>get.treetext method</i>
--------------	----------------------------

Description

access tree text (newick text) from tree object

Usage

```
get.treetext(object, ...)
```

Arguments

object	treedata object
...	additional parameter

Value

phylo object

getNodeNum *getNodeNum*

Description

calculate total number of nodes

Usage

`getNodeNum(tree)`

`Nnode2(tree)`

Arguments

`tree` tree object

Value

number

Author(s)

Guangchuang Yu

Examples

`getNodeNum(rtree(30))`
`Nnode2(rtree(30))`

is.ggtree *is.ggtree*

Description

test whether input object is produced by `ggtree` function

Usage

`is.ggtree(x)`

Arguments

`x` object

Value

TRUE or FALSE

Author(s)

Guangchuang Yu

jplace-class	<i>Class "jplace" This class stores phylogenetic placements</i>
--------------	---

Description

Class "jplace" This class stores phylogenetic placements

Slots

phylo phylo object for tree structure
 treetext newick tree string
 data associated data
 extraInfo extra information, reserve for merge_tree
 file tree file
 placements reserve for jplace file to store placement information
 info extra information, e.g. metadata, software version etc.

Author(s)Guangchuang Yu <https://guangchuangyu.github.io>

label_branch_paml	<i>label_branch_paml</i>
-------------------	--------------------------

Description

label branch for PAML to infer selection pressure using branch model

Usage

label_branch_paml(tree, node, label)

Arguments

tree	phylo object
node	node number
label	label of branch, e.g. #1

Value

updated phylo object

Author(s)

Guangchuang Yu

mask	<i>mask</i>
------	-------------

Description

site mask

Usage

```
mask(tree_object, field, site, mask_site = FALSE)
```

Arguments

tree_object	tree object
field	selected field
site	site
mask_site	if TRUE, site will be masked. if FALSE, selected site will not be masked, while other sites will be masked.

Value

updated tree object

Author(s)

Guangchuang Yu

<code>merge_tree</code>	<i>merge_tree</i>
-------------------------	-------------------

Description

merge two tree object

Usage

```
merge_tree(obj1, obj2)
```

Arguments

<code>obj1</code>	tree object 1
<code>obj2</code>	tree object 2

Value

tree object

Author(s)

Guangchuang Yu

<code>print.treedataList</code>	<i>print</i>
---------------------------------	--------------

Description

print information of a list of treedata objects

Usage

```
## S3 method for class 'treedataList'  
print(x, ...)
```

Arguments

<code>x</code>	a list of treedata objects
<code>...</code>	no used

Value

message

raxml2nwk	<i>raxml2nwk</i>
-----------	------------------

Description

convert raxml bootstrap tree to newick format

Usage

```
raxml2nwk(infile, outfile = "raxml.tree")
```

Arguments

infile	input file
outfile	output file

Value

newick file

Author(s)

Guangchuang Yu

read.astral	<i>read.astral</i>
-------------	--------------------

Description

parse ASTRAL output newick text

Usage

```
read.astral(file)
```

Arguments

file	ASTRAL Newick file
------	--------------------

Value

treedata object

Author(s)

Guangchuang Yu

Examples

```
tt <- paste0(
  "((species1,(species2,species3)'[pp1=0.75;pp2=0.24;pp3=0.01]':",
  "1.2003685744180805)'[pp1=0.98;pp2=0.02;pp3=0]':0.9679599282730038,",
  "((species4,species5)'[pp1=0.88;pp2=0.11;pp3=0.01]':1.2454851536484994))"
)
read.astral(textConnection(tt))
```

read.beast

read.beast

Description

read.beast/mrbayes/mega Nexus output
read.beast/mrbayes/mega newick file format

Usage

```
read.beast(file, threads = 1, verbose = FALSE)
read.mrbayes(file, threads = 1, verbose = FALSE)
read.beast.newick(file, threads = 1, verbose = FALSE)
read.mega(file, threads = 1, verbose = FALSE)
```

Arguments

file	newick file
threads	number of threads for multithreading (default: 1)
verbose	set TRUE to log progress (default: FALSE)

Value

treedata object
treedata object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>
Bradley R Jones

Examples

```

file <- system.file("extdata/BEAST", "beast_mcc.tree", package="treeio")
read.beast(file)
file <- system.file("extdata/MrBayes", "Gq_nxs.tre", package="treeio")
read.mrbayes(file)
tr <- read.beast.newick(
  textConnection(
    '(a[&rate=1]:2,(b[&rate=1.1]:1,c[&rate=0.9]:1)[&rate=1]:1);'
  )
)

```

read.codeml

read.codeml

Description

read baseml output

Usage

```
read.codeml(rstfile, mlcfile, tree = "mlc", type = "Joint")
```

Arguments

rstfile	rst file
mlcfile	mlc file
tree	one of 'mlc' or 'rst'
type	one of 'Marginal' or 'Joint'

Value

A treedata object

Author(s)

Guangchuang Yu

Examples

```

rstfile <- system.file("extdata/PAML_Codeml", "rst", package="treeio")
mlcfile <- system.file("extdata/PAML_Codeml", "mlc", package="treeio")
read.codeml(rstfile, mlcfile)

```

read.codeml_mlc *read.codeml_mlc*

Description

read mlc file of codeml output

Usage

```
read.codeml_mlc(mlcfile)
```

Arguments

mlcfile mlc file

Value

A codeml_mlc object

Author(s)

Guangchuang Yu

Examples

```
mlcfile <- system.file("extdata/PAML_Codeml", "mlc", package="treeio")
read.codeml_mlc(mlcfile)
```

read.fasta *read.fasta*

Description

read FASTA file

Usage

```
read.fasta(fasta, type = "auto")
```

Arguments

fasta fasta file
type sequence type of the input file, one of 'NT' or 'AA'. Default is 'auto' and guess the sequence type automatically

Details

This function supports both DNA or AA sequences

Value

DNABin or AABin object

Author(s)

Guangchuang Yu

read.hyphy	<i>read.hyphy</i>
------------	-------------------

Description

read HYPHY output

Usage

```
read.hyphy(nwk, ancseq, tip.fasfile = NULL)
```

Arguments

nwk	tree file in nwk format, one of hyphy output
ancseq	ancestral sequence file in nexus format, one of hyphy output
tip.fasfile	tip sequence file

Value

A hyphy object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

Examples

```
nwk <- system.file("extdata/HYPHY", "labelledtree.tree", package="treeio")
ancseq <- system.file("extdata/HYPHY", "ancseq.nex", package="treeio")
read.hyphy(nwk, ancseq)
```

read.hyphy.seq *read.hyphy.seq*

Description

parse sequences from hyphy output

Usage

```
read.hyphy.seq(file)
```

Arguments

file output of hyphy ancestral sequence inference; nexus format

Value

DNABin object

Author(s)

Guangchuang Yu

Examples

```
ancseq <- system.file("extdata/HYPHY", "ancseq.nex", package="treeio")
read.hyphy.seq(ancseq)
```

read.iqtree *read.iqtree*

Description

parse IQ-TREE output

Usage

```
read.iqtree(file)
```

Arguments

file IQ-TREE Newick text

Value

treedata object

Author(s)

Guangchuang Yu

read.jplace *read.jplace*

Description

read jplace file

Usage

read.jplace(file)

Arguments

file jplace file

Value

jplace instance

Author(s)

Guangchuang Yu

Examples

```
jp <- system.file("extdata", "sample.jplace", package="treeio")
read.jplace(jp)
```

read.jtree *read.jtree*

Description

Import tree data from jtree file, which is JSON-based text and probably output by write.jtree

Usage

read.jtree(file)

Arguments

file tree file

Value

treedata object

Author(s)

Guangchuang Yu

read.mcmctree	<i>read.mcmctree</i>
---------------	----------------------

Description

read MCMCTree output Tree

Usage

```
read.mcmctree(file, force.ultrametric = FALSE)
```

Arguments

`file` the output tree file of MCMCTree

`force.ultrametric`

logical whether convert the tree to be ultrametric, if it is not ultrametric, default is FALSE. When the tree is ultrametric, branch times will be calculated automatically.

Value

treedata object

Examples

```
file <- system.file("extdata/MCMCTree", "mcmctree_output.tree", package="treeio")
tr <- read.mcmctree(file)
tr
```

read.mega_tabular *read.mega_tabular*

Description

parse tabular output of MEGA

Usage

```
read.mega_tabular(file)
```

Arguments

file MEGA tabular file

Value

treedata object

Author(s)

Guangchuang Yu

read.newick *read.newick*

Description

read newick tree

Usage

```
read.newick(file, node.label = "label", ...)
```

Arguments

file newick file
node.label parse node label as 'label' or 'support' value
... additional parameter, passed to 'read.tree'

Value

phylo or treedata object

Author(s)

Guangchuang Yu

read.nextstrain.json *read.nextstrain.json*

Description

read.nextstrain.json

Usage

```
read.nextstrain.json(x)
```

Arguments

x the json tree file of auspice from nextstrain.

Value

treedata object

Author(s)

Shuangbin Xu

Examples

```
file1 <- system.file("extdata/nextstrain.json", "minimal_v2.json", package="treeio")
tr <- read.nextstrain.json(file1)
tr
```

read.nhx *read.nhx*

Description

read.nhx tree file

Usage

```
read.nhx(file)
```

Arguments

file nhx file

Value

nhx object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

Examples

```
nhxfile <- system.file("extdata/NHX", "ADH.nhx", package="treeio")
read.nhx(nhxfile)
```

<code>read.paml_rst</code>	<i>read.paml_rst</i>
----------------------------	----------------------

Description

read rst file from paml (both baseml and codeml) output

Usage

```
read.paml_rst(rstfile, type = "Joint")
```

Arguments

<code>rstfile</code>	rst file
<code>type</code>	one of 'Marginal' or 'Joint'

Value

A treedata object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

Examples

```
rstfile <- system.file("extdata/PAML_Baseml", "rst", package="treeio")
read.paml_rst(rstfile)
```

read.phylip *read.phylip*

Description

parsing phylip tree format

Usage

```
read.phylip(file)
```

Arguments

file phylip file

Value

an instance of 'phylip'

Author(s)

Guangchuang Yu

Examples

```
phyfile <- system.file("extdata", "sample.phy", package="treeio")
read.phylip(phyfile)
```

read.phylip.seq *read.phylip.seq*

Description

read aligned sequences from phylip format

Usage

```
read.phylip.seq(file)
```

Arguments

file phylip file, currently only sequential format is supported

Value

DNABin object

Author(s)

Guangchuang Yu

References

<http://evolution.genetics.washington.edu/phylip/doc/sequence.html>

`read.phylip.tree` *read.phylip.tree*

Description

parse tree from phylip file

Usage

`read.phylip.tree(file)`

Arguments

`file` phylip file

Value

phylo or multiPhylo object

Author(s)

Guangchuang Yu

`read.phyloxml` *read.phyloxml*

Description

`read.phyloxml`

Usage

`read.phyloxml(file)`

Arguments

`file` phyloxml file

Value

treedata class or treedataList class

Examples

```
xmlfile1 <- system.file("extdata/phyloxml", "test_x2.xml", package="treeio")
px1 <- read.phyloxml(xmlfile1)
px1
xmlfile2 <- system.file("extdata/phyloxml", "phyloxml_examples.xml", package="treeio")
px2 <- read.phyloxml(xmlfile2)
px2
```

read.r8s

read.r8s

Description

parse output from r8s

Usage

```
read.r8s(file)
```

Arguments

file r8s output log file

Value

multiPhylo object

Author(s)

Guangchuang Yu

Examples

```
read.r8s(system.file("extdata/r8s", "H3_r8s_output.log", package="treeio"))
```

read.raxml	<i>read.raxml</i>
------------	-------------------

Description

parse RAxML bootstrapping analysis output

Usage

```
read.raxml(file)
```

Arguments

file RAxML bootstrapping analysis output

Value

treedata object

Author(s)

Guangchuang Yu

Examples

```
raxml_file <- system.file("extdata/RAxML", "RAxML_bipartitionsBranchLabels.H3", package="treeio")
read.raxml(raxml_file)
```

read.treeqza	<i>read.treeqza</i>
--------------	---------------------

Description

read.treeqza

Usage

```
read.treeqza(treeqza, node.label = "label", ...)
```

Arguments

treeqza the qiime2 output file contained tree file.
node.label parse node label as 'label' or 'support' value.
... additional parameter, passed to 'read.tree'.

Value

phylo tree object or treedata object when node.label was parsed 'support'.

Examples

```
qzaf1 <- system.file("extdata/qiime2treeqza", "fasttree-tree.qza", package="treeio")
qzaf2 <- system.file("extdata/qiime2treeqza", "iqt-tree.qza", package="treeio")
qzaf3 <- system.file("extdata/qiime2treeqza", "raxml-cat-tree.qza", package="treeio")
tr1 <- read.treeqza(qzaf1)
tr1
tr2 <- read.treeqza(qzaf2)
tr2
tr3 <- read.treeqza(qzaf3)
tr3
# parse node label as 'support' value.
qzaf4 <- system.file("extdata/qiime2treeqza", "raxml-cat-bootstrap-tree.qza", package="treeio")
tr4 <- read.treeqza(qzaf4, node.label="support")
tr4
```

read.treetime

read.timetree

Description

read timetree output

Usage

```
read.treetime(file)
```

```
read.timetree(file)
```

Arguments

file the output tree file of timetree

Value

treedata object

reexports

*Objects exported from other packages***Description**

These objects are imported from other packages. Follow the links below to see their documentation.

ape [as.phylo](#), [is.rooted](#), [Nnode](#), [Ntip](#), [read.nexus](#), [read.tree](#), [root](#), [rtree](#), [write.nexus](#), [write.tree](#)

dplyr [full_join](#), [inner_join](#)

magrittr [%<>%](#), [%>%](#)

rlang [.data](#)

tibble [as_tibble](#), [tibble](#)

tidytree [ancestor](#), [as.phylo](#), [as.treedata](#), [child](#), [drop.tip](#), [get.data](#), [get.fields](#), [isTip](#), [MRCA](#), [nodeid](#), [nodelab](#), [offspring](#), [parent](#), [rootnode](#), [treedata](#)

rename_taxa

*rename_taxa***Description**

rename tip label of phylogenetic tree

Usage

```
rename_taxa(tree, data, key = 1, value = 2)
```

Arguments

tree	tree object, either treedata or phylo
data	data frame
key	column in data that match tip label (use 1st column by default)
value	column in data for rename tip label (use 2nd column by default)

Value

tree object

Author(s)

Guangchuang Yu

Examples

```
tree <- rtree(3)
d <- data.frame(old = paste0('t', 1:3), new = LETTERS[1:3])
rename_taxa(tree, d)
rename_taxa(tree, d, old, new)
```

rescale_tree	<i>rescale_tree</i>
--------------	---------------------

Description

rescale branch length of tree object

Usage

```
rescale_tree(tree_object, branch.length)
```

Arguments

tree_object tree object
branch.length numerical features (e.g. dN/dS)

Value

update tree object

Author(s)

Guangchuang Yu

spt	<i>spt method</i>
-----	-------------------

Description

spt method

Usage

```
spt(x, from, to, weights = NULL, ...)
```

Arguments

x	a igraph object
from	a specific node of network.
to	other nodes of the network, length of it must be larger than 2.
weights	a numeric vector giving edge weights or a character. If this is NULL and the graph has a weight edge attribute, then the attribute is used. If this is NA then no weights are used even if the graph has a weight attribute. If this is a character, the graph has the edge attribute which is numeric, then it will be used, default is NULL.
...	additional parameters

Value

phylo object

Examples

```
library(igraph)
set.seed(123)
g <- igraph::sample_gnp(100, .1) %>%
  set_edge_attr(name='weight', value=abs(rnorm(E(.),3)))
tr1 <- spt(g, from = 6, to=V(g), weights = 'weight')
tr1
tr2 <- spt(g, from = 6, to = V(g), weights = NA)
tr2
```

write.beast

write.beast

Description

Export treedata object to BEAST NEXUS file. This function was adopted and modified from ape::write.nexus

Usage

```
write.beast(treedata, file = "", translate = TRUE, tree.name = NULL)
```

Arguments

treedata	treedata object, list of treedata, phylo, or list of phylo
file	output file. If file = "", print the output content on screen
translate	whether to translate taxa labels
tree.name	names of the trees, NULL to use existing tree names

Value

output file or file content on screen

Author(s)

Guangchuang Yu

Examples

```
nhxfile <- system.file("extdata/NHX", "phyldog.nhx", package="treeio")
nhx <- read.nhx(nhxfile)
write.beast(nhx)
```

```
write.beast.newick    write.beast.newick
```

Description

Export treedata object to BEAST Newick file. This is useful for making BEAST starting trees with metadata

Usage

```
write.beast.newick(
  treedata,
  file = "",
  append = FALSE,
  digits = 10,
  tree.prefix = ""
)
```

Arguments

treedata	treedata object
file	output file. If file = "", print the output content on screen
append	logical. Only used if the argument 'file' is the name of file (and not a connection or "lcmd"). If 'TRUE' output will be appended to 'file'; otherwise, it will overwrite the contents of file.
digits	integer, the indicating the number of decimal places, default is 10.
tree.prefix	character the tree prefix, default is "".

Value

output file or file content on screen

Author(s)

Guangchuang Yu

Examples

```
nhxfile <- system.file("extdata/NHX", "phyldog.nhx", package="treeio")
nhx <- read.nhx(nhxfile)
write.beast.newick(nhx)
```

write.jplace	<i>write.jplace</i>
--------------	---------------------

Description

Export jplace object to jplace file.

Usage

```
write.jplace(x, outfile)
```

Arguments

x	a jplace object.
outfile	the output file name

Examples

```
jp <- system.file("extdata", "sample.jplace", package="treeio")
tr1 <- read.jplace(jp)
outfile <- tempfile()
write.jplace(tr1, outfile)
tr2 <- read.jplace(outfile)
tr2
```

write.jtree	<i>write.jtree</i>
-------------	--------------------

Description

Export treedata object to json tree file

Usage

```
write.jtree(treedata, file = "")
```

Arguments

treedata treedata object
file output file. If file = "", print the output content on screen

Value

output file or file content on screen

Author(s)

Guangchuang Yu

Index

- * **classes**
 - jplace-class, 8
- * **internal**
 - reexports, 27
 - treeio-package, 3
- .data, 27
- .data (reexports), 27
- %<>% (reexports), 27
- %>% (reexports), 27
- %<>%, 27
- %>%, 27

- ancestor, 27
- ancestor (reexports), 27
- as.phylo, 27
- as.phylo (reexports), 27
- as.treedata, 27
- as.treedata (reexports), 27
- as.treedata.phylo, 4
- as_tibble, 27
- as_tibble (reexports), 27

- child, 27
- child (reexports), 27

- drop.tip, 27
- drop.tip (reexports), 27

- find.hclust, 4
- full_join, 27
- full_join (reexports), 27

- get.data, 27
- get.data (reexports), 27
- get.fields, 27
- get.fields (reexports), 27
- get.placements, 5
- get.tree, 6
- get.treetext, 6
- getNodeNum, 7

- inner_join, 27
- inner_join (reexports), 27
- is.ggtree, 7
- is.rooted, 27
- is.rooted (reexports), 27
- isTip, 27
- isTip (reexports), 27

- jplace-class, 8

- label_branch_paml, 8

- mask, 9
- merge_tree, 10
- MRCA, 27
- MRCA (reexports), 27

- Nnode, 27
- Nnode (reexports), 27
- Nnode2 (getNodeNum), 7
- nodeid, 27
- nodeid (reexports), 27
- nodelab, 27
- nodelab (reexports), 27
- Ntip, 27
- Ntip (reexports), 27

- offspring, 27
- offspring (reexports), 27

- parent, 27
- parent (reexports), 27
- print.treedataList, 10

- raxml2nwk, 11
- read.astral, 11
- read.beast, 12
- read.codeml, 13
- read.codeml_mlc, 14
- read.fasta, 14
- read.hyphy, 15

read.hyphy.seq, 16
read.iqtree, 16
read.jplace, 17
read.jtree, 17
read.mcmctree, 18
read.mega (read.beast), 12
read.mega_tabular, 19
read.mrbayes (read.beast), 12
read.newick, 19
read.nextstrain.json, 20
read.nexus, 27
read.nexus (reexports), 27
read.nhx, 20
read.paml_rst, 21
read.phylip, 22
read.phylip.seq, 22
read.phylip.tree, 23
read.phyloxml, 23
read.r8s, 24
read.raxml, 25
read.timetree (read.treetime), 26
read.tree, 27
read.tree (reexports), 27
read.treeqa, 25
read.treetime, 26
reexports, 27
rename_taxa, 27
rescale_tree, 28
root, 27
root (reexports), 27
rootnode, 27
rootnode (reexports), 27
rtree, 27
rtree (reexports), 27

spt, 28

tibble, 27
tibble (reexports), 27
treedata, 27
treedata (reexports), 27
treeio (treeio-package), 3
treeio-package, 3

write.beast, 29
write.beast.newick, 30
write.jplace, 31
write.jtree, 31
write.nexus, 27
write.nexus (reexports), 27
write.tree, 27
write.tree (reexports), 27