

# Package ‘FunciSNP’

October 16, 2018

**Type** Package

**Title** Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs

**Version** 1.24.0

**Date** 2013-01-19

**Author** Simon G. Coetzee <simon@simoncoetzee.com> and Houtan Noushmehr, PhD <houtan@usp.br>

**Maintainer** Simon G. Coetzee <simon@simoncoetzee.com>

**biocViews** Infrastructure, DataRepresentation, DataImport, SequenceMatching, Annotation

**Depends** R (>= 2.14.0), ggplot2, TxDb.Hsapiens.UCSC.hg19.knownGene, FunciSNP.data

**Imports** methods, BiocGenerics, Biobase, S4Vectors, IRanges, GenomicRanges, Rsamtools (>= 1.6.1), rtracklayer (>= 1.14.1), ChIPpeakAnno (>= 2.2.0), VariantAnnotation, plyr, snpStats, ggplot2 (>= 0.9.0), reshape (>= 0.8.4), scales

**Suggests** org.Hs.eg.db

**Enhances** parallel

**Description** FunciSNP integrates information from GWAS, 1000genomes and chromatin feature to identify functional SNP in coding or non-coding regions.

**License** GPL-3

**URL** [http://coetzeeseq.usc.edu/publication/Coetzee\\_SG\\_et\\_al\\_2012/](http://coetzeeseq.usc.edu/publication/Coetzee_SG_et_al_2012/)

**LazyData** yes

**git\_url** <https://git.bioconductor.org/packages/FunciSNP>

**git\_branch** RELEASE\_3\_7

**git\_last\_commit** 5b0453b

**git\_last\_commit\_date** 2018-04-30

**Date/Publication** 2018-10-15

## R topics documented:

FunciSNP-package . . . . .	2
CorrelatedSNPs-class . . . . .	3

FunciSNPAnnotateSummary . . . . .	5
FunciSNPbed . . . . .	6
FunciSNPidsFromSummary . . . . .	7
FunciSNPplot . . . . .	8
FunciSNPsummaryOverlaps . . . . .	10
FunciSNPtable . . . . .	11
getFSNPs . . . . .	12
TagSNP-class . . . . .	14
TSList-class . . . . .	17

<b>Index</b>	<b>19</b>
--------------	-----------

---

FunciSNP-package	<i>Functional Identification of SNPs with Phenotype by Coincidence with Chromatin Biofeatures</i>
------------------	---

---

## Description

The package includes functions to identify and annotate putative functional SNPs using information derived from GWAS, 1000 genomes database, and sequences around peaks.

## Details

Package:	FunciSNP
Type:	Package
Version:	0.99.0
Date:	2012-05-18
License:	GPL-3
LazyLoad:	yes

## Author(s)

Simon G. Coetzee (maintainer: [scoetzee@gmail.com](mailto:scoetzee@gmail.com)); Houtan Noushmehr, PhD ([houtan@usp.br](mailto:houtan@usp.br))

## References

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., *Nucleic Acids Research*, In press, 2012 (doi:10.1093/nar/gks542).

## See Also

[FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

## Examples

```
##
## Glioblastoma analysis using FunciSNP
##
```

```

## Full path to the example regions file for Glioblastoma
# (collected from SNPedia)
glioma.snp <- file.path(system.file('extdata',
  package='FunciSNP'),
  dir(system.file('extdata',package='FunciSNP'),
  pattern='.snp$'));

## Full path to the example biological features BED files
# derived from the ENCODE project for Glioblastoma U-87
# cell lines.
glioma.bio <- system.file('extdata',package='FunciSNP');

## FunciSNP analysis, extracts correlated SNPs from the
# 1000 genomes db ("ncbi") and finds overlaps between
# correlated SNP and biological features and then
# calculates LD (Rsquare, Dprime, distance, p-value).
# Do not run. Can take more than 5 min depending on internet connection and number of CPUs.
#glioma <- FunciSNP(snp.regions.file=glioma.snp,
# bio.features.loc = glioma.bio, bio.features.TSS=FALSE);

##
data(glioma);
class(glioma);
glioma;
summary(glioma);

```

---

CorrelatedSNPs-class *Class "CorrelatedSNPs"*

---

## Description

Class for CorrelatedSNPs

## Usage

```

## S4 method for signature 'CorrelatedSNPs'
alt.allele(x)
## S4 replacement method for signature 'CorrelatedSNPs'
alt.allele(x) <- value
## S4 method for signature 'CorrelatedSNPs'
chr(x)
## S4 replacement method for signature 'CorrelatedSNPs'
chr(x) <- value
## S4 method for signature 'CorrelatedSNPs'
overlapping.features(x)
## S4 replacement method for signature 'CorrelatedSNPs'
overlapping.features(x) <- value
## S4 method for signature 'CorrelatedSNPs'
pop.genotype(x, population)
## S4 replacement method for signature 'CorrelatedSNPs'
pop.genotype(x) <- value

```

```

## S4 method for signature 'CorrelatedSNPs'
position(x)
## S4 replacement method for signature 'CorrelatedSNPs'
position(x) <- value
## S4 method for signature 'CorrelatedSNPs'
ref.allele(x)
## S4 replacement method for signature 'CorrelatedSNPs'
ref.allele(x) <- value
## S4 method for signature 'CorrelatedSNPs'
snpid(x)
## S4 replacement method for signature 'CorrelatedSNPs'
snpid(x) <- value

```

### Arguments

x	The CorrelatedSNPs object from/on which to get/set snp information.
value	Examine the section "Slots" for the values taken by each method.
population	Population for which to set/get genotype information, either "AFR", "AMR", "ASN", "EUR" or "ALL".

### Objects from the Class

Objects can be created by calls of the form `new("CorrelatedSNPs", ...)`.

### Slots

```

chromosome: Object of class "integer" ~~
position: Object of class "integer" ~~
snpid: Object of class "character" ~~
ref.allele: Object of class "character" ~~
alt.allele: Object of class "character" ~~
overlapping.features: Object of class "GRanges" ~~
genotype: Object of class "CorrGeno" ~~

```

### Methods

```

alt.allele<- signature(x = "CorrelatedSNPs"): ...
alt.allele signature(x = "CorrelatedSNPs"): ...
chr<- signature(x = "CorrelatedSNPs"): ...
chr signature(x = "CorrelatedSNPs"): ...
overlapping.features<- signature(x = "CorrelatedSNPs"): ...
overlapping.features signature(x = "CorrelatedSNPs"): ...
pop.genotype<- signature(x = "CorrelatedSNPs"): ...
pop.genotype signature(x = "CorrelatedSNPs"): ...
position<- signature(x = "CorrelatedSNPs"): ...
position signature(x = "CorrelatedSNPs"): ...
ref.allele<- signature(x = "CorrelatedSNPs"): ...
ref.allele signature(x = "CorrelatedSNPs"): ...
snpid<- signature(x = "CorrelatedSNPs"): ...
snpid signature(x = "CorrelatedSNPs"): ...

```

**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: scoetzee@gmail.com); Houtan Noushmehr, PhD (houtan@usp.br)

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., *Nucleic Acids Research*, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
showClass("CorrelatedSNPs")
```

---

FunciSNPAnnotateSummary

*Genomic Annotation of YAFSNPs.*

---

**Description**

This will annotate all identified YAFSNP for it's distance to the nearest known TSS, whether it overlaps a known exon, intron, 5'UTR, 3'UTR, promoter, lincRNA or in gene desert (intergenic) regions.

**Usage**

```
FunciSNPAnnotateSummary(snp.list)
```

**Arguments**

`snp.list` a FunciSNP object: `snp.list` represents the FunciSNP object output from FunciSNP. See [getFSNPs](#).

**Details**

All known genomic features (exon, intron, 5'UTR, 3'UTR, promoter, lincRNA or in gene desert (intergenic)) are used to annotate the newly identified YAFSNP. Information described in this `data.frame` is used for all summary plots, table, and bed file generations.

**Value**

`data.frame` with rows for each correlated SNP.

**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: scoetzee@gmail.com); Houtan Noushmehr, PhD (houtan@usp.br)

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., Nucleic Acids Research, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
data(glioma);
gl <- FunciSNPAnnotateSummary(glioma);
dim(gl)
head(gl)
names(gl)
```

---

FunciSNPbed

*Creates a BED file to view YAFSNPs in your favorite genome browser*

---

**Description**

FunciSNPbed will output a BED file to a specified folder. The BED file is in standard UCSC Genome Browser format (<http://genome.ucsc.edu/FAQ/FAQformat>). Each tagSNP is colored black and each YAFSNP is colored red.

**Usage**

```
FunciSNPbed(dat, rsq, path = getwd(), filename = NULL)
```

**Arguments**

dat	FunciSNP data.frame: dat is a data.frame object from FunciSNPAnnotateSummary. Need to run <a href="#">FunciSNPAnnotateSummary</a> first.
rsq	an interger (0-1): rsq is the Rsquared cutoff used to subset.
path	a character: path is the path to the folder where to save the BED file. Default to getwd() or current working directory.
filename	a character: filename is the name of the BED file. If NULL, filename is 'FunciSNP_results_rsq.RSQ.value.bed'

**Details**

FunciSNPbed outputs a unique BED file which can be used to view in any genomic browser compatible with BED formats. To learn more about BED formats, see UCSC Genome Browser FAQ (<http://genome.ucsc.edu/FAQ/FAQformat>). Each tagSNP which is in LD to a corresponding YAFSNP overlapping at least one biofeature is colored black, while the YAFSNP is colored red. The initial position is provided by the first tagSNP and the first linked YAFSNP. We recommend using UCSC genome browser to view your BED files. This is useful so you can view all public and private tracks in relation to FunciSNP results.

**Value**

BED file is outputted as a tab-delimited file in the specified 'path' folder. See example below.

**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: scoetzee@gmail.com); Houtan Noushmehr, PhD (houtan@usp.br)

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., Nucleic Acids Research, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
##
data(glioma);
glioma.anno <- FunciSNPAnnotateSummary(glioma);
FunciSNPbed(glioma.anno, rsq=0.9);
####
#Bed file "FunciSNP_results_rsq.0.9.bed" created successfully.
#(See folder: "/home/houtan/Downloads/")
#Total corSNP (RED): 15
#Total tagSNP (BLK): 1

#To view results, submit bed file as a
# custom track in UCSC Genome Browser (genome.ucsc.edu),

#Now have fun with your new Func-y SNPs!!
####
```

---

FunciSNPidsFromSummary

*coming soon.*

---

**Description**

placeholder<<<<

**Usage**

```
FunciSNPidsFromSummary(dat, tag SNP id = NULL, num.features, rsq = 0)
```

**Arguments**

dat placeholder<<<<  
 tagsnpid placeholder<<<<  
 num.features placeholder<<<<  
 rsq placeholder<<<< placeholder<<<<

**Details**

placeholder<<<<

**Value**

placeholder<<<<

**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: scoetzee@gmail.com); Houtan Noushmehr, PhD (houtan@usp.br)

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., Nucleic Acids Research, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
## coming soon
```

---

FunciSNPplot

*FunciSNPplot to visualize YAFSNP summary.*

---

**Description**

FunciSNPplot is a function developed to plot various types of plots to summarize and assist end-user in making informed discoveries of FunciSNP results. Plots can be stored in a folder for future reference.

**Usage**

```
FunciSNPplot(dat, rsq = 0, split = FALSE, splitbysnp = FALSE, tagSummary = FALSE, heatmap = FALSE,
```



**Arguments**

<code>dat</code>	FunciSNP data.frame: <code>dat</code> is a data.frame object from <code>FunciSNPAnnotateSummary</code> . Need to run <code>FunciSNPAnnotateSummary</code> first.
<code>rsq</code>	an interger (0-1): <code>rsq</code> is the Rsquared cutoff used to subset.
<code>split</code>	logical: <code>split</code> will generate distribution plot of all Correlated SNPs by Rsquare values.
<code>splitbysnp</code>	logical: <code>splitbysnp</code> is similar to <code>split</code> but instead split the distribution by tagSNP.
<code>tagSummary</code>	logical: <code>tagSummary</code> Will output two plots per biofeature. The first one is a scatter plot showing the relationship between Rsquare and Distance to tagSNP for each YAFSNP. The second plot is a histogram distribution of number of correlated SNPs at each Rsquare value. Each set of plot is further divided by tagSNP. Best if used with <code>rsq</code> value.
<code>heatmap</code>	logical: <code>heatmap</code> correlation heatmap to visualize the number of correlated SNPs at each tagSNP overlapping each biological feature. Most informative if used with a <code>rsq</code> value.
<code>heatmap.key</code>	logical: <code>heatmap.key</code> Places the count of each cell on the heatmap.
<code>genomicSum</code>	logical: <code>genomicSum</code> Stacked bar chart summarizing all correlated SNPs for each of the identified genomie features (exon, intron, 5'UTR, 3'UTR, promoter, lincRNA or in gene desert (intergenic)). Most informative if used with a <code>rsq</code> value.
<code>save</code>	logical: <code>save</code> to save outputs to folder. Set at <code>getwd()</code> , in folder 'FunciSNP.VERSION/plots
<code>pathplot</code>	a character: <code>pathplot</code> is the path to the folder where to save the plots. Default to <code>getwd()</code> or current working directory.
<code>text.size</code>	Text size passed to graphing functions
<code>save.width</code>	Width of saved images in inches
<code>save.height</code>	Height of saved images in inches

**Details**

NA

**Value**

Plots are generated either in X11 or in specified folder.

**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: [scoetzee@gmail.com](mailto:scoetzee@gmail.com)); Houtan Noushmehr, PhD ([houtan@usp.br](mailto:houtan@usp.br))

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., *Nucleic Acids Research*, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
data(glioma)
gl <- FunciSNPAnnotateSummary(glioma)
FunciSNPplot(gl)
FunciSNPplot(gl, rsq=0, genomicSum=TRUE, save=FALSE)
FunciSNPplot(gl, rsq=0.5, genomicSum=TRUE, save=FALSE)
# DO NOT RUN
#FunciSNPplot(gl, tagSummary=TRUE, rsq=0.5)
#
```

---

FunciSNPsummaryOverlaps

*Summarizes FunciSNP results by overlaps*

---

**Description**

This will summarize the total number of YAFSNPs identified by the number of biofeatures per tagSNP

**Usage**

```
FunciSNPsummaryOverlaps(dat, rsq = 0)
```

**Arguments**

dat	FunciSNP data object
rsq	Rsquare value used to filter the summary report

**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: scoetzee@gmail.com); Houtan Noushmehr, PhD (houtan@usp.br)

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., Nucleic Acids Research, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
data(glioma);
glioma.anno <- FunciSNPAnnotateSummary(glioma);
FunciSNPsummaryOverlaps(glioma.anno, rsq = 0.2);
```

---

FunciSNPtable	<i>Will output a summary report from FunciSNP at specified Rsquare cut-offs.</i>
---------------	--

---

**Description**

Using a specified Rsquare value (0-1) to subset the data, a table is generated which summarizes the total number of YAFSNPs, associated tagSNPs, and number of overlapping biofeatures.

**Usage**

```
FunciSNPtable(dat, rsq, geneSum = FALSE)
```

**Arguments**

dat	FunciSNP data.frame: dat is a data.frame object from FunciSNPAnnotateSummary. Need to run <a href="#">FunciSNPAnnotateSummary</a> first.
rsq	an interger (0-1): rsq is the Rsquared cutoff used to subset.
geneSum	logical: geneSum is set to FALSE. Setting to TRUE will output a list of Gene names which are nearest to the YAFSNP.

**Details**

Using a specified Rsquare value (0-1) to subset the data, a table is generated which summarizes the total number of YAFSNPs, associated tagSNPs, and number of overlapping biofeatures. This will provide user a first look at the total number of available YAFSNP at a particular Rsquare cutoff. If geneSum is set to TRUE, a list of gene names is reported instead.

**Value**

Standard output which summarizes FunciSNP results.

**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: scoetzee@gmail.com); Houtan Noushmehr, PhD (houtan@usp.br)

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., Nucleic Acids Research, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
data(glioma);
gl <- FunciSNPAnnotateSummary(glioma);
FunciSNPtable(gl, rsq=0.5);
FunciSNPtable(gl, rsq=0.5, geneSum=TRUE);
```

---

getFSNPs

*Functional Identification of SNPs with Phenotype by Coincidence with Chromatin Biofeatures*

---

**Description**

Given a set of known tag-SNPs associated with a particular phenotype (e.g. disease, trait), and a set of available biological features (e.g. peaks derived from ChIP-seq experiments for phenotype), returns correlated SNPs (from the 1000 genomes db) which are in linkage disequilibrium (LD) to a known disease associated tag-SNP and overlaps chromatin biological features. These identified correlated SNPs are characterized as putative functional SNPs for a particular trait.

**Usage**

```
getFSNPs(snp.regions.file, bio.features.loc = NULL,
        built.in.biofeatures = TRUE,
        par.threads=detectCores()/2,
        verbose = par.threads < 2, method.p = "BH",
        search.window = 200000)
```

**Arguments**

snp.regions.file

path: Location of the regions file: Regions file is tab-delimited and contains three elements per row. First element defines the genomic location of the tagSNP, 'chr:position' (e.g. 5:5420030). Second element contains the tagSNP name, 'rsID' (e.g. rs6010620). Third element defines the 'POPULATION' (ASN, EUR, AFR, ALL) where the tagSNP was identified (e.g. ASN, EUR, AFR, ALL).

SNP Region file is imported and each row element (tagSNP element) is parsed for tagSNP name (rsXXXX), population (ASN, EUR, AFR, or ALL), and genomic location. Genomic location is used to define the window size (see 'search.window' argument). See example file here: `file.path(system.file('data',package='FunciSNP'), dir(system.file('data',package='FunciSNP'), pattern='.snp$'))`;

bio.features.loc

path: Location of the biological features folder: Each biological feature for a particular genomic phenotype should be separated as individual BED files (tab delimited file with chr, start and end). See UCSC for more information about BED formats <http://genome.ucsc.edu/FAQ/FAQformat.html#format1>. See example below. Default set to NULL.

<code>built.in.biofeatures</code>	logical: To include promoter regions, Encode DNaseI and CTCF sites as an additional biofeature in the analysis. Promoters defined as -1000 to +100 bp of a known TSS. File extracted on Feb. 9, 2012 from UCSC genome table browser. Default set to TRUE.
<code>par.threads</code>	an integer: Number of CPU cores to use for FunciSNP analysis. Default set at <code>detectCores()/2</code> . If <code>par.threads &gt; 1</code> , then by default "verbose" = FALSE.
<code>verbose</code>	logical: If set to TRUE, then regardless of <code>par.threads</code> value, all verbose message will output to terminal. If set to FALSE, no verbose message will output to terminal, except for warnings(). Default setting depends on number of 'par.threads' value.
<code>method.p</code>	method: p-value correction (or adjustment) method (see <code>?p.adjust</code> ). Default set at "BH" (Benjamini & Hochberg (1995)).
<code>search.window</code>	an integer: genomic window size used to extract all available correlated SNPs from the 1000 genomes db. The window size is centered around the tagSNP position as defined in the <code>regions.file</code> .

## Details

This is the main function of FunciSNP. It will identify correlated SNPs which are in linkage disequilibrium (LD) to a known disease associated tagSNP. It will also determine if the correlated SNP in LD to the tagSNP overlaps a genomic biological feature. Correlated SNPs are directly imported from the current public release of the 1000 genomes database.

Correlated SNPs in LD to a tagSNP and overlapping genomic biological features are known as putative functional SNPs (also defined as 'YAFSNP' elsewhere in the package.).

## Value

TList            FunciSNP object.

## Note

NA

## Author(s)

Simon G. Coetzee (maintainer: [scoetzee@gmail.com](mailto:scoetzee@gmail.com)); Houtan Noushmehr, PhD ([houtan@usp.br](mailto:houtan@usp.br))

## References

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., *Nucleic Acids Research*, In press, 2012 (doi:10.1093/nar/gks542).

## See Also

[FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
##
## Glioblastoma analysis using FunciSNP
##
## Full path to the example regions file for Glioblastoma
# (collected from SNPedia)
glioma.snp <- file.path(system.file('extdata',
  package='FunciSNP'),
  dir(system.file('extdata',package='FunciSNP'),
  pattern='.snp$'));

## Full path to the example biological features BED files
# derived from the ENCODE project for Glioblastoma U-87
# cell lines.
glioma.bio <- system.file('extdata',package='FunciSNP');

## FunciSNP analysis, extracts correlated SNPs from the
# 1000 genomes db ("ncbi") and finds overlaps between
# correlated SNP and biological features and then
# calculates LD (Rsquare, Dprime, distance, p-value).
# Do not run. Can take more than 5 min depending on internet connection and number of CPUs.
#glioma <- getFSNPs(snp.regions.file=glioma.snp,
# bio.features.loc = glioma.bio);

##
data(glioma);
class(glioma);
glioma;
summary(glioma);
```

---

TagSNP-class

*Class "TagSNP"*


---

**Description**

In the code snippets below, `x` is a TagSNP object. for the usage of `alt.allele`, `chr`, `position`, `ref.allele`, and `snpid` for the object `CorrelatedSNPs`, see `?CorrelatedSNPs-class`

**Usage**

```
## S4 method for signature 'TagSNP'
alt.allele(x)
## S4 replacement method for signature 'TagSNP'
alt.allele(x) <- value
## S4 method for signature 'TagSNP'
chr(x)
## S4 replacement method for signature 'TagSNP'
chr(x) <- value
## S4 method for signature 'TagSNP'
correlated.snps(x)
## S4 replacement method for signature 'TagSNP'
```

```

correlated.snps(x) <- value
## S4 method for signature 'TagSNP'
genotype(x)
## S4 replacement method for signature 'TagSNP'
genotype(x) <- value
## S4 method for signature 'TagSNP'
population(x)
## S4 replacement method for signature 'TagSNP'
population(x) <- value
## S4 method for signature 'TagSNP'
position(x)
## S4 replacement method for signature 'TagSNP'
position(x) <- value
## S4 method for signature 'TagSNP'
ref.allele(x)
## S4 replacement method for signature 'TagSNP'
ref.allele(x) <- value
## S4 method for signature 'TagSNP'
snpid(x)
## S4 replacement method for signature 'TagSNP'
snpid(x) <- value
## S4 method for signature 'TagSNP'
yafsnp.rsq(x)
## S4 replacement method for signature 'TagSNP'
yafsnp.rsq(x) <- value
## S4 method for signature 'TagSNP'
yafsnp.dprime(x)
## S4 replacement method for signature 'TagSNP'
yafsnp.dprime(x) <- value
## S4 method for signature 'TagSNP'
yafsnp.pvalue(x)
## S4 replacement method for signature 'TagSNP'
yafsnp.pvalue(x) <- value
## S4 method for signature 'TagSNP'
AFR.overlapping.snps.geno(x)
## S4 method for signature 'TagSNP'
AMR.overlapping.snps.geno(x)
## S4 method for signature 'TagSNP'
ASN.overlapping.snps.geno(x)
## S4 method for signature 'TagSNP'
EUR.overlapping.snps.geno(x)

```

### Arguments

x	The TagSNP object from/on which to get/set snp information.
value	Examine the section "Slots" for the values taken by each method.

### Objects from the Class

Objects can be created by calls of the form `new("TagSNP", ...)`.

**Slots**

chromosome: Object of class "integer" ~~  
 position: Object of class "integer" ~~  
 snpid: Object of class "character" ~~  
 population: Object of class "character" ~~  
 ref.allele: Object of class "character" ~~  
 alt.allele: Object of class "character" ~~  
 genotype: Object of class "SnpMatrix" ~~  
 yafsnp.rsq: Object of class "dgCMatrix" ~~  
 yafsnp.dprime: Object of class "dgCMatrix" ~~  
 yafsnp.pvalue: Object of class "list" ~~  
 correlated.snps: Object of class "CorrelatedSNPs" ~~

**Methods**

**alt.allele**<- signature(x = "TagSNP"): ...  
**alt.allele** signature(x = "TagSNP"): ...  
**chr**<- signature(x = "TagSNP"): ...  
**chr** signature(x = "TagSNP"): ...  
**correlated.snps**<- signature(x = "TagSNP"): ...  
**correlated.snps** signature(x = "TagSNP"): ...  
**genotype**<- signature(x = "TagSNP"): ...  
**genotype** signature(x = "TagSNP"): ...  
**population**<- signature(x = "TagSNP"): ...  
**population** signature(x = "TagSNP"): ...  
**position**<- signature(x = "TagSNP"): ...  
**position** signature(x = "TagSNP"): ...  
**ref.allele**<- signature(x = "TagSNP"): ...  
**ref.allele** signature(x = "TagSNP"): ...  
**R.squared.corrsnps**<- signature(x = "TagSNP"): ...  
**R.squared.corrsnps** signature(x = "TagSNP"): ...  
**show** signature(object = "TagSNP"): ...  
**snpid**<- signature(x = "TagSNP"): ...  
**snpid** signature(x = "TagSNP"): ...  
**yafsnp.rsq**<- signature(x = "TagSNP"): ...  
**yafsnp.rsq** signature(x = "TagSNP"): ...  
**yafsnp.dprime**<- signature(x = "TagSNP"): ...  
**yafsnp.dprime** signature(x = "TagSNP"): ...  
**yafsnp.pvalue**<- signature(x = "TagSNP"): ...  
**yafsnp.pvalue** signature(x = "TagSNP"): ...  
**AFR.overlapping.snps.geno** signature(x = "TagSNP"): ...  
**AMR.overlapping.snps.geno** signature(x = "TagSNP"): ...  
**ASN.overlapping.snps.geno** signature(x = "TagSNP"): ...  
**EUR.overlapping.snps.geno** signature(x = "TagSNP"): ...



**Note**

NA

**Author(s)**

Simon G. Coetzee (maintainer: scoetzee@gmail.com); Houtan Noushmehr, PhD (houtan@usp.br)

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., Nucleic Acids Research, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
showClass("TagSNP")
```

---

TSList-class

*Class "TSList"*


---

**Description**

ffff

**Objects from the Class**

Objects can be created by calls of the form `new("TSList", ...)`.

**Slots**

snp.data: Object of class "list" ~~

summary.data: Object of class "data.frame" ~~

elementType: Object of class "character" ~~

elementMetadata: Object of class "DataTableORNULL" ~~

metadata: Object of class "list" ~~

**Methods**

**show** signature(object = "TSList"): ...

**summary** signature(object = "TSList"): ...

**Note**

NA

**Author(s)**

Simon G. Coetzee and Houtan Noushmehr, PhD

**References**

SG. Coetzee, SK. Rhie, BP. Berman, GA. Coetzee and H. Noushmehr, FunciSNP: An R/Bioconductor Tool Integrating Functional Non-coding Datasets with Genetic Association Studies to Identify Candidate Regulatory SNPs., *Nucleic Acids Research*, In press, 2012 (doi:10.1093/nar/gks542).

**See Also**

[getFSNPs](#), [FunciSNPplot](#), [FunciSNPAnnotateSummary](#), [FunciSNPtable](#), [FunciSNPbed](#)

**Examples**

```
showClass("TSList")
```

# Index

## \*Topic **Functional**

getFSNPs, [12](#)

## \*Topic **SNP**

getFSNPs, [12](#)

## \*Topic **\textasciitildekw1**

FunciSNPbed, [6](#)

FunciSNPidsFromSummary, [7](#)

FunciSNPplot, [8](#)

FunciSNPsummaryOverlaps, [10](#)

FunciSNPtable, [11](#)

## \*Topic **\textasciitildekw2**

FunciSNPbed, [6](#)

FunciSNPidsFromSummary, [7](#)

FunciSNPplot, [8](#)

FunciSNPsummaryOverlaps, [10](#)

FunciSNPtable, [11](#)

## \*Topic **annotation**

FunciSNPAnnotateSummary, [5](#)

## \*Topic **classes**

CorrelatedSNPs-class, [3](#)

TagSNP-class, [14](#)

TSList-class, [17](#)

## \*Topic **package**

FunciSNP-package, [2](#)

AFR.overlapping.snps.geno  
(TagSNP-class), [14](#)

AFR.overlapping.snps.geno, TagSNP-method  
(TagSNP-class), [14](#)

alt.allele (TagSNP-class), [14](#)

alt.allele, CorrelatedSNPs-method  
(CorrelatedSNPs-class), [3](#)

alt.allele, TagSNP-method  
(TagSNP-class), [14](#)

alt.allele<- (TagSNP-class), [14](#)

alt.allele<-, CorrelatedSNPs-method  
(CorrelatedSNPs-class), [3](#)

alt.allele<-, TagSNP-method  
(TagSNP-class), [14](#)

AMR.overlapping.snps.geno  
(TagSNP-class), [14](#)

AMR.overlapping.snps.geno, TagSNP-method  
(TagSNP-class), [14](#)

ASN.overlapping.snps.geno  
(TagSNP-class), [14](#)

ASN.overlapping.snps.geno, TagSNP-method  
(TagSNP-class), [14](#)

chr (TagSNP-class), [14](#)

chr, CorrelatedSNPs-method  
(CorrelatedSNPs-class), [3](#)

chr, TagSNP-method (TagSNP-class), [14](#)

chr<- (TagSNP-class), [14](#)

chr<-, CorrelatedSNPs-method  
(CorrelatedSNPs-class), [3](#)

chr<-, TagSNP-method (TagSNP-class), [14](#)

class:CorrelatedSNPs  
(CorrelatedSNPs-class), [3](#)

class:TagSNP (TagSNP-class), [14](#)

correlated.snps (TagSNP-class), [14](#)

correlated.snps, TagSNP-method  
(TagSNP-class), [14](#)

correlated.snps<- (TagSNP-class), [14](#)

correlated.snps<-, TagSNP-method  
(TagSNP-class), [14](#)

CorrelatedSNPs (CorrelatedSNPs-class), [3](#)

CorrelatedSNPs-class, [3](#)

EUR.overlapping.snps.geno  
(TagSNP-class), [14](#)

EUR.overlapping.snps.geno, TagSNP-method  
(TagSNP-class), [14](#)

FunciSNP-package, [2](#)

FunciSNP.data (getFSNPs), [12](#)

FunciSNPAnnotateSummary, [2](#), [5](#), [5](#), [6–13](#), [17](#),  
[18](#)

FunciSNPbed, [2](#), [5](#), [6](#), [6](#), [7](#), [8](#), [10](#), [12](#), [13](#), [17](#), [18](#)

FunciSNPidsFromSummary, [7](#)

FunciSNPplot, [2](#), [5–8](#), [8](#), [10](#), [12](#), [13](#), [17](#), [18](#)

FunciSNPsummaryOverlaps, [10](#)

FunciSNPtable, [2](#), [5–8](#), [10](#), [11](#), [12](#), [13](#), [17](#), [18](#)

genotype (TagSNP-class), [14](#)

genotype, TagSNP-method (TagSNP-class),  
[14](#)

genotype<- (TagSNP-class), [14](#)

- genotype<- ,TagSNP-method  
(TagSNP-class), 14
- getFSNPs, 5–8, 10, 12, 12, 17, 18
- glioma (getFSNPs), 12
- overlapping.features  
(CorrelatedSNPs-class), 3
- overlapping.features,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- overlapping.features<-  
(CorrelatedSNPs-class), 3
- overlapping.features<- ,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- pop.genotype (CorrelatedSNPs-class), 3
- pop.genotype,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- pop.genotype<- (CorrelatedSNPs-class), 3
- pop.genotype<- ,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- population (TagSNP-class), 14
- population,TagSNP-method  
(TagSNP-class), 14
- population<- (TagSNP-class), 14
- population<- ,TagSNP-method  
(TagSNP-class), 14
- position (TagSNP-class), 14
- position,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- position,TagSNP-method (TagSNP-class),  
14
- position<- (TagSNP-class), 14
- position<- ,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- position<- ,TagSNP-method  
(TagSNP-class), 14
- ref.allele (TagSNP-class), 14
- ref.allele,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- ref.allele,TagSNP-method  
(TagSNP-class), 14
- ref.allele<- (TagSNP-class), 14
- ref.allele<- ,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- ref.allele<- ,TagSNP-method  
(TagSNP-class), 14
- show,TagSNP-method (TagSNP-class), 14
- show,TList-method (TList-class), 17
- snpid (TagSNP-class), 14
- snpid,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- snpid,TagSNP-method (TagSNP-class), 14
- snpid<- (TagSNP-class), 14
- snpid<- ,CorrelatedSNPs-method  
(CorrelatedSNPs-class), 3
- snpid<- ,TagSNP-method (TagSNP-class), 14
- summary,TList-method (TList-class), 17
- TagSNP (TagSNP-class), 14
- TagSNP-class, 14
- TList (TList-class), 17
- TList-class, 17
- yafsnp.dprime (TagSNP-class), 14
- yafsnp.dprime,TagSNP-method  
(TagSNP-class), 14
- yafsnp.dprime<- (TagSNP-class), 14
- yafsnp.dprime<- ,TagSNP-method  
(TagSNP-class), 14
- yafsnp.pvalue (TagSNP-class), 14
- yafsnp.pvalue,TagSNP-method  
(TagSNP-class), 14
- yafsnp.pvalue<- (TagSNP-class), 14
- yafsnp.pvalue<- ,TagSNP-method  
(TagSNP-class), 14
- yafsnp.rsq (TagSNP-class), 14
- yafsnp.rsq,TagSNP-method  
(TagSNP-class), 14
- yafsnp.rsq<- (TagSNP-class), 14
- yafsnp.rsq<- ,TagSNP-method  
(TagSNP-class), 14