

Package ‘SWATH2stats’

April 16, 2019

Type Package

Title Transform and Filter SWATH Data for Statistical Packages

Version 1.12.1

Date 2018-11-30

Author Peter Blattmann, Moritz Heusel and Ruedi Aebersold

Maintainer Peter Blattmann <blattmann@imsb.biol.ethz.ch>

Description This package is intended to transform SWATH data from the OpenSWATH software into a format readable by other statistics packages while performing filtering, annotation and FDR estimation.

License GPL-3

Depends R(>= 2.10.0)

Imports data.table, reshape2, grid, ggplot2, stats, grDevices, graphics, utils, biomaRt

Suggests testthat, aLFQ, knitr, PECA

Enhances imsbInfer, MSstats

biocViews Proteomics, Annotation, ExperimentalDesign, Preprocessing, MassSpectrometry, ImmunoOncology

NeedsCompilation no

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/SWATH2stats>

git_branch RELEASE_3_8

git_last_commit af27a5f

git_last_commit_date 2018-11-30

Date/Publication 2019-04-15

R topics documented:

SWATH2stats-package	2
add_genesymbol	3
assess_decoy_rate	4
assess_fdr_byrun	5
assess_fdr_overall	6

convert4aLFQ	7
convert4mapDIA	8
convert4MSstats	9
convert4PECA	10
convert4pythonscript	11
convert_protein_ids	12
count_analytes	13
disaggregate	14
filter_all_peptides	14
filter_mscore	15
filter_mscore_fdr	16
filter_on_max_peptides	17
filter_on_min_peptides	18
filter_proteotypic_peptides	18
import_data	19
load_mart	20
mscore4assayfdr	21
mscore4pepfdr	22
mscore4protfdr	23
MSstats_data	24
OpenSWATH_data	24
plot.fdr_cube	25
plot.fdr_table	26
plot_correlation_between_samples	27
plot_variation	28
plot_variation_vs_total	29
reduce_OpenSWATH_output	30
removeDecoyProteins	31
sample_annotation	31
Spyogenes	32
Study_design	33
transform_MSstats_OpenSWATH	33
unifyProteinGroupLabels	34
write_matrix_peptides	35
write_matrix_proteins	36

Index	37
--------------	-----------

SWATH2stats-package	<i>SWATH2stats</i>
---------------------	--------------------

Description

This package is intended to transform SWATH data from the OpenSWATH software into a format readable by other statistics packages while performing filtering, annotation and FDR assessment.

Details

Package: SWATH2stats
Type: Package
Version: 1.9.3
Date: 2018-04-23
License: GPLv3

Author(s)

Peter Blattmann, Moritz Heusel and Ruedi Aebersold

Maintainer: Peter Blattmann <blattmann@imsb.biol.ethz.ch>

References

Blattmann P, Heusel M, Aebersold R. SWATH2stats: An R/Bioconductor Package to Process and Convert Quantitative SWATH-MS Proteomics Data for Downstream Analysis Tools. PLoS ONE 11(4): e0153160 (2016). doi: 10.1371/journal.pone.0153160.

Rost HL, Rosenberger G, Navarro P, Gillet L, Miladinovic SM, Schubert OT, Wolski W, Collins BC, Malmstrom J, Malmstrom L, Aebersold R. OpenSWATH enables automated, targeted analysis of data-independent acquisition MS data. Nature Biotechnology. 2014 Mar;32(3):219-23. doi: 10.1038/nbt.2841.

Choi M, Chang CY, Clough T, Broudy D, Killeen T, MacLean B, Vitek O. MSstats: an R package for statistical analysis of quantitative mass spectrometry-based proteomic experiments. Bioinformatics. 2014 Sep 1;30(17):2524-6. doi: 10.1093/bioinformatics/btu305.

Rosenberger G, Ludwig C, Rost HL, Aebersold R, Malmstrom L. aLFQ: an R-package for estimating absolute protein quantities from label-free LC-MS/MS proteomics data. Bioinformatics. 2014 Sep 1;30(17):2511-3. doi: 10.1093/bioinformatics/btu200.

Suomi T., Corthals G., Nevalainen O.S., and Elo L.L. (2015). Using Peptide-Level Proteomics Data for Detecting Differentially Expressed Proteins. J Proteome Res. Nov 6;14(11):4564-70. doi: 10.1021/acs.jproteome.5b00363.

Suomi, T. and Elo L.L. (2017). Enhanced differential expression statistics for data-independent acquisition proteomics" Scientific Reports 7, Article number: 5869. doi:10.1038/s41598-017-05949-y

add_genesymbol

add_genesymbol: Adds gene symbols to a table

Description

This function adds an additional gene or protein symbol to a table.

Usage

```
add_genesymbol(data_table, gene.ID.table, column.name = "Protein",  
ID1 = "uniprotswissprot", ID2 = "hgnc_symbol", id.separator = "/", copy_nonconverted = TRUE)
```

Arguments

<code>data_table</code>	A data frame or file name.
<code>gene.ID.table</code>	A dictionary table containing the original and new identifiers.
<code>column.name</code>	The column name where the original protein identifiers are present.
<code>ID1</code>	The type of the original protein identifiers.
<code>ID2</code>	The type of the converted protein identifiers.
<code>id.separator</code>	Separator between protein identifiers of shared peptides.
<code>copy_nonconverted</code>	Option defining if the identifiers that cannot be converted should be copied.

Value

Returns the data frame with an added column of the converted protein identifiers.

Note

Protein identifiers from shared peptides should be separated by a forward slash.

Author(s)

Peter Blattmann

Examples

```
gene.ID.table <- data.frame(uniprotswissprot = c("Q01581", "P49327", "P60709"),
hgnc_symbol = c("HMGCS1", "FASN", "ACTB"))
data_table <- data.frame(Protein = c("Q01581", "P49327", "2/P63261/P60709"),
Abundance = c(100, 3390, 43423))
add_genesymbol(data_table, gene.ID.table)
```

`assess_decoy_rate` *assess_decoy_rate: Assess decoy rate*

Description

This function counts the number of decoy peptides.

Usage

```
assess_decoy_rate(data)
```

Arguments

<code>data</code>	A data frame that contains at least a column named "FullPeptideName" and "decoy".
-------------------	---

Details

A printout is generated to indicate the number of non-decoy, decoy peptides and the rate of decoy vs non-decoy peptides. Unique peptides are counted, so a precursor with different charge states is counted as one peptide. In the column "decoy" the values need to be 1,0 or TRUE and FALSE.

Value

Prints the decoy rate.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data <- OpenSWATH_data
assess_decoy_rate(data)
```

assess_fdr_byrun	<i>Assess assay, peptide and protein level FDR by run (for each MS_injection separately) in OpenSWATH output table</i>
------------------	--

Description

This function estimates the assay, peptide and protein FDR by run in an OpenSWATH result table in dependence of a range of m_score cutoffs. The results can be visualized and summarized by the associated method plot.fdr_table(). It counts target and decoy assays (unique transition_group_id), peptides (unique FullPeptideName) and proteins (unique ProteinName) in the OpenSWATH output table in dependence of m-score cutoff, the useful m_score cutoff range is evaluated for each dataset individually on the fly.

To arrive from decoy counts at an estimation of the false discovery rate (false positives among the targets remaining at a given mscore cutoff) the ratio of false positives to true negatives (decoys) (FFT) must be supplied. It is estimated for each run individually by pyProphet and contained in the pyProphet statistics [Injection_name]_full_stat.csv. As an approximation, the FFTs of multiple runs are averaged and supplied as argument FFT. For further details see the Vignette Section 1.3 and 4.1.

To assess fdr over the entire dataset, please refer to function assess_fdr_overall.

FDR is calculated as $FDR = (TN * FFT / T)$; TN=decoys, T=targets, FFT=see above

Usage

```
assess_fdr_byrun(data, FFT, n.range = 20, output = "pdf_csv", plot = TRUE,
filename = "FDR_report_byrun", output_mscore_levels = c(0.01, 0.001))
```

Arguments

- data Annotated OpenSWATH/pyProphet output table. Refer to function sample_annotation from this package for further information.
- FFT Ratio of false positives to true negatives, q-values from [Injection_name]_full_stat.csv in pyProphet stats output. As an approximation, the q-values of multiple runs are averaged and supplied as argument FFT. Numeric from 0 to 1. Defaults to 1, the most conservative value (1 Decoy indicates 1 False target).
- n.range Option to set the number of magnitude for which the m_score threshold is decreased (e.g. n.range = 10, m-score from 0.1 until 10^-10)^.

output	Choose output type. "pdf_csv" creates the output as files in the working directory, "Rconsole" triggers delivery of the output to the console enabling further computation or custom plotting / output.
plot	Logical, whether or not to create plots from the results (using the associated method plot.fdr_cube())
filename	Optional, modifying the basename of the result files if applicable.
output_mscore_levels	Define m-score levels to plot and write the estimated FDR results.

Value

Returns an array of target/decoy identification numbers and calculated FDR values at different m-score cutoffs.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
assess_fdr_byrun(data, FFT=0.7, output = "pdf_csv", plot = TRUE,
filename="Testoutput_assess_fdr_byrun")
```

assess_fdr_overall	<i>Assess overall FDR in annotated OpenSWATH/pyProphet output table in dependence of m_score cutoff</i>
--------------------	---

Description

This function estimates the assay, peptide and protein FDR over a multi-run OpenSWATH/pyProphet output table. It counts target and decoy assays (unique transition_group_id), peptides (unique FullPeptideName) and proteins (unique ProteinName) in dependence of the m-score cutoff (1e-2 to 1e-20).

To arrive from decoy counts at an estimation of the false discovery rate (false positives among the targets remaining at a given mscore cutoff) the ratio of false positives to true negatives (decoys) (FFT) must be supplied. It is estimated for each run individually by pyProphet and contained in the pyProphet statistics [Injection_name]_full_stat.csv. As an approximation, the FFTs of multiple runs are averaged and supplied as argument FFT. For further details see the Vignette Section 1.3 and 4.1.

Protein FDR control on peak group quality level is a very strict filter and should be handled with caution.

FDR is calculated as $FDR = (TN * FFT / T)$; TN=decoys, T=targets, FFT=see above

Usage

```
assess_fdr_overall(data, FFT, n.range = 20, output = "pdf_csv", plot = TRUE,
filename="FDR_report_overall")
```

Arguments

data	Data table that is produced by the OpenSWATH/pyProphet workflow
n.range	Option to set the number of magnitude for which the <code>m_score</code> threshold is decreased (e.g. <code>n.range = 10</code> , <code>m-score</code> from 0.1 until 10^{-10}).
FFT	Ratio of false positives to true negatives, q-values from <code>[Injection_name]_full_stat.csv</code> in pyProphet stats output. As an approximation, the q-values of multiple runs are averaged and supplied as argument FFT. Numeric from 0 to 1. Defaults to 1, the most conservative value (1 Decoy indicates 1 False target).
output	Choose output type. "pdf_csv" creates the output as files in the working directory, "Rconsole" triggers delivery of the output to the console enabling further computation or custom plotting / output.
plot	Logical, whether or not to create plots from the results (using the associated method <code>plot.fdr_table()</code>)
filename	Optional, modifying the basename of the result files if applicable.

Value

Returns a list of class "fdr_table". If output "pdf_csv" and plot = TRUE were chosen, report files are written to the working folder.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
assess_fdr_overall(data, FFT=0.7, output = "Rconsole", plot = TRUE,
filename="Testoutput_assess_fdr_overall")
```

 convert4aLFQ

convert4aLFQ: Convert table into the format for aLFQ

Description

This functions selects the columns necessary for the aLFQ R package.

Usage

```
convert4aLFQ(data, annotation = TRUE, check_transitions = TRUE)
```

Arguments

data	A data frame containing the SWATH data in transition-level format
annotation	Option to indicate if the data has been annotated, i.e. if the columns Condition, Replicate, Run are present. If option is set to true it will write a new <code>run_id</code> as a string of the combination of these three columns.

check_transitions

Option if number of transitions should be checked. As input only transition-level data should be used and therefore this is checked. However, this makes the function slow and herewith be omitted.

Value

Returns a data frame in the appropriate format for aLFQ.

Author(s)

Peter Blattmann

References

Rosenberger G, Ludwig C, Rost HL, Aebersold R, Malmstrom L. aLFQ: an R-package for estimating absolute protein quantities from label-free LC-MS/MS proteomics data. *Bioinformatics*. 2014 Sep 1;30(17):2511-3. doi: 10.1093/bioinformatics/btu200.

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
raw <- disaggregate(data.filtered.decoy)
data.aLFQ <- convert4aLFQ(raw)
```

 convert4mapDIA

convert4mapDIA: Convert table into the format for mapDIA

Description

This functions selects the columns necessary for mapDIA.

Usage

```
convert4mapDIA(data, RT=FALSE)
```

Arguments

data	A data frame containing SWATH data.
RT	Option to export the retention times.

Value

Returns a data frame in the appropriate format for mapDIA.

Note

The table must not contain any technical replica, the intensity of technical replica is averaged. This function requires the package reshape2.

Author(s)

Peter Blattmann

References

Teo, G., et al. (2015). "mapDIA: Preprocessing and statistical analysis of quantitative proteomics data from data independent acquisition mass spectrometry." J Proteomics 129: 108-120.

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
raw <- disaggregate(data.filtered.decoy)
data.mapDIA <- convert4mapDIA(raw, RT=TRUE)
```

convert4MSstats

convert4MSstats: Convert table into the format for MSstats

Description

This functions selects the columns necessary for MSstats and renames them if necessary.

Usage

```
convert4MSstats(data, replace.values = TRUE, replace.colnames = TRUE,
replace.Unimod = TRUE)
```

Arguments

`data` A data frame containing SWATH data.

`replace.values` Option to indicate if negative and 0 values should be replaced with NA.

`replace.colnames` Option to indicate if column names should be renamed and columns reduced to the necessary columns for MSstats

`replace.Unimod` Option to indicate if Unimod Identifier should be replaced from ":" to "_".

Details

The necessary columns are selected and three columns renamed: FullPeptideName -> PeptideSequence Charge -> PrecursorCharge filename -> File

Value

Returns a data frame in the appropriate format for MSstats.

Author(s)

Peter Blattmann

References

Choi M, Chang CY, Clough T, Broudy D, Killeen T, MacLean B, Vitek O. MSstats: an R package for statistical analysis of quantitative mass spectrometry-based proteomic experiments. *Bioinformatics*. 2014 Sep 1;30(17):2524-6. doi: 10.1093/bioinformatics/btu305.

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
raw <- disaggregate(data.filtered.decoy)
data.mapDIA <- convert4MSstats(raw)
```

convert4PECA

convert4PECA: Convert table into the format for ROPECA

Description

This functions selects the columns necessary for ROPECA.

Usage

```
convert4PECA(data)
```

Arguments

data A data frame containing SWATH data.

Value

Returns a data frame in the appropriate format for ROPECA.

Note

The table must not contain any technical replica, the intensity of technical replica is averaged. This function requires the package reshape2.

Author(s)

Peter Blattmann

References

Suomi, T. and Elo L.L. (2017). "Enhanced differential expression statistics for data-independent acquisition proteomics" *Scientific Reports* 7, Article number: 5869. doi:10.1038/s41598-017-05949-y

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
data.PECA <- convert4PECA(data.filtered.decoy)
```

convert4pythonscript *convert4bashscript: Convert data into the format for running a bash script*

Description

This functions selects the columns suggested to run a python script to change the data from peptide-level to transition-level.

Usage

```
convert4pythonscript(data, replace.Unimod = TRUE)
```

Arguments

data A data frame containing SWATH data.

replace.Unimod Option to indicate if Unimod Identifier should be replaced form ":" to "_".

Details

The necessary columns are selected and the run column is renamed to filename for the script. The intensities are taken from the column `aggr_Peak_Area` and therefore the `Intensity` column is not exported.

Value

Returns a data frame in the appropriate format to be used by a custom python script stored in the `scripts` folder.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data,0.01)
data.pythonscript <- convert4pythonscript(data.filtered.decoy)
```

convert_protein_ids *convert_protein_ids: Convert protein ids*

Description

This function renames protein ids in a data frame or file

Usage

```
convert_protein_ids(data_table,
                    column.name = "Protein",
                    species = "hsapiens_gene_ensembl",
                    host = "www.ensembl.org",
                    mart = "ENSEMBL_MART_ENSEMBL",
                    ID1 = "uniprotswissprot",
                    ID2 = "hgnc_symbol",
                    id.separator = "/",
                    copy_nonconverted = TRUE,
                    verbose = FALSE)
```

Arguments

data_table	A data frame or file name.
column.name	The column name where the original protein identifiers are present. Default: "Protein".
species	The species of the protein identifiers in the term used by biomaRt (e.g. "hsapiens_gene_ensembl", "mmusculus_gene_ensembl", "drerio_gene_ensembl", etc.). Default: "hsapiens_gene_ensembl".
host	Path of the biomaRt database (e.g. "www.ensembl.org", "dec2017.archive.ensembl.org"). Default: "www.ensembl.org".
mart	The type of mart (e.g. "ENSEMBL_MART_ENSEMBL", etc.). Default: "ENSEMBL_MART_ENSEMBL"
ID1	The type of the original protein identifiers (e.g. "uniprotswissprot", "ensembl_peptide_id"). Default: "uniprotswissprot".
ID2	The type of the converted protein identifiers (e.g. "hgnc_symbol", "mgi_symbol", "external_gene_name"). Default: "hgnc_symbol".
id.separator	Separator between protein identifiers of shared peptides. Default: "/".
copy_nonconverted	Option defining if the identifiers that cannot be converted should be copied. Default: TRUE.
verbose	Option to write a file containing the version of the database used. Default: FALSE.

Value

Returns the data frame with an added column of the converted protein identifiers.

Note

Protein identifiers from shared peptides should be separated by a forward slash. The host of archived ensembl databases can be introduced as well (e.g. "dec2017.archive.ensembl.org")

Author(s)

Peter Blattmann

Examples

```
data_table <- data.frame(Protein = c("Q01581", "P49327", "2/P63261/P60709"),
  Abundance = c(100, 3390, 43423))
convert_protein_ids(data_table)
```

count_analytes

count_analytes: Counts analytes in different injections

Description

This functions counts the number of different peakgroups, peptides and proteins in different injections

Usage

```
count_analytes(data, column.levels = c("transition_group_id", "FullPeptideName",
  "ProteinName"), column.by="run_id", rm.decoy=TRUE)
```

Arguments

data	A data frame containing SWATH data.
column.levels	Columns in which different identifiers should be counted.
column.by	Column for which the different identifiers should be counted for, e.g. for the different injections.
rm.decoy	Option to not remove decoy before counting.

Value

Returns a data frame with the count of the different identifiers per e.g. injection.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
count_analytes(data)
```

disaggregate	<i>disaggregate: Transforms the SWATH data from a peptide- to a transition-level table.</i>
--------------	---

Description

If the SWATH data should be analyzed on transition-level the data needs to be transformed from peptide-level table to a transition-level table (one row per transition instead of one row per peptide). The columns "aggr_Fragment_Annotation" and "aggr_Peak_Area" are disaggregated into the new columns "FragmentIon" and "Intensity". The following columns are renamed if they exist: FullPeptideName -> PeptideSequence, Charge -> PrecursorCharge, Area -> Intensity, Fragment -> FragmentIon, Sequence -> NakedSequence.

Usage

```
disaggregate(data, all.columns = FALSE)
```

Arguments

data	A data frame containing SWATH data.
all.columns	Option that all columns are processed. Otherwise only the typical columns needed for downstream analysis are processed.

Value

Returns a data frame containing the SWATH data in a transition-level table.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
raw <- disaggregate(data.filtered.decoy)
```

filter_all_peptides	<i>Select all proteins that are supported by peptides.</i>
---------------------	--

Description

This functions counts all proteins that are supported by peptides (including non proteo-typic peptides). All peptides (incl. non proteotypic peptides) are selected. For the proteins supported by proteotypic peptide the "1/" in front of the identifier is removed to facilitate further data processing.

Usage

```
filter_all_peptides(data)
```

Arguments

data A data frame containing SWATH data.

Value

Returns a data frame with the data from both proteotypic and non-proteotypic peptides.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
data.all <- filter_all_peptides(data.filtered.decoy)
```

filter_mscore *filter_mscore: Filter openSWATH output table according to mscore*

Description

This function filters the SWATH data according to the m_score value, as well as to the number of occurrence in the data (requant) and within a condition (condition)

Usage

```
filter_mscore(data, mscore, rm.decoy=TRUE)
filter_mscore_freqobs(data, mscore, percentage=NULL, rm.decoy = TRUE)
filter_mscore_condition(data, mscore, n.replica, rm.decoy = TRUE)
```

Arguments

data A data frame containing SWATH data.

mscore Value that defines the mscore threshold according to which the data will be filtered.

n.replica Number of measurements within at least one condition that have to pass the mscore threshold for this transition.

percentage Percentage in which replicas the transition has to reach the mscore threshold

rm.decoy Option to remove the decoys during filtering.

Value

Returns a data frame with the filtered data.

Author(s)

Peter Blattmann

Examples

```

data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered <- filter_mscore(data, 0.01)
data.filtered <- filter_mscore_freqobs(data, 0.01, 0.8)
data.filtered <- filter_mscore_condition(data, 0.01, 3)

```

filter_mscore_fdr	<i>Filter annotated OpenSWATH/pyProphet output table to achieve a high FDR quality data matrix with controlled overall protein FDR and quantitative values for all peptides mapping to these high-confidence proteins (up to a desired overall peptide level FDR quality).</i>
-------------------	--

Description

This function controls the protein FDR over a multi-run OpenSWATH/pyProphet output table and filters all quantitative values to a desired overall/global peptide FDR level.

It first finds a suitable m-score cutoff to minimally achieve a desired global FDR quality on a protein master list based on the function `mscore4protfdr`. It then finds a suitable m-score cutoff to minimally achieve a desired global FDR quality on peptide level based on the function `mscore4pepfdr`. Finally, it reports all the peptide quantities derived based on the peptide level cutoff for only those peptides mapping to the protein master list. It further summarizes the protein and peptide numbers remaining after the filtering. It further evaluates the individual run FDR qualities of the peptides (and quantitation events) selected.

Usage

```

filter_mscore_fdr(data, FFT = 1, overall_protein_fdr_target = 0.02,
upper_overall_peptide_fdr_limit = 0.05, rm.decoy = TRUE)

```

Arguments

data	Annotated OpenSWATH/pyProphet data table
FFT	Ratio of false positives to true negatives, q-values from [Injection_name]_full_stat.csv in pyProphet stats output. As an approximation, the q-values of multiple runs are averaged and supplied as argument FFT. Numeric from 0 to 1. Defaults to 1, the most conservative value (1 Decoy indicates 1 False target). For further details see the Vignette Section 1.3 and 4.1.
overall_protein_fdr_target	FDR target for the protein master list for which quantitative values down to the less strict peptide_fdr criterion will be kept/reported. Defaults to 0.02.
upper_overall_peptide_fdr_limit	FDR target for the quantitative values kept/reported for all peptides mapping to the high-confidence protein master list. Defaults to 0.05. If all values up to m_score 0.01 shall be kept, set = 1.
rm.decoy	Logical T/F, whether decoy entries should be removed after the analysis. Defaults to TRUE. Can be useful to disable to track the influence on decoy fraction by further filtering steps such as requiring 2 peptides per protein.

Value

data.filtered the filtered data frame

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.fdr.filtered <- filter_mscore_fdr(data, FFT=0.7, overall_protein_fdr_target=0.02,
upper_overall_peptide_fdr_limit=0.1)
```

filter_on_max_peptides

Filter only for the highest intense peptides

Description

In order to reduce the data, the data is filtered only for the proteins with the highest intensity peptides.

Usage

```
filter_on_max_peptides(data, n_peptides, rm.decoy = TRUE)
```

Arguments

data	A data frame containing SWATH data with the column names: ProteinNames, PeptideSequence, PrecursorCharge, Intensity.
n_peptides	Maximum number of highest intense peptides to filter the data on.
rm.decoy	Option to remove the decoys during filtering.

Value

Returns a data frame of the filtered data

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered <- filter_mscore_freqobs(data, 0.01,0.8)
data.max <- filter_on_max_peptides(data.filtered, 5)
```

filter_on_min_peptides

Filter openSWATH output for proteins that are identified by a minimum of n independent peptides

Description

This function removes entries mapping to proteins that are identified by less than n_peptides.

Removing single-hit proteins from an analysis can significantly increase the sensitivity under strict protein fdr criteria, as evaluated by e.g. assess_fdr_overall.

Usage

```
filter_on_min_peptides(data, n_peptides, rm.decoy = TRUE)
```

Arguments

data	Data table that is produced by the openSWATH/iPortal workflow.
n_peptides	Number of minimal number of peptide IDs associated with a protein ID in order to be kept in the dataset.
rm.decoy	Option to remove the decoys during filtering.

Value

Returns the filtered data frame with only peptides that map to proteins with \geq n_peptides peptides.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered <- filter_mscore_freqobs(data, 0.01,0.8)
data.max <- filter_on_max_peptides(data.filtered, 5)
data.min.max <- filter_on_min_peptides(data.max, 3)
```

filter_proteotypic_peptides

Filter for proteins that are supported by proteotypic peptides.

Description

Peptides can match to several proteins. With this function proteotypic peptides, peptides that are only contained in one protein are selected. Additionally the number of proteins are counted and printed.

Usage

```
filter_proteotypic_peptides(data, rm.decoy = TRUE)
```

Arguments

data A data frame containing SWATH data.
rm.decoy Option to remove the decoys during filtering.

Value

Returns a data frame with only the data supported by proteotypic peptides.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")  
data("Study_design", package="SWATH2stats")  
data <- sample_annotation(OpenSWATH_data, Study_design)  
data.filtered.decoy <- filter_mscore(data, 0.01)  
data.all <- filter_proteotypic_peptides(data.filtered.decoy)
```

import_data	<i>import_data: Transforms the column names from a data frame to the required format.</i>
-------------	---

Description

This functions transforms the column names from a data frame from another format to a data frame with column names used by the OpenSWATH output and required for these functions. During executing of the function the corresponding columns for each column in the data need to be selected. For columns that do not correspond to a certain column 'not applicable' needs to be selected and the column names are not changed.

Usage

```
import_data(data)
```

Arguments

data A data frame containing the SWATH-MS data (one line per peptide precursor quantified) but with different column names.

Value

Returns the data frame in the appropriate format.

Note

List of column names of the OpenSWATH data:

ProteinName: Unique identifier for protein or proteingroup that the peptide maps to. Proteotypic peptides should be indicated by 1/ in order to be recognized as such by the function `filter_proteotypic_peptides`.

FullPeptideName: Unique identifier for the peptide.

Charge: Charge of the peptide precursor ion quantified.

Sequence: Naked peptide sequence without modifications.

aggr_Fragment_Annotation: aggregated annotation for the different Fragments quantified for this peptide. In the OpenSWATH results the different annotation in OpenSWATH are concatenated by a semicolon.

aggr_Peak_Area: aggregated Intensity values for the different Fragments quantified for this peptide. In the OpenSWATH results the aggregated Peak Area intensities are concatenated by a semicolon.

transition_group_id: A unique identifier for each transition group used.

decoy: Indicating with 1 or 0 if this transition group is a decoy.

m_score: Column containing the score that is used to estimate FDR or filter. M-score values of identified peak groups are equivalent to a q-value and thus typically are smaller than 0.01, depending on the confidence of identification (the lower the m-score, the higher the confidence).

Column containing the score that is used to estimate FDR or filter.

RT: Column containing the retention time of the quantified peak.

filename: Column containing the filename or a unique identifier for each injection.

Intensity: column containing the intensity value for each quantified peptide.

Columns needed for FDR estimation and filtering functions: ProteinName, FullPeptideName, transition_group_id, decoy, m_score

Columns needed for conversion to transition-level format (needed for MSSstats and mapDIA input): aggr_Fragment_Annotation, aggr_Peak_Area

Author(s)

Peter Blattmann

Examples

```
data('Spyogenes', package = 'SWATH2stats')
head(data)
str(data)
```

load_mart

load_mart: Load a biomart database

Description

This function loads a biomart database

Usage

```
load_mart(species, ensembl.path, mart, verbose = FALSE)
```

Arguments

species	The species of the protein identifiers in the term used by biomaRt (e.g. "hsapiens_gene_ensembl", "mmusculus_gene_ensembl", "drerio_gene_ensembl", etc.)
ensembl.path	Path of the biomaRt database.
mart	The species of the protein identifiers in the term used by biomaRt (e.g. "hsapiens_gene_ensembl", "mmusculus_gene_ensembl", "drerio_gene_ensembl", etc.)
verbose	Option to write a file containing the version of the database used.

Value

Returns the mart from biomaRt.

Note

Protein identifiers from shared peptides should be separated by a forward slash. The host of archived ensembl databases can be introduced as well (e.g. "dec2017.archive.ensembl.org")

Author(s)

Peter Blattmann

Examples

```
organism.mart <- load_mart("hsapiens_gene_ensembl", "www.ensembl.org", "ENSEMBL_MART_ENSEMBL")
class(organism.mart)
```

mscore4assayfdr	<i>Find m_score cutoff to reach a desired FDR on assay level (over the entire OpenSWATH/pyProphet output table)</i>
-----------------	---

Description

This function estimates the `m_score` cutoff required in a dataset to reach a given overall assay level FDR. It counts target and decoy assays at high resolution across the `m_score` cutoffs and reports a useful `m_score` cutoff - assay FDR pair close to the supplied `fdr_target` level over the entire dataset. The `m_score` cutoff is returned by the function and can be used in the context of the filtering functions, e.g.:

```
data.assayFDR1pc<-filter_mscore(data, mscore4assayfdr(data, fdr_target=0.01))
```

To arrive from decoy counts at an estimation of the false discovery rate (false positives among the targets remaining at a given `mscore` cutoff) the ratio of false positives to true negatives (decoys) (FFT) must be supplied. It is estimated for each run individually by pyProphet and contained in the pyProphet statistics [Injection_name]_full_stat.csv. As an approximation, the FFTs of multiple runs are averaged and supplied as argument FFT. For further details see the Vignette Section 1.3 and 4.1.

For FDR evaluations on peptide and protein level, please refer to functions `mscore4pepfdr` `mscore4protfdr`

Usage

```
mscore4assayfdr(data, FFT = 1, fdr_target = 0.01)
```

Arguments

data	Annotated OpenSWATH/pyProphet data table. See function sample_annotation from this package.
FFT	Ratio of false positives to true negatives, q-values from [Injection_name]_full_stat.csv in pyProphet stats output. As an approximation, the q-values of multiple runs are averaged and supplied as argument FFT. Numeric from 0 to 1. Defaults to 1, the most conservative value (1 Decoy indicates 1 False target).
fdr_target	Assay FDR target, numeric, defaults to 0.01. An m_score cutoff achieving an $FDR < fdr_target$ will be selected. Calculated as $FDR = (TN * FFT / T)$; TN=decoys, T=targets, FFT=see above.

Value

Returns the m_score cutoff selected to arrive at the desired FDR

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
mscore4assayfdr(data, FFT=0.7, fdr_target=0.01)
```

mscore4pepfdr	<i>Find m_score cutoff to reach a desired FDR on peptide level (over the entire OpenSWATH/pyProphet output table)</i>
---------------	---

Description

This function estimates the m_score cutoff required in a dataset to reach a given overall peptide level FDR. It counts target and decoy peptides (unique FullPeptideName) at high resolution across the m_score cutoffs and reports a useful m_score cutoff - peptide FDR pair close to the supplied fdr_target level over the entire dataset. The m_score cutoff is returned by the function and can be used in the context of the filtering functions, e.g.:

```
data.pepFDR2pc<-filter_mscore(data, mscore4pepfdr(data, fdr_target=0.02))
```

To arrive from decoy counts at an estimation of the false discovery rate (false positives among the targets remaining at a given mscore cutoff) the ratio of false positives to true negatives (decoys) (FFT) must be supplied. It is estimated for each run individually by pyProphet and contained in the pyProphet statistics [Injection_name]_full_stat.csv. As an approximation, the FFTs of multiple runs are averaged and supplied as argument FFT. For further details see the Vignette Section 1.3 and 4.1.

For FDR evaluations on assay and protein level, please refer to functions mscore4assayfdr mscore4protfdr

Usage

```
mscore4pepfdr(data, FFT = 1, fdr_target = 0.01)
```

Arguments

data	Annotated OpenSWATH/pyProphet data table. See function sample_annotation from this package.
FFT	Ratio of false positives to true negatives, q-values from [Injection_name]_full_stat.csv in pyProphet stats output. As an approximation, the q-values of multiple runs are averaged and supplied as argument FFT. Numeric from 0 to 1. Defaults to 1, the most conservative value (1 Decoy indicates 1 False target).
fdr_target	FDR target, numeric, defaults to 0.01. An m_score cutoff achieving an FDR < fdr_target will be selected. Calculated as $FDR = (TN * FFT / T)$; TN=decoys, T=targets, FFT=see above.

Value

Returns the m_score cutoff selected to arrive at the desired FDR

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
mscore4pepfdr(data, FFT=0.7, fdr_target=0.01)
```

mscore4protfdr	<i>Find m_score cutoff to reach a desired FDR on protein level (over the entire OpenSWATH/pyProphet output table)</i>
----------------	---

Description

This function estimates the m_score cutoff required in a dataset to reach a given overall protein level FDR. This filter is to be used with caution as the resulting quantitative matrix is relatively sparse. It can be filled with quantitative values at a lower FDR quality level. It counts target and decoy peptides (unique ProteinName) at high resolution across the m_score cutoffs and reports a useful m_score cutoff - peptide FDR pair close to the supplied fdr_target level over the entire dataset. The m_score cutoff is returned by the function and can be used in the context of the filtering functions, e.g.:

```
data.protFDR5pc<-filter_mscore(data, mscore4protfdr(data, fdr_target=0.02))
```

To arrive from decoy counts at an estimation of the false discovery rate (false positives among the targets remaining at a given mscore cutoff) the ratio of false positives to true negatives (decoys) (FFT) must be supplied. It is estimated for each run individually by pyProphet and contained in the pyProphet statistics [Injection_name]_full_stat.csv. As an approximation, the FFTs of multiple runs are averaged and supplied as argument FFT. For further details see the Vignette Section 1.3 and 4.1.

For FDR evaluations on assay and peptide level, please refer to functions mscore4assayfdr mscore4pepfdr

Usage

```
mscore4protfdr(data, FFT, fdr_target)
```

Arguments

data	Annotated OpenSWATH/pyProphet data table. See function <code>sample_annotation</code> from this package.
FFT	Ratio of false positives to true negatives, q-values from <code>[Injection_name]_full_stat.csv</code> in <code>pyProphet</code> stats output. As an approximation, the q-values of multiple runs are averaged and supplied as argument FFT. Numeric from 0 to 1. Defaults to 1, the most conservative value (1 Decoy indicates 1 False target).
fdr_target	FDR target, numeric, defaults to 0.01. An <code>m_score</code> cutoff achieving an $FDR < fdr_target$ will be selected. Calculated as $FDR = (TN * FFT / T)$; <code>TN</code> =decoys, <code>T</code> =targets, <code>FFT</code> =see above.

Value

Returns the `m_score` cutoff selected to arrive at the desired FDR quality

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
mscore4protfdr(data, FFT=0.7, fdr_target=0.01)
```

MSstats_data	<i>Testing dataset in MSstats format</i>
--------------	--

Description

A small table with the column names corresponding to the MSstats format. This data is intended only to test functions.

Author(s)

Peter Blattmann

OpenSWATH_data	<i>Testing dataset from OpenSWATH</i>
----------------	---------------------------------------

Description

A small selection of the data obtained from the iPortal pipeline for an experiment with perturbations relating to cholesterol regulation. Protein and Peptides have been anonymized as the data is unpublished. The FDR version of the test data contains modified (lowered) decoy peak group `m_scores` to simulate FDR behaviour of a large dataset.

Author(s)

Peter Blattmann

plot.fdr_cube	<i>Plot functionality for FDR assessment result arrays as produced by e.g. the function assess_fdr_byrun()</i>
---------------	--

Description

This function creates standard plots from result arrays as produced by e.g. the function `assess_fdr_byrun()`, visualizing assay, peptide and protein level FDR for each run at m-score cutoffs 1e-2 and 1e-3. Furthermore, Target and Decoy ID numbers are visualized.

Usage

```
## S3 method for class 'fdr_cube'  
plot(x, output = "Rconsole", filename = "FDR_report_byrun",  
plot_mscore_levels = c(0.01, 0.001), ...)
```

Arguments

x	Array of by-run FDR assessment results as produced e.g. by the function <code>assess_fdr_byrun()</code> from this package.
output	Choose output type. "pdf_csv" creates the output as files in the working directory, "Rconsole" triggers delivery of the output to the console enabling further computation and/or custom plotting / output.
filename	Basename for output files to be created (if output = "pdf_csv" has been selected).
plot_mscore_levels	Define m-score levels to plot the estimated FDR results.
...	further arguments passed to method.

Value

Plots in Rconsole or report files.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")  
data("Study_design", package="SWATH2stats")  
data <- sample_annotation(OpenSWATH_data, Study_design)  
x <- assess_fdr_byrun(data, FFT=0.7, output = "Rconsole", plot = FALSE)  
plot.fdr_cube(x, output = "pdf_csv", filename = "Assess_fdr_byrun_testplot",  
plot_mscore_levels=0.01)
```

plot.fdr_table	<i>Plot functionality for results of class "fdr_table" as produced by e.g. the function assess_fdr_overall()</i>
----------------	--

Description

This function created standard plots from results of class "fdr_table" as produced by e.g. the function assess_fdr_overall() visualizing ID numbers in dependence of estimated FDR and also estimated FDR in dependence of m_score cutoff.

Usage

```
## S3 method for class 'fdr_table'  
plot(x, output = "Rconsole", filename = "FDR_report_overall", ...)
```

Arguments

x	List of class "fdr_table" as produced e.g. by the function assess_fdr_overall() from this package.
output	Choose output type. "pdf_csv" creates the output as files in the working directory, "Rconsole" triggers delivery of the output to the console enabling further computation or custom plotting / output.
filename	Basename for output files to be created (if output = "pdf_csv" has been selected).
...	further arguments passed to method.

Value

Plots in Rconsole or report files.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")  
data("Study_design", package="SWATH2stats")  
data <- sample_annotation(OpenSWATH_data, Study_design)  
x <- assess_fdr_overall(data, FFT=0.7, output = "Rconsole", plot = FALSE)  
plot.fdr_table(x, output = "pdf_csv", filename = "Assess_fdr_overall_testplot")
```

`plot_correlation_between_samples`*Plots the correlation between injections.*

Description

This function plots the Pearson's and Spearman correlation between samples. If decoys are present these are removed before plotting.

Usage

```
plot_correlation_between_samples(data, column.values = "Intensity",  
Comparison = transition_group_id ~ Condition + BioReplicate,  
fun.aggregate = NULL, label=TRUE, ...)
```

Arguments

<code>data</code>	Data frame that is produced by the OpenSWATH/pyProphet workflow
<code>column.values</code>	Indicates the columns for which the correlation is assessed. This can be the Intensity or Signal, but also the retention time.
<code>Comparison</code>	The comparison for assessing the variability. Default is to assess the variability per <code>transition_group_id</code> over the different Condition and Replicates. Comparison is performed using the <code>dcast()</code> function of the <code>reshape2</code> package.
<code>fun.aggregate</code>	If for the comparison values have to be aggregated one needs to provide the function here.
<code>label</code>	Option to print correlation value in the plot.
<code>...</code>	further arguments passed to method.

Value

Plots in Rconsole a correlation heatmap and returns the data frame used to do the plotting.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")  
data("Study_design", package="SWATH2stats")  
data <- sample_annotation(OpenSWATH_data, Study_design)  
plot_correlation_between_samples(data)
```

plot_variation	<i>Plots the coefficient of variation for different replicates</i>
----------------	--

Description

This function plots the coefficient of variation within replicates for a given value. If decoys are present these are removed before plotting.

Usage

```
plot_variation(data, column.values = "Intensity",
  Comparison = transition_group_id + Condition ~ BioReplicate,
  fun.aggregate = NULL, label=TRUE, ...)
```

Arguments

data	Data frame that is produced by the OpenSWATH/pyProphet workflow
column.values	Indicates the columns for which the variation is assessed. This can be the Intensity or Signal, but also the retention time.
Comparison	The comparison for assessing the variability. Default is to assess the variability per transition_group_id and Condition over the different Replicates. Comparison is performed using the dcast() function of the reshape2 package.
fun.aggregate	If for the comparison values have to be aggregated one needs to provide the function here.
label	Option to print value of median cv.
...	further arguments passed to method.

Value

Returns a list with the data and calculated cv and a table that summarizes the mean, median and mode cv per Condition (if Condition is contained in the comparison). In addition it plots in Rconsole a violin plot with the observed coefficient of variations.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
plot_variation(data)
```

`plot_variation_vs_total`*Plots the total variation versus variation within replicates*

Description

This function plots the total variation and the variation within replicates for a given value. If decoys are present these are removed before plotting.

Usage

```
plot_variation_vs_total(data, column.values = "Intensity",
  Comparison1 = transition_group_id ~ BioReplicate + Condition,
  Comparison2 = transition_group_id + Condition ~ BioReplicate,
  fun.aggregate = NULL, label=TRUE, ...)
```

Arguments

<code>data</code>	Data table that is produced by the OpenSWATH/pyProphet workflow
<code>column.values</code>	Indicates the columns for which the variation is assessed. This can be the Intensity or Signal, but also the retention time.
<code>Comparison1</code>	The comparison for assessing the total variability. Default is to assess the variability per <code>transition_group_id</code> over the combination of Replicates and different Conditions.
<code>Comparison2</code>	The comparison for assessing the variability within the replicates. Default is to assess the variability per <code>transition_group_id</code> and <code>Condition</code> over the different Replicates.
<code>fun.aggregate</code>	If depending on the comparison values have to be aggregated one needs to provide the function here.
<code>label</code>	Option to print value of median cv.
<code>...</code>	further arguments passed to method.

Value

Plots in Rconsole a violin plot comparing the total variation with the variation within replicates. In addition it returns the data frame from which the plotting is done and a table with the calculated mean, median and mode of the cv for the total or replicate data.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
plot_variation_vs_total(data)
```

`reduce_OpenSWATH_output`*Reduce columns of OpenSWATH data*

Description

This function selects the columns from the standard OpenSWATH output to column needed for MSstats, aLFQ and mapDIA.

Usage

```
reduce_OpenSWATH_output(data, column.names=NULL)
```

Arguments

`data` A data frame containing SWATH data.
`column.names` A vector of column names that can be selected.

Value

Returns a data frame with the selected columns.

Note

A basic set of columns are defined in the function and are used if no column names are indicated

Note

The `column.names` can be omitted and then the following columns are selected that are needed for MSstats and mapDIA analysis: ProteinName, FullPeptideName, Sequence, Charge, aggr_Fragment_Annotation, aggr_Peak_Area, filename, m_score, decoy, Intensity, RT. This function should be omitted if the data is analyzed afterwards with the aLFQ or imsbInfer package that needs further columns.

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered <- reduce_OpenSWATH_output(data)
```

removeDecoyProteins	<i>Removes decoy proteins from the protein group label</i>
---------------------	--

Description

There exist peptides annotated as protein groups with 2/ProteinA/DECOY_ProteinB. However these are in principal proteotypic peptides and should be annotated 1/ProteinA. This function changes these labels accordingly. The subfunction rmDecoyProt removes the Decoy protein, calling removeDecoyProteins also changes the number before the protein group accordingly.

Usage

```
removeDecoyProteins(data)
```

Arguments

data A data frame containing SWATH data.

Value

Returns a data frame with changed protein labels.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
data.2 <- removeDecoyProteins(data.filtered.decoy)
```

sample_annotation	<i>sample_annotation: Annotate the SWATH data with the sample information</i>
-------------------	---

Description

For statistical analysis and filtering the measurements need to be annotated with Filename, Condition, BioReplicate, and Run. This function takes this information from a txt file containing this meta-data.

Usage

```
sample_annotation(data, sample.annotation, data.type="OpenSWATH",
column.file = "filename", change.run.id = TRUE, verbose=FALSE)
```

Arguments

<code>data</code>	A data frame containing SWATH data.
<code>sample.annotation</code>	A data frame containing the columns: Filename, Condition, BioReplicate, Run. The values contained in the column filename have to be present in the filename of the SWATH data.
<code>data.type</code>	Option to specify the format of the table, if the column names from an OpenSWATH output or MSstats table are used.
<code>column.file</code>	Option to specify the column name where the injection file is specified. Default is set to "filename".
<code>change.run.id</code>	Option to choose if the run_id column shall be reassigned to a unique value combining the values of Condition, BioReplicate and Run. (Option only possible if data is of format "OpenSWATH")
<code>verbose</code>	Option to turn on reporting on which filename it is working on.

Value

Returns a dataframe with each row annotated for the study design

Author(s)

Peter Blattmann

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
```

Spyogenes

S.pyogenes example data

Description

A table containing SWATH-MS data from *S.pyogenes*

Source This table was generated from the original data deposited on PeptideAtlas (PASS00289, file "rawOpenSwathResults_1pcnt_only.tsv") by selecting only the column necessary for the SWATH2stats.

References Rost, H. L., et al. (2014). OpenSWATH enables automated, targeted analysis of data-independent acquisition MS data. *Nat Biotechnol* 32(3): 219-223.

Study_design

*Study design table***Description**

A table containing the meta-data defining the study design.

Filename A unique identifier corresponding to the filename in the SWATH data.

Condition The Condition explains the perturbation performed on this sample.

BioReplicate Number indicating the biological replicate of this sample.

Run A unique number for each MS-injection.

Author(s)

Peter Blattmann

Source

Peter Blattmann

transform_MSstats_OpenSWATH

transform_MSstats_OpenSWATH: Transforms column names to OpenSWATH column names

Description

This functions transforms the column names from a data frame in MSstats format to a data frame with column names used by the OpenSWATH output. The original table needs to contain at least the 10 columns defined by MSstats: ProteinName, PeptideSequence, PrecursorCharge, FragmentIon, ProductCharge, IsotopeLabelType, Condition, BioReplicate, Run, Intensity.)

Usage

```
transform_MSstats_OpenSWATH(data)
```

Arguments

data A data frame containing the SWATH data in the MSstats format

Value

Returns the data frame in the appropriate format.

Author(s)

Peter Blattmann

References

Choi M, Chang CY, Clough T, Broudy D, Killeen T, MacLean B, Vitek O. MSstats: an R package for statistical analysis of quantitative mass spectrometry-based proteomic experiments. *Bioinformatics*. 2014 Sep 1;30(17):2524-6. doi: 10.1093/bioinformatics/btu305.

Examples

```
data("MSstats_data", package="SWATH2stats")
transform_MSstats_OpenSWATH(MSstats_data)
```

unifyProteinGroupLabels

Unify the protein group labels

Description

Unify the protein group labels (2/ProteinA/ProteinB and 2/ProteinB/ProteinA) to one common label (e.g. 2/ProteinA/ProteinB)

Usage

```
unifyProteinGroupLabels(data)
```

Arguments

data A data frame containing SWATH data.

Value

Returns a data frame with the unified protein labels.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")
data("Study_design", package="SWATH2stats")
data <- sample_annotation(OpenSWATH_data, Study_design)
data.filtered.decoy <- filter_mscore(data, 0.01)
data.unified <- unifyProteinGroupLabels(data.filtered.decoy)
```

`write_matrix_peptides` *write_matrix_peptides: Writes out an overview matrix of peptides mapping to a FDR quality controlled protein master list at controlled global peptide FDR quality.*

Description

Writes out an overview matrix on peptide level of a supplied (unfiltered or prefiltered) OpenSWATH results data frame. The peptide quantification is achieved by summing the areas under all 6 transitions per precursor and summing all precursors per FullPeptideName. In order to keep the peptide-to-protein association, the FullPeptideName is joined with the ProteinName.

Usage

```
write_matrix_peptides(data, write.csv=FALSE,  
filename = "SWATH2stats_overview_matrix_peptidelevel.csv",  
rm.decoy = FALSE)
```

Arguments

<code>data</code>	A data frame containing annotated OpenSWATH/pyProphet data.
<code>write.csv</code>	Option to determine if table should be written automatically into csv file.
<code>filename</code>	File base name of the .csv matrix written out to the working folder
<code>rm.decoy</code>	Logical whether decoys will be removed from the data matrix. Defaults to FALSE. It's sometimes useful to know how decoys behave across a dataset and how many you allow into your final table with the current filtering strategy.

Value

No return value, output .csv matrix is written to the working folder.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")  
data("Study_design", package="SWATH2stats")  
data <- sample_annotation(OpenSWATH_data, Study_design)  
write_matrix_peptides(data)
```

`write_matrix_proteins` *write_matrix_proteins*: Writes out an overview matrix of summed signals per protein identifier (lines) over run_id(columns).

Description

Writes out an overview matrix on protein level of a supplied (unfiltered or filtered) OpenSWATH results data frame. The protein quantification is achieved by summing the areas under all 6 transitions per precursor, summing all precursors per FullPeptideName and all FullPeptideName signals per ProteinName entry.

This function does not select consistently quantified or top peptides but sums all signals available that may or may not originate from the same set of peptides across different runs. A more detailed overview can be generated using the function `write_matrix_peptides()`.

Peptide selection can be achieved upstream using e.g. the functions `filter_mscore_requant()`, `filter_on_max_peptides()` and `filter_on_min_peptides()`.

Usage

```
write_matrix_proteins(data, write.csv = FALSE,  
filename = "SWATH2stats_overview_matrix_proteinlevel.csv",  
rm.decoy = FALSE)
```

Arguments

<code>data</code>	A data frame containing annotated OpenSWATH/pyProphet data.
<code>write.csv</code>	Option to determine if table should be written automatically into csv file.
<code>filename</code>	File base name of the .csv matrix written out to the working folder
<code>rm.decoy</code>	Logical whether decoys will be removed from the data matrix. Defaults to FALSE. It's sometimes useful to know how decoys behave across a dataset and how many you allow into your final table with the current filtering strategy.

Value

No return value, output .csv matrix is written to the working folder.

Author(s)

Moritz Heusel

Examples

```
data("OpenSWATH_data", package="SWATH2stats")  
data("Study_design", package="SWATH2stats")  
data <- sample_annotation(OpenSWATH_data, Study_design)  
write_matrix_proteins(data)
```

Index

- *Topic **SWATH2stats**
 - SWATH2stats-package, 2
- add_genesymbol, 3
- assess_decoy_rate, 4
- assess_fdr_byrun, 5
- assess_fdr_overall, 6

- convert4aLFQ, 7
- convert4mapDIA, 8
- convert4MSstats, 9
- convert4PECA, 10
- convert4pythonscript, 11
- convert_protein_ids, 12
- count_analytes, 13

- disaggregate, 14

- filter_all_peptides, 14
- filter_mscore, 15
- filter_mscore_condition (filter_mscore), 15
- filter_mscore_fdr, 16
- filter_mscore_freqobs (filter_mscore), 15
- filter_on_max_peptides, 17
- filter_on_min_peptides, 18
- filter_proteotypic_peptides, 18

- import_data, 19

- load_mart, 20

- mscore4assayfdr, 21
- mscore4pepfdr, 22
- mscore4protfdr, 23
- MSstats_data, 24

- OpenSWATH_data, 24
- OpenSWATH_data_FDR (OpenSWATH_data), 24

- plot.fdr_cube, 25
- plot.fdr_table, 26
- plot_correlation_between_samples, 27
- plot_variation, 28

- plot_variation_vs_total, 29

- reduce_OpenSWATH_output, 30
- removeDecoyProteins, 31
- rmDecoyProt (removeDecoyProteins), 31

- sample_annotation, 31
- Spyogenes, 32
- Study_design, 33
- SWATH2stats (SWATH2stats-package), 2
- SWATH2stats-package, 2

- transform_MSstats_OpenSWATH, 33

- unifyProteinGroupLabels, 34

- write_matrix_peptides, 35
- write_matrix_proteins, 36