

Package ‘seqCAT’

October 16, 2019

Title High Throughput Sequencing Cell Authentication Toolkit

Version 1.6.3

Description The seqCAT package uses variant calling data (in the form of VCF files) from high throughput sequencing technologies to authenticate and validate the source, function and characteristics of biological samples used in scientific endeavours.

Depends R (>= 3.6), GenomicRanges (>= 1.26.4), VariantAnnotation(>= 1.20.3)

Imports dplyr (>= 0.5.0), GenomeInfoDb (>= 1.13.4), ggplot2 (>= 2.2.1), grid (>= 3.5.0), IRanges (>= 2.8.2), lazyeval (>= 0.2.0), methods, rlang, scales (>= 0.4.1), S4Vectors (>= 0.12.2), stats, SummarizedExperiment (>= 1.4.0), tidyr (>= 0.6.1), utils

Suggests knitr, BiocStyle, rmarkdown, testthat, BiocManager

biocViews Coverage, GenomicVariation, Sequencing, VariantAnnotation

License MIT + file LICENCE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/seqCAT>

git_branch RELEASE_3_9

git_last_commit f8f03b3

git_last_commit_date 2019-08-14

Date/Publication 2019-10-15

Author Erik Fasterius [aut, cre]

Maintainer Erik Fasterius <erik.fasterius@outlook.com>

R topics documented:

calculate_similarity	2
compare_many	3
compare_profiles	4
create_profile	4

create_profiles	5
filter_variants	6
list_cosmic	7
list_variants	8
plot_heatmap	8
plot_impacts	9
plot_variant_list	10
read_cosmic	11
read_profile	11
read_profiles	12
seqCAT	13
test_comparison	13
test_profile_1	14
test_profile_2	15
test_profile_3	16
test_similarities	16
test_variant_list	17

Index	18
--------------	-----------

calculate_similarity *SNV profile similarity calculations*

Description

Calculate the similarity statistics for SNV profile comparisons.

Usage

```
calculate_similarity(data, similarity = NULL, a = 1, b = 5)
```

Arguments

data	The input SNV data dataframe.
similarity	Optional dataframe to add results to.
a	Similarity score parameter a (integer).
b	Similarity score parameter b (integer).

Details

This function calculates various summary statistics and sample similarities for a given profile comparison dataframe. It returns a small dataframe with the overall similarity score (whose parameters ‘a’ and ‘b’ can be adjusted in the function call), total SNV data, the concordance of the data and the sample names in question. This dataframe can also be given to the function, in which case it will simply add another row for the current samples, facilitating downstream aggregate analyses.

Value

A dataframe with summary statistics.

Examples

```
# Load test data
data(test_comparison)

# Calculate similarities
similarity <- calculate_similarity(test_comparison)

# Add another row of summary statistics
calculate_similarity(test_comparison, similarity = similarity)
```

compare_many	<i>Comparisons of many SNV profiles</i>
--------------	---

Description

Overlap and compare genotypes in many SNV profiles.

Usage

```
compare_many(many, one = NULL, a = 1, b = 5)
```

Arguments

many	SNV profiles to be compared (list of GRanges objects).
one	SNV profile to be compared to all others (GRanges object).
a	Similarity score parameter a (integer).
b	Similarity score parameter b (integer).

Details

This is a function that compares all the combinations of the SNV profiles input to it, either in a one-to-many or many-to-many manner. It returns both a dataframe containing summary statistics for all unique combinations and a list of dataframes with all the performed comparisons, for easy re-use and downstream analyses of said comparisons.

Value

A list of summary statistics and comparisons.

Examples

```
# Load test data
data(test_profile_1)
data(test_profile_2)

# Perform many-to-many comparisons
profiles <- list(test_profile_1, test_profile_2)
comparisons <- compare_many(profiles)

# View aggregate similarities
## Not run: comparisons[[1]]

# View data of first comparison
## Not run: head(comparisons[[2]][[1]])
```

compare_profiles	<i>Binary SNV profile comparisons</i>
------------------	---------------------------------------

Description

Overlap and compare genotypes in two SNV profiles.

Usage

```
compare_profiles(profile_1, profile_2, mode = "intersection")
```

Arguments

profile_1	The first SNV profile (GRanges object).
profile_2	The second SNV profile (GRanges object).
mode	Merge profiles using "union" or "intersection" (character).

Details

This is a function for finding overlapping variants in two different SNV profiles (stored as GenomicRanges objects), followed by comparing the genotypes of the overlapping variants. The "compare_overlaps" function calls the "add_metadata" function twice in succession in order to merge the metadata for the two profiles (supplied as GRanges objects), returns the results as a dataframe, compares the genotypes of the overlapping variants using the "compare_genotypes" function and, finally, returns the final dataframe with all variant overlaps and their similarity.

Value

A dataframe.

Examples

```
# Load test data
data(test_profile_1)
data(test_profile_2)

# Compare the two profiles
comparison <- compare_profiles(test_profile_1, test_profile_2)
```

create_profile	<i>SNV profile creation</i>
----------------	-----------------------------

Description

Create an SNV profile from data in a VCF file.

Usage

```
create_profile(vcf_file, sample, output_file, min_depth = 10,
              filter = TRUE, python = FALSE)
```

Arguments

vcf_file	The VCF file from which the profile will be created (path).
sample	The sample in the VCF for which a profile will be created (character).
output_file	The output file with the SNV profile (path).
min_depth	Remove variants below this sequencing depth (integer).
filter	Remove variants not passing filtering criteria (boolean).
python	Extract variants using Python instead of R (boolean).

Details

This function creates a SNV profile from a given VCF file by extracting the variants that pass the filtering criterias. It can either be performed using R, or by the create_profile.py function included (which requires that Python is installed, along with the PyVCF package). Profile creation is performed to facilitate and accelerate the cell authentication procedures, which is especially relevant when more than one pairwise comparison will be performed on the same sample.

Value

Does not return any data object, but outputs results to output_file (to save computational time from having to repeatedly create profiles).

Examples

```
# Path to the test VCF file
vcf_file = system.file("extdata", "test.vcf.gz", package = "seqCAT")

# Create SNV profiles
## Not run:
create_profile(vcf_file, "sample1", "profile1.txt")
create_profile(vcf_file, "sample1", "profile1.txt", min_depth = 15)
create_profile(vcf_file, "sample1", "profile1.txt", python = TRUE)

## End(Not run)
```

create_profiles	<i>SNV profile creation</i>
-----------------	-----------------------------

Description

Create SNV profiles from all VCF files in a directory

Usage

```
create_profiles(vcf_dir, output_dir = ".", pattern = NULL,
               recursive = FALSE, min_depth = 10, filter = TRUE, python = FALSE)
```

Arguments

vcf_dir	The VCF directory from which the profiles will be created (path).
output_dir	The output directory to put the SNV profiles in (path).
pattern	Only create profiles for a subset of files corresponding to this pattern (character).
recursive	Find VCF files recursively in sub-directories as well (boolean).
min_depth	Remove variants below this sequencing depth (integer).
filter	Remove variants not passing filtering criteria (boolean).
python	Extract variants using Python instead of R (boolean).

Details

This functions is a convenience-wrapper for the ‘create_profile’ function, which will create SNV profiles for each and every VCF file in the provided directory. The file naming scheme used is ‘<sample>.vcf’ and will dictate the output profile filenames.

Value

Does not return any data object, but outputs results to output_dir (to save computational time from having to repeatedly create profiles).

Examples

```
# Path to the test VCF directory
vcf_dir = system.file("extdata", package = "seqCAT")

# Create SNV profiles
## Not run:
create_profiles(vcf_dir, output_dir = "profiles")
create_profiles(vcf_dir, output_dir = "profiles", pattern = "test")
create_profiles(vcf_dir, output_dir = "profiles", recursive = TRUE)

## End(Not run)
```

filter_variants	<i>Variant filtering</i>
-----------------	--------------------------

Description

Filter variants on sequencing depth.

Usage

```
filter_variants(data, min_depth = 10)
```

Arguments

data	The dataframe containing the variant data to be filtered.
min_depth	Threshold for variant depth (integer; default 10).

Details

This is a function for filtering variants on sequencing depth. Variants with a depth lower than 10 are removed by default, but can be changed in the function call.

Value

A data frame containing the filtered variants.

Examples

```
# Load test comparisons
data(test_comparison)

# Filter variants
filt_1 <- filter_variants(test_comparison)
filt_2 <- filter_variants(test_comparison, min_depth = 20)
```

list_cosmic	<i>List COSMIC sample names</i>
-------------	---------------------------------

Description

List all available samples in the COSMIC database

Usage

```
list_cosmic(file_path)
```

Arguments

file_path The file containing COSMIC data (path).

Details

This function lists the available sample names in the provided COSMIC file (e.g. CosmicCLP_MutantExport.tsv.gz), and takes about half the time it takes to read the full file with the read_cosmic function, making it useful for just seeing if your particular sample is listed in COSMIC or not.

Value

A vector of sample names

Examples

```
file <- system.file("extdata",
                    "subset_CosmicCLP_MutantExport.tsv.gz",
                    package = "seqCAT")
cosmic_samples <- list_cosmic(file)
```

list_variants	<i>List known variants</i>
---------------	----------------------------

Description

List known variants present in SNV profiles

Usage

```
list_variants(profiles, known_variants)
```

Arguments

profiles The SNV profiles to analyse (list)
known_variants The known variants to look for (dataframe)

Details

This is a function for listing known variants present in SNV profiles. Input is a list of profiles and a dataframe of known variants, containing at least the genomic locations ("chr" and "pos"). Any additional columns will be retained.

Value

A dataframe containing the known variant genotypes in each profile.

Examples

```
# Load test data
data(test_profile_1)
data(test_profile_2)

# Create some variants to analyse
known_variants <- data.frame(chr = 1, pos = 16229, gene = "DDX11L1")

# List the known variants in each profile
profiles <- list(test_profile_1, test_profile_2)
known_variants <- list_variants(profiles, known_variants)
```

plot_heatmap	<i>Plot similarity heatmap</i>
--------------	--------------------------------

Description

Plot a heatmap of similarities from many-to-many SNV profile comparisons.

Usage

```
plot_heatmap(similarities, cluster = TRUE, annotate = TRUE,
  annotate_size = 9, legend = TRUE, legend_size = c(36, 8),
  limits = c(0, 50, 90, 100), text_size = 14, colour = "#1954A6")
```


Arguments

similarities	The long-format dataframe containing the data.
cluster	Cluster the samples based on similarity (boolean).
annotate	Annotate each cell with the score (boolean).
annotate_size	Text size of the annotations (numeric).
legend	Show a legend for the colour gradient (boolean).
legend_size	Height and width of the legend (vector of two integers).
limits	The limits for the colour gradient (vector of four integers).
text_size	Text size for axes, labels and legend (numeric).
colour	The main colour to use for the gradient (character).

Details

This function creates publication-ready plots of heatmaps for many-to-many sample comparisons, taking a long-format dataframe containing the summary statistics of each comparison as input.

Value

A ggplot2 graphical object.

Examples

```
# Load test similarities
data(test_similarities)

# Plot a similarity heatmap
heatmap <- plot_heatmap(test_similarities)
```

plot_impacts	<i>Plot SNV impact distribution</i>
--------------	-------------------------------------

Description

Plot SNV impact distributions for a binary SNV profile comparison.

Usage

```
plot_impacts(comparison, legend = TRUE, annotate = TRUE,
  annotate_size = 9, text_size = 14, palette = c("#0D2D59",
  "#1954A6"))
```

Arguments

comparison	The SNV profile comparison to be plotted.
legend	Show the legend (boolean).
annotate	Annotate each category (boolean).
annotate_size	Text size for annotations (numeric).
text_size	Text size for axes, ticks and legend (numeric).
palette	Colour palette for filling of bars (character vector).

Details

This function creates publication-ready plots of the impact distribution from a binary dataset comparison across the matched/mismatched SNVs.

Value

A ggplot2 graphical object.

Examples

```
# Load test comparison data
data(test_comparison)

# Plot the impact distribution
impacts <- plot_impacts(test_comparison)
```

plot_variant_list *Plot known variants list*

Description

Plot a genotype grid from a list of known variants

Usage

```
plot_variant_list(variant_list, legend = TRUE, legend_size = 22,
  text_size = 14, palette = c("#4e8ce4", "#a6c6f2", "#999999",
  "#cccccc"))
```

Arguments

variant_list	The data containing the variants (dataframe)
legend	Show a legend for the genotype colours (boolean)
legend_size	Size of the legend (numeric).
text_size	Text size for axes and legend (numeric).
palette	Nucleotide colour palette (4-element character vector)

Details

This function creates publication-ready plots from lists of known variants, taking a dataframe containing all the genotypes (on "A1/A2" format) for each sample (columns) and variant (row names).

Value

A ggplot2 graphical object.

Examples

```
# Load test variant list
data(test_variant_list)

# Plot each variant's genotype per sample
genotype_grid <- plot_variant_list(test_variant_list)
```

read_cosmic	<i>Read COSMIC data</i>
-------------	-------------------------

Description

Read COSMIC sample-specific mutational data.

Usage

```
read_cosmic(file_path, sample_name)
```

Arguments

file_path	The COSMIC data file path (path).
sample_name	The sample to be investigated (character).

Details

This function reads the COSMIC data files (e.g. "CosmicCLP_MutantExport.tsv.gz") and returns a GRanges object with all the listed mutations for the specified sample, which can then be use in downstream profile comparisons. Only non-duplicated (gene-level) SNVs are included in COSMIC profiles.

Value

A GRanges object with COSMIC SNVs.

Examples

```
# Path to COSMIC test data
file <- system.file("extdata",
                   "subset_CosmicCLP_MutantExport.tsv.gz",
                   package = "seqCAT")

# Read COSMIC test data for the HCT116 cell line
cosmic_hct116 <- read_cosmic(file, "HCT116")
```

read_profile	<i>Read SNV profile</i>
--------------	-------------------------

Description

Read an SNV profile for use in downstream comparisons.

Usage

```
read_profile(file, sample_name, remove_mt = TRUE)
```

Arguments

file The SNV profile to be read (path).
sample_name The sample of the SNV profile (character).
remove_mt Remove or keep mitochondrial variants (boolean).

Details

This is a function for reading SNV profiles created from VCF files. The data is returned as a GenomicRanges object, suitable for merging of metadata.

Value

A GRanges object.

Examples

```
# Path to test data
profile = system.file("extdata",
                      "test_1.profile.txt.gz",
                      package = "seqCAT")

# Read test profile
profile_1 <- read_profile(profile, "sample1")
profile_1 <- read_profile(profile, "sample1", remove_mt = FALSE)
```

read_profiles	<i>Read SNV profiles</i>
---------------	--------------------------

Description

Read SNV profiles in a directory.

Usage

```
read_profiles(profile_dir, remove_mt = TRUE)
```

Arguments

profile_dir The directory containing the profiles to be read (path).
remove_mt Remove or keep mitochondrial variants (boolean).

Details

This is a wrapper function for reading multiple SNV profiles present in a directory (and its sub-directories in recursive mode).

Value

A list of GRanges objects.

Examples

```
# Path to test data
profile_dir = system.file("extdata",
                          package = "seqCAT")

# Read test profiles
profile_list <- read_profiles(profile_dir)
```

seqCAT

*seqCAT: High Throughput Sequencing Cell Authentication Toolkit***Description**

The **seqCAT** package provides a number of functions for performing evaluation, characterisation and authentication of biological samples through analysis of high throughput sequencing data.

test_comparison

*Overlapping and compared SNVs***Description**

Overlapping and compared variants from "sample1" and "sample2" originating from the example.vcf file included in the inst/extdata directory, for use in unit tests.

Usage

```
data(test_comparison)
```

Format

A dataframe with 51 rows and 39 columns:

chr chromosome

pos SNV position

DP.sample_1 total variant depth, sample 1

AD1.sample_1 allelic depth, allele 1, sample 1

AD2.sample_1 allelic depth, allele 2, sample 1

A1.sample_1 allele 1, sample 1

A2.sample_1 allele 2, sample 1

warnings.sample_1 warnings from variant calling, sample 1

DP.sample_2 total variant depth, sample 2

AD1.sample_2 allelic depth, allele 1, sample 2

AD2.sample_2 allelic depth, allele 2, sample 2

A1.sample_2 allele 1, sample 2

A2.sample_2 allele 2, sample 2

warnings.sample_2 warnings from variant calling, sample 2

sample_1 name, sample 1
sample_2 name, sample 2
match status of genotype comparison
rsID mutation ID
gene associated gene
ENSGID ensembl gene ID
ENSTID ensembl transcript ID
REF reference allele
ALT alternative allele
impact putative variant impact
effect variant effect
feature transcript feature
biotype transcript biotype

test_profile_1	<i>SNV profile 1</i>
----------------	----------------------

Description

SNV profile in GRanges format from "sample1", originating from the test_profile_1.txt in the inst/extdata directory, for use in unit tests.

Usage

```
data(test_profile_1)
```

Format

A GRanges object with 383 elements and 17 metadata columns:

rsID mutation ID, if available
gene associated gene
ENSGID ensembl gene ID
ENSTID ensembl transcript ID
REF reference allele
ALT alternative allele
impact putative variant impact
effect variant effect
feature transcript feature
biotype transcript biotype
DP total variant depth
AD1 allelic depth, allele 1
AD2 allelic depth, allele 2
A1 allele 1
A2 allele 2
warnings warnings from variant calling
sample sample name

test_profile_2	<i>SNV profile 2</i>
----------------	----------------------

Description

SNV profile in GRanges format from "sample2", originating from the test_profile_2.txt in the inst/extdata directory, for use in unit tests.

Usage

```
data(test_profile_2)
```

Format

A GRanges object with 382 elements and 17 metadata columns:

rsID mutation ID, if available

gene associated gene

ENSGID ensembl gene ID

ENSTID ensembl transcript ID

REF reference allele

ALT alternative allele

impact putative variant impact

effect variant effect

feature transcript feature

biotype transcript biotype

DP total variant depth

AD1 allelic depth, allele 1

AD2 allelic depth, allele 2

A1 allele 1

A2 allele 2

warnings warnings from variant calling

sample sample name

test_profile_3	<i>SNV profile 3</i>
----------------	----------------------

Description

SNV profile in GRanges format from "sample3", originating from the test_profile_3.txt in the inst/extdata directory, for use in unit tests.

Usage

```
data(test_profile_3)
```

Format

A GRanges object with 99 elements and 9 metadata columns:

rsID mutation ID, if available

REF reference allele

ALT alternative allele

DP total variant depth

AD1 allelic depth, allele 1

AD2 allelic depth, allele 2

A1 allele 1

A2 allele 2

sample sample name

test_similarities	<i>Collated similarities object</i>
-------------------	-------------------------------------

Description

Collated similarities of multiple sample comparisons from "sample1" and "sample" from the example.vcf file, for use in unit tests.

Usage

```
data(test_similarities)
```

Format

A dataframe with 3 rows and 6 columns:

sample_1 name of sample 1

sample_2 name of sample 2

overlaps the number of overlaps for the comparison

matches the number of matches for the comparison

concordance the concordance of the profiles

similarity_score the similarity score of the profiles

test_variant_list	<i>Modified variant list object</i>
-------------------	-------------------------------------

Description

A variant list object from the 'list_variants' function, where the row names have been defined as "chr: pos (gene)" and the corresponding columns removed, for use in plotting.

Usage

```
data(test_variant_list)
```

Format

A dataframe with 2 rows and 2 columns:

sample1 the genotypes of sample1

sample2 the genotypes of sample2

Index

*Topic **datasets**

- test_comparison, [13](#)
- test_profile_1, [14](#)
- test_profile_2, [15](#)
- test_profile_3, [16](#)
- test_similarities, [16](#)
- test_variant_list, [17](#)

- calculate_similarity, [2](#)
- compare_many, [3](#)
- compare_profiles, [4](#)
- create_profile, [4](#)
- create_profiles, [5](#)

- filter_variants, [6](#)

- list_cosmic, [7](#)
- list_variants, [8](#)

- plot_heatmap, [8](#)
- plot_impacts, [9](#)
- plot_variant_list, [10](#)

- read_cosmic, [11](#)
- read_profile, [11](#)
- read_profiles, [12](#)

- seqCAT, [13](#)
- seqCAT-package (seqCAT), [13](#)

- test_comparison, [13](#)
- test_profile_1, [14](#)
- test_profile_2, [15](#)
- test_profile_3, [16](#)
- test_similarities, [16](#)
- test_variant_list, [17](#)